


## ELECTRIC OPERATING TABLE WITH TR AND RTR



• **44775 ELECTRIC OPERATING TABLE with TR and RTR**  
Electric operating table for general surgical procedures, mainly made of 304 stainless steel.  
It is driven by low-voltage DC motor with safe and stable performance. Table movements can be controlled by means of an easy-to-use hand controller.  
Super wide table top, super long sliding distance.  
Leg rest with integrated gas spring for easy control.  
Suitable for X-ray and C-arm surgery thanks to an extra-long horizontal sliding. Max. load: 200 kg.



### TECHNICAL SPECIFICATIONS

Size:	210x50xh 80-100 cm
Max. load:	200 kg
Trendelenburg:	0-25°
Reverse Trendelenburg:	0-22°
Lateral tilt (left/right):	0-20°
Head rest (up/down):	0-45°/0-90°
Back plate (up/down):	0-75°/0-20°
Foot plate (up/down):	0-15°/0-90°
Foot plate horizontal positioning:	0-90°
Horizontal sliding:	30 cm
Kidney bridge elevation:	11 cm
Voltage:	110-220 V, 50/60 Hz
Power capacity:	1.0 Kw

### STANDARD ACCESSORIES

Mattress	2 leg supports with cushion
1 anesthesia screen frame	2 foot supports with cushion
2 shoulder holders with cushion	1 kidney bridge handle
2 arm holders with cushion	1 IV stand

## INOX WORKING TABLE



• **27909 INOX WORKING TABLE**  
Working table, equipped with two drawers (47x30x12 cm) each side, to work on both sides. Stainless steel AISI 304 frame, structure made of square tubular, table top and lower shelf made of smooth stainless steel. Mounted on 4 castors Ø 100 mm, two with brakes. Size 120x70xh 95 cm. Weight 50 kg. Max load (x shelf): 40 kg. Delivered in kit form 122x35x72 cm

## OPERATING THEATRE INSTRUMENT TABLES

Shelf size: 120x65 cm



• **27913 INSTRUMENT TABLE 2 SHELVES**  
Operating room instruments table made of stainless steel AISI 304 scotch brite finish.  
125 mm Ø revolving castors (2 with brake).  
Weight: 28 kg. Load for shelf: 40 kg.  
Size: 120x65xh 95 cm.  
Delivered in kit form (123x13x68 cm).

Stainless steel adjustable  
105-136 cm upper part  
with 4 instrument hooks.



• **27914 INSTRUMENT TABLE 1 SHELF**  
Operating room instruments table made of stainless steel AISI 304, scotch brite finish. 125 mm Ø revolving castors (2 with brake).  
Weight: 21 kg. Load: 40 kg.  
Size: 120x65xh 95 cm.  
Delivered in kit form (123x13x68 cm).

## OPERATING ROOM INOX CABINETS

27917



MADE IN ITALY

### • 27917 INOX CABINET

Made of AISI 304 stainless steel. Two lockable doors (10/10 thickness), 4 adjustable shelves (8/10 stainless), 4 adjustable feet, with stainless steel cover. Size: 100x48xh 190 cm. Weight: 130 kg.

27918



MADE IN ITALY

### • 27918 GLASS-INOX CABINET

Made of AISI 304 stainless steel with two lockable doors in tempered glass 5 mm thick, 4 shelves in tempered glass 6 mm thick and 4 adjustable feet. Size: 100x48xh 190 cm. Weight: 105 kg.

27916



MADE IN ITALY

### • 27916 PAINTED STEEL CABINET

Epossidic powder painted steel cabinet with 4 adjustable shelves, lockable doors, 4 adjustable feet. Size: 100x50xh 200 cm.



## SHELVING SYSTEM



MADE IN ITALY

27908

### • 27908 SHELVING SYSTEM

Shelving system, made of AISI 304 stainless steel, scotch brite finish. With 5 stainless steel reinforced shelves at fixed position. Possibility to fix together several shelving systems. Size: 100x50xh 200 cm. Load x shelf: 25 kg. Weight: 30kg

3 shelving systems fixed together



## INSTRUMENT TROLLEY



MADE IN ITALY

27442

### • 27442 INSTRUMENT TROLLEY

Made of satinized welded AISI 304 stainless steel. With 4 sliding drawers (internal, 49x33xh 18 cm) Top drawer lockable, upper shelf with safety edges to carry instruments. 4 revolving castors Ø 80 mm. Size: 60x40xh 110 cm. Weight: 37 kg

## ANAESTHETIC TROLLEY



MADE IN ITALY

27437

### • 27437 ANAESTHETICS TROLLEY

Made of satinized AISI 304 stainless steel, with 6 drawers (internal 26x37xh 7 cm), a lockable vertical compartment and an open space. Top with 3.5 cm upstand. 4 revolving castors Ø 80 mm. Size: 60x40xh 110 cm. Weight: 39 kg

Drawers are locked once vertical compartment is locked


## BOWL STANDS

- 27456 SINGLE BOWL STAND
- 27457 DOUBLE BOWL STAND

Chrome plated steel stand with stainless steel base and 5 plastic wheels, one with brake. Adjustable height from 60 to 95 cm. Stainless steel bowl Ø 32 cm, 4 l capacity included.

Available with one or two bowls. **Delivered in kit form.**

- 27459 S/S BOWL Ø 32 cm - spare



## MAYO TABLES



- 27453 MAYO TABLE - 5 spokes

S/s tray, 5 spokes with castors, Ø 50 mm and adjustable height. Manual: GB, IT. **Delivered in kit form.**



- 27454 MAYO TABLE - s/s base

With removable s/s tray, s/s AISI 304 base with 4 castors (50 mm) and adjustable height. **Delivered in kit form.** Manual: GB, IT.



- 45830 MAYO TABLE - U-SHAPE

Stainless steel base with castors Ø 50 mm: 5 spokes (45832) or U-shape (45830). Stainless steel frame and removable tray. Adjustable height. **Delivered in kit form.**

### TECHNICAL SPECIFICATIONS

	27453	27454	27455	45830-45832
S/S tray size:	68x44 cm	70x45 cm	70x45xh 1.8 cm	70x45xh 1.7 cm
Adjustable height:	70-110 cm	74-110 cm	85-120 cm	90-115 cm
Weight:	8 kg	12 kg	19 kg	10 kg
Load:	20 kg	40 kg	40 kg	10 kg

## MAYO TABLES WITH PUMP



- 45834 HYDRAULIC MAYO TABLE with pump
- Serving trolley used as instrument holder in operating rooms. Not removable tray made of AISI 304 stainless steel. Equipped with hydraulic pump for height adjustment. Base made of aluminium with 5 spokes and swiveling castors Ø 50 mm. **Delivered in kit form.**

### TECHNICAL SPECIFICATIONS

	45834	45835
S/S tray size:	70x45xh 1.8 cm	90x126 cm
Adjustable height:	85 to 120 cm	90 to 126 cm
Load:	40 kg	20 kg
Weight:	14 kg	17 kg
Packing size:	60x17xh 77 cm	98x68xh 15 cm



- 45835 HYDRAULIC MAYO TABLE with pump and removable tray
- Height adjustable instruments trolley with removable tray in AISI 304 stainless steel, scotch brite finish. Tray can be rotated through 360° with tightening knob. Base in AISI 304 stainless steel tubular frame fixed to the hydraulic pump that allows height adjustment by foot pedal. Three castors Ø 75 mm, one antistatic and two with brake. **Delivered in kit form.**

## REX TROLLEY



- 27439 REX TROLLEY

Complete stainless steel dressing trolley. Supplied with 3 shelves, waste bin, drawer, support for bottles, guard rails on the two bottom shelves, 4 wheels, Ø 100 mm (2 with brakes). Load 50 kg. Size: 79x50xh 120 cm (handle included). Drawer size 64x43xh 9.5 cm. **Delivered in kit form (114x54x37 cm).**



## STAINLESS STEEL INSTRUMENT AND DRESSING TROLLEYS



27430

MADE IN ITALY

### • 27430 INOX TROLLEY

AISI 304 Stainless steel trolley with plastic drawer internally divided in 4 sectors. 2 shelves with upstands (3,5 cm) on four sides. Revolving rubber castors Ø 80 mm (two with brake).  
Size: 70x50xh 82 cm.  
Max load (x shelf): 25 kg.  
Delivered in kit form.



27433

MADE IN ITALY

Delivered in kit form.

### • 27433 MEDICAZIONE TROLLEY - small

Size: 60x40xh 81 cm - weight 8 kg

### • 27434 MEDICAZIONE TROLLEY - medium

Size: 70x50xh 82 cm - weight 9 kg

### • 27435 MEDICAZIONE TROLLEY - large

Size: 90x60xh 85 cm - weight 15 kg  
AISI 304 stainless steel trolleys, with push handle, 2 shelves with upstands (3,5 cm) on four sides, 4 revolving rubber castors Ø 80/80/100 mm. Max load (x shelf): 25 kg.



27431

MADE IN ITALY

### • 27431 TER TROLLEY

AISI 304 Stainless steel trolley, with push handle. 3 shelves with upstands (3,5 cm) on four sides, 4 revolving rubber castors Ø 80 mm. Size: 70x50xh 82 cm - weight 13 kg  
Max load (x shelf): 25 kg  
Delivered in kit form.



27436

MADE IN ITALY

Delivered in kit form.

### • 27436 DRESSING TROLLEY

Dressing trolley made of AISI 304 stainless steel with 2 shelves (70x50 cm), 1 drawer (40x50xh 15 cm), basin holder and basin. 4 revolving castors Ø 100 mm.  
Size: 70x50xh 85 cm - weight: 18 kg.  
Max load (x shelf): 25 kg.



45800

MADE IN ITALY

### • 45800 MEDICAZIONE PLUS TROLLEY With removable trays

Stainless steel trays mounted on castors Ø 80 mm.  
Size: 61x43xh 78 cm. Weight: 10 kg.  
Maximum load (x shelf): 10 kg.  
Delivered in kit form.



45805

MADE IN ITALY

### • 45805 TER PLUS TROLLEY With removable trays

Stainless steel frame, mounted on castors Ø 80 mm.  
Size: 49x30xh 78 cm. Weight: 9 kg.  
Maximum load (x shelf): 10 kg.  
Delivered in kit form.

## STAINLESS STEEL TROLLEYS WITH ABS SHELVES

- 45791 UTILITY TROLLEY 3 shelves
- 45792 UTILITY TROLLEY 2 shelves + 1 drawer

Practical trolleys with stainless steel frame and two or three high quality ABS shelves. All shelves provided with three-sided stainless steel siderails to prevent items from falling down. Two push handles for easy moving. Wear resistant, high quality silent castors, Ø 100 mm, two with brake.  
Size: 73x48x90 cm  
Drawer size: 50x42x12 cm (45792 only).  
Max load: 60 kg (30 kg per shelf).



45791



45792



## ALUMINIUM TROLLEYS



- **27429 GIMA 2 TROLLEY**  
- small: 60x40xh 77 cm - weight 11 kg
  - **27425 GIMA 2 TROLLEY**  
- medium 70x50xh 78 cm - weight 14 kg
- Practical trolleys with aluminium body and handles. Two white bilaminated shelves 18 mm thick, black PVC bordered, with guard-rail. Two large lateral handles facilitate transport or lift up of the trolley. 4 revolving nylon castors Ø 80 mm. Max load (x shelf): 40 kg.
- **27426 GIMA 3 TROLLEY** - medium 70x50xh 78 - weight 15 kg. Same as GIMA 2, but without guard rail. Delivered in kit form.

## ANODIZED ALLOY TROLLEYS

TOP QUALITY



- **27460 DELUXE TROLLEY**
  - **27461 DELUXE TROLLEY with drawer**
  - **27422 DELUXE TROLLEY with 2 drawers**
- Size: 65x45xh 80 cm  
Drawer size: ext. 58x40xh 10.5 cm, int. 51.5x38.5xh 8.5 cm.  
Top quality trolleys made of lightweight anodized special alloy with detachable stainless steel shelves. 4 revolving rubber castors Ø 80 mm. Max load (x shelf): 20 kg. Instructions: GB, FR, IT, ES PT, DE, GR. Delivered in kit form.

## LANCART: STAINLESS STEEL TROLLEYS TO BUILD UP



### LANCART TROLLEYS


Stainless steel trolleys mounted on castors Ø 80 mm. Maximum trolley load: 60 kg. Range of optional accessories to customize your trolley. Drawer size (45808-45809 only): 29x30xh 7.5 cm. Delivered in kit form.

GIMA code	LANCART TROLLEYS	Size	Shelves	Drawer
45810	Lancart trolley - small	60x40xh 80	2	-
45811	Lancart trolley - medium	72x50xh 80	2	-
45812	Lancart Ter trolley - small	60x40xh 80	3	-
45813	Lancart Ter trolley - medium	72x50xh 80	3	-
45808	Lancart trolley - small	60x40xh 80	2	yes
45809	Lancart trolley - medium	72x50xh 80	2	yes
GIMA code	ACCESSORIES FOR LANCART			
45815	Set of siderails (for 1 shelf) for 45808, 45810, 45812			
45816	Set of siderails (for 1 shelf) for 45809, 45811, 45813			
45817	Bottle rack			
45818	Waste bin			

### BUILD UP YOUR TROLLEY



## SMART CARTS - WITH 2, 3 OR 4 SHELVES OR DRAWER

**27893**4 twinned castors  
Ø 65 mm (2 with brake)**27895 + 27873  
+ 27874 + 27888****27889****27896**

MADE IN ITALY

### SMART CARTS - grey/white RAL 7035

Carts with base and 2, 3, or 4 wide, sturdy shelves in 3 different widths 40, 50 or 60 cm.

Aluminium columns and 4 twinned castors Ø 65 mm (2 with brake).

First shelf can be mounted flat or tilted  $\pm 10^\circ$ .

Fully removable drawer (27893-4) without ball bearing guides.

Designed for medical devices.

Illustrated assembly instructions.

### TECHNICAL SPECIFICATIONS

Dimensions (cm):	48,2x50x78 (27893, 27895)
	58,2x50x78 (27894, 27889)
Load capacity:	48,2x50x88 (27896)
	48,2x50x115 (27897)
Material:	68,2x50x78 (27890)
	total load 80 kg, shelf 15 kg
Shelf:	- vertical aluminium extrusions
	- plastic parts in ABS
Total weight:	steel sheet epoxy powder coated
	13 kg (27895)
	15 kg (27893, 27896, 27889)
	17 kg (27890)
	18 kg (27897)
	18.5 kg (27894)


GIMA code	SMART CARTS	Height (cm)
<b>27893</b>	2 shelves 40x36 cm + base + drawer	78
<b>27894</b>	2 shelves 50x42 cm + base + drawer	78
<b>27895</b>	2 shelves 40x36 cm + base	78
<b>27896</b>	3 shelves 40x36 cm + base	88
<b>27897</b>	4 shelves 40x36 cm + base	115
<b>27889</b>	2 shelves 50x42 cm + base	78
<b>27890</b>	2 shelves 60x42 cm + base	78

### ACCESSORIES FOR SMART CARTS

<b>27873</b>	Basket
<b>27874</b>	Infusion stand - fixed height*
<b>27888</b>	Cardio arm for ECG

\*Trolley with adjustable height infusion stand available on request in 40 days

## EASY AND EASY POWER CARTS

**27880****27881****27883  
+  
27874****27886**

MADE IN ITALY

### EASY CARTS AND EASY POWER CARTS

A complete line of stylish and sturdy carts with 2, 3 or 4 shelves and with power.

Adjustable height of sturdy shelves, aluminium columns and 4 twinned castors Ø 65 mm (2 with brake).

All shelves with anti-fall edges.

Designed for medical devices.

Illustrated assembly instructions.

#### Easy power carts

Easy power carts are equipped with cable pipe inside lateral columns and 4 connection sockets.

### TECHNICAL SPECIFICATIONS

Dimensions (WxDxH):	50x45x75/83.5/107.5 cm (Easy)
	50x45x75/83.5 cm (Easy power)
Load capacity:	total load 140 kg
	shelf 25 kg
Shelves:	40x36 cm
	4 twinned castors Ø 65 mm
Castors:	(2 with brake)
	- vertical aluminium extrusions
Material:	- plastic parts in ABS
	steel sheet epoxy powder coated
Shelf:	

GIMA code	EASY CARTS	Height (cm)
<b>27880</b>	2 shelves 40x36 cm + base	75
<b>27881</b>	3 shelves 40x36 cm + base	83.5
<b>27882</b>	4 shelves 40x36 cm + base	107.5

### EASY POWER CARTS

<b>27883</b>	2 shelves 40x36 cm + base	75
<b>27886</b>	3 shelves 40x36 cm + base	83.5


### ACCESSORIES EASY AND EASY POWER CARTS

<b>27873</b>	Basket 30x16xh 14.5 cm
<b>27874</b>	Infusion stand - fixed height*
<b>27884</b>	Extra shelf 40x36 cm
<b>27888</b>	Cardio arm for ECG

\*Trolley with adjustable height infusion stand available on request in 40 days

## SUPER EASY MULTIFUNCTIONAL CARTS

**BUILD UP YOUR CART**  
YOU CAN ADD: EXTRA SHELF, BASKET,  
INFUSION STAND, CARDIO ARM



**SUPER EASY CART:** A new stylish and quality cart you can build according to your needs. Carts with base and 1 or 2 sturdy shelves, aluminium columns and 4

GIMA code	SUPER EASY CARTS - with handle	Shelf size (cm)
27870	Cart + shelf + base	32x26
27871	Cart + shelf + base	40x36
27869	Cart + shelf + base + monitor support*	40x36

\*Can not be used with 27874

twinned castors Ø 65 mm (2 with brake). Illustrated assembly instructions.

GIMA code	ACCESSORIES for SUPER EASY CARTS
27872	Extra shelf 32x26 cm
27873	Basket
27874	Infusion stand - fixed height**
27875	Extra shelf 40x36 cm
27888	Cardio arm for ECG (not suitable for 27869)

\*\*Trolley with adjustable height infusion stand available on request in 40 days

### TECHNICAL SPECIFICATIONS


Dimensions:	47x42x79 cm (27870-1) 47x42x102 cm (27869)
Load capacity:	total 120 kg - shelf 10 kg 4 twinned castors Ø 65 mm (2 with brake)
Material:	- extrusions in aluminium - plastic parts in ABS
Shelf:	steel sheet epoxy powder coated

## TROLLEY FOR PATIENT MONITORS, VENTILATORS, ...

• **45760 TROLLEY FOR MONITORS - without plate adapter**  
Trolley specially designed for support and mobility of patient monitors and ventilators of most manufacturers. Trolley needs plate adapter (not included) to be chosen depending on brand/model.

- 10 mm thickness steel base with high resistance ABS cover
  - column in extruded aluminium with epoxy powders oven coated surface treatment
  - ergonomic rear handle in ABS with reinforced structure
  - 5 twin pivoting anti-noise castors Ø 65 mm made of thermoplastic rubber and ABS, 3 with brake
- Storage basket made of ABS plastic (30.5x15.6xh 14.9 cm).  
Size: 52.5x50xh 105 cm.

Max load: 15 kg.



GIMA Code	Type	PLATE ADAPTERS
45761	A	Mindray adapter
45762	B	Philips adapter
45763	C	Philips "Horn" adapter
45764	D	Other brands adapter

GIMA Code	Type	BRAND	MODEL
45764	D	Colin	Press-Mate 8800
45764	D	Fukuda Denshi	Dynascope DS-8007 and DSA-81
45764	D	General Electric	GE Dash 2000, 3000, 4000 monitors Carescape B650, B450 Carescape B20, B40, B105, B125 Root M series Rad-97 M series
45764	D	Masimo	ePM Compact: ePM10-12-15 ePM Modular: ePM10M, ePM12M Vet
45761	A	Mindray	iPM: iPM 8-10-12, iMEC: iMEC 8-10-12 uMEC: uMEC 8-10-12 Benevision: N12-15-17 VS600, VS900 Accutor 3-7
45764	D	Nellcor	N-595, N-550 Pulse Oximeter Bedside SpO <sub>2</sub> PM100N
45764	D	Nihon Kohden	Life Scope i, Life Scope L, BSM 2301, BSM 2303 Vismo PVM 2700, Vismo PVM 4000 Life Scope VS, BSM 3500, BSM 3700, Vismo PVM 2700 Life Scope P, BSM 4103, BSM 4113 Life Scope A, BSM 5105, BSM 5135 Life Scope TR, BSM 6301K, BSM 6501K, BSM 6701K Life Scope G5, Life Scope N, OPV 1500 GF-210R Multigas Unit CSM-1501, CSM-1502, BSM-6XXX, WEP-5200, GF-200 series
45764	D	Oridion	Capnostream™ 20 and Capnostream™ 20p
45764	D	Philips	Efficia CM10-12-100-120-150 EarlyVue VS30 IntelliVue MP5-20-30-40-50-60-70 IntelliVue MX400-450-500-550-600-700-800
45763	C	Philips	SureSigns Vsi, VS2+
45762	B	Philips	SureSigns VM4-6-8 and VS3-VS4-VSV series
45764	D	Sanuwave	MIST and UltraMIST series
45764	D	Sonosite	S and M series



## DOUBLE FACE PHARMACY TROLLEY



27499

FRONT

MADE IN ITALY



45730

FRONT



45731

FRONT

• **27499 DOUBLE FACE PHARMACY TROLLEY** - 3 large, 30 small drawers  
Two trolleys in one: 3 large drawers on one side, 30 (6+9+15) monodose cassettes on other side; with locking system.

Size of cassettes:

- 6 cassettes 115x290xh 75 mm
- 9 cassettes 115x290xh 45 mm
- 15 cassettes 70x290xh 45 mm

Size of trolley:

920x590xh 810 mm  
Provided with 4 revolving castors Ø 125 mm (3 with brake, 1 of trolley, antistatic).



BACK

• **45730 DOUBLE FACE PHARMACY TROLLEY** - 3 large, 22 small drawers  
Two trolleys in one: 3 large drawers on one side, 22 (6+6+10) monodose cassettes on other side; with locking system.

Size of cassettes:

- 6 cassettes 115x290xh 75 mm
- 10 cassettes 115x290xh 45 mm

Size of trolley:

920x590xh 810 mm  
Provided with 4 revolving castors Ø 125 mm (3 with brake, 1 of trolley, antistatic).



BACK

• **45731 DOUBLE FACE PHARMACY TROLLEY** - 62 small drawers  
Two trolleys in one: 31 (6+10+15) monodose cassettes on both sides; with locking system.

Size of cassettes:

- 6 cassettes 115x290xh 75 mm
- 10 cassettes 115x290xh 45 mm
- 15 cassettes 70x290xh 45 mm

Size of trolley:

920x590xh 810 mm  
Provided with 4 revolving castors Ø 125 mm (3 with brake, 1 of trolley, antistatic).



BACK

## EXCEL TROLLEY

Multilingual instructions:  
GB, FR, IT, ES,  
PT, DE, GR.



27441


Castors  
Ø 100 mm  
(2 with brake).

Without upstands  
at four sides for an easier  
cleaning.

MADE IN ITALY

• **27440 EXCEL TROLLEY** - 3 shelves (60x45cm) Size: 67x69xh 80 cm.  
• **27441 EXCEL TROLLEY** - 4 shelves (60x45cm) Size: 67x69xh 110 cm.  
Maximum load: 80kg  
Delivered in kit form.

## TRIS TROLLEY



27438

MADE IN ITALY

• **27438 TRIS TROLLEY**  
A practical trolley for ECG, Electrosurgical unit or any other device, with 4 nylon castors and 2 lateral handles for easy moving.  
Size: 49x37xh 77 cm. Shelf size: 40x30 cm.  
Total load: 39 kg, max per shelf 13 kg  
Colour: RAL 9002  
Multilingual manual: GB, FR, IT, ES, PT, DE.  
Delivered in kit form.

## PROFESSIONAL CARTS

All professional carts are  
supplied with cable pipe  
inside lateral columns.

27887  
+  
27873

MADE IN ITALY

• **27885 PRO CART** 2 shelves - h 80 cm  
• **27887 PRO CART** 2 shelves + keyboard and monitor support  
• **27873 BASKET**  
• **27874 INFUSION STAND**

### TECHNICAL SPECIFICATIONS

Load capacity:	- total load 240kg	- shelf 35kg
Base:	60.8x50 cm	
Shelves:	2 shelves 50x50 cm + base	
Material:	- vertical extrusions in aluminium - plastic parts in ABS	

## DRUGS & MEDICINE TROLLEYS



27495



27497



27494

- 27494 PHARMACY TROLLEY - small - 67x64xh 100 cm with 15 3-compartment partition
- 27495 PHARMACY-TROLLEY - standard - 82x64xh 100 cm with 20 3-compartment partition
- 27497 PHARMACY TROLLEY - large - 115x64xh 100 cm with 30 3-compartment partition

A portable pharmacy, allowing to manage daily or weekly treatment of patients, with 15/20/30 3 compartments small drawers for easy drug storage (45-60-90 spaces).

Painted steel frame, technopolimer surface and panels. Can be completely closed by safety key lock.

Provided with 4 revolving castors Ø 125 (2 with brake).

- 27498 PARTITION - 3 compartments - spare



27498

4 x 27498

MADE IN ITALY

## DRUGS & MEDICINE CABINETS



27942, 27944

MADE IN ITALY



27941

**MEDICINE CABINETS 100x60xh 195 cm**  
**With drugs compartment, 60 medicine compartments and 5 adjustable shelves**  
 - made of bilaminated board (27944/5) or melamine board (27942) 20 mm thick  
 - epoxy powder painted steel base frame with 4 adjustable feet Ø 50 mm  
 - 2 external lockable doors turning through 180° with 10 medicine compartments each  
 - perimetrical anti-dust gaskets  
 - inside 2 containers with 10 medicine compartments each side turning through 90°  
 - dangerous drugs compartment 40x22x40 cm provided with lock



• **27941 COMBO MEDICINE CABINETS 96x66xh 195 cm** with 30 medicine compartments one side and 6 ISO trays 1 shelf and 3 drawers other side  
 - made of bilaminated board 20 mm thick  
 - epoxy powder painted steel base frame with 4 adjustable feet Ø 50 mm  
**Right side**  
 - 1 external lockable door turning through 180° with 10 medicine compartments each  
 - perimetrical anti-dust gaskets  
 - inside 1 container with 10 medicine compartments each side, turning through 90°, provided with lock  
**Left side**  
 - glass door, internal side, with runners for ISO trays  
 - 3 drawers on the bottom  
 Supplied with 6 ISO trays different heights (2xh 5 cm, 3xh 10 cm and 1xh 20 cm) and 1 shelf.




GIMA code	MEDICINE CABINET	Material	Colour
27942	Medicine cabinet	melamine particle board	white
27944	Medicine cabinet	bi-laminated board	white
27945	Medicine cabinet	bi-laminated board	any colour*
Colours:	412	431	441
	482	484	499
	854	861	1818

\*You have to indicate requested colour with order. Available in 30 days



## BAG HOLDER TROLLEYS



45904+45910

MADE IN ITALY



45905+45910

MADE IN ITALY



45906+45910

MADE IN ITALY

- 45904 BAG HOLDER TROLLEY - 1 bag
- 45905 BAG HOLDER TROLLEY - 2 bags
- 45906 BAG HOLDER TROLLEY - 3 bags

Bag holder trolleys with pedal operated opening. Rigid, sturdy, self-supporting ABS plastic base with edges. The bag holding ring (35x25.5 cm) is made of glass reinforced nylon with a rubber gasket to hold the bag in place. Two vertical tubes made of AISI 304 stainless steel are welded to the base and carry the bag holding ring.

Non marking grey rubber swivelling wheels Ø 80 mm (two with pedal operated brake).

Pedal system equipped with shock absorber for silent lid closure.

- 45910 PUSH HANDLE
  - 27466 WRAPPING BAG - yellow strip
  - 27462 WRAPPING BAG - blue strip
  - 45908 WRAPPING BAG - green strip
- White synthetic bag with strip, washable up to 200 times.  
Size 57xh 103 cm.



45905+27462+27466+45910

## LAUNDRY TROLLEY



45913

- 45913 LAUNDRY TROLLEY
- Laundry trolley with stainless steel structure. Canvas bag and three shelves. Silent and antistatic castors Ø 7.5 cm with brake assembled on the vertical column line for better stability. Size 900x450xh 1050 mm. Supplied with canvas bag.

- 45914 CANVAS BAG - spare



Noiseless castors with brake



Velcro for canvas bag


## SHUT BAG HOLDER



45900

MADE IN ITALY

- 45900 SHUT BAG HOLDER - 70 l
- Trolley suitable for carrying one 70 l bag (not included). Stainless steel AISI 304 structure. Equipped with swivelling castors with brake and bumpers. For use with standard 70 l plastic bag. Can use also wrapping bag (27462, 27466, 45908)



## LINEN TROLLEYS



27467

- 27467 SOILED LINEN TROLLEY
  - 27468 DOUBLE SOILED LINEN TROLLEY
- Chrome plated frame with 3 or 4 castors Ø 80 mm. Removable bag. Size: Ø 46xh 90 cm. Delivered in kit form.



27468

Size:  
92x90 cm



## LAUNDRY TROLLEYS



MADE IN ITALY

27465 + 27462 + 27466

- 27464 LAUNDRY TROLLEY - painted steel
- 27465 LAUNDRY TROLLEY - stainless steel

Trolleys to collect dirty laundry while distributing clean linen to the patient. Stainless steel or painted steel frame. Equipped with 4 Ø 125 mm castors (2 with brake) and 4 rubber bumpers at corners. Size: 135x65xh 102 cm.

- 27463 SIDE PANEL - stainless steel
- 27466 WRAPPING BAG - yellow strip
- 27462 WRAPPING BAG - blue strip

washable up to 200 times, 57xh 103 cm



27464+27462

27465+27462+27463

MADE IN ITALY

45926 + 27462 + 27466

- 45925 CLOSED LAUNDRY TROLLEY - painted steel
- 45926 CLOSED LAUNDRY TROLLEY - stainless steel

Trolleys for collection of dirty laundry and distribution of clean linen to the patient. Stainless steel or painted steel frame.

Equipped with 4 Ø 125 mm anti-thread swivelling castors (2 with brake), 2 rectangular supports with rubber bag stop ring, 2 lids and 3 shelves of which 2 adjustable.

Suitable for 70 litres waste bags.

Size: 1330x650xh 1200 mm (45925)

1330x650xh 1140 mm (45926)

- 27466 WRAPPING BAG - yellow strip
- 27462 WRAPPING BAG - blue strip

White washable laundry synthetic bag with yellow or blue strip.

Size: 57xh 103 cm.

MADE IN ITALY

45915

- 45915 LAUNDRY TROLLEY - laminated

Closed trolley with doors, 3 shelves plus top and 2 bag holders.

Laminated particle board body and stainless steel AISI 304 structure.


Equipped with swivelling castors, 2 with brake and bumpers.

Size: 110x66x132 cm.

- 27462 WRAPPING BAG - blue strip
- 27466 WRAPPING BAG - yellow strip

White washable laundry synthetic bag with yellow or blue strip.

Size: 57xh 103 cm.



## CLEAN LINEN AND PATIENT HYGIENE TROLLEYS



45930

45931

45933

45934

MADE IN ITALY

### CLEAN LINEN TROLLEYS 2 DOORS

Solid and sturdy trolleys for distribution of clean linen and patient hygiene. Steel painted with antimicrobial epoxy powders to obtain maximum lightness. Upper part has large support surface in technopolymer plastic material. Integrated ergonomic push handle. Supplied with 2 doors with 3 internal shelves (45930, 45933 only) or 2 doors with 2 internal shelves and one drawer made of antimicrobial epoxy powder coated steel (45931, 45934 only). Key closures.

4 castors Ø 125 mm, anti-wire, pivoting, two of which with lever locking system and reinforced plastic support.

GIMA code	CLEAN LINEN TROLLEYS	Size (mm)	Drawer size (mm)
45930	Clean linen trolley - small	670x640xh 1280	-
45931	Clean linen trolley - small	670x640xh 1280	600x480xh 150
45933	Clean linen trolley - standard	820x640xh 1280	-
45934	Clean linen trolley - standard	820x640xh 1280	750x480xh 150

## ISO SERVICE TROLLEYS



Size:  
65x47xh 100 cm  
Weight: 12.5 kg

Size:  
59x99.3xh 88 cm

Adaptable to  
any model of ISO  
600x400 baskets  
and trays thanks  
to the special rail  
sides, which allow  
an easy sliding  
and pull out.

**27935**  
MADE IN ITALY

**27934**



Lockable with  
double key

**27936**

Equipped with key  
lock and doors kit  
made of transparent  
polycarbonate.

Side plastic  
runners for "ISO"  
trays or baskets

(baskets and trays  
not included)

Handle for  
transport

**27936**



- **27935 ISO SERVICE TROLLEY - empty**  
Service trolley for  
"ISO" trays or baskets  
(not included) made  
of epoxy powder  
painted steel. Supplied  
with 5 height  
adjustable  
runners for  
ISO  
trays/baskets.



Both side basket pulling out with  
stopper to avoid accidental fall.

- **27934 AURION MINI 600 - ISO trolley - empty**  
Basic body made of Baydur Polyurethane -  
Bayer AG: it can be washed and disinfected.  
It does not react with diluted acids, alkali  
and solvents. Self-extinguishing according  
to class UL V0 - Latex Free. For safety,  
handles are moulded into the body on both  
sides, trolley top has a 4-sided moulded  
containing rim to avoid any spill or fall of  
materials. No sharp edges. All around bumper.  
Lightweight and easy to move.


- **27936 ISO TRANSPORT TROLLEY - empty**  
Transport trolley  
for ISO trays and  
baskets (not included).  
Made of stainless steel AISI 304 sheet,  
scotch brite finishing. Anti-dust gasket.  
Internal side with plastic runners for ISO  
trays or baskets.  
Supplied with handle for transport.  
External size: 52x68xh 159 cm  
Internal size: 40x60xh 129 cm

## ISO FORMAT UNIVERSAL MODULAR TRAY SYSTEM

**27996**

ISO MODULAR TRAYS GREY ABS		
Closed	Open	SIZE mm
<b>27924</b>	-	600x400x50
<b>27925</b>	<b>27938</b>	600x400x100
<b>27928</b>	<b>27939</b>	600x400x200
TRANSPARENT PC		
Closed	Open	SIZE mm
<b>27957</b>	-	600x400x50
<b>27958</b>	<b>27965</b>	600x400x100
-	<b>27966</b>	600x400x200


Intelligent solutions for storing all kind  
of drugs, bandages, accessories and small  
components in a space saving and clear  
manner.



27995	
GIMA code	DIVIDERS
<b>27994</b>	400x50 mm
<b>27995</b>	600x50 mm
<b>27996</b>	400x100 mm
<b>27997</b>	600x100 mm
<b>27998</b>	400x200 mm
<b>27999</b>	600x200 mm
<b>28001</b>	Drawer stopper

## NEO EMERGENCY TROLLEY

- **45722 NEO EMERGENCY TROLLEY**  
Heavy duty construction emergency trolley size 75x47.5x92 cm  
with five drawers. Four castors (Ø 10 cm) assembled on the  
vertical column line for better stability.  
One piece counter top with a fully guarded handle for comfort  
and protection.



**STANDARD ACCESSORIES**  
Defibrillator plate  
Sliding side shelf  
Sharp container  
Oxygen bottle holder  
Power outlet  
Utility container

IV pole  
CPR board  
2 waste bins  
Dividers  
Central lock

## NEO MEDICINE TROLLEY

- **45725 NEO MEDICINE TROLLEY - double side**  
Two sided medicine trolley 75x48x92 cm with steel and  
aluminium structure inside, ABS and antibacterial material  
outside. 4 nylon castors Ø 12.5 cm, one with brake.



**STANDARD ACCESSORIES**  
Central lock  
2 waste bin  
Utility container

4 covered castors  
Dividers



# EMERGENCY TROLLEYS - PAINTED OR STAINLESS STEEL

## EMERGENCY TROLLEYS

Professional, solid and sturdy emergency trolleys with components in plastic material (technopolymer) or stainless-steel sheet painted with epoxy powders to obtain maximum lightness, maneuverability and ease of use.

Self-supporting and monocoque structure.

Upper part has large support surface in technopolymer plastic material to facilitate cleaning and disinfection.

Ergonomic push handle firmly attached on the right side of the trolley.

Front part designed for insertion of modular drawers: silent sliding of the drawers on guides with ball bearings, equipped with limit stops and designed for central locking with key.

Defibrillator plate has a plexiglass plate and tubular support in stainless steel, 360° rotatable and lockable every 10°, device can be locked by means of straps that can be adapted to any size.

Stainless steel IV stand adjustable in height with locking device.

Heart massage plate made of transparent plexiglass.

Four or five standard drawers entirely made of AISI 304 stainless steel (45695-6) or plastic material (27479, 27482, 45693-4).

Additional extractable worktop in technopolymer plastic material on the left side; built-in compartment complete with four shelves with front panel all made of technopolymer plastic material.

4 castors Ø 125 mm, anti-thread, pivoting of which 2 antistatic and 2 with locking system with lever, wheel and fork on ball bearings.



GIMA code	EMERGENCY TROLLEYS	Trolley size (cm)	Number of drawers	Drawers material	GIMA code	ACCESSORIES
27479	Painted steel emergency trolley - small	67x64xh 100-160	4	plastic	27471	Divider kit for 27479 (drawer 45 cm)
27482	Painted steel emergency trolley - standard	82x64xh 100-160	4	plastic	27472	Divider kit for 27482 (drawer 60 cm)
45693	Painted steel emergency trolley - small	67x64xh 100-160	5	plastic	27485	Disposable numbered seals - box of 100
45694	Painted steel emergency trolley - standard	82x64xh 100-160	5	plastic	27474	Premium disposable numbered seals - box of 100
45695	Stainless steel emergency trolley - small	67x64xh 100-160	5	stainless steel		
45696	Stainless steel emergency trolley - standard	82x64xh 100-160	5	stainless steel		

### TECHNICAL SPECIFICATIONS

	27479	27482	45693	45694	45695	45696
Drawers number/size:	3 45x48.5xh 13.5 cm 1 45x48.5x h 27.5 cm -	3 60x47.5xh 13.7 cm 1 60x47.5xh 27.4 cm -	2 45x48.5xh 7.5 cm 2 45x48.5xh 15 cm 1 45x48.5xh 22.5 cm	2 60x47.5xh 7.5 cm 2 60x47.5xh 15 cm 1 60x47.5xh 22.5 cm	2 45x48.5xh 7.5 cm 2 45x48.5xh 15 cm 1 45x48.5xh 22.5 cm	2 60x47.5xh 7.5 cm 2 60x47.5xh 15 cm 1 60x47.5xh 22.5 cm
Defibrillator plate:	39x32xh 2 cm					
Size (cm):	67x64xh 100-160	82x64xh 100-160	67x64xh 100-160	82x64xh 100-160	67x64xh 100-160	82x64xh 100-160

### STANDARD ACCESSORIES

<b>Right side</b> Waste container Catheter or probes holder Shelf with front panel Recessed compartment  <b>Upper part</b> IV stand Defibrillator tray	<b>Left side</b> Extractable worktop Compartment with 4 shelves and front panel  <b>Rear side</b> Built-in gas bottle compartment with fastening straps Bar with hooks for accessories
--	--





## MULTI-FUNCTIONAL TROLLEYS: BASIC AND DRESSING

### MULTIFUNCTIONAL TROLLEYS: BASIC - DRESSING

These multifunctional professional trolleys have painted steel structure and external plastic finishing. Basic and Dressing are available in 3 different sizes (small, standard, medium). Provided with 4, 8 or 9 drawers, one lateral waste container (manual opening, capacity 15 l) and one extra lateral table.

Four swivelling rubber castors Ø 125 mm (2 with brake).

#### BASIC



45702  
Standard

#### BASIC TROLLEY - 3 sizes

Standard version without accessories



27476  
Standard



27477  
Small



**DIVIDER KIT** - size: 20/35/50x43xh 7 cm

- 27470 KIT for drawer 30 cm - 8 compartments
- 27471 KIT for drawer 45 cm - 20 compartments
- 27472 KIT for drawer 60 cm - 25 compartments

Partitions  
are removable

#### DRESSING



27481  
Standard



45701  
Small



27484  
Medium

MADE IN ITALY

#### DRESSING TROLLEY - 3 sizes

Same as Basic, but equipped with instrument tray and upper dispenser (10 tilting bins).

BASIC		DRESSING		Size Type	Size of trolley (cm) (without accessories)	Number of drawers	Size of drawers cm					
Yellow	Blue	Yellow	Blue				45x48xh13	45x48xh27	60x48xh13	60x48xh27	30x48xh13	30x48xh27
27477	45700	27478	45701	Small	67x64xh 100	4	3	1	-	-	-	-
27480	45702	27481	45703	Standard	82x64xh 100	4	-	-	3	1	-	-
27476	45704	-	-	Standard	82x64xh 100	9	-	-	-	-	8	1
27483	-	27484	-	Medium	102x64xh 100	8	3	1	-	-	3	1
27486	-	-	-	Large	115x64xh 100	8	-	-	3	1	3	1

## RECORD HOLDERS AND X-RAY FILM HOLDERS TROLLEYS

For 25+25 file racks (not included)

Keeps 25 file racks  
(not included)

MADE IN ITALY

Keeps 40 file racks  
(not included)

Sliding up



27492



27491



27490



27488

- 27490 RECORD HOLDERS TROLLEY - sliding top
- 27491 RECORD HOLDERS TROLLEY
- 27492 RECORD HOLDERS TROLLEY - 2 large drawers

Record trolleys are designed to hold clinical reports in A3/ A4 format or specific format. Frame in epoxy painted steel, working surface and panels in technopolimer plastic. Equipped with 4 Ø 125 mm swivelling rubber castors (2 with brake).

Bumpers around the perimeter.

Size: 820x640xh 1,000 mm (code 27491 and 27490)

820x640xh 1,150 mm (code 27492).

- 27493 FILE RACK A3 465x390 mm plastic



27493

- 27488 X-RAY FILM HOLDER

This trolley has 32 extractable compartments, a wide top surface, 4 side document holders, and a sliding out writing surface. Frame is in painted steel with sliding-in bilaminated doors with a 270° opening. Base and lateral cabinets are made of technopolimer material. Equipped with 4 Ø 125 mm swivelling rubber castors (2 with brake).

Size 820x640xh 1, 200 mm.

## MULTIFUNCTIONAL TROLLEYS WITH CENTRAL BREAKING SYSTEM

### • 45711 MULTIFUNCTIONAL TROLLEY 65x88xh 100 cm

### • 45713 DRESSING TROLLEY 65x88xh 100 cm with dispenser

Solid and robust construction with steel sheet painted with antimicrobial epoxy powders and technopolymers for maximum lightness, maneuverability and ease of use.

**Upper part:** large support surface in PST with ergonomic and integrated push handle. Push handle has a central mechanism for locking and unlocking wheels' brakes.

**Front part:** retractable worktop support with "push and pull" opening.

Four modular drawers with soft self-closure, ball bearings and central locking with key. Drawers are made of painted steel.

**Left side:** recessed compartment and retractable worktop made of technopolymer plastic; 10 L waste bin with knee opening and technopolymer catheter holder.

**Right side:** recessed compartment with three tilting pockets made of technopolymer material.

Supplied with four Ø 100 mm twinned castors with automatic locking system.



Left side




Central breaking system



MADE IN ITALY

45711



Dispenser with pole including 10 tilting bins

Medium drawer size: 45x48.5xh 15 cm

Large drawer size: 45x48.5xh 22.5 cm

45713

## KS MULTIFUNCTIONAL TROLLEYS

### MULTIFUNCTIONAL TROLLEYS: BASIC, DRESSING, EMERGENCY

Professional trolleys in 2 sizes (small and standard) and 3 models (Basic, Dressing and Emergency).

- antimicrobial epoxy painted body with seal lock (Emergency) or key lock (Basic and Dressing)
- top surface with 4-sided rim
- top surface with built-in compartment

MADE IN ITALY

- ball-bearing full-extension sliding drawer with self-closing system
- built-in handle
- 4 swivelling castors Ø 125 mm - 2 antistatic (only 45688/9) and with brake
- lateral waste container 15 l with lid and catheter holder (Dressing and Basic only)
- size: small 760x714xh 1,022 mm  
standard 911x704xh 1,075 mm

Lateral side with waste container 15 l with lid and catheter holder



45680



Dispenser with pole including 10 tilting bins

45685

Back with large oxygen tank compartment and stainless steel holding rail with hooks

Lateral side with waste containers 15 l with lid

45689



45681

2 small drawers: 600xh 75 mm  
2 medium drawers: 600xh 151 mm  
1 large drawer: 600xh 228 mm

Writing surface

Lateral container unit with 4 supply trays



45684

3 medium drawers: 450xh 151 mm  
1 large drawer: 450xh 228 mm

Writing surface

Lateral container unit with 4 supply trays

Height adjustable I.V. pole with 2 hooks

Defibrillator/monitor rotating tray



45689

2 small drawers: 600xh 75 mm  
2 medium drawers: 600xh 151 mm  
1 large drawer: 600xh 228 mm

- 45680 BASIC TROLLEY - small
- 45681 BASIC TROLLEY - standard

- 45684 DRESSING TROLLEY - small
- 45685 DRESSING TROLLEY - standard  
Dressing trolley is supplied with upper dispenser (10 tilting bins).

- 45688 EMERGENCY TROLLEY - small
- 45689 EMERGENCY TROLLEY - standard  
Emergency trolley is supplied with rotating defibrillator/monitor tray, height adjustable I.V. pole with 2 hooks.




# AURION MULTIFUNCTIONAL TROLLEYS - TOP QUALITY

## AURION TROLLEYS

A multifunctional and revolutionary line of carts with innovative design, superior quality and complete accessories.

### Made in Baydur® polyurethane

Baydur® Polyurethane is a high performance material that combines the best characteristics of plastics and metals. Light, sturdy, high resistance to scratching and impact. Resistant to UV rays. Chemical inert, doesn't react to acids, organic and inorganic, alkali and solvents (DIN 68861/1).



- 45751 AURION EMERGENCY TROLLEY - dark blue - 5 drawers
- 45750 AURION EMERGENCY TROLLEY - red - 4 drawers with IV stand, defibrillator tray, suction unit shelf (45751 only), CPR massage board, electric plug (45751 only).

Fire resistant, self-extinguishing (Class I, UL94 V-O). Non-toxic, in case of combustion it doesn't produce dioxin.

### Well-designed

The Aurion trolleys are ergonomic, modular, highly customizable and upgradable over the years. The handles are moulded and integrated into the body as well as the worktop that has large surface and perimetrical anti-drip containing rim. Every drawer is equipped with a label holder.

### Easy to move

Lightweight structure combined with the high quality non-marking and anti corrosion castors. Every wheel is mounted on ball bearings with sealed lubrication (2 per wheel), 3 with brake, 1 antistatic.

### Hygienic and safe

The smoothly shaped design, without edges, guarantees safety to the user and avoids dirty and bacterial accumulation points. Easy to clean and disinfect also with aggressive detergents.

### Safe and secure

All-around soft rubber bumper help to avoid damages to hospital staff, patients, objects or to the trolley itself.

Central locking device with key (45740-45746) or with seal (45750-45751).

Size 775x710xh 920 mm



- 45755 AURION AMAGNETIC TROLLEY - yellow - 5 drawers with amagnetic wheels, without locking system



- 45740 AURION THERAPY TROLLEY - green - 4 drawers
- 45741 AURION THERAPY TROLLEY - light blue - 5 drawers with IV stand (45751 only), upper drawers, bin (45741 only)
- 45744 AURION DRESSING TROLLEY - blue - 5 drawers
- 45746 AURION MONODOSE TROLLEY - brown - 2 drawers + 2 monodose cassettes (10 small drawers each)




# MULTIFUNCTIONAL AND EMERGENCY KARTS

## MULTIFUNCTIONAL KARTS

High quality aluminium multifunctional and emergency carts with superior features.

- work-top in high performance copolymer, with perimetric edge for liquid containment
- extruded aluminium frame, with superficial silver antioxidant treatment offering more lightness, resistance and reliability
- ergonomic stainless steel handles, fitted on both sides for easy handling
- drawer structure built in steel sheets, epoxy powder coated
- full pull-out sliding drawers

- interchangeable drawer position
- aluminium drawer handle with "hook/unhook" system to prevent accidental opening of drawers



- **45660 COMPACT KART** - 5 drawers - blue  
Size: 654x605xh 975 mm
- **45661 UPPER DRAWERS (9+5)** - blue for 45660
- **45662 MEDIUM KART** - 5 drawers - blue  
Size: 804x616xh 975 mm
- **45663 UPPER DRAWERS\* (9+5)** - blue for 45662

\*Included support for glove box

- **45677 PARTITION KIT** for compact kart drawers h2/h3



- high drawers capacity: 20 kg (35 kg for drawer h-200-283 mm)
- centralized locking system with front key or single use seals (emergency karts only)
- 6 integrated side pockets (3+3) to hold bottles or small items
- swivelling wheels Ø 125 mm (two with brake) in thermoplastic rubber with threadguards, hub on precision ball bearings.

## TECHNICAL SPECIFICATIONS

Frame size:	COMPACT: 654x605xh 975 mm	MEDIUM: 804x616xh 975 mm
Drawer size Compact/Medium:	Front width/height	Inner sizes
small	h1= 1/10 490/640xh 64 mm	432/582x448xh 58 mm
medium	h2= 2/10 490/640xh 137 mm	432/582x448xh 131 mm
large	h3= 3/10 490/640xh 210 mm	432/582x448xh 204 mm
folder holders	h4= 4/10 490/640xh 283 mm	432/582x448xh 270 mm



- **45665 EMERGENCY COMPACT KART** - 5 drawers - red
- **45666 EMERGENCY COMPACT KART** - 4 drawers - orange  
Size: 654x605xh 975 mm
- **45667 EMERGENCY MEDIUM KART** - 5 drawers - red
- **45668 EMERGENCY MEDIUM KART** - 4 drawers - orange  
Size: 804x616xh 975 mm


Supplied with infusion stand holder 4 hooks, Ø 120-150 mm defibrillator holder tray, cylinder holder (double for 45667/8) and CPR board (only 45666/8).

- **27485 DISPOSABLE NUMBERED SEALS** - box of 100
- **27474 PREMIUM DISPOSABLE NUMBERED SEALS** - box of 100



- **45671 VIEWER KART**  
Compact kart with slim LED viewer, 2 small drawers and 2 folder holders.
- **45678 HANGING FILE FOLDERS\***

- **45672 VIEWER KART 2**  
Compact kart with slim LED viewer, 2 small and 1 medium drawers, 10 compartments for folders (44x48xh 43,8 cm).



- **45656 PEDIATRIC KART**  
Pediatric compact kart with 2 medium and 2 large drawers.
- **45657 UPPER DRAWERS (9+5)**

- **45674 MULTIPURPOSE KART**  
Compact kart with 2 small drawers and 2 folder holders.
- **45675 UPPER DRAWERS (9+5)**
- **45678 HANGING FILE FOLDERS\***

• **45650 PERSONALIZED KART: CONFIGURATE YOUR KART SELECTING COLOUR, DRAWERS AND MODEL** - available in 45 days

Available drawers

Small 1/10 h	Medium 2/10 h	Large 3/10 h	Folder holder 4/10 h
-----------------	------------------	-----------------	-------------------------

Available colours

Red RAL3020	Orange RAL2004	Turquoise RAL5018	Blue RAL5010	Ceil blue RAL5012	Green RAL6018	Yellow RAL1021
----------------	-------------------	----------------------	-----------------	----------------------	------------------	-------------------

\* Box of 25 hanging file folders 365 x 240 mm

You can choose your drawers considering:

- interchangeable position of drawers
- sum of selected drawers should be 10/10 h

## PAINTED OR STAINLESS STEEL MODULAR TROLLEYS SYSTEM



### MODULAR TROLLEYS SYSTEM

Modular trolleys made of painted steel or stainless steel, one-piece structure, with wide technopolymer plastic worktop with borders on 3 sides to be cleaned easily, no sharp corners, ergonomic tubular push-handle.

Different drawers (small-yellow, medium-blue, large-red), depending on model, with epoxy painted panels and

integrated handle grip, silent sliding with end-run block. Possibility to remove the drawers from the guides for an easy cleaning and disinfection. Central lock key. Overall bumpers and 4 antistatic 125 mm castors, 2 with brakes.

Size: 67x63x104 cm. Weight: 53 kg.

Personalization for minimum 10 pcs: drawers in your colour.

Painted	Stainless steel	TROLLEYS
45600	45620	Trolley with 7 small drawers
45601	45621	Trolley with 1 small, 3 medium drawers
45602	45622	Trolley with 2 small, 1 medium, 1 large drawers
45603	45623	Trolley with 1 small drawer, 1 compartment with shelf
45604	45624	Trolley with 2 medium, 1 large drawer

### ACCESSORIES FOR ALL MODULAR SYSTEM TROLLEYS

45640	IV stand
45641	Upper drawers (5 medium + 4 large)
45644	Partition h 4 cm for yellow drawer (49x48x10 cm)
45645	Partition h 14 cm for blue drawer (49x48x20 cm)
45646	Partition h 20 cm for red drawer (49x48x30 cm)



## WASH-BASIN - PUMP

### • 45410 WASH-BASIN PUMP SYSTEM - white

Automatic wash-basin with round bowl in satin stainless steel, non-connected to the water mains. The system ensures the availability of water when it is expensive or impossible to lay drain-pipes in the walls or floors.



Dimensions:  
47x54xh 86 cm

It only requires a 230V power socket: the low voltage transformer (12V) drives a pump for supplying water by a simple pressure of the foot on the base.

Equipped with 2x20 litre tanks for water supply and drain

## UTILITY TROLLEY



45595

Blue Avio  
RAL 5014  
available  
in stock

MADE IN ITALY

### • 45595 UTILITY TROLLEY - blue avio • 45597 UTILITY TROLLEY - other colours\*

RAL 5010	RAL 2003	RAL 6019	RAL 1013	RAL 3020
----------	----------	----------	----------	----------

\*Available in 30 days. Minimum order 5 pcs.

Smart and strong steel structure painted with epoxy powder. Technopolymer plastic one-piece top with border, without sharp corners, with compartment for accessories. Ergonomic push handle.

3 medium drawers 45.1x48.5xh 15 cm and 1 large drawer 45x49.5xh 22.5 cm with silent sliding and end-run block. Central lock key. Size: 60x50xh 100 cm. Overall bumpers and 4 antistatic 125 mm swivelling castors, 2 with brake.



45597 Utility trolleys other colours available in 30 days




## MULTI-PURPOSE WALL UNITS

Multi-purpose wall unit to organize dispensers of disposable products. All components and slots are modular and can be organized to match professional user needs. Available in 2 sizes: standard (103x20xh 40 cm) and large (153x20xh 40 cm) and 15 colours. Powder coated galvanized metal pull-up door with vertical opening. Supplied with automatic soap dispenser, cups dispenser and 5 (standard) or 7 (large) slots.



STANDARD ACCESSORIES	45290	45295
Dispenser for disposable cups	1	1
Automatic soap dispenser	1	1
Slot for gloves or wipes	2	3
Slot for masks	1	1
Slot for napkins or cannula	-	1
Roll holder	2	2



### MULTIFUNCTIONAL WALL UNITS

Model	white	RAL 1015	RAL 1018	Apricot	RAL 3000	RAL 5000	RAL 5010	RAL 5012
Standard	45290	RAL 5014	RAL 5022	RAL 6019	RAL 6027	RAL 7038	RAL 9001	RAL 9002
Large	45295							

\*Available in 60 days, please specify colour with order

## GIMA MOBILE SPACE: WORKTOPS AND MOBILE UNITS



**Mobile space** is a programme of safe and ergonomic technical furniture for medical, physiotherapy and professional beauty use. These units feature wheels and offer the same levels of functionality as trolleys. The visible edges are radiating and covered in shockproof material. The steel handles provide good grip without dangerous edges. Stability is optimised by the inner and outer sides, the extra-thick backs and invisible wheel positioning. The steel runners of the drawers with rocker arm closing ensure smooth opening while preventing undesired opening during transport.

The independent worktop makes it possible to fully pull out the units for easier floor cleaning and position the trolleys according to need. It is available with or without washbasin (left or right). The broad choice of unit configurations and colour range make it possible to personalise interiors according to individual requirements.

GIMA code	STANDARD WORKTOPS - WHITE
45420	Worktop 106 cm - right washbasin
45421	Worktop 106 cm - left washbasin
45422	Worktop 106 cm - without washbasin
45423	Worktop 156 cm - right washbasin
45424	Worktop 156 cm - left washbasin
45425	Worktop 156 cm - without washbasin
45426	Worktop 206 cm - right washbasin
45427	Worktop 206 cm - left washbasin
45428	Worktop 206 cm - without washbasin
ACCESSORIES	
45459	Chromed mixer tap 45459



### MOBILE UNITS

white	blue	green	orange	Model
45440		45450*		4 drawers
45441		45451*		4 drawers
45442		45452*		6 drawers
45443		45453*		under washbasin

\*Available in 45 days, please specify colour with order

# 1 OR 3 ENGINES GYNAECOLOGICAL CHAIRS AND STOOLS





**GYNEX - GYNAECOLOGICAL CHAIR**  
GYNEX: a chair offering a unique combination of functional, aesthetic and working characteristic.

Thanks to its self-balancing seat and backrest, GYNEX can be adjusted to any build for the greatest patient comfort. The chair is provided with an electromechanical lifting device, having a power supply at 24 V.

The electric actuators enable the movement up and down from 57 cm off the floor ("0" position) up to a maximum of 96 cm. The backrest is supplied with adjustable headrest and paper roll holder. The legrest can be independently adjusted and it has an automatic-locking device.

The chair can be flattened to a bed position for examination activity, the armrest can be removed and independently oriented.

The electric control of the chair for upright position is operated by means of a foot pedal.



**GYNEX PROFESSIONAL**  
with 3 engines



**GYNEX PROFESSIONAL - GYNAECOLOGICAL CHAIR**

Gynex professional chair offers functionality, aesthetics, ergonomics. It can satisfy all patient and user needs for a professional gynaecologic visit. Gynex professional is provided with versatile accessories: back paper-roll dispenser, metal basin, leg-supports. 3 engines allow, in addition to lifting, electric backrest and legrest movements. The combined movement of backrest and seat by means of self-balancing system (operated by a silent low tension actuator of 2,500 N) grants maximum comfort to the patient. The padded and pelted armrests allow a relaxing protecting sitting position, armrests are individually revolving and removable. Backrest is provided with removable height-adjustable headrest. The wide and soft backrest has independent adjustment movement through silent low tension actuator. This chair is moved by a silent low tension engine which allows a vertical excursion of 40 cm from zero position. The electrical drives are controlled by an ergonomic hand switch control, connected to the chair by a cable. Gynex professional can be easily transformed into an examination bed (horizontal position).



## STANDARD ACCESSORIES

	GYNEX	GYNEX PROFESSIONAL
Polyurethane leg-rest	•	•
Padded leg-rest (colour coordinated)	•	•
Paper-roll holder	•	•
Basin	• (plastic)	• (metal)
Remote control	•	•

## STOOL - with or without ring

For professional use, completely built in stainless steel, 360° pivoting self-braking castors, rubber-tyred. Height can be comfortably adjusted by means of a gas pump; back-rest is 180° revolving and depth-adjustable. Seat is balanced density padded and Peltex-lined.



• **27518 WORK STATION SW2**  
- steel structure, painted with epossidic powder  
- 4 antistatic pivoting wheels  
MADE IN ITALY

## TECHNICAL SPECIFICATIONS

	GYNEX	GYNEX PROFESSIONAL
Power supply tension:	230V - 50 Hz (110V - 60 Hz on request)	24 V
Motor tension:	24 V	24 V
Lifting motor push:	6,000 N	6,000 N
Backrest push:	800 N (gas spring)	2,500 N (motor)
Legrest motor push:	-	2,500 N
Lifting capacity:	180 kg	180 kg
Maximum power:	90 VA	90 VA
Fuses protection:	1.6 A	1.6 A

## GYNEX CHAIRS AND STOOLS

	Light blue Parigi	Green Toronto	Blue Chicago	Orange Rotterdam	Metal Apricot	Metal Sea blue	Colour on request
Gynex professional	27514	27512**	27513	27512**	27515	27512**	27512**
Gynex	27521	27522	27523	27524	27525	27526	27520**
Stool with ring	27531	27532	27533	27534	27535	27536	27530**
Stool without ring	27527				27528**		

\*\*Available in 60 days, specify colour with order

## COLOUR ON REQUEST: CLASSIC COLOURS

White Helsinki	Beige Roma	Beige Tunisi	Brown Perugia	Yellow Parma	Orange Praga	Red Mosca	Pink Malaga	Bordeaux Bangkok
Green New Delhi	Green David	Green Melbourne	Green Ireland	Green Honolulu	Green Caracas	Violet Nizza	Violet Ankara	Light blue Palm beach
Blue Berna	Blue Baltico	Blue Anversa	Grey Oslo	Grey Amburgo	Grey Londra	Black Odessa		

## COLOUR ON REQUEST: METALLIC COLOURS

Metal Ice	Metal Silver	Metal Bronze	Metal Gold	Metal Lemon	Metal Red	Metal Sky Blue	Metal Blue	Metal Dust Grey
--------------	-----------------	-----------------	---------------	----------------	--------------	-------------------	---------------	--------------------



## GYNAECOLOGICAL AND DELIVERY BEDS



27501

Multilingual instructions:  
GB, FR, IT, ES, PT, DE, GR.

Standard leg holders



27503

Quality leg holders



27504

MADE IN ITALY



27510

- 27500 DELUXE GYN BED - quality leg holders
  - 27501 GYNAECOLOGY BED - standard leg holders
- Strong chrome-plated structure. Rectangular steel tube. Adjustable head and leg sections. Simulated leather, black colour, washable upholstery, self extinguishing. Load: 110 kg. Complete with s/s bowl Ø 31 cm and leg-holders.
- 26586 S/S BOWL Ø 31 cm - spare

- 27510 DELUXE DELIVERY BED - quality leg holders
- Same as 27500, but with three sections with independent controls and Trendelenburg position. Load: 110 kg.
- 27503 STANDARD LEG HOLDERS - couple - spare
  - 27504 QUALITY LEG HOLDERS - couple - spare
- Kit leg holders includes 2 leg-holders and arms.
- 27418 COUCH ROLL HOLDER

## 3- SECTION MULTIFUNCTIONAL AND GYNAECOLOGICAL BEDS



- 27502 3-SECTION MULTIFUNCTIONAL BED - blue
- 27505 3-SECTION GYNAECOLOGICAL BED - blue

Strong and stylish structure in oval tube 50x25 mm, painted with epoxy powder, metallic grey colour. The three sections top has high density padding, covered with washable, fire proof, leatherette material Class 1 IM. Back-rest and leg-rest section are fully adjustable by self mechanical system. Gynaecological bed is supplied with 2 foam padded leg holders and stainless steel bowl Ø 32 cm. Maximum load: 150 kg - Weight: 36 kg.

- 27508 STANDARD LEG HOLDER for 27505 - couple - spare
  - 27509 QUALITY LEG HOLDER for 27505 - couple - optional
- Kit leg holder, includes 2 leg-holders and arms.
- 27511 COUCH ROLL HOLDER for 27502-5
  - 27919 DESK with 2 drawers - 130x71xh 80 cm
- Strong structure in oval tube 40x20 painted with epoxy powder, metal grey colour. White work top with rubber edge and round corner.
- 27979 FOOT STOOL - 2 steps



## 3-SECTION DELIVERY BED WITH TRENDLENBURG



- 27538 3-SECTION DELIVERY BED - with Trendelenburg

- structure made of epoxy painted oval steel tube
- three sections with independent control and Trendelenburg position
- padding made of high density polyurethane foam, fireproof Class 1 IM
- covering made of washable, plastic material (leatherette) fireproof Class 1 IM
- adjustable rubber feet

Size: 181x60xh 80 cm  
Carton size: 75x20xh 196 cm.  
Maximum load: 150 kg.

Net weight: 43 kg.

Supplied with a pair of height-adjustable, padded, anatomic leg-holders, a couple of shoulder rests, handgrips, a paper roll holder and a stainless steel basin Ø 32 cm. Delivered in kit form.

- 27509 QUALITY LEG HOLDER - couple - spare

MADE IN ITALY

## DONOR ARMCHAIR

- 27557 DONOR ARMCHAIR - blue - mechanical
- 27563 DONOR ARMCHAIR - blue - electrical
- 27567 DONOR ARMCHAIR WITH WHEELS - white

Strong and stylish armchair with structure made of oval, round and square metal tubing fully coated with white epoxy powder (legs oval tubing 50x25x1.5 cm; central frame square tubing 30x30x1.5 cm, cushions round tubing 20xØ 1.5 cm). High density polyurethane foam platform with wooden base covered by leatherette upholstery.

Flame resistant materials Class 1 IM.

Synchronized adjustment of the two cushions by a gas spring, cylinder/piston, (27557, 27567) or by a linear actuator (27563) with a push-button panel, allow a quick moving into TR/RTR position. Backrest inclination from +60° to -5° in Trendelenburg position, leg rest from -80° to +5°.


Reclinable arm-rests can be height adjusted or rotated up to 180° when removed.

Four adjustable feet ensure maximum stability (27557 and 27563) or 4 castors, 2 with directional brake (27567) ensure mobility. Load: 150 kg. Size: 175x55xh 51 cm.

- 27553 IV STAND

- 27556 COUCH ROLL HOLDER

Other colours available in 20 days, see below:



27557

White ral colour 9003 structure, minimum thickness 70/80 micron. Glossy finish.



WITH WHEELS



27567



MADE IN ITALY



27563

## DONOR WHEELCHAIR

- 27561 DONOR WHEELCHAIR

Donor wheelchair with structure made of epoxy painted oval and round steel tube.

Backrest adjustable by gas pump.

Padded leg rest manually adjustable.

Metal footrest extractable. Armrest with articulations, manually adjustable in height.

Padding made of high-density polyurethane foam, fireproof Class 1 IM. Covering made of washable, plastic material (leatherette), fireproof Class 1 IM.

Back push handle.

Mattress overall size: 166x55 cm. Carton size: 185x67xh 58 cm

Four wheels Ø 100 mm, 2 directional and 2 with brake.

Net weight: 53 kg. Gross weight: 55 kg. Maximum load: 150 kg.

Supplied with blanket tray with belts to fix oxygen bottle, IV stand and chart holder support.



Chart holder support



MADE IN ITALY



27561

Blanket tray with belts to fix oxygen bottle (bottle not included)

## HEIGHT ADJUSTABLE GYNAECOLOGICAL BED

- 27506 HEIGHT ADJUSTABLE GYN BED - green
- 27507 HEIGHT ADJUSTABLE GYN BED - blue
- 27496 HEIGHT ADJUSTABLE GYN BED - any colour\*

\*Available in 20 days, see below available colours

Strong and solid structure in oval tube 50x25x2 mm painted with epoxy powder, white colour.

The three sections top has high density padding, covered with washable, fire proof, leatherette material Class 1 IM.

Full adjustable

Height, up to 95 cm, is adjustable by electric engine

(6000 N power) with foot control, head section is

adjusted by a gas cylinder (400 N power), central

section by a gas cylinder (600 N power) up to 65°.


This gyn bed is supplied with 2 quality foam leg holders, stainless steel tray and couch roll holder.

Maximum load: 150 kg. Weight: 70 kg.

- 27509 QUALITY LEG HOLDER - couple - spare

Kit leg holder includes 2 leg holder and arms.

Suitable for 27496, 27505, 27506, 27507.




27506

Size: 195 x 60 x h 48/95 cm




## ENT CHAIRS



- 27545 NEW OTO/PV ENT CHAIR with headrest - colour on request\*
  - 27548 NEW OTO/PV ENT CHAIR with headrest - green Melbourne
  - 27549 NEW OTO/PV ENT CHAIR with headrest - light blue Parigi
- Patient chair with Peltex-lined seat and backrest. Electric up and down movements by silent engine controlled through foot switch. Back-rest can be adjusted up to  $-5^{\circ}$   $+90^{\circ}$  by a gas spring. Chair rotates  $360^{\circ}$  and is provided with a rotation locking device placed at the bottom. Power: 230 V - 50 Hz (Available 110 V - 60 Hz).

- 27550 OTOPEX ENT CHAIR with headrest - colour on request\*
  - 27551 OTOPEX ENT CHAIR with headrest - blue Chicago
  - 27552 OTOPEX ENT CHAIR with headrest - green Toronto
- ENT chair designed also for ambulatory operations. Moved by very silent electrical engines operated by joystick foot-control. Also provided with button to re-set to previously selected working position. Upholstery made of simulated leather, high density undeformable foam padding ( $50 \text{ kg/cm}^3$ ). Seat and leg-rest are joined in a single piece. Power: 230 V - 50 Hz (Available 110 V - 60 Hz).

## ENT CABINETS




## • 27540 OTOPLUS - ENT UNIT

The E.N.T. unit has rubber pivoting castors, a working surface made of scratch-proof rolled sections, 2 small and one large drawers provided of removable internal partitions, one drawer with inside germicidal lamps to keep instrument sterilization. Otoplus is provided with a silent suction pump of 34 l/min, with power supply complete with dim adjustment device for Clar/Storz lamp, larynx-mirror warmer, twin-cylinder dry compressor for tubal insufflation, 2-litres distilled water tank with acoustic signal for reserve level. The articulated arm with instrument holding tray is complete with terminal suction cannula and terminal insufflation cannula, ear rinsing syringe with automatic water temperature control, (a microprocessor keeps temperature at a constant level of  $37^{\circ}\text{C}$ ). Power 230 V - 50 Hz (Available 110 V - 60 Hz).

## • 27539 OTOPLUS COMPLETE

Same as code 27540 with vasister drawers (code 27541) and endoscope support (code 27543) included.



## • 27554 OTOPLUS DC ENT UNIT

Otoplus unit with column for diagnostic equipment (light source, camera or printer) and a support pole for monitor.

## • 27555 OTOPLUS DC ENT UNIT - complete

Same as code 27554 with hopper frame drawers (code 27541) and endoscope support (code 27543) included.

## • 27541 HOPPER FRAME DRAWERS - 2 independent drawers

## • 27543 ENDOSCOPE SUPPORT - 2 transparent plastic tubes

1 tube 50 cm long and 1 tube 25 cm long both closed at the bottom.


## • 27542 SYRINGE MEDICATION KIT including 1 syringe, 2 atomizers (1 for liquid and 1 for powder) and 3 ampoules in dark glass. To be ordered with ENT unit, should be installed at factory.

## • 28239 FILTER - spare for 27539, 27540, 27554-5

## • 27544 LED LIGHT SOURCE

Makes cold white light ( $5500^{\circ}\text{K}$ , 200 lumen) for endoscopy use.


It can be connected to endoscopes without need of F.O. cable. Handle connect directly to rigid endoscopes (Storz connection).



## ELECTRIC CHAIRS WITH FOOT CONTROL - 3 MOTORS



- 28040 CLEOPATRA ELECTRIC CHAIR - 3 motors - beige
  - 28041 CLEOPATRA ELECTRIC CHAIR - 3 motors - blue
- Electrically controlled 3 motors chair to adjust separately height, backrest and seat inclination by foot switch or push button panel. Footrest adjustable by gas lift pump. Reversible arms and adjustable headrest. Cushion included. Operating power: 100-240 V - 50/60 Hz. Manual: GB, FR, IT, ES.
- 28013 COUCH ROLL HOLDER - optional
  - 28014 REMOTE HANDLE CONTROL - optional
  - 45232 STOOL - blue
  - 45242 STOOL WITH BACKREST - blue
  - 45234 STOOL - beige
  - 45244 STOOL WITH BACKREST - beige



- 28046 NEFERTITI ELECTRIC CHAIR - 3 motors - white
- Electrical chair with very stable structure and high comfort. Specially designed to optimize the workspace due to 240° rotation. 3 motors control height, backrest and seat inclination by foot switch or push button panel. Footrest adjustable by gas lift pump, reversible arms and adjustable headrest. Operating power: 220-240 V - 50/60 Hz. Manual: GB, FR, IT, ES.
- 28013 COUCH ROLL HOLDER - optional
  - 45231 STOOL - white
  - 45241 STOOL WITH BACKREST - white

## MECHANICAL CHAIR



Manual: GB, FR, IT, ES

- 28005 LUXOR CHAIR - mechanical - white
  - 28006 LUXOR CHAIR - mechanical - blue
- Chair can move up and down and rotate 360°. Backrest and footrest are adjustable. Removable armrests.
- STOOLS**
- 45231 STOOL - white
  - 45232 STOOL - blue
  - 45241 STOOL - white
  - 45242 STOOL - blue

## ELECTRIC CHAIR- 2 MOTORS



- 28008 AMIRA CHAIR - 2 motors - white
  - 28009 AMIRA CHAIR - 2 motors - blue
- Electrically controlled chair to adjust separately height and backrest. Manual adjustment of angle of the seat inclination and footrest. Supplied with cushion. Manual: GB, FR, IT, ES.
- STOOLS**
- 45231 STOOL - white
  - 45232 STOOL - blue
  - 45241 STOOL - white
  - 45242 STOOL - blue



## ELECTRIC CHAIRS WITH FOOT CONTROL - 4 MOTORS




Size: 185x88xh 63-90 cm  
Net weight: 98 kg  
Max load: 175 kg

28048

- 28047 SABA ELECTRIC CHAIR - 4 motors - white
  - 28048 SABA ELECTRIC CHAIR - 4 motors - dark blue
- Electrically controlled 4 motors chair to adjust separately angle of the backrest, seat inclination, footrest and lifting of the whole chair. Hand controller and built-in foot controller which allow operator to adjust chair. High-grade upholstery leather easy to clean and fresh feeling. Headrest with face hole. Supplied with removable cushion and remote controller. Metal base for high stability. Operating power: 100-240V - 50/60Hz. Manual: GB, FR, IT, ES.
- 28013 COUCH ROLL HOLDER - optional
  - 45231 STOOL - white
  - 45235 STOOL - dark blue
  - 45241 STOOL WITH BACKREST - white
  - 45245 STOOL WITH BACKREST - dark blue



45235



## PODOLOGY CHAIRS

Size: 186x86xh 58-89 cm  
Net/Gross weight: 72/92 kg  
Max load: 175 kg  
Operating power: 220-240 V - 50/60 Hz.



45232

- 28025 ELECTRIC PODOLOGY CHAIR - 3 motors - blue
- Electrically controlled chair to independently adjust height, backrest and seat inclination, by foot switch or push button panel. Headrest can be inclined, arm rests are movable. Manual: GB, IT.
- 28013 COUCH ROLL HOLDER
  - 45232 STOOL - blue
  - 45242 STOOL WITH BACKREST - blue

Size: 180x80xh 51-65 cm  
Net weight: 41 kg  
Max load: 175 kg




28020

- 28020 PODOLOGY CHAIR - mechanical - white
- This chair can move up and down and rotate. Backrest and footrests are adjustable. Heavy round base provides maximum stability. Manual: GB, IT.
- 45231 STOOL - white
  - 45241 STOOL WITH BACKREST - white

## PODOLOGICAL CABINETS

- 28030 GAMMA1 CABINET - 61x45xh 77 cm - small
  - 28031 GAMMA3 CABINET - 108x45xh 77 cm - large
- Equipped with tabletop in scratch-resistant wood, drawers and doors, designed to keep tools sterile. Supplied with connections to the mains: germicide compartment, lampholder and other electric sockets. Power supply: 220 V - 50/60 Hz.

	Cabinet		Table top		Germicide compartment	Large compartment
	28030	28031	28030	28031		
Length:	61 cm	108 cm	61 cm	108 cm	28 cm	28 cm
Width:	45 cm	45 cm	42 cm	42 cm	38 cm	28 cm
Height:	77 cm	77 cm			4 cm	15 cm



28030

28031

## GIMA ADJUSTABLE HEIGHT ELECTRIC TABLES - FOOTSWITCH

Sturdy and highly stable examination and treatment table with white metal painted frame. Adjustable height by electric footswitch.  
Fixed leg-section and manually adjustable head-section with mouth-nose hole.

Available in 12 colours. Fireproof padding.

Class I Medical Devices, complies with MDR 2017/745.

Lifting capacity: 135 kg. Length: 193 cm. Weight: 54 kg.

Power supply 100-240 V, 50-60 Hz.

Multilingual manual: GB, FR, IT, ES, PT, DE, GR.

Matching stools see page 181.

ADJUST. HEIGHT ELECTRIC TABLE - FOOTSWITCH				
Electric table		Colour	No.	Mouth-nose hole plug - optional
27628	Electric table - footswitch	green	4	27625
27633	Electric table - footswitch	blue	2	27631
27634	Electric table - footswitch	beige	5	27620
27635	Electric table - footswitch	black	1	27621
27632	Electric table - footswitch	any colour*	other	27630

\*Available in 20 days, see beside available colours

ACCESSORIES	
27629	Couch roll holder
27650	Foot Switch - spare



## GIMA ADJUSTABLE HEIGHT ELECTRIC TABLES - FOOTBAR

Sturdy and highly stable examination and treatment table.

Adjustable height by electric footbar.

Adjustable head-section by gas pump with mouth-nose hole.

Sturdy tubular steel frame painted with non-toxic epoxy powder, RAL 9010. Chromed footbar. Intended for professional use in hospitals, physiotherapy, treatments. Supplied with 6 cm thickness mattress and mouth-nose hole plug 23x11 cm included.

Fireproof padding. Available in 12 colours.

Class I, Medical Devices, complies with MDR 2017/745.

Maximum overall dimensions 195x59,5xh 54-71 cm.

Weight: 65 kg. Lifting capacity: 135 kg.

Multilingual manual: GB, FR, IT, ES, PT, DE, GR.

ADJUST. HEIGHT ELECTRIC TABLE - FOOTBAR			
Electric table		Colour	No.
44520	Electric table - footbar	blue	2
44521	Electric table - footbar	beige	5
44522	Electric table - footbar	black	1
44525	Electric table - footbar	any colour*	other

\*Available in 20 days, see beside available colours

ACCESSORIES	
27629	Couch roll holder



## VARIABLE HEIGHT EXAMINATION COUCH WITH TR/RTR

• 44510 LORD VARIABLE HEIGHT EXAMINATION COUCH - water green - 5

• 44516 LORD VARIABLE HEIGHT EXAMINATION COUCH - any colour\*

\*available in 20 days, see below available colours

Stable and sturdy examination couch made of high quality tubular for furniture. Very practical and user friendly. Height adjustable thanks to the two electrical columns that can move simultaneously or separately (allowing the Trendelenburg/Reverse Trendelenburg position) by a push-button panel.

Under the top frame, an ergonomic lever activates a gas spring that reclines the cushions. High density, rubber padded, fire retardant and Class 1 IM top, covered in coated fabric (vinyl, synthetic leather, flame retardant Class 1 IM).

It can be cleaned with common detergents.

Complies with: EU 93/42 CEE. Maximum load: 200 kg.

Supplied with mouth/nose hole plug, paper roll holder and 4 adjustable feet.

• 44505 RETRACTABLE/REMOVABLE/TURNABLE WHEELS





# ELECTRIC OR HYDRAULIC HEIGHT-ADJUSTABLE TABLES



**BRUXELLES TABLES - electric or hydraulic**  
Examination and treatment table with high stability. Electric height adjustment by a foot-switch (low tension 24 V) or manual by hydraulic piston. One mobile section, gas-spring supported adjustment of the head-section (with mouth-nose hole) and fixed leg-section. The large head-section can be adjusted positively and negatively and serves as back-rest. Sturdy frame with all moving parts having self-lubricating components to avoid early wear and noise. Power 230 V - 50/60 Hz.

**WIDTH  
80 cm**



Standard 68 cm	Large 80 cm	BRUXELLES TABLES	SWL (Safe Working Load)
27587	27595	Electric - any colour**	200 kg
27588	27593	Electric - blue	200 kg
27589	27596	Hydraulic - any colour**	250 kg
27586	-	Hydraulic - blue	250 kg

\*\*Available in 30 days



**THER TRENDLENBURG TABLES - electric or hydraulic**  
Examination and treatment tables with electric height adjustment by a foot switch (low tension 24 V) or hydraulic height adjustment by a piston.

Features: three mobile sections adjustable by gas spring. The table can easily assume the "flexion", "relax" and "Trendelenburg" position even if the patient is lying on the table.

The large head-section (with mouth-nose hole) can be adjusted positively and negatively. Chair position. Power 230 V - 50/60 Hz.

Supplied with mouth-nose hole plug.

GIMA code	THER TRENDLENBURG TABLES	SWL (Safe Working Load)
27602	Electric - any colour**	200 kg
27603	Electric - blue	200 kg
27599	Electric with armrests - blue	200 kg
27604	Hydraulic - any colour**	250 kg

\*\*Available in 30 days



**SINTHESI MI.TO TABLES - electric**

Two-motor examination and treatment tables, electric height adjustment by foot rail or a low voltage (24 V) foot switch. The couches have six or eight sections: the trunk section can be electrically adjusted by the operator with no effort, using the keyboard behind the head of the table, while the patient undergoes a treatment; other sections can be adjusted by one or more gas springs system. The head section is equipped with an elongated breathing hole for a higher comfort. It's a dedicated therapy table for the myofascial release techniques and postural analysis. Wide range of possible positions in flexion/extension, symmetrical or asymmetrical. Power 230 V - 50/60 Hz. Supplied with mouth-nose hole plug and postural education exercises manual.

GIMA code	SINTHESI MI.TO. TABLES	Sections	SWL*	Height adjustment
27578	Electric - blue	6	180 kg	foot switch
27579	Electric - any colour**	6	180 kg	foot switch
27581	Electric - any colour**	6	180 kg	foot rail
27583	Electric with armrest - any colour**	8	180 kg	foot switch

\*SWL: Safe Working Load

\*\*Available in 30 days



**Upholstery  
colour code**

**TABLES  
AVAILABLE IN  
24 COLOURS**

A	N	8	4	B	Z	G	F	9
H	S	T	6	E	R	1	2	Q
3	L	7	K	M	P			

GIMA code	ACCESSORIES FOR ALL TABLES
27591	Wheels set Ø 6.5 cm*** - retractable
27594	Mouth-nose hole plug - any colour** for Bruxelles tables
27590	Couch roll holder for rolls 50 to 63 cm for Bruxelles and Ther tables
27592	Couch roll holder for rolls 50 to 68 cm for Sinthesi tables

\*\*Available in 30 days

\*\*\*Optional wheels set to be ordered with table

## 2 SECTION EXAMINATION COUCHES - CHROMED AND STAINLESS STEEL

- 44461 CHROME PLATED EXAMINATION COUCH
- 44463 STAINLESS STEEL EXAMINATION COUCH

MADE IN ITALY

Structure made of chrome plated steel (44461) or stainless steel (44463) tube Ø 25x25 mm.

Backrest adjustable by rack.

Padding and covering made of washable, flame retardant, plastic material. Rubber feet.

Supplied with a paper roll holder, which can be placed either in the front or in the back part of the examination couch.

Fireproof padding and covering, Class 1 IM.

Dimension: 177x60xh 75 cm.

Weight: 25kg

Delivered disassembled.



## KING HEIGHT ADJUSTABLE EXAMINATION COUCH

- 27613 KING HEIGHT ADJUSTABLE EXAMINATION COUCH - blue - 9
- 27612 KING HEIGHT ADJUSTABLE EXAMINATION COUCH - any colour\*

\*available in 30-40 days, see below available colours

Height adjustable (48-95 cm) examination couch by electric actuator (Linak engine 6.000 N) controlled by foot switch with head section easily adjustable (to +60° and -10°) by a gas pump. Strong and stylish leg structure in oval tubing 50x25x2 mm, central frame in rectangular tubing 50x20x1.5 mm painted with RAL 9003 white epoxy powder.

Minimum thickness 70/80 micron, glossy finish.

High density polyurethane foam platform with wooden base covered by leatherette upholstery.

Both materials are fireproof Class 1 IM.

Leatherette washable with the most common detergents. Size: 190x60xh 48/95 cm

Weight: 70 kg

Maximum load: 150 kg.

Couch roll holder included.



## SUN 2-SECTION VARIABLE HEIGHT TREATMENT COUCH

- 44530 SUN 2-SECTION VARIABLE HEIGHT TREATMENT COUCH - orange - 3
- 44536 SUN 2-SECTION VARIABLE HEIGHT TREATMENT COUCH - any colour\*

\*available in 20 days, see below available colours

Couch made in high quality tubular that makes it very sturdy.

The cushions can be reclined by a gas spring activated by an ergonomic lever under the top frame.

Head section movable to +45° and to -30°.

Height adjustable thanks to the two electrical columns by a push-button panel.

High density, rubber padded, fire retardant and Class 1 IM top, covered in flame retardant Class 1 IM coated fabric (synthetic leather).

Washable and disinfected with common detergents.

Overall size: 195x68xh 48/89 cm. Weight: 80 kg.

Complies with: EU 93/42 CEE.

Maximum load: 200 kg.

Supplied with mouth/nose hole plug, paper roll holder, 2 adjustable armrests and 4 adjustable feet.

- 44505 RETRACTABLE/REMOVABLE WHEELS


- 44540 WEDGE CUSHION 50x50xh 15 cm - orange

- 44545 WEDGE CUSHION 50x50xh 15 cm - any colour\*

- 44550 SEMI-CYLINDRICAL CUSHION 20x50xh 10 cm - orange

- 44555 SEMI-CYLINDRICAL CUSHION 20x50xh 10 cm - any colour\*

\*Available in 20 days, see below available colours





## KING EXAMINATION COUCH

### KING EXAMINATION COUCH

Strong and stilish structure in oval tube 50x25 mm painted with metallic grey epoxy powder.

Top in washable, fire proof, leatherette material class 1 IM with high density padding. Head section adjustable by mechanical system, maximum 75°.

Mattress thickness: 4.5 cm

Size: 190x60xh 80 cm. Maximum load: 150 kg.

Delivered in kit form.

GIMA Code	KING EXAMINATION COUCH
27614	King examination couch - water green - 5
27615	King examination couch - white - 7
27616	King examination couch - blue - 9
27617	King examination couch - black - 6
44486	King examination couch - any colour*
KING EXAMINATION COUCH WITH HOLE	
27618	King examination couch - green
27619	King examination couch - white

\*available in 20 days, see below available colours



27978

27979

ACCESSORIES	
27511	Couch roll holder
27978	Foot stool - 1 step
27979	Foot stool - 2 steps



27616



MADE IN ITALY



27619

WIDTH: 60 cm

MAX LOAD 150 kg



## KING PLUS EXAMINATION COUCH


• 44490 KING PLUS EXAMINATION COUCH - blue - 9

• 44491 KING PLUS EXAMINATION COUCH - beige - 2

• 44496 KING PLUS EXAMINATION COUCH - any colour\*

\*available in 20 days, see below available colours

Same as King examination couch, but with extra thick 7 cm mattress with lateral white band




Yellow Beige Orange Red Water green



Black White Lilac Blue Green



44490



44491

MAX LOAD 150 kg

MADE IN ITALY

## ELITE EXAMINATION COUCH

• 44500 ELITE EXAMINATION COUCH - blue - 9

• 44503 ELITE EXAMINATION COUCH - any colour\*

\*available in 20 days, see below available colours

Stylish, comfortable and innovative examination couch available in 10 colours with lateral white band.

Realized with high quality furniture tubing that guarantees stability and robustness.

The couch is made with rectangular and rounded tubing, Uni 7947/81 and 8913, DIN 2394.

Fireproof rubber padding covered with class 1 IM fireproof woven imitation leather.

Adjustable head section through 2 cogwheels.

The roll holder, included, can be placed in the feet or in the head side. 4 adjustable feet.

Size 193x68xh 78 cm. Padding size 190x68xh 7 cm.

Max. load 200 kg. Weight 70 kg.

Disassembled, very simple to assemble.

• 44505 RETRACTABLE/REMOVABLE/TURNABLE WHEELS



LOAD 200 KG



44503

MADE IN ITALY

## COUCH PAPER ROLLS

### COUCH PAPER ROLLS


A complete range of hygienic and resistant couch paper manufactured in Italy in pure cellucotton or cellucotton/polythene. Each roll is individually packed in plastic bag for best protection. Atoxic. Available with standard 38 or 40 cm perforation or 190 cm perforation (full person size).

#### • 27418 COUCH ROLL HOLDER

Adjustable roll holder suitable for round (Ø 27-30 mm) or square (27-30 mm x 27-30 mm) metal couch leg.

MADE IN ITALY

OTHER SIZES OF COUCH ROLL PAPERS  
AVAILABLE ON REQUEST



### COUCH PAPER ROLLS

MATERIAL	Cellucotton embossed		Microembossed glued mikrogeprägt verleint - gaufré collé						Pure wadding of cellulose ply coated with a polythene protection		
	27410	27411	27412	27424	27427	27428	27432	27419	27414	27413	27415
Colour	white	white	white	white	white	white	white	white	light blue	white	white
Ply	1 ply	2 ply	2 ply	2 ply	2 ply	2 ply	2 ply	2 ply	14 g/m <sup>2</sup> polyth.	14 g/m <sup>2</sup> polyth.	8 g/m <sup>2</sup> polyth
Weight	30 g/m <sup>2</sup>	2x20 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	2x17 g/m <sup>2</sup>	26/28 g/m <sup>2</sup>	26/28 g/m <sup>2</sup>	26/28 g/m <sup>2</sup>
Length	95 m	47.5 m	46 m	50 m	100 m	50 m	80 m	80 m	50 m	50 m	50 m
Height	50 cm	59 cm	50 cm	50 cm	50 cm	59 cm	59 cm	59 cm	50 cm	50 cm	60 cm
Number of sheet	250	125	135	132	263	132	210	42	132	132	125
Perforation	38 cm	38 cm	34 cm	38 cm	38 cm	38 cm	38 cm	190 cm	38 cm	38 cm	40 cm
Rolls per box	6	6	9	9	6	9	6	6	6	6	6

## SUITCASE COUCH

MADE IN ITALY



Couch size:  
187.5x64xh 71 cm (open)  
93x68xh 14 cm (folded)

• **27407 SUITCASE COUCH - black**  
Chromed steel and folding legs.  
Upholstered covering in washable material. Resin padded.  
Max load: 100 kg.  
Weight: 16.5 kg  
Supplied with a velvet bag for easy transport.  
Packing: 95x18x73.5 cm  
Manual: GB, IT, NL.

## ALUMINIUM SUITCASE COUCH

MADE IN ITALY




Manual: GB, FR, IT, ES, PT, DE, GR.



27406

• **27406 ALUMINIUM SUITCASE COUCH with hole**  
Light, foldable, two sections, suitcase couch with aluminium frame. Central double legs for improved safety and block system on the hinges.  
Head rest with mouth/nose hole.  
Upholstered and covered with simulated leather.  
Max load: 100 kg.  
Weight: 13 kg.  
Packing: 94x21.5x66.5 cm





## VALUE EXAMINATION COUCHES

- 44452 VALUE EXAMINATION COUCH - white painted - black
- 44453 VALUE EXAMINATION COUCH - white painted - white
- 44457 VALUE EXAMINATION COUCH - chrome - blue
- 44458 VALUE EXAMINATION COUCH - chrome - beige

Suitable for medical practices or small surgeries.

Top is made with wooden panel, foam rubber and covered with washable, fireproof simulated leather Class 1.

Two sections: one fixed 131x62xh 6 cm and one adjustable (backrest) 51x62xh 6 cm.

Couch size: 182x62xh 79 cm. Weight 27 kg.

Maximum load: 120 kg.

**Delivered in kit form:** 173x74xh 16 cm. Easy to assemble.

Multilanguage manual (GB, FR, IT, ES, PT, DE).

- 27418 COUCH ROLL HOLDER - optional

**STOOLS:** see at page 181




44453



44457



44458



44452

## EXAMINATION COUCHES

- 27401 EXAMINATION COUCH - chromed - black
- 27402 EXAMINATION COUCH - white painted - grey
- 27444 EXAMINATION COUCH - white painted - green

**STOOLS:** see matching stools page 181

Suitable for medical office or small surgeries.

Easy to assemble, following enclosed instructions (GB, FR, IT, ES, PT, DE, SE).

Comes complete with mattress.

Upholstery in two sections:

one 131x62xh 6 cm fixed

and a 51x62xh 6 cm backrest

adjustable through different positions.


Load: 120 kg.

Net weight 26.4 kg

**Delivered in kit form** (173x16x74 cm).

- 27418 COUCH ROLL HOLDER

Adjustable roll holder suitable for round (Ø 27-40 mm) or square (25x25 to 35x35 mm) metal couch leg.



27401

27402

- 27404 CLASSIC EXAMINATION COUCH - chromed - beige
- 27405 CLASSIC EXAMINATION COUCH - chromed - blue- backrest with hole
- 27445 CLASSIC EXAMINATION COUCH - chromed - apricot

Chromed mainframe and legs constructed in chrome-plated steel.

Legs fitted with plastic feet.

The two-section top has resilient foam padding covered with washable and fire-proof plastic material.

Backrest fully adjustable.

Available in beige, blue, apricot colour.

Other colours on request, minimum 10 pieces.

Size: 180x57xh 73 cm.


Maximum load 120 kg.

**Delivered in kit form** (198x17x64 cm).

Instructions: GB, FR, IT, ES, PT, DE, GR.

- 27408 MOUTH-NOSE HOLE PLUG 23x12xh 6 cm for 27405 - blue

**STOOLS:** see matching stools page 181



27405

27404

MADE IN ITALY


## EXAMINATION AND TREATMENT TABLE - HIGH LOAD

- 27622 STANDARD TREATMENT TABLE - any colour\*
- 27623 STANDARD TREATMENT TABLE - blue
- 27624 STANDARD TREATMENT TABLE - cream
- 27626 LARGE TREATMENT TABLE - any colour\*
- 27627 LARGE TREATMENT TABLE - blue

Professional examination and treatment table with one movable section and manual adjustment. Sturdy detachable metal structure painted with scratch-proof, non corrosive epoxy powder. The section trim facilitates reaching the patient. Head section with mouth-nose hole. Multilingual manual: GB, FR, IT, ES, PT, DE, GR.

- 27629 COUCH ROLL HOLDER
- 27630 MOUTH-NOSE PLUG - any colour\*
- 27631 MOUTH-NOSE PLUG - blue
- 27620 MOUTH-NOSE PLUG - cream

\*available in 30 days



27631




27629

**STD TABLE:**  
width 68 cm  
max load 180 kg



27622

High-density foam padding. Superior cover finish made of high-quality fireproof simulated leather. Vinyl is resistant to disinfectants, urine, and blood.



27627

**LARGE TABLE:**  
width 80 cm  
max load 200 kg

**AVAILABLE IN 6 COLORS**



- 1 Black
- 2 Blue
- 3 Grey
- 4 Green
- 5 Cream
- 6 Apricot

MADE IN ITALY

## WOODEN COUCHES

### WOODEN COUCHES

Comfortable couches, ideal for physical therapy, esthetics and wellness centres. Superior quality wood. Back rest adjustable in 13 positions. Resilient foam padding covered with washable skay. Padding in beige colour. Size: 190x70xh 75 cm.



27416

Directional wheels

27443



27417+27409

**MAXIMUM COUCH LOAD: 200 KG**

Mouth nose hole plug included.  
Average hole Ø 14 cm

Delivered in kit form. Easy assembly, tool provided. Couch roll holder included only with 27450 and 27451 can be hung on back or front.



27451

Backrest adjustable in 13 positions



27452

Size: 50x40xh 77 cm  
Shelf load: 20 kg each

**MAXIMUM COUCH LOAD: 250 KG**



27450


MADE IN ITALY

- 27416 WOODEN COUCH - beech
- 27417 WOODEN COUCH - with face hole - beech
- 27443 DANTE WOODEN TROLLEY - beech
- 27409 COUCH ROLL HOLDER for 27416 and 27417

- 27450 FIRENZE WOODEN COUCH - wenge
- 27451 FIRENZE WOODEN COUCH - with face hole - cherry wood
- 27452 DANTE WOODEN TROLLEY - cherry wood



## FOLDABLE MASSAGE TABLE - WOOD OR ALUMINIUM



WOODEN 2-SECTIONS

44003



WOODEN 3-SECTIONS

44011



ALUMINIUM 2-SECTIONS

44024



27421

- 44000 2-SECTION WOODEN MASSAGE TABLE - black
- 44001 2-SECTION WOODEN MASSAGE TABLE - blue
- 44002 2-SECTION WOODEN MASSAGE TABLE - turquoise
- 44003 2-SECTION WOODEN MASSAGE TABLE - cream

Two-section foldable height adjustable massage table with German beech wood frame and PVC vinyl cover with 5 cm foam thickness.

Tables are supplied with headrest, hanged armrest, mouth-nose plug and carrying bag.

Product open size: 185x70xh 62/87 cm

Packing size: 95x20xh 75 cm

Net/Gross weight: 14/17 kg

Maximum working load: 200 kg (441 lbs)

Manual: GB, FR, IT, ES, PT, DE

Carrying bag for all tables



- 44011 3-SECTION WOODEN MASSAGE TABLE - blue
- 44013 3-SECTION WOODEN MASSAGE TABLE - cream

Three-section foldable height adjustable massage table with German beech wood frame and PVC vinyl cover with 5 cm foam thickness. Tables are supplied with headrest, armrests, hanged armrest, mouth-nose plug and carrying bag.

Product open size: 185x70xh 62/87 cm

Packing size: 95x20xh 75 cm

Net/Gross weight: 16/19 kg

Maximum working load:

220 kg (485 lbs)

Manual: GB, FR, IT, ES, PT, DE



- 44020 2-SECTION ALUMINIUM MASSAGE TABLE - black
- 44021 2-SECTION ALUMINIUM MASSAGE TABLE - blue
- 44024 2-SECTION ALUMINIUM MASSAGE TABLE - white

Two-section foldable, height adjustable massage table with aluminium frame and PVC vinyl cover with 5 cm thickness. Tables are supplied with headrest, side armrests, hanged armrest, mouth-nose plug and carrying bag.

Product open size: 186x70xh 59/80 cm

Packing size: 95x20xh 75 cm

Net/Gross weight: 13/16 kg

Maximum working load:

250 kg (551 lbs)

Manual: GB, FR, IT, ES, PT, DE



## MASSAGE BED WITH HOLE

- 27421 MASSAGE BED

Comfortable massage bed, with face hole and removable pillow. Ideal for physical therapy and wellness centres.

Adjustable back rest 0 to 45 degree

Supplied with couch roll holder and multilingual instructions (GB, FR, IT, ES).

Product size: 183x61x75 cm

Packing size: 188x17x66 cm

Net/Gross weight: 28/31 kg

Maximum load: 175 kg



## FOLDABLE MASSAGE CHAIR

- 44050 FOLDABLE MASSAGE CHAIR

Comfortable foldable massage chair ideal for physical therapy and wellness centres.

Made of PVC vinyl with 5-6 cm foam thickness Metal frame


Packing size: 106x27xh 50 cm

Net/Gross weight: 7/13 kg

Maximum working load: 120 kg



Folded massage chair



44050

## WING SCREEN WITH TREVIRA CURTAINS



45561 +  
3x45570

### SCREEN WITH TREVIRA CURTAINS

Build up the screen you need choosing among 4 frames and 6 colours of Trevira curtains.

#### Wing screen

Aluminium alloy tubular frame mounted on feet or castors (Ø 50 mm).

Size: 150xh 167.5 cm (45560)

150xh 174 cm (45561)


200xh 167.5 cm (4 wings)

Packing size: 176x57x13 cm (all wing screens)

**Trevira curtains** are flame-proof (Class I), antiallergic, avoid bacterial growth, waterproof and highly resistant to abrasion. Thick weft to avoid dust infiltration and improve privacy, washable up to 60°C.

Available in 6 colours to match any need. **Custom-made curtains available on request.**

Multilingual manual: GB, FR, IT.



Light blue

Blue

White

GIMA Code	WING SCREEN FRAME without curtain
45560	3 wing screen
45561	3 wing screen with castors
45562	4 wing screen
45563	4 wing screen with castors
GIMA code	CURTAINS* IN TREVIRA 45xh 129 cm
45570	Curtains - light blue
45571	Curtains - blue
45572	Curtains - white
45573	Curtains - beige
45574	Curtains - green
45575	Curtains - peach

\*you have to buy 3 or 4 curtains depending on frame you choose



MADE IN ITALY



Beige

Green

Peach

## 3 OR 4 WINGS SCREEN WITH PLASTIC CURTAINS



27970



27974

- 27970 3 WINGS SCREEN
  - 27971 3 WINGS SCREEN with castors
  - 27972 4 WINGS SCREEN
  - 27974 4 WINGS SCREEN with castors
- Aluminium alloy tubular frame.  
Weight 5 kg (3 wings), 8 kg (4 wings).  
Foldable washable white plastic curtains mounted on feet or castors (Ø 50 mm).  
Size: 150xh 170 cm - 3 wings (50 cm each)  
200xh 170 cm - 4 wings (50 cm each)

MADE IN ITALY

SEPARATION SYSTEMS AND CURTAINS see page 139

## 2 OR 3 WINGS WARD SCREENS WITH TREVIRA OR COTTON CURTAINS



45580

Height: 180 cm



45579

Width: 60+60+60 cm

Width: 60+60 cm

- 45578 2 WINGS SCREEN - white cotton cloth
  - 45579 2 WINGS SCREEN - light blue Trevira
  - 45580 3 WINGS SCREEN - white cotton cloth
  - 45581 3 WINGS SCREEN - light blue Trevira
- Exclusive 2 or 3 wings ward screens with sturdy structure in oval tube (30x15 mm), painted with epoxidic powder metal grey.  
Light blue Trevira curtains or white washable cotton cloth.  
Equipped with 4 adjustable feet that ensure increased stability.  
Class I Medical Device complying with European Directive 93/42

MADE IN ITALY



## CABINETS FOR MEDICINES AND INSTRUMENTS

CABINETS ARE  
SUPPLIED  
DISASSEMBLED

MADE IN ITALY



**27898**

Size: 52x35x138 cm  
Pack size: 65x26x134 cm  
Weight: 31 kg



**27899**

Size: 75x37x164 cm  
Pack size: 72x24x156 cm  
Weight: 45 kg



**27900**

Size: 75x37x164 cm  
Pack size: 72x24x156 cm  
Weight: 50 kg



**27902**

Size: 79x36x186 cm  
Pack size: 88x36x96 cm  
Weight: 56 kg

- **27898 VALUE CABINET - 1 door**
- **27899 VALUE CABINET - 2 doors**

Cabinets made of enamelled steel sheet with tempered glass doors. Hinged glass door with lock and key. Three stainless steel shelves adjustable in height. **Delivered in kit form.**

- **27900 VALUE CABINET - 4 doors (hinged)**
- **27902 VALUE CABINET - 4 doors (2 hinged, 2 sliding)**

Cabinets made of enamelled steel sheet with 2 overlapped compartments. Upper compartment with 2 tempered glass doors (hinged doors 27900 or sliding doors 27902), lock with key and 2 stainless steel, height adjustable shelves. Inferior compartment with 2 doors made of enamelled steel plate and 1 enamelled steel sheet shelf. **Delivered in kit form.**

## CABINETS WITH 1, 2, 4 DOORS AND WALL CABINETS

MADE IN ITALY



**27901**

**27905**

**27903**

Lower section  
with 1 steel shelf



**27912**

Hanging cabinet with 2 lockable doors. Inside division in 2 compartments left side with 2 removable shelves, right side with 1 removable shelf.



**27911**


Hanging cabinet to keep medicine with 2 glass tempered doors and 2 tempered glass shelves adjustable on master rack to be hung by two holes on the back. Supplied with lock.

**GIMA CABINETS** Choice of cabinets with epoxy coated steel structure and tempered glass. Rack-mounted adjustable glass shelves. Rubber feet.

TECHNICAL SPECIFICATIONS	27901	27905	27903	27911	27912
Door:	1	2	4	2	2
Adjustable glass shelves:	3	4	2	2	3
Weight kg:	30	47	45	16	18
Size cm:	53x36xh 144	75x38xh 169	75x38xh 169	60x30xh 60	80x33xh 45

- **27901 CABINET - 1 door**
- **27905 CABINET - 2 doors**
- **27903 CABINET - 4 doors**
- **27911 WALL CABINET - glass sliding door**
- **27912 WALL CABINET - painted door**

## DOCTOR CABINET



EN 60598-1  
EN 60598-2-4

**27990 STUDIO LIGHT - 100 W**  
Halogen lamp with aluminium tubular frame and flexible chromed steel arm. Plastic base Ø 60 cm with plastic wheels Ø 50mm (1 with brake). 220-240 V, 50-60 Hz. Lamp not included.

GIMA code	Product	Description	Size	Weight
27920	DESK - with 2 drawers	Desk with 2 side drawers with locking top drawer and enamelled tubular steel frame	120x70x78	31
27403	EXAMINATION COUCH	Single-hinged examination table with aluminium tubular frame. Comes complete with simulated leather mattress (grey), backrest adjustable through different positions max 45°. Delivered in kit form.	176x60x78	22
27989	COAT HANGER	Free-standing coat hanger with chromed steel frame with 8 knobs and umbrella holder		5
27990	LIGHT	Aluminium tubular frame with 5 spoke base on 50 mm castors. Adjustable height thanks to flexible arm. Lamp 100 W. (connection E27) not included. Not medical device.		3


## STACKABLE CHAIRS



- 45007 STACKABLE CHAIR - blue
  - 45008 STACKABLE CHAIR - grey
  - 45011 STACKABLE CHAIR with arms - blue
  - 45012 STACKABLE CHAIR with arms - grey
- Chromed steel frame, self-extinguishing plastic seat. Stackable up to 20 chairs. Weight 5 kg (45007-8), or 7 kg (45011-2). Self-extinguishing Class 1. Maximum load: 110 kg.

MADE IN ITALY

## CHAIRS



- 27932 CHAIR padded seat
  - 27933 CHAIR padded seat with armchairs
- Stainless steel white painted frame chair with grey padded seat and back. Stackable. Load 120 kg. Same as 27932 but with padded arm-rests.

MADE IN ITALY

## S/S WASTE BINS WITH PEDAL

- 27984 WASTE BIN 9.5 l - with pedal - Ø 25xh 35 cm
  - 27985 S/S WASTE BIN 9.5 l - with pedal - Ø 25xh 35 cm
  - 27986 S/S WASTE BIN 12 l with pedal - Ø 32xh 36 cm
  - 27983 S/S WASTE BIN 70 l with pedal - Ø 42xh 72 cm
- Made of enamelled steel with plastic inner bucket - weight: 2 kg  
Made of AISI 304 stainless steel with plastic inner bucket - weight: 2 kg  
Made of stainless steel AISI 430. Metal handle for easy emptying. Removable inner plastic bucket.  
Made of stainless steel. Non-slip rubber pedal.  
Two lateral handles avoid fingers pinching. Galvanized inner bucket with handle.



27984

27985

27986

27983



## DOCTOR CABINET



GIMA code	Product	Description	GIMA code	Product
45581	WING SCREEN Trevira curtain	3 wings screen with sturdy structure in oval tube, painted with epoxy powder metal grey. Light blue Trevira curtains. Curtains specifications see page	27616	KING EXAM. COUCH See page 172
45580	WING SCREEN	Same as above but with white washable cloth.	30723	ALFA-FLEX LIGHT See page 248
27921	TROLLEY	Structure in oval tube, painted with epoxy powder metal grey. White shelves with PVC edge, guard-rail on 3 sides. Size 50x60xh80 cm. Max load: 30 kg	27984	WASTE BIN See page 179
27987	COAT HANGER	Free standing coat hanger with 5 knobs, epoxy powder grey painted steel structure and umbrella holder.	45211	STOOL See page 181
			45082	CREMONA CHAIR See page 182

## DESK

### • 27919 DESK with 2 drawers

Desk with 2 lockable side drawers with strong structure in oval tube painted with epossidic powder, metal grey. White work top with rubber edge and round corner. Size 130x71xh 80 cm



27919

MADE IN ITALY

## DESK WITH SIDES

### • 27922 DESK with sides and 2 drawers

Desk with sides and 2 side drawers. First drawer is lockable. Anti-reflective white melamine structure and top. Desk top has ABS edges on 4 sides with rounded corners. Sides complete with adjustable feet. Desk size: 120x70xh 73 cm. Drawer size: 35x40x h 24 cm. Delivered disassembled.



27922

MADE IN ITALY

## FOOT STOOLS - 1 OR 2 STEPS

### • 27980 FOOT-STOOL - one step - aluminium

### • 27982 FOOT-STOOL - two steps - painted

Mounting steps with painted tubular frame and plastic foot board. Load 90 kg. Non slipping grey platform 40x20 cm. Size: 40x51xh 25 (27980), 40x53xh 44 (27982).

MADE IN ITALY

### • 27978 FOOT-STOOL - one step

### • 27979 FOOT-STOOL - two steps

Structure in oval tube 30x15 painted with epossidic powder. Non slipping black platform. Size: 45x26xh 20 cm (27978) 44x40xh 22/45 cm (27979) Maximum load: 100 kg

MADE IN ITALY

### • 27976 FOOT-STOOL - one step - disassembled

### • 27977 FOOT-STOOL - two steps - disassembled

Structure made of chrome plated steel tube with rubber feet. Load: 100 kg. Non slipping black plastic platform. Size: 40xh 24 cm (27976) 40xh 42 cm (27977) 45x27xh 9 cm (27976) 51x42xh 12 cm (27977)

MADE IN ITALY

27977



27980

27982



27978




27979



27976

DELIVERED DISASSEMBLED

## HEIGHT ADJUSTABLE STOOLS



- 27949 STOOL - feet
  - 27954 STOOL - castors
- Stainless steel seat AISI 304 Ø 32 cm. Height adjustable 45-64 cm (27949), 50-68 cm (27954).



- 27947 STOOL - feet
- Stainless steel seat AISI 304 Ø 32 cm. Height adjustable 46-65 cm. Aluminium base with feet.



- 27955 STOOL - grey
- Washable padded simulated leather seat Ø 31 cm. Height adjustable 48-67 cm. Plastic base with feet.



- 27956 STOOL - grey
- Washable padded simulated leather seat Ø 31 cm. Height adjustable 53-71 cm. Plastic base with 5 castors Ø 50 mm.

## HEIGHT ADJUSTABLE STOOLS



- 45230 STOOL - black
  - 45231 STOOL - white
  - 45232 STOOL - blue
  - 45234 STOOL - beige
  - 45235 STOOL - dark blue
- Padded simulated leather seat Ø 34 cm. Height adjust. 55 to 75 cm.
- 45228 CASTOR - spare

- 45240 STOOL - black
  - 45241 STOOL - white
  - 45242 STOOL - blue
  - 45244 STOOL - beige
- Padded simulated leather seat Ø 34 cm with backrest. Height adjustable 55 to 75 cm.
- 45228 CASTOR - spare

## ERGONOMIC HEIGHT ADJUST. STOOLS



- 45250 ERGO STOOL - black
  - 45251 ERGO STOOL - white
  - 45252 ERGO STOOL - blue
- Ergonomically designed comfortable stool with saddle-shaped seat and height adjustment with a gas piston. Height adjustable 52 to 67 cm.
- 45228 CASTOR - spare

- 45260 ERGO B STOOL - black
  - 45261 ERGO B STOOL - white
  - 45262 ERGO B STOOL - blue
- Ergonomically designed comfortable stool with saddle-shaped seat. Three levers with a gas piston allow adjustment of height, backrest angle and seat. Height adjustable 63 to 83 cm.
- 45228 CASTOR - spare



## OFFICE CHAIRS WITH OR WITHOUT ARMREST



45071

45070

45065

45075

45060

45076

Maximum  
load: 110 kg

Functional office upholstered chair, with armrests and polypropylene swivel base, movable backrest with permanent contact.

### CUNEO CHAIR without armrest

	Red	Grey	Black	Blue	Any colour*
Fabric	-	-	-	45060	45063
Leatherette	-	-	45065	-	45069

### CUNEO CHAIR with armrest

	Red	Grey	Black	Blue	Any colour*
Fabric	45070	45071	-	-	45073
Leatherette	-	-	45075	45076	45079

\*Available in 30 days. Minimum order 12 pieces.

Select colour on [www.gimaitaly.com](http://www.gimaitaly.com) and indicate with order

Weight	Backrest height	Seat height	Width	Depth
12 kg	98/111 cm	45/52 cm	56 cm	49 cm



45081

45082

45083

Superior quality chair with neat lines, upholstered seat and backrest for greater comfort, swivel base, armrests, permanent contact movement of the backrest.

High density foam.

UNI EN 1335/1/2/3. Maximum load: 110 kg.

### CREMONA CHAIR with armrest

	Red	Grey	Blue
Fabric	45083	45081	45082

Weight	Backrest height	Seat height	Width	Depth
12 kg	90/107 cm	45/52 cm	58 cm	44 cm



45091

45095

45092

45096

Quality chair with upholstered seat and backrest, permanent contact movement of backrest and swivel base. Maximum load: 110 kg. UNI EN 1335/1/2/3.

### VARESE CHAIR without armrest

	Red	Blue
Fabric	45091	45092

### VARESE CHAIR with armrest

	Red	Blue
Fabric	45095	45096

Weight	Backrest height	Seat height	Width	Depth
11.6 kg	94/112 cm	46/59 cm	60 cm	47 cm

## VISITOR CHAIRS



45030

45032

45036

45035

- 45030 ISO - fabric - red
- 45032 ISO - fabric - blue
- 45035 ISO - leatherette - black
- 45036 ISO - leatherette - blue

Comfortable upholstered chair with 4 legged frame.

Can be used for patient and waiting rooms, with Cuneo, Cremona and Varese chairs.

Comfortable seat made of expanded polyurethane hit injected heliocell foams. Maximum load: 110 kg.

Weight	Backrest height	Seat height	Width	Depth
7 kg	82 cm	45 cm	53 cm	43 cm

## EXECUTIVE CHAIRS



45110  
Back reclines  
from 0 to 30°

45110

### 45110 SIDNEY EXECUTIVE CHAIR


Stylish and comfort executive chairs with bracket to adjust height and back. Interwoven mesh cloth, skin friendly, smooth, breathable and easy to clean with plastic armrests.

Chair base Ø 58 cm with chromed plated frame. Five nylon 360° rotating castors.

### 45111 SIDNEY VISITOR CANTILEVER

Soft and comfortable foam seat. Back made of durable mesh, breathable fabric.

GIMA code	Backrest size	Seat height	Width	Depth
45110	49x48 cm	45/55 cm	48 cm	50 cm
45111	-	-	47 cm	43 cm



45124

45136

MADE IN ITALY 45128

Maximum load:  
110 kg

### ELITE EXECUTIVE CHAIR

Executive low-backed or high-backed armchair. Fabric or leatherette. Steel and chrome plated base and arms. Height adjustable by gas pump.

### ELITE low-backed chair - 83-93 cm

	Red	Black	Beige	Any colour*
Fabric	45124	-	-	45126
Leatherette	-	45127	45128	45132

### ELITE PLUS high-backed chair - 101-111 cm

	Red	Black	Beige	Any colour*
Leatherette	-	45136	-	45140

\*Available in 30 days. Minimum order 4 pieces.

Select colour on [www.gimaitaly.com](http://www.gimaitaly.com) and indicate with order

Weight	Backrest height**	Seat height	Width	Depth
15 or 16 kg***	83/93 cm	39/49 cm	51 cm	45 cm

\*\*Low-backed chair \*\*\*Low-backed 15 kg, high-backed 16 kg

## X-RAY ILLUMINATORS - LIGHT BOXES

MADE IN ITALY

### X-RAY ILLUMINATORS

GIMA light boxes are designed according to clinical standards for an extra white light for an accurate and precise reading of any detail. They incorporate a 3 mm acrylic screen compliant with safety norms (fuses, Schuko plug, green light On/Off, ...). Can be used on the table placed horizontally or vertically, depending on model or wall mounted. Body made of oven-fired epoxy powder coated aluminium and injected ABS (colour RAL 7035).


#### TECHNICAL SPECIFICATIONS

Colour temperature: Cool white 6,500 °K  
Power supply: 230 V - 50 Hz (60 Hz available with surcharge)  
Protection fuse: 2x1A  
Bipolar light switch  
Schuko plug with 2 m cable  
All components UL, DVE, IMQ approved



GIMA code	X-RAY ILLUMINATORS - LIGHT BOXES	External dimensions (cm)				Types
		Length	Height	Depth	Weight	
27364	Light box 38x38 cm	43	43	12	6	1 panel
27365	Light box 38x62 cm	67	43	12	8	1,5 panel
27366	Light box 38x92 cm	97	43	12	11	2 panels
27367	Light box 38x122 cm	127	43	12	14	3 panels
27368	Light box 38x153 cm	158	43	12	18	4 panels
27369	Light box 76x122 cm	127	2x43	12	28	2x3 panels
27370	Light box 76x153 cm	158	2x43	12	36	2x4 panels
27372	Light box 92x38 cm	43	97	12	11	2 panels vertical
27373	Light box 122x38 cm	43	127	12	14	3 panels vertical
27378	Neon tube for 27364					
27379	Neon tube for 27366, 27372					
27388	Neon tube for 27365					

## VALUE FOR MONEY LIGHT BOXES



GIMA X-ray illuminators have been designed according to clinical recommendations for an extra white light to give an accurate and precise reading of any detail. Made of enamelled sheet steel. Unbreakable white monochromatic diffuser, stainless steel gripping system. On/off switch for separate use of each panel for 44692.

MADE IN ITALY

GIMA code	X-RAY ILLUMINATORS - LIGHT BOXES	External dimensions (cm)				Types
		Length	Height	Depth	Weight	
44690	40x43 cm	43	46	14	6	1 panel
44692	80x43 cm	83	46	14	10	2 panels
44695	Round fluorescent light 32 W - spare					

## ILLUMINATED AND NOT ILLUMINATED OPTOMETRIC CHARTS

MADE IN ITALY



GIMA luminous optotypes have been designed according to clinical recommendations for an extra white light to give an accurate and precise reading of any detail.

Manufactured with acrylic screen, and according to safety norms (fuses, Schuko plug, green light On/Off,...)



OPTOMETRIC CHARTS	Illuminated GIMA code	Not illuminated GIMA code
Armagnac - 5 m	27380	27390
Monoyer - 3 m	27381	27391
Mixed decimal - 3m	27382*	27392*
Children - 3 m	27383	27393
Animals - 5 m	27384	-
Spare Tube 700	27388	-

#### TECHNICAL SPECIFICATIONS

Viewing Area: 24 x 62 cm 24 x 61 cm  
External dimensions: 29.5x67.5x12 cm 29 x 66 x 2.5 cm  
Weight: 6 kg 2 kg  
Power supply: 230 V - 50 Hz (60 Hz on request) only 27380-4  
Other specifications like X-ray illuminators 27364-72


**MONOYER** 3m • 27381  
**MIXED DECIMAL** 3m • 27382\*  
**ARMAGNAC** 5m • 27380  
**CHILDREN** 3m • 27383  
**ANIMALS** 5m • 27384

\*Not suitable for Portugal

See economic optometric charts at page 273



## LED ULTRA SLIM X-RAY ILLUMINATORS - DESKTOP AND WALL



### LED TECHNOLOGY SLIM X-RAY ILLUMINATORS

The new generation of LED X-ray illuminators with colour temperature of 7,200°K for superior viewing and reading of radiography. Complete elimination of light flickering and 5,000 cd/mq luminance for more uniform light diffusion. Frame in antiscratch anodized aluminium. Film gripping system incorporated. Dimmer for luminance adjustment from 30% to 100%. - FAS: automatic switching on/off at the positioning/removal of the film.

Economic advantages:

- LED life 80,000 hours, with low maintenance costs
- low energy consumption compliant with European law
- Double support for horizontal or vertical wall mounting or desktop.

#### Fully adjustable desktop model:

Position of panel can be totally adjusted:

- height adjustment 13 cm
- inclination 35° (+25°/-5°)
- vertical or horizontal positioning (44705 only)
- horizontal rotation 10° (270° for 44705 only)

GIMA code	WALL LED SLIM VIEWERS viewing area	External size - cm			Weight kg	Switches	Types
		Length	Height	Depth			
44700	Light box 42x36 cm	46	50.5	3.8	4	1	1 panel
44701	Light box 42x72 cm	82	50.5	3.8	8	1	2 panels
44702	Light box 42x108 cm	118	50.5	3.8	12	1	3 panels
44703	Light box 42x144 cm	154	50.5	3.8	16	1	4 panels
GIMA code	DESKTOP LED SLIM VIEWERS viewing area	External size - cm			Weight kg	Switches	Types
		Length	Height	Depth			
44705	Light box 42x36 cm x1	46x1	50.5	3.8	6	1	1 panel
44706	Light box 42x36 cm x2	46x2	50.5	3.8	20	2	2 panels
44707	Light box 42x36 cm x3	46x3	50.5	3.8	26	3	3 panels

#### TECHNICAL SPECIFICATIONS

Colour temperature: Cool white 7,200°K

Power supply: 110-230 V - 50/60 Hz

Conformity to Low Voltage Directive 2014/35/CE


Conformity to Electro Magnetic compatibility 2014/30/CE

Conformity to EEC directive 2007/47 medical Device Class I

All components UL, DVE, IMQ approved

Brightness: 5,000 cd/m<sup>2</sup>  
LED life: 80,000 hours

#### PANELS ADJUSTMENT




## LED ULTRA SLIM OPTOMETRIC CHARTS

### LED ULTRA SLIM OPTOMETRIC CHARTS

New generation of optometric charts with same specifications as above X-ray illuminators.

GIMA code	LED ULTRA SLIM OPTOMETRIC CHARTS - WALL		
		Viewing area	External size
44710	Armagnac - 5 m	25.5x63 cm	34x72x3.8 cm
44711	Monoyer - 3 m	25.5x63 cm	34x72x3.8 cm
44712	Mixed decimal - 3m	25.5x63 cm	34x72x3.8 cm
44713	Children - 3 m	25.5x63 cm	34x72x3.8 cm



## HEATING BLANKETS



28660

- **28660 HEATING UNDERBLANKET - single**
  - **28661 HEATING UNDERBLANKET - double**
- Electric underblankets made of non-woven fabric (polyester) with stamp welding manufacturing. They warm and relax the entire body, night and day. 3 temperature settings with level indicator. Double underblanket (28661) has 2 controllers. Detachable hand controller allows to wash the blanket. Overheating protection. Supplied with multilingual box and manual GB, FR, IT, DE, NL, PT, GR, SE, PL, RO, FI, CZ.

### TECHNICAL SPECIFICATIONS

	28660	28661	28664
Size (cm):	150x80	160x140	160x120
Power consumption:	60 W	2x60 W	120 W
Voltage:	220-240 V		



28664

- **28664 HEATING OVER BLANKET**
- Electric over blanket made of soft micro plush provides warmth and comfort night and day. 3 temperature setting with LED indicator (0, 1, 2, 3). Automatic switch off after 3 hours. Detachable hand controller allows to wash the blanket. Fast heating and overheating protection. Supplied with multilingual box and manual GB, FR, IT, DE, NL, PT, GR, SE, PL, RO, FI, CZ.



28664

## FOOT WARMER



28668

- **28668 FOOT WARMER WITH MASSAGE**
- Comfortable foot warmer made of super cozy fleece surface and liner. Two motor vibration. Two heat settings. High and low massage intensities. Removable and washable liner. Supplied with multilingual box and manual: GB, FR, IT, DE, NL, PT, GR, SE, PL, RO, FI, CZ.

### TECHNICAL SPECIFICATIONS

Size:	30x30x24 cm
Power consump.:	18 W
Voltage:	220-240 V



## HEATING PADS FOR MUSCLE AND PAIN RELIEFS



28670

- **28670 HEATING PAD WITHOUT COVER**
  - **28671 HEATING PAD WITH COVER**
- Super cozy fleece pads with or without cover. Temperature settings with level indicator: 3 settings (28670) or 6 (28671). Automatic switch off after 90 minutes. Detachable hand controller allows to wash the pad. Fast heating and overheating protection. Supplied with multilingual box and manual GB, FR, IT, DE, NL, PT, GR, SE, PL, RO, FI, CZ.



28671

### TECHNICAL SPECIFICATIONS

Size:	40x30 cm (28670), 63x42 cm (28671),
Power consump.:	100 W
Voltage:	220-240 V



28670



28674

- **28674 NECK AND SHOULDER HEATING PAD**
- Heating pad for neck and shoulder made of micro plush surface. Individually adjustable by press stud. 3 temperature settings with level indicator. Automatic switch off after 90 minutes. Detachable hand controller allows to wash the pad. Fast heating and overheating protection. Supplied with multilingual box and manual: GB, FR, IT, DE, NL, PT, GR, SE, PL, RO, FI, CZ.

### TECHNICAL SPECIFICATIONS

Size:	60x62 cm
Power consumption:	100 W
Voltage:	220-240 V



28674



28675

- **28675 WAIST WRAP HEATING PAD**
- Waist heating pad made of super cozy fleece surface with stamp welding manufacturing. 3 temperature settings with level indicator. Automatic switch off after 90 minutes. Detachable hand controller allows to wash the pad. Fast heating and overheating protection. Supplied with multilingual box and manual: GB, FR, IT, DE, NL, PT, GR, SE, PL, RO, FI, CZ.

### TECHNICAL SPECIFICATIONS

Size:	29x69 cm
Power consumption:	100 W
Voltage:	220-240 V



28675



## HOT-COLD GEL


Individually packed in single box



34114

- **34114 HOT-COLD THERMO GEL - box of 30 pcs.**  
Special gel keeps temperature (hot or cold) for long time. Size: 14x28 cm. Multilingual box and instructions: GB, FR, IT, ES, PT, DE, GR.

## HOT WATER BOTTLES



Capacity 2,000 cc

28600

28601

- **28600 HOT WATER BOTTLE 2 l - British standard - blue**  
55% made of rubber.
- **28601 HOT WATER BOTTLE 2 l - red**  
25% made of rubber.  
Both are two side ribbed.  
Packed in plastic bag with multilingual user manual (GB, FR, IT, DE, ES, PT, GR).

## ICE BAGS



Both made of polyester fabric + PVC.

Neck of bag: PP

Neck of bag: aluminium

28605

28606

- **28605 ICE BAG - Ø 28 cm - large top cap - light blue**  
Cap Ø: external 8.78 cm, internal 6 cm  
Single packed in carton box, with multilingual manual (GB, FR, IT, PL, ES, PT, GR, Arabic).
- **28606 ICE BAG - Ø 28 cm - small top cap - blue**  
Cap Ø: external 7.15 cm, internal 4.7 cm  
Transparent bag with multilingual manual (GB, FR, IT, DE, ES, PT, GR).

## INFRARED THERAPY LAMP - 250 W

- **28652 INFRARED THERAPY LAMP - 250 W - desk with table clamp**
- **28653 INFRARED THERAPY LAMP - 250 W - trolley**


The infrared light relieves the suffering caused by sore muscles and joints ankylosis. The comfortable warmth created by infrared light penetrates deep into the skin, stimulates blood circulation and warms the muscles.

While the muscles are relieved, they automatically stretch and relax.

At the same time, the blood circulation helps your body get rid of impurities and quickly sends oxygen-rich blood to stressed or aching muscles, causing an effective pain relief.

Class II Electric.

- **28654 SPARE BULB - 250 W**



28652

28653

Arm length 90 cm (45+45)

Head Ø 21 cm

MIMSAL

Internal spring balanced arm allows different positions

## INFRARED LAMP

- **28646 MOMERT INFRARED LAMP 150 W**  
The lamp's deep penetrating infrared heat relaxes the muscles and stimulates the blood circulation.

The pleasant heat expands the capillary veins, resulting in a better oxygen and nutrition supply to the tissues. Can be used for rheumatic diseases, allergies, cold diseases, alternative medicine (detoxication), beauty care. Operating voltage: 230 V - 50 Hz.

- **28647 SPARE BULB - 150 W Philips**



CE

Multilingual manual and box (GB, IT, DE, HU, SK, HR, CZ, EE, PL, RU, RO).

## I-TECH LA 500 LASER THERAPY

- **28410 I-TECH LA 500 LASER THERAPY**

Laser therapy device equipped with a new probe with an emitting diode that allows beam laser application directly to the treatment area.

I-TECH LA 500 is able to stimulate deep tissues by promoting a rapid cellular regeneration thanks to 500 mW power output and 810 nm wavelength. Professional user can adjust power output, therapy time and operation mode (continuous or pulse). I-TECH LA 500 guarantees a fast intervention for the treatment of inflammatory and degenerative pathologies in orthopedic, neurologic and dermatologic area.

Thanks to its high performance healing time is significantly reduced. Supplied with probe, belts for probe fastening and safety glasses. Manual in: GB, IT, FR, ES, DE.

### LASER THERAPY

The laser therapy uses the effects of energy produced by the light source penetration into the tissues.

Biochemical reactions are activated across the cellular membrane.

It has been observed that right doses of Laser light can stimulate cellular functions, in particular into the cells damaged by functional deficits.

The main effects of Laser therapy are:

- improved blood flow: capillary and artery vasodilatation that results in local heat increase
- biostimulation: accelerated tissues repair, stimulation of protein synthesis, ADP production, electrolyte changes in the intra- and extra-cellular fluids and mitosis of fibroblasts, increase of collagen and elastin
- anti-inflammatory effect
- anti-oedema effect: lymphatic drainage stimulation
- analgesic effect



28410

CE 0476

### TECHNICAL SPECIFICATIONS

- |  |  |
|--|--|
| Power supply: 230 V, 50-60 Hz, ±10%    | Fixed width duration                   |
| Maximum laser output: 500 mW ± 20%     | Continuous or pulse mode of operation  |
| Adjustable laser power output: 0%-100% | Pointing red light                     |
| Laser diode wavelength: 810 nm         | Diode probe (with reserved connection) |
| Beam divergence angle: 260 mrad        | Adjustable therapy time: 0-30 minutes  |
| Continuous output emission             | Diameter of laser beam: <10 mm         |
| Fixed emission frequency               | Dimensions: 300x150x120 mm             |

### MAIN TREATMENTS

- Polyarthrititis - Epicondylitis/Epitrochleitis - Knee pain - Myositis
- Oedema - Sciatalgia/Lumbago - Articular sprains - Chronic Tenosynovitis - Muscle strains - Overcharge pathologies - Ecchymosis - Bursitis - Degenerative arthritis - Adhesive capsulitis - Arthrosis pains - Post-traumatic disorders
- Scars - Rheumatic diseases

# AIR COMPRESSION THERAPY SOLUTIONS

Human body has a peripheral circulation of blood and lymph. Air compression therapy is an automatic drainage and circulation system which helps patients to recover from their disease by improving blood and lymph circulation and metabolism. It consists of air chambers and an air pump offering air compression massage to legs, arms or waist.


## Medical indications (only 28441)

- DVT (Deep Vein Thrombosis)
- Lymph edema
- Post-paralytic
- Limb convulsion
- Phleboscrosis
- Chronic venous insufficiency (CVI)
- Post-mastectomy
- Post-trauma
- Spinal cord injury
- Varicose veins
- Sciatica
- Diabetes
- Sprains
- Arterial insufficiency

## Home care indications


- Lymph edema
- Diseases caused by interrupted blood circulation
- Cellulitis fat dissolution
- Pregnant woman's limb treat.
- Numb feet or hands
- Cold feet or hands
- Settlement of stress
- Exercise effects
- Insomnia
- Healthier body and elastic skin
- Old age, weakness and fatigue

**HELP  
BLOOD  
CIRCULATION**



## ANYCARE DIGITAL COMPRESSION MASSAGE

- 28415 ANYCARE DIGITAL COMPRESSION MASSAGE - LEG A
  - 28416 ANYCARE DIGITAL COMPRESSION MASSAGE - LEG B
- Pressure intensity and time can be adjusted according to user's needs. Individual chambers pressure testing. Portable and easy operation. For homecare use. Supplied with 2 legs A (74x62 cm) or B (79x75 cm) 4 chambers, 1 double hose and 2 plastic feet guides, multilingual manual (GB, FR, IT, ES).



### ACCESSORIES FOR ANYCARE AND MAYLEA

New*	Old**	LEG SLEEVES	Patient height	Thigh	Ankle	Length
28418	-	Leg sleeve A	160-170 cm	62 cm	41 cm	74 cm
28419	-	Leg sleeve B	170-180 cm	75 cm	43 cm	79 cm
28420	-	Leg sleeve C	> 180 cm	76 cm	46 cm	94 cm
ARM - WAIST SLEEVES				Girth		Length
28422	28436	Arm sleeve		50 cm		88 cm
28424	28437	Waist sleeve		122 cm		38 cm
HOSES						
28426	-	Single hose to connect one sleeve				
28427	28440	Double hose to connect two sleeves				
28428	-	Distribution hose to connect three sleeves - needs 28426+28427				

\*New sleeves can be used only with Anycare standard hose or codes 28426-8

\*\*Old sleeves can be used only with Maylea standard hose or 28440

## MK400L PROFESSIONAL COMPRESSION SYSTEM

- 28441 MK400L PROFESSIONAL COMPRESSION SYSTEM with 2 legs (XL), and 2 single hoses

MK400L is a professional air compression therapy system with essential functions for different kinds of patients. This system provides 3 compression modes (wave, squeezing, double squeezing), reverse compression settings, skip functions to select directly part to be pressurized and compression speed controller. Touch key pad display. Manual: GB, IT, ES.

### TECHNICAL SPECIFICATIONS

- Pressure range: 10-200 mmHg
- Use time: 1-90 minutes
- Automatic pressure detection
- Body size: 415x310x160 mm
- Operating voltage: 220-240 V, 50/60 Hz, 50 VA
- Body weight: 6.5 kg

You can use 2 cuffs at the same time, MK400 has 2 connection plugs



- 28442 LEG CUFF L - 6 CHAMBERS - spare
- 28443 LEG CUFF XL - 6 CHAMBERS - spare
- 28444 LEG EXTENSION ZIPPER XL - 10 cm extra extension for 28443
- 28445 SINGLE HOSE - spare
- 28446 ARM CUFF - 6 CHAMBERS - universal
- 28447 WAIST CUFF - 6 CHAMBERS - min-max girth 94-125 cm

### A mode (Wave)

The selected air chamber inflates and deflates by one chamber sequentially from foot up to thigh.


### B mode (Squeezing)

After all the selected air chambers inflate sequentially from foot up to thigh the inflated chambers deflate at once.

### C mode (B mode two times + Reverse A mode 1 time)

The selected air chambers inflate and deflate by two chambers sequentially from foot up to thigh.

**Reverse setting:** it allows to change automatically the selected mode to reverse mode.



		Leg dimension (cm)						
Cuff	Size	A	B	C	D	E	F	G
L	L	64,0	49,5	40,5	34,5	75,0	38,0	28,0
	XL	73,5	55,0	42,0	35,5	85,0	43,0	31,0



## CR200 - PROFESSIONAL TECAR THERAPY

### • 28364 CR200 TECAR THERAPY with 2 probes

Diathermy, also known as TECAR Therapy (meaning Capacitive and Resistive Energy Transfer), is a therapy stimulating the physiological healing process by accelerating the recovery time of motor function. Diathermy stimulates tissues endogenous heat production through the interaction of electromagnetic field and tissue. The heat is increased in a uniform controlled way. The electromagnetic interaction results in a ionic flow and consequently increases blood flow in the treated area. This process stimulates endogenous substances release (in particular cortisol and endorphins) that are necessary to reduce inflammations, pain and edemas.

The new CR200 resistive capacitive diathermy is a modern and highly performing device easy to use by professionals. Preset programmes help use the device from the start.

Moreover the device can set parameters (power, time therapy, capacitive/resistive modes) according to therapeutic needs.

It allows the memorization of customized programmes.


In this way patient protocols are easily consulted by therapists at any time.

Equipped with a wide graphic display showing therapy parameters and different working modes.

Selectable software language (GB, IT, ES).


### • 28361 RESISTIVE PROBE - spare

### • 28362 CAPACITIVE PROBE - spare



#### Capacitive mode

Electrode coated with ceramic material (mobile) and return plate (fixed). Indicated especially for soft tissues (muscle mass and lymphatic/vascular system). Benefits: specific intervention, easy control of the treated area.



#### Resistive mode

Non isolated electrode (mobile) and return plate (fixed). Indicated especially for tissues with greater resistance (bones, joints, tendons, ligaments, cartilages). Benefits: high level of diathermy; chronic diseases with fibrosis and degeneration

#### STANDARD ACCESSORIES

2 multi-function probes for capacitive and resistive mode  
2 electrodes Ø 35 mm (1 resistive + 1 capacitive) with 9.61 cm<sup>2</sup> effective working area  
2 electrodes Ø 60 mm (1 resistive + 1 capacitive) with 28.26 cm<sup>2</sup> effective working area  
2 integrated supports for probes  
1 steel plate  
Bottle of conductive cream 1 kg  
Power supply cable  
User Manual: GB, IT (ES, FR on request)



#### MAIN TREATMENTS

Skeletal-muscle pathologies  
Lymphedema

Acute and chronic pain  
Osteoarticular pathologies

#### 24 REHAB PROGRAMMES

Phantom limb, knee arthrosis, arthrosynovitis, bursitis, neck pain, whiplash syndrome, chondropathy, muscle contracture, contusion, muscular sprain, sprain, muscle distraction, joint pain, edema, epicondylitis, epitrochleitis, anterior cruciate ligament, lymphedema, low back pain, meniscopathy,

muscle tear, acute tendinitis, chronic tendinitis, rotator cuff tendinopathy

#### 10 SPORT PROGRAMMES

muscle contracture, contusion, muscle recovery, sprain, hematoma, tendon injury, superficial massage, deep massage, muscle sprain, muscle tear

#### 10 FREE MEMORIES

#### TECHNICAL SPECIFICATIONS

Power supply: 100-240 V, 50/60 Hz  
Max power consumption: 160 W (100 ohm load)  
Carrier frequency: 500 kHz  
Adjustable power: 0-100%  
Touch screen graphic display 7"  
Preset programmes, free memories

## CONDUCTIVE CREAMS

### • 28345 DIATER CONDUCTIVE CREAM 1 l - neutral base

### • 28346 DIATER CONDUCTIVE CREAM 1 l - arnica

### • 28347 DIATER CONDUCTIVE CREAM 1 l - hyaluronic acid

Essential, simple and effective conductive creams. Rich in active ingredients which are recognized in musculoskeletal therapies, in support of the functional recovery of athletes and in the aesthetic treatments of epidermis and dermis.

Exceptional absorption and therapies enhancement keep the activity focused on the portion of treated tissue, with marked stability and effectiveness. Absence of parabens or petrolatum. **Neutral base conductive cream** moisturizes and protects tissue; suitable for mixes and cocktails.

**Arnica Montana conductive cream** decongests and protects tissue. For acute and chronic inflammation of tissues or joints and Lipodystrophy.

**Hyaluronic acid conductive cream** for hydro balancing of the tissues. Protective of cartilage and against phlegm and tissue trauma spills. Treatment of scars, hypotonia and post-surgery outcomes. Suitable for passive mobilizations.

Creams are preserved into thermo/photo protected PET containers with cap and undercap and dispenser.

For professional use only in different fields: Physiotherapy, Physiatry, Plastic Surgeons, Aesthetics, Orthodermic therapy,

Athletic Preparation, Massage and Podiatry

Label in: GB, IT, FR, ES.

### • 28348 ADAPTOR CAP WITH DOSING PUMP



## MIO-SONIC ULTRASOUND THERAPY DEVICE - 9 PROGRAMS

### • 28309 MIO-SONIC ULTRASOUND THERAPY

Innovative and high performance device both for home use and professional use. Suitable for muscle contractures and joints stiffness. It combines compactness and high performances in a small, light and easy to use applicator. The lightness and handiness allows a continuous use without any difficulty.

Mio Sonic can be used for the following applications:

- pain therapy;
- sport injuries;
- aesthetic treatments.

Supplied with gel bottle, carrying and storage bag, medical power supply and multilingual manual: GB, FR, IT, ES. On request DE.



28309

#### TECHNICAL SPECIFICATIONS

9 programs;  
1 MHz ultrasound, maximum output power 6.4 W, maximum intensity 1.6 W/cm<sup>2</sup>;  
Collimated ultrasound beam for an optimal penetration beam;  
3 ultrasound beam intensity levels 0,08 W/cm<sup>2</sup> (low) - 0,8 W/cm<sup>2</sup> (medium) - 1,6 W/cm<sup>2</sup> (high);  
Power supply: 100-240V, 50/60 Hz  
Direct contact device (not suitable for water immersion)  
Size-weight: 200x47x69 mm - 190 g

#### TREATMENTS

Osteoporosis  
Arthritis  
Neuralgias  
Cervicalgias  
Sciatalgy  
Sprains  
Cruralgy  
Wrinkles

Periarthritis  
Tendinitis  
Pubalgy  
Tallonitis  
Contusions  
Chondropathy  
Microlifting  
Epitrochleitis

Adhesions  
Algodystrophy  
Bursitis  
Brachialgy  
Capsulitis  
Stretch marks  
Epycondilitis  
Lymphedema

Muscular contractures  
Cramps  
Massage  
Drainage  
Modelling  
Carpal Tunnel  
Oedema  
Venous stagnation

Arms cavitation  
Abdomen cavitation  
Limb cavitation  
Gluteus cavitation  
Lumbalgy  
Hematoma  
Acne  
Phonophoresis

## I-TECH UT2 - PROFESSIONAL ULTRASOUND THERAPY



### • 28358 I-TECH UT2 ULTRASOUND THERAPY - 2 probes

Professional ultrasound device equipped with 2 handles respectively with 5 cm<sup>2</sup> and 1 cm<sup>2</sup> probe. Its equipment and parameters setting allow high performance suitable for professional users.

It is provided with 10 preset programmes within which professional user can adjust following parameters:

- Frequency (1 or 3 MHz)
- Effective intensity (up to 3 W/cm<sup>2</sup>)
- Duty cycle (10%÷100% stepping 10)
- Therapy time (up to 30 minutes)

#### TECHNICAL SPECIFICATIONS

Operating voltage: 100-240 V, 47/63 Hz, 1.35A, output 15V 3A max  
Ultrasound frequency: 1 MHz  $\pm$  10% and 3 MHz  $\pm$  10%  
Output power: 0.5-10 W  $\pm$  20% when duty cycle  $\geq$  80% for 5 cm<sup>2</sup> ultrasound head  
0.5-15 W  $\pm$  20% when duty cycle  $\leq$  70% for 5 cm<sup>2</sup> ultrasound head  
0.1-2 W  $\pm$  20% when duty cycle  $\geq$  80% for 1 cm<sup>2</sup> ultrasound head  
0.1-3 W  $\pm$  20% when duty cycle  $\leq$  70% for 1 cm<sup>2</sup> ultrasound head  
Max Power: 3 W/cm<sup>2</sup>  $\pm$  20% (1 MHz); 3 W/cm<sup>2</sup>  $\pm$  20% (3 MHz)  
Working frequency: 100 Hz  
Duty cycle: 10%-100% stepping 10%  
Maximum adjustable therapy time 30 minutes  
Effective radiating area 5 cm<sup>2</sup>  $\pm$  20%; 1 cm<sup>2</sup>  $\pm$  20%  
Collimated beam type Ultrasound head (material) aluminium  
Direct contact and water immersion use  
Led indicator Size: 250x185x82 mm

#### APPLICATIONS

Tendinitis - Bursitis/Capsulitis - Hematomas and tissue reconstruction -  
Muscle contractures/Cramps - Neuralgias - Periarthritis - Cervicalgias -  
Sciatalgy/Lumbalgy - Carpal tunnel syndrome - Epicondylitis/epitrochleitis -  
Contusions/sprains - Chondropathy - Massage - Arms/abdomen/legs/gluteus  
cavitation - Acne

#### STANDARD ACCESSORIES

1 handle with 5 cm<sup>2</sup> probe      1 power supply 15 V, 3 A  
1 handle with 1 cm<sup>2</sup> probe      1 ultrasound gel  
1 power supply cable      User manual: GB, IT, ES, FR. DE on request

## IONO BASE PLUS - GALVANIC IONOPHORESIS

### • 28306 IONO BASE - PLUS - 2 channels

Local administration of medicines by ionophoretics, electric osmosis and treatment of hyper hydrosis (sweating disease) and cellulitis. Current generator for hydro galvanization, aesthetic shaping and against cellulitis slight blemish.

Microprocessor controlled, with selection of parameters and internal programs. Simple and safe to use, although it maintains characteristics of a professional equipment.

### • 28335 RUBBER ELECTRODES 50x50 mm - box of 10

### • 28336 SPONGE BAGS for electrodes 50x50 mm - box of 10

#### TECHNICAL SPECIFICATIONS

Operating Voltage: 230 V - 50/60 Hz      Size: 138x68x193 mm  
Absorbed Max Power: 10 VA      Max Output Current: 20 mA  
Safety class: II BF - C  $\epsilon$  93/42/EEC.

Supplied with ABS case, velcro elastic bands, rubber conductive electrodes 80x120 mm and 50x50 mm and envelopes sponges for electrodes.  
MADE IN ITALY



28306



# T-ONE COACH AND T-ONE MEDI SPORT - 4 CHANNELS ELECTROTHERAPY

## 28401 T-ONE COACH ELECTROTHERAPY - 4 channels

A high performant muscle stimulator designed to improve physical activity. Easy to use programs ideal device for not professional athletes and for sports lovers. It is not only a muscle stimulator equipment. It is supplied by TENS protocols for pain relief and injuries recovery.

## 28402 T-ONE MEDISPORT ELECTROTHERAPY - 4 channels

Professional equipment specifically designed for sport specialist users. Muscle stimulation specialized programs improve sport performance. It increases strength and helps recovery of sport injuries with specific treatment protocols.

### Main features

- constant current generator (can guarantee a constant current even when skin condition changes, the device automatically stops in the event of accidental electrodes disconnection)
- four independent channels unit (up to 8 connectable electrodes)
- compensated biphasic square wave: current quantity from positive pole to negative one is constant to avoid polarization effect;
- monophasic wave generator (only for iontophoresis programs)
- 2+2 users programs
- backlight graphic colour display
- user feedback: the device recognizes patient connection
- soft-touch easy to use keyboard
- on-line 5 languages guide (GB, FR, IT, ES, DE) on display
- 4,8 V rechargeable battery pack
- personalized programs for man and woman
- maximum intensity 240 mApp, with 1 mA step regulation

Size: 150x90x35 mm



- 28351 PRE GELLED ELECTRODES 40x40 cm with cable - box of 4
- 28373 PRE GELLED ELECTRODES 45x80 cm with cable - box of 4
- 28381 IONOPHORESIS KIT - spare
- (1 elastic band, 2 silicone conductive electrodes, 2 sponges)
- 28403 Ni-Mh BATTERY 4.8 V 2300 mA for 28401, 28402

### STANDARD ACCESSORIES

4 connection cables (8 connectable electrodes)  
Kit of pre-gelled self-adhesive electrodes (square, rectangular, round)  
Iontophoresis kit: elastic belt, 2 silicone electrodes, 2 sponges, carrying bag (28402 only)  
Internal Ni-Mh rechargeable battery pack and battery charger  
Electrode position manual and user manual (GB, FR, IT, ES). On request DE, PT

BEAUTY 18 programmes 28401 and 28402	REHA 10 programmes only 28402	TENS 16 programmes 28401 and 28402	NEMS 14 programmes 28401 and 28402	MEM Only 28402	2+2 28401 and 28402
Firming up Toning up Definition Modelling Microlifting Lipolysis abdomen Lipolysis thighs Lipolysis glutei and hips Lipolysis arms Tissue elasticity Capillarization Heaviness in legs Face Microlifting Handy Trode Breast Microlifting Handy Trode Décolleté Microlifting Handy Trode Face Wrinkles Handy Trode Forehead Wrinkles Handy Trode Collagen	Ionophoresis L Ionophoresis M Ionophoresis H MENS microcurrent Haematomas Oedema Tens sequential Tens Burst Atrophy prevention Atrophy	Tens rapid Tens endorphinic Tens max values Inflammatory Neck pain Backache/Sciatic pain Sprains/Bruises Vascularization Muscle relaxant Hand and wrist pain Plantar stimulation Epicondylitis Epitroclea Periarthritis Tens Burst Microcurrent	Warming up Resistance Resistance strength Basic strength Fast strength Explosive strength Deep capillarization Muscle recovery Agonist/Antagonist Sequential tonic contractions Sequential phasic contractions Muscle relaxant Deep massage EMS  Only 28402 30' Resistance 30' Resistance strength 20' Basic strength 20' Fast strength 20' Explosive strength 20' Hypertrophy	Tens mem 1 Tens mem 2 Tens mem 3 Tens mem 4 Tens mem 5 NEMS mem 1 NEMS mem 2 NEMS mem 3 NEMS mem 4 NEMS mem 5 NEMS alternated NEMS alternated Battery test	Tens rapid Tens endorphinic Firming up Toning up Definition Modelling Microlifting Muscle relaxant Massage Capillarization  Only 28402 Inflammatory Resistance, Resistance strength Basic strength, Fast strength Explosive strength, Hypertrophy Face Microlifting Handy Trode Breast Microlifting Handy Trode Décolleté Microlifting Handy Trode Face Wrinkles Handy Trode Forehead Wrinkles Handy Trode

# GIMA UTC 2: COMBINED ULTRASOUND AND ELECTROTHERAPY UNIT

## 28301 GIMA UTC 2 AUTOMATIC

Programmable driver unit for ultrasound transducers with working frequencies from 1 up to 3 MHz together with 2 channels of electrotherapeutic current. UTC 2 delivers continuous or modulated ultrasound with programmable intensity and delivery time, suitable for thermo therapeutic deep treatment of different pathologic conditions. Transducer handpieces can be used under water. UTC 2 delivers Dyadinamic, Faradic, Galvanic, Impulsive, T.E.N.S. and Bipolar electrotherapeutical currents.

- high brightness graphic touchscreen display
- controls of unit by multifunction knob, keys or touchscreen
- wide range of preset protocols
- customized programmes
- multi frequency handpieces
- automatic identification of the connected accessory
- continuous or pulsed delivery
- sequence of treatment phases planning for each channel
- independent channels
- safety control blocks the output current in case of accidental disconnection of electrodes.

- 28302 1-3 MHz ULTRASOUND HEAD Ø 15 mm
- 28303 CONNECTING CABLE for electrotherapy - spare
- 28304 CLIP RUBBER ELECTRODES 120x80 mm - box of 12
- 28305 CLIP RUBBER ELECTRODES 45x60 mm - box of 12
- 28323 VELCRO ELASTIC BAND 100x8 cm - spare



6 language software: GB, FR, IT, ES, DE, PT.

### TECHNICAL SPECIFICATIONS

Output frequency (MHz): 1.0 to 3.0	Max output direct current (mA): 30
Max intensity (W/cm <sup>2</sup> ): 3.0	Max output pulse current (mA): 70
ET channels: 2	Max output voltage (Vdc): 100
Electrical input power (VA): 70	Power supply (Vac/Hz): 90-240 / 50-60

### STANDARD ACCESSORIES

1-3 MHz ultrasound head Ø 35 mm  
Connecting cable for electrotherapy 1-2 (28303)  
4 rubber electrodes 120x80 mm; 4 rubber electrodes 45x60 mm  
3 velcro elastic belt: 8x40, 8x60, 8x100 cm Power cable 2 m

## ORTHOMAG LOW FREQUENCY MAGNETOTHERAPY - 2 PROGRAMMES

- Osteogenesis
- Biostimulation
- Pain management

CE 0068



28298

### • 28298 ORTHOMAG low frequency magnetotherapy kit

A professional low frequency magnetotherapy (PEMF) device that can be used everywhere. Lightweight, comfortable and flexible, fitting your body shape. Battery powered for dynamic use or power socket for use at home or in the office. Orthomag includes 2 programmes (75 Hz and 50 Hz) indicated for bone tissue pathologies, joint diseases and pain management. Up to 25 Gauss per programme. Supplied with rechargeable lithium battery 3.7 V 900 mAh, wall mount charger (cable 1.5 m), universal flexible applicator (cable 1.5 m), test emission magnet, 2 elastic bands (S and L), carrying bag, manual (GB, FR, IT, ES).



In motion magnetotherapy

## MAG 700 LOW FREQUENCY, HIGH INTENSITY MAGNETOTHERAPY

CE 0068



28296

### • 28296 MAG 700 MAGNETOTHERAPY - 1 channel

New portable magnetotherapy ideal for home therapy.

MAG 700 offers a high level of professional performances and it's indicated for several pathologies.

It allows comfortable home therapy through its basic accessories.

MAG 700 has 7 pre-set programmes for the treatment of several pathologies,

3 programmes identified by the working frequency (from 5 to 20 Hertz) and an Autoscan programme with continuous frequency variation for the treatment of both hard and soft tissues at the same time.

Possibility to adjust the magnetic field intensity for all programmes up to 70 Gauss.

Working frequencies are between 5 and 100 Hertz.

Supplied with elastic therapeutic belt with 2 solenoids, power supply, carrying bag and manual (GB, FR, IT, ES). On request DE.



28296

#### 11 PROGRAMMES

7 pre-set programmes	3 working freq.+autoscan	
Osteoarthritis	5 Hz	Autoscan
Osteoporosis	10 Hz	
Arthritis	20 Hz	
Fractures		
Articular pain		
Muscle pain		
Anti-inflammatory		

## MT BASE: MAGNETOTHERAPY

### • 28321 GIMA MT BASE PLUS - magnetotherapy

Magneto Base Plus is an ELF low frequency magnetotherapeutic unit designed for domiciliary applications.

The most important effects of the magnetic fields are:

Antiedemigen, Analgesic, Antiphlogistic, Regenerative.

Applications in: traumatology, rheumatology, angiology, neurology, dermatology, endocrinology.

The magnetic field produced is impulsive.

The internal generator produces square waveform electrical current with frequency varying from 10 to 99 Hz and impulse time varying so to obtain a field's intensity determined from 10 to 80 Gauss. Internal sound sensor of magnetic field and safety system in case of short-circuit.


Two transducers can be connected at the same time (the field produced by each transducer is half of the total).

### • 28322 PLATE TRANSDUCER 70x120 mm - spare

### • 28323 VELCRO ELASTIC BAND 100x8 cm - spare

#### TECHNICAL SPECIFICATIONS

Waveform:	square
Max. ratio emission/pause:	50%
Selectable magnetic field:	from 10 to 80 Gauss
Selectable frequency:	from 10 to 99 Hz
Intensity of magnetic field:	80 Gauss (8mT)
Operating voltage:	230V/50-60 Hz
Size:	193x138xh 68 mm
Weight:	1 kg
Safety class:	II BF - Norms: EN60601-1 (CEI)



MADE IN ITALY

It is supplied with all accessories in a plastic case.

28321

#### STANDARD ACCESSORIES

Power cable	1 velcro elastic band 100xh 8 cm
2 plate transducers 80 gauss - 120x70 mm	ABS carrying case
1 velcro elastic band 60xh 8 cm	Manual (GB, IT)



## MAG 2000 LOW FREQUENCY, HIGH INTENSITY PEMF MAGNETOTHERAPY



CE 0068

Size:  
180x110x50 mm

28300

- **28300 MAG 2000 PEMF MAGNETOTHERAPY - 2 channels - 300 Gauss**
- **28311 MAG 2000 PLUS PEMF MAGNETOTHERAPY - 2 channels - 400 Gauss**

Ideal devices for domiciliary and professional magnetotherapy. **35 programmes: 20 pre-set programmes** for the treatment of several pathologies, **14 programmes identified by the working frequency** (from 1 to 100 Hertz) and an **Autoscan** programme with continuous frequency variation for the treatment of both hard and soft tissues at the same time.

MAG 2000 PLUS has also the possibility to store **10 user memories**, choosing the frequency up to 120 Hz, intensity and therapy time: a great possibility for the professional user who need to use a specific treatment for each patient. Possibility to set the intensity of magnetic field for all the programmes up to **300 Gauss (150 Gauss each channel)** for MAG 2000 or up to **400 Gauss (200 Gauss each channel)** for MAG 2000 Plus

to easily treat different body parts through elastic therapeutic belt with 3 solenoids.

Supplied with elastic therapeutic belt with 3 solenoids, couple of professional solenoids (28311 only), power supply, carrying bag and manual (GB, FR, IT, ES, DE).

- **28299 ELASTIC THERAPEUTIC BELT - green - spare**  
Belt with cable with 3 solenoids for low frequency treatments.
- **28316 COUPLE OF PROFESSIONAL SOLENOIDS**  
Couple of professional solenoids Ø 11 cm for high intensity therapy.



28311

35 PROGRAMMES (28300) - 45 PROGRAMMES (28311)	
20 pre-set programmes	14 working freq.+autoscan
Osteoporosis	Intercostal Contusion
Arthrosis	Lumbalgy
Arthritis	Lumbar pain
Cervical arthrosis	Shoulder arthrosis
Articular pain	Knee arthrosis
Cervicalgias	Periarthritis
Sprains	Coxarthrosis
Fractures	Muscular Atrophy
Epicondylitis	Muscular contracture
Epitrocleitis	Osteonecrosis
	10 memories (28311 only)

## MAG 3000 LOW FREQUENCY, HIGH INTENSITY PEMF MAGNETOTHERAPY



CE 1936

Size:  
180x110x50 mm

28314

- **28314 MAG 3000 PEMF MAGNETOTHERAPY - 2 channels**

MAG 3000 is a certified medical device for pulsed electromagnetic field magnetotherapy (PEMF). Suggested for the treatment of delayed union, osteoporosis, bone oedema, osteonecrosis, as well as ulcers and neuropathies.

Thanks to the high intensity of the magnetic field, it is also suitable for the treatment of bone fractures even in the presence of rigid bandages or plaster casts.

- two independent channels
  - colour display
  - magnetic field intensity up to 150 gauss per channel
  - frequency from 1 to 100 hz
  - 41 programmes available
  - possibility to manage two treatments at the same time by setting different times and programmes (double user)
  - list of the last 10 programmes used
- For professional users (doctors, therapist, ...) and for in-home therapy.

Operating power 110-240 V.

- **28315 ELASTIC THERAPEUTIC BELT - light blue - spare**  
Belt with cable with 3 solenoids for low frequency treatments.
- **28316 COUPLE OF PROFESSIONAL SOLENOIDS**  
Couple of professional solenoids Ø 11 cm for high intensity therapy.

### STANDARD ACCESSORIES

3 solenoids belt applicator	Medical power supply
User manual (GB, FR, IT, ES)*	Magnet to verify therapy operation
Carrying bag	Three non-woven fabric strips 15x150 cm
*on request DE	



28314

41 PROGRAMMES		
Osteoporosis	Knee arthrosis	Healing
Arthrosis	Scapulo humeral periarthritis	Cutaneous ulcers
Arthritis	Coxarthrosis	Discopathy
Cervical arthrosis	Muscular atrophy	Myalgia
Articular pain	Muscular treatment	Neuropathy
Cervicalgias	Osteonecrosis	Muscle strain
Chronic pain	Algodystrophy	Muscular cramp
Fractures	Cartilage lesion	Rizarthrosis
Epicondylitis	Ligament lesion	Impingement syndrome
Epitrocleitis	Bone cedema	Carpal Tunnel
Pseudoarthrosis	Tendinitis	Titanium prosthesis
Lumbalgy	Chondropathy	Rotator cuff
Lumbar pain	Antinflammatory	Tarsal Tunnel
Shoulder arthrosis	Whiplash syndrome	

## OSTEOMAT: MATTRESS FOR LOW FREQUENCY MAGNETOTHERAPY TREATMENTS

- **28318 OSTEOMAT MATTRESS FOR MAGNETOTHERAPY**

Osteomat is composed of 4 active sectors, containing 2 solenoids each, for a total of 8 professional solenoids.

The Osteomat is the ideal solution for total body treatment in a single session, thanks to easy-to-use mode and extreme flexibility.

The configuration of Osteomat stimulates the body areas (shoulders, column, pelvis) that are more affected by bone mass reduction.


This is typical of osteoporosis pathology.

Suitable for MAG 2000, MAG 2000 PLUS, MAG 3000 and LaMagne models.

Supplied with non-woven fabric cover (pack of 2 pieces).

Suggested for night therapy during sleep, day therapy in paralyzed patients, active patients that don't tolerate long treatments with therapeutic belt and prefer night therapy.

28318



4 active sectors  
(2 solenoids for each sector, totally 8 solenoids)

Manual:  
GB, FR, IT, ES


## GIMA TENS/EMS/MASSAGE - 2 CHANNELS

• **28405 GIMA-CARE TENS** - 60 medical programmes  
Dual channel multi-functional electrotherapeutic device generates electric stimulation to help easing aches and pain, muscle training and relaxation. Easy to use, Gima-care has 2 pre-set treatment programmes with adjustable treatment time and 1 custom programme for each body part, allowing the user to adjust treatment time and pulse rate and width.

- 3 in 1 Tens + Ems + Massage
  - professional tens waveform (variable pulse frequency and width)
  - body part illustration
  - 60 programmes (10 body parts, 40 levels)
  - powerful output (max. 120 mA) (at 500 ohm load)
  - solid and clear design.
- Continuous operation for around 10 treatments if fully charged.

Supplied with 4 pads 50x50 mm, 2 output cables, 1 USB cable.  
User manual (GB, FR, IT, ES, DE).

• **28408 REUSABLE GELLED ELECTRODES** 50x50 mm - bag of 4



**60 PROGRAMMES**



60 PROGRAMMES - TENS/EMS/MASSAGE	
<b>TENS</b> (Transcutaneous Electrical Nerve Stimulation)	
Body parts:	neck, shoulder, arm, hand, back, abd, hip, leg, foot, joint
Treating programme:	30 programmes, 10 adjustable programmes
<b>EMS</b> (Electrical Muscle Stimulation)	
Body parts:	neck, shoulder, arm, hand, back, abd, hip, leg, foot
Treating programme:	27 programmes, 9 adjustable programmes
<b>MASSAGE</b>	
Methods:	knead, rub, tap
Treating programme:	3 massage manipulations to all body parts

TECHNICAL SPECIFICATIONS	
Channel:	2
Waveform:	Bi-phase square-wave pulse
Output current:	Max. 120 mA (at 500 ohm load)
Output intensity:	0 to 40 levels, adjustable
Power supply:	3.7 V Li-ion rechargeable batteries
Display:	backlight white display
Dimension - Weight:	109x54.4x23 mm - 85g
Classification:	BF type applied part, internal power equipment, IP22
Norms:	IEC60601, IEC61000-4-2, IEC61000-4-4, IEC61000-4-5, IEC61000-4-11, IEC61000-4-8, IEC61000-4-3

• **28406 GIMA-THER TENS** - 36 medical programmes  
Gima-Ther is a dual channel stimulator with 3 basic functions: TENS, EMS and MASSAGE.

It has 36 programmes (18 TENS, 15 EMS and 3 Massage) and applies electric currents in the low-frequency range for therapy. It helps with blood circulation and to relieve chronic and postoperative pains. Recommended for muscle training and also for body building. Electric impulses are transcutaneous and transmitted to nerves, muscle fibers or tissues through electrode. The intensity of the dual channel can be adjusted independently and can be applied individually to one body part.

Supplied with 4 pads 50x50 mm, 2 output cables, 4 AAA batteries and instruction manual (GB, FR, IT, ES, DE).

• **28408 REUSABLE GELLED ELECTRODES** 50x50 mm - bag of 4



**36 PROGRAMMES**



36 PROGRAMMES - TENS/EMS/MASSAGE	
<b>TENS</b> (Transcutaneous Electrical Nerve Stimulation)	
Body parts:	shoulder, low back, joint, hip, arms, legs
Treating programme:	18 programmes
Treating time:	30 minutes
<b>EMS</b> (Electrical Muscle Stimulation)	
Body parts:	shoulder, back, limb and hip
Treating programme:	15 programmes
Treating time:	28, 30 and 32 minutes
<b>MASSAGE</b>	
Treating programme:	3 programmes
Treating time:	30 minutes


TECHNICAL SPECIFICATIONS	
Channel:	2
Waveform:	Bi-phase square-wave pulse
Output voltage:	Max. 120 Vpp (at 1000 ohm load)
Output current:	Max. 60 mA (at 1000 ohm load)
Output intensity:	0 to 60 levels, adjustable
Output characteristics:	Constant Current (CC)
Power supply:	6.0 V D.C., 4x AAA batteries 1.5 V
Display:	Large backlit LCD
Dimension - Weight:	120.5x69.5x27 mm - 104 g
Classification:	BF type applied part, internal power equipment, IP22
Norms:	IEC60601-1, IEC60601-1-2, IEC60601-1-11, IEC60601-2-10, IEC62304

## DISPOSABLE GELLED ELECTRODES FOR ELECTROTHERAPY



**DISPOSABLE GELLED ELECTRODES WITH CABLE** - latex free  
High material flexibility allows easy application of electrodes on treated areas. Solid gel maintains the electrode adhesion and conductivity unchanged during procedure. The electrodes are equipped with 10 cm long cable, with 2 mm socket.

- **28384 GELLED ELECTRODES** with cable 45x35 mm - bag of 4
- **28351 GELLED ELECTRODES** with cable 40x40 mm - bag of 4
- **28372 GELLED ELECTRODES** with cable 46x47 mm - bag of 4
- **28373 GELLED ELECTRODES** with cable 45x80 mm - bag of 4



**DISPOSABLE GELLED ELECTRODES AND ADAPTORS** - latex free  
High material flexibility allows easy application of electrodes on treated areas. Solid gel maintains the electrode adhesion and conductivity unchanged during procedure.

- **28387 GELLED ELECTRODES** 45x35 mm - bag of 4
- **28388 GELLED ELECTRODES** 46x47 mm - bag of 4
- **28317 GELLED ELECTRODES** 45x80 mm - bag of 4
- **28390 2 mm CLIP ADAPTORS** - black - box of 10
- **28391 2 mm CLIP ADAPTORS** - red - box of 10
- **28392 4 mm CLIP ADAPTORS** - black - box of 10
- **28393 4 mm CLIP ADAPTORS** - red - box of 10

### ADAPTORS





## MIO-CARE - 2 CHANNEL TENS

- 28370 MIO-CARE TENS - 20 medical programmes
  - 28376 MIO-CARE FITNESS - 55 programmes (20 medical + 15 beauty + 20 fitness programmes)
  - 28377 MIO-CARE PRO - 63 programmes (14 medical + 15 beauty + 21 fitness + 13 free memories)
  - 2 independent channels stimulator
  - compensated biphasic square wave: avoids hazardous thermic effect of polarization
  - easy to use, digital keyboard
  - remaining therapy time and programmes instruction shown on graphic display
  - internal rechargeable battery pack
  - maximum intensity 100 mA (200 mA pk-pk)
  - compliance with 93/42/EEC MDD
- Supplied in a carrying bag with 2 connection cables with splitters, user manual\* (GB, FR, IT, DE, ES), 8 adhesive pads, internal rechargeable battery with battery charger.

\*PT on request for 28370, 28376

- 28372 GELLED ELECTRODES with cable 46x47 mm - bag of 4
- 28373 GELLED ELECTRODES with cable 45x80 mm - bag of 4
- 28383 Ni-Mh BATTERY 4.8 V for 28370/6/7, 28380/2
- 28374 BLUE AND YELLOW CABLES, 2 mm MALE PLUG - kit of 2 - spare



20 PROGRAMMES  
300 APPLICATIONS



28370

55 PROGRAMMES  
500 APPLICATIONS



28376

50 PROGRAMMES  
13 FREE MEMORIES



28377

14 MEDICAL PROGRAMMES (all)	15 BEAUTY PROGRAMMES (28376, 28377)	20 FITNESS PROGRAMMES (28376, 28377)
Tens conventional (rapid) Tens endorphinic (delayed) Tens maximum values Inflammatory Neck pain/cervicogenic headache Backache/sciatic pain Sprains/bruises	Vascularization Muscle relaxant Hand and wrist pain Plantar stimulation Epicondylitis Epitroclea Periarthritis	Firming up - upper limbs and trunk Firming up - lower limbs and trunk Toning up - upper limbs and trunk Toning up - lower limbs and trunk Definition - upper limbs and trunk Definition - lower limbs and trunk Modelling Microlifting Lipolysis - abdomen
+6 MEDICAL PROGRAMMES (28370, 28376) Haematomas Atrophy prevention Atrophy (trophism rehabilitation)	Microcurrent Stress incontinence Urgency incontinence	Lipolysis - thighs Lipolysis - glutei and hips Lipolysis - arms Tissue elasticity Capillarization Heaviness in legs Warming up Resistance-upper limbs and trunk Resistance-lower limbs Resistant strength - upper limbs and trunk Resistant strength - lower limbs Basic strength - upper limbs and trunk Basic strength - lower limbs Fast strength - upper limbs and trunk Fast strength - lower limbs Explosive strength - upper limbs and trunk Explosive strength - lower limbs +1 FITNESS PROGRAMME (28377 only) EMS
Deep capillarization Muscle recovery Agonist - antagonist Sequent. tonic contract. - upper limbs and trunk Sequential tonic contractions - lower limbs and trunk Sequential phasic contract. - upper limbs and trunk Sequential phasic contractions - lower limbs and trunk Muscle relaxant Deep massage		

## I-TECH PHYSIO PROFESSIONAL 2 CHANNELS STIMULATOR

- 28382 I-TECH PHYSIO PROFESSIONAL STIMULATOR
- Professional stimulator with 2 independent channels
- compensated biphasic square wave: current quantity from positive pole to negative one is constant to avoid hazardous thermal effect of polarization
- monophasic square wave
- incontinence and ionophoresis programmes
- denervated treatment
- programmable TENS - EMS memories
- adjustable frequency, width impulse, time, ramp
- remaining therapy time and programmes instructions shown on the LCD
- maximum intensity 200 mApp;
- Can use same gelled electrodes with cable as Mio-Care
- 28381 IONOPHORESIS KIT - spare (1 elastic band, 2 silicone conductive electrodes, 2 sponges)
- 28383 Ni-Mh BATTERY 4.8 V for 28370/6/7, 28380/2
- 28374 BLUE AND YELLOW CABLES, 2 mm MALE PLUG - kit of 2 - spare

Supplied in a carrying bag with:

- rechargeable battery and battery charger
- 1 set of 4 pregelled electrodes 48x48 mm
- 1 set of 4 pregelled electrodes 50x90 mm
- 2 silicon conductive electrodes 60x90 mm
- 2 sponges 70x100 mm
- 1 elastic belt for electrodes fastening
- 2 cables, 2 mm connection male plug
- 4 cable splitter 2 mm male and female plug

User manual: GB, FR, IT, ES, on request PT, DE.

Backlit display



Digital easy to use keyboard

PROGRAMMES:  
21 NEMS  
15 BEAUTY  
27 REHABILITATION  
14 TENS  
9 UROLOGY  
13 FREE MEMORIES

## MIO IONOTENS, 2 CHANNELS

- 28380 MIO-IONOTENS 37 programmes
- 2 channel stimulator with high output power and a complete list of TENS programmes, rehabilitation programmes and free memories. Portable and easy to use with backlit display and digital keyboard. 14 TENS programmes, 10 rehabilitation programmes including 3 ionophoresis treatments and 13 free memories (adjustable frequency, width impulse and time). Supplied in a carrying bag, with 2 cables, ionophoresis kit, 1 set of 4 pre-gelled electrodes (41x41 mm), 1 set of 4 pre-gelled electrodes (40x80 mm), belt clip, internal rechargeable battery (long lasting), charger, user manual GB, FR, IT, ES (DE on request).
- 28381 IONOPHORESIS KIT - spare (1 elastic band, 2 silicone conductive electrodes, 2 sponges)
- 28383 Ni-Mh BATTERY 4.8 V for 28370/6/7, 28380/2
- 28374 BLUE AND YELLOW CABLES, 2 mm MALE PLUG - kit of 2 - spare



28380

## LATEX-FREE RESISTIVE EXERCISE BANDS

Latex-free bands available in 7 colour-coded levels of resistance and 3 lengths (1.5, 5.5 and 45 m).

These reliable and effective bands are ideal to improve strength, range of motion.



Use of these bands for resistive exercise provides force on the muscles.

Excellent for upper and lower body therapy.

Latex-Free Exercise Bands provide the same benefits as regular bands.



Latex-free exercise bands - 1.5 m



GIMA Code	LATEX FREE EXERCISE BANDS - 1.5 m	
47000	Latex-free band 1.5 m x 14 cm x 0.20 mm	Yellow
47001	Latex-free band 1.5 m x 14 cm x 0.25 mm	Green
47002	Latex-free band 1.5 m x 14 cm x 0.30 mm	Red
47003	Latex-free band 1.5 m x 14 cm x 0.35 mm	Blue
47004	Latex-free band 1.5 m x 14 cm x 0.40 mm	Black
47007	Set of 5 latex-free bands (1x5 levels) 1.5 m x 14 cm mix	
LATEX FREE BANDS - 5.5 m		
47010	Latex-free band 5.5 m x 14 cm x 0.20 mm	Yellow
47011	Latex-free band 5.5 m x 14 cm x 0.25 mm	Green
47012	Latex-free band 5.5 m x 14 cm x 0.30 mm	Red
47013	Latex-free band 5.5 m x 14 cm x 0.35 mm	Blue
47014	Latex-free band 5.5 m x 14 cm x 0.40 mm	Black
47015	Latex-free band 5.5 m x 14 cm x 0.50 mm	Grey
47016	Latex-free band 5.5 m x 14 cm x 0.60 mm	Purple
LATEX FREE BANDS - 45 m		
47020	Latex-free band 45 m x 14 cm x 0.20 mm	Yellow
47021	Latex-free band 45 m x 14 cm x 0.25 mm	Green
47022	Latex-free band 45 m x 14 cm x 0.30 mm	Red
47023	Latex-free band 45 m x 14 cm x 0.35 mm	Blue
47024	Latex-free band 45 m x 14 cm x 0.40 mm	Black



## LATEX TONE LOOPS

### • 47040 SET OF 4 TONE LOOPS

The closed-loop flat band fits comfortable around the upper and lower legs.

It helps to exercise the muscles of hips and legs.


Set includes 4 below loops: each in a different colour-coded level.

Tone loop 18 mm x 58 cm x 1.4 mm

Tone loop 24 mm x 58 cm x 1.4 mm

Tone loop 24 mm x 58 cm x 1.6 mm

Tone loop 30 mm x 58 cm x 1.6 mm



47040


## EXERCISE MATS

### • 47070 EXERCISE MAT 180x60xh 1.6 cm - light blue

### • 47080 EXERCISE MAT WITH HANG RING - 180x60xh 1.6 cm - green

Thick mats with sponge-like foam structure offer comfortable feeling. The closed-cell foam structure resists moisture.

Easy roll for storage.



This model has 2 rings to allow hang on the wall or on the rack

## RESISTIVE EXERCISE TUBING

Tubing is an affordable and convenient training tool which provides effective upper and lower-body workout.

Elastic properties for resistive and strengthening exercise.

Latex exercise tubing

47063



GIMA Code	LATEX EXERCISE TUBING	Thickness	Strength	Length
47060	Latex tube	1.5 mm	Yellow	25 m
47061	Latex tube	2 mm	Green	25 m
47062	Latex tube	2.5 mm	Red	25 m
47063	Latex tube	3 mm	Blue	25 m
47064	Latex tube	3.5 mm	Black	25 m

Available also with two pre-attached durable foam covered handles for comfort and grip.


5 colour-coded resistance levels available.



GIMA Code	LATEX TUBE WITH TPR HANDLES	Strength	Length
47050	Latex tube with TPR handles	Yellow	125 cm
47051	Latex tube with TPR handles	Green	125 cm
47052	Latex tube with TPR handles	Red	125 cm
47053	Latex tube with TPR handles	Blue	125 cm
47054	Latex tube with TPR handles	Black	125 cm




## HAND/FINGER/WRIST EXERCISERS



Ø 36 cm

- 47130 GRIP TRAINER - X-light
- 47131 GRIP TRAINER - light
- 47132 GRIP TRAINER - medium
- 47133 GRIP TRAINER - heavy
- 47134 GRIP TRAINER - X-heavy

Releases typing and mousing tension. Improves hand and finger flexibility. Excellent for finger and wrist strengthening and rehabilitation.



- 47170 TPR FLEX BAR - light
- 47171 TPR FLEX BAR - medium
- 47172 TPR FLEX BAR - heavy

Flex bar is a flexible, durable resistance device with ridge surface for enhanced grip during use. It is used to improve grip strength by bending, twisting or vibrating.



- 47160 SET OF 3 FINGER EXERCISERS

Unique design for rehabilitation, excellent stress-reliever for users. Simply insert fingers into circles and stretch. Multiple resistance level available, set of light, medium and heavy resistance.




- 47180 POWER GRIP - light
- 47181 POWER GRIP - medium
- 47182 POWER GRIP - heavy

Develop finger flexibility, strength and coordination. Increase hand, wrist and forearm strength. Improve the injured finger recovery.




- 47140 SQUEEZE EGG - X-soft
- 47141 SQUEEZE EGG - soft
- 47142 SQUEEZE EGG - medium
- 47143 SQUEEZE EGG - firm
- 47144 SQUEEZE EGG - X-firm

These TPE (Thermoplastic elastomers) eggs offer variable resistance training for hands and fingers. Help grip strengthening and reduce stress.



- 28790 HAND GRIP METER - plastic
- Indicator remains at maximum until reset and is calibrated 0-75 kg. Size 20x15 cm. Sold in a blister. Manual in: GB, FR, IT, ES.

## BALANCE AND WEDGE CUSHION




47090

- 47090 BALANCE CUSHION Ø 35 cm

- 47095 WEDGE CUSHION

Air filled cushions made of soft, pliable material. Both have two surfaces: smooth and bubbled which provide two kinds of user experience. Great for improving intramuscular coordination as well as balance training ergonomic sitting and rehabilitation.

Maximum load: 136 kg (300 lb)




47095

## RESISTANT BALLS

- 47102 BURST RESISTANT BALL - Ø 55 cm
- 47103 BURST RESISTANT BALL - Ø 65 cm
- 47104 BURST RESISTANT BALL - Ø 75 cm

Designed for dynamic workouts that incorporate moderate level of resistance.

Deflate slowly if punctured. 136 kg (300 lb) burst resistance level.




47104

136 kg burst resistance level

47103

47102

## MASSAGE BALLS



- 47120 MASSAGE BALLS

Set of 3 massage balls Ø 6, 7, 8 cm



## NASAL WASH



28084

• **28084 SINUS A NASAL WASH - for adult** - bottle 120 ml + 12 saline sachets  
Nasal wash helps to remove the sinus symptoms such as runny nose, nasal dryness and nasal congestion. By performing a nasal wash, you can remove particles such as pollen and dust in order to reduce the mucous membranes inflammation and make it more resistant to allergies.

## HUMI-RAINBOW

Mist output can be adjusted in direction (360° rotative head) and speed (adjustable knob)



28070

• **28070 HUMI-RAINBOW HUMIDIFIER**  
A cold-mist ultrasonic humidifier with an attractive design and cromatic 7-led colours change  
• **28071 BALSAMIC ESSENCE - pine**  
• **28072 BALSAMIC ESSENCE - citrus**



### TECHNICAL SPECIFICATIONS

Power feeding: AC 110-240V / 50-60 Hz  
Max mist output: 280 ml/h  
Water Tank capacity: 2.8 l  
Suitable for room size: min 10, max 25 m<sup>2</sup>  
Max operating hours (non-stop): 10 hours  
Size (individual box): Ø 19xh 30 cm - Weight: 1.4 kg

## VAPINAL INHALER



MADE IN ITALY

• **28110 VAPINAL THERMAL WATER INHALER**  
Warm jet mineral water inhaler ideal for home spring water inhalation treatment. It delivers hot humid steam through a nozzle working with the Venturi system and mixing the steam with the principles of thermal water. Stainless steel boiler. Supplied with polycarbonate ampulla.  
• **28112 VAPINAL AMPULLA - spare part**

### TECHNICAL SPECIFICATIONS

Capacity: 800 ml  
Steam boiler in stainless steel  
Security valve and thermostat  
Operating voltage: 230 V - 50 Hz - 600 Watt  
Heating time: 5-8 min  
Inhalation time (for 1 l): 12-15 min

## MAMILAT BREAST PUMP

• **28148 MAMILAT - BREAST PUMP - 230 V - 50 Hz**  
Easily transportable from one maternity ward to another, or for use at home. Made of highly heat-resistant, electrically insulated plastic material in conformity with the latest European safety standards. Working time: 20 minutes ON, 40 OFF. Suction adjustment knob. Supplied with 2 polycarbonate milk bottles (150 cc and 250 cc) antibacterial and hydrofobic filter, set of tubes 6x10 mm, breast shield, PVC air tube.

• **28229 HYDROPHOBIC ANTIBACTERIAL FILTER - spare**

• **28149 SPARE KIT**  
Includes two plastic bottles (125 cc and 250 cc) nipple shield, filter and tubes.



CE

MADE IN ITALY

5 languages manual:  
IT, GB, ES, FR, DE.

28149

### TECHNICAL SPECIFICATIONS

Regulator for suction intensity: max suction -0.33 bar (-248 mmHg)  
Operating voltage: 220-230 V - 50/60 Hz - available on request 110 V - 60 Hz  
Max flow (air litres/min): 14 l/min  
Power consumption: 184 VA  
Size: 235x190x165 mm  
Noise level: 63 dB  
Weight: 2.2 kg  
Norms: CEI 62-5 (IEC601-1). IP Protection Class: IP21

28148

## BREAST PUMPS

• **41700 MANUAL BREAST PUMP**

• **41701 SINGLE ELECTRIC BREAST PUMP**

Compact and lightweight breast pumps for efficient and discreet pumping. Easy to assemble, use and clean. Supplied with breast shield, nipple with cover, milk bottle with lid, multilingual box and manual (GB, FR, IT, ES, PT, DE).



CE 0197

All parts that touch breast milk are made without BPA, phthalate free

2 phase design, easy for stimulation and expression

10 vacuum levels

Soft and comfortable breast shield  
Graduated bottle (ml/Oz)

41701

• **41706 BREAST MILK BOTTLE 150 ml with lid - set of 3 - spare**

• **41705 BREAST SHIELD + NIPPLE - spare**

• **41708 AC ADAPTER for 41701 - optional**

### TECHNICAL SPECIFICATIONS

	41700	41701
Vacuum mmHg:	- 250	stimulate: - 60-130 expression: - 60-250
Weight:	159 g	265 g
Size mm:	205x186x90	129x129x55
Operation:	manual	4AA batteries not included or AC adapter (optional)



CE

41700



## MESH NEBULIZER

### • 28066 MESH NEBULIZER

Small, handy, lightweight nebulizer for the treatment of respiratory diseases such as acute inflammation, tracheitis, bronchitis, swelling and pain in throat. It can operate with 2xAA standard batteries or USB cable.

- maximize the benefits of medicine
  - portable, handheld design (117 mm height)
  - ultra-low noise, ultra-light only 104g
  - one-button operation for easy use
  - for adult and child: noiseless use and compact design allow to make inhalation even while children are sleeping.
- Supplied with adult and child mask, mouthpiece, 2xAA batteries, USB cable, carrying bag, multilingual manual and box (GB, IT, FR, ES, PT, DE).

### • 28067 RESPIRATORY ACCESSORY KIT

(adult and child mask, mouthpiece) - spare

### • 28068 NEBULIZER HEAD - spare



28068

#### TECHNICAL SPECIFICATIONS

Power supply:	2xAA batteries or USB cable DC 5V
Ultrasonic frequency:	approximately 110kHz
Nebulizer rate:	≥0.25ml / min
Max. / min. liquid volume:	10ml / 0.5ml
MMAD	approximately 4µm
Nebulizing head life:	180 hours
Battery life:	60 minutes
Shutdown:	automatic without liquid
Safety level:	Type BF, Class II, IP 22



## MYNEB NEBULIZER

### • 28073 MYNEB NEBULIZER - piston

Compact, fast and silent nebulizer. Suitable for the treatment of the respiratory tract diseases, bronchial and asthmatic diseases, allergies.

Ideal for nebulizing any medicine, even oily ones such as cortisones essentials oils, and active ingredients with solid elements (suspensions). Supplied with carrying bag, fasterjet bulb, adult and pediatric mask, air tube, mouthpiece and nosepiece.

Multilingual box and manual: GB, FR, IT, ES, DE. Class IIa.

### • 28093 FILTER - spare - box of 3



28073

MADE IN ITALY

COMPACT AND SILENT


#### TECHNICAL SPECIFICATIONS

AC adapter:	input 100-240 V - 50/60 Hz - 0,6 A
	output 12 V - DC 2A
Operating cycle:	30/30 min. ON/OFF
Noise level:	51 dB
Nebulization rate:	0.45 ml/min with NaCl 0.9%
Air Flow:	12 l/min
Max pressure:	165 kPa/1.65 bar
Particle size:	75% < 5 µm (NaCl 0.9%)
Size and weight:	132x140xh 60 mm - 450 g

## ACCESSORIES FOR ANY BRAND OF NEBULIZER

### ACCESSORIES FOR NEBULIZER

Gima offers different nebulizer bulbs with their line of accessories, suitable for any brand of nebulizer.



28158

28157 Includes mouth piece and nasal prong

28146

28139

28140

28147

Standard accessories with Corsia, Eolo, Mistral, Myneb

### FASTERJET BULB with Valve System

A new designed Jet Nebulizer capable of delivering any medication in a very short time with a high amount of respirable particles. The Valve System makes therapy extremely efficient by reducing the amount of wasted medication while optimizing the output to the patient.

#### TECHNICAL SPECIFICATIONS FASTERJET

Capacity:	16 ml	Neb rate:	0.60 ml/min
Respirable volume:	<5 µm 80%		
Residual volume:	0.8 ml		
MMAD (Mass Median Aerodynamic Diameter):	2.7 µm		

Fasterjet bulb: For delivering any medication in a very short time

28163 + 28165



28164

28166

28168

28169

28145

GIMA code	NEBULIZER ACCESSORIES	Compatible with
	Standard accessories with Myneb, Corsia, Eolo, Mistral	
28158	PVC connection tube - 1m	all nebulizers
28139	Nebulizer bulb	all nebulizers
28146	Facemask - adult* - replaces 28143	bulb 28139/28140
28147	Facemask - paediatry* - replaces 28144	bulb 28139/28140
28157	Mouthpiece - nasal prong	bulb 28139/28140
28138	Nebulizer kit	all nebulizers
	adult and pediatric facemask, pvc-tube, bulb, nasal prong, mouthpiece	
28140	Nebulizer bulb	all nebulizers

\*With elastic

GIMA code	NEBULIZER ACCESSORIES	Compatible with
28163	Fasterjet bulb* with Valve System	all nebulizers
28164	Nebjet bulb** with Double Venturi Effect	all nebulizers
28165	Mouthpiece bi-valve	bulb 28163
28166	Mouthpiece	bulb 28164,
28167	Nasal Prong	bulb 28164, 28163
28168	Facemask-adult***	bulb 28164, 28163
28169	Facemask-pediatry***	bulb 28164, 28163
28145	Filter - spare	28130/1/2/3/4/5

\*Standard with Happyneb II, Hospyneb

\*\*Standard with Happyneb I, III, Betaneb

\*\*\*Without elastic

## HAPPYNEB NEBULIZERS FOR DOMESTIC USE - PISTON

• 28132 HAPPYNEB II NEBULIZER - piston 230V- Faster-Jet

• 28135 HAPPYNEB III NEBULIZER - piston 230V

Happyneb stylish and portable piston nebulizer for a quick and efficacious aerosol therapy.

**Reliable, practical and safe.**

Noiseless and lubrication free.

Unit includes an air filter to be replaced every 70 applications, and handle for easy carrying.

It is built in accordance with European Standard EN 60601-1.

**5 languages box and manuals:**

GB, FR, IT, ES, DE

• 28145 FILTER - spare

MADE IN ITALY

Faster-jet bulb  
Nebulizing time: 1 cc  
about 3 minutes



CE 0051

### NEBULIZER TECHNICAL DATA

Happyneb III with Nebjet Happyneb II with Fasterjet

Capacity:	12 ml	16 ml
Respirable volume < 5 µm	75%	80%
MMAD (Mass Media Aerodynamic Diameter)	2.32 µm	2.7 µm
Neb rate	0.45 ml/min	0.60 ml/min
Residual volume	0.7 ml	0.7 ml

### STANDARD ACCESSORIES

Adult and pediatric face mask	Mouthpiece
Nasal prong	Fasterjet bulb (28132 only)
Connection tubing	Nebjet bulb (28135 only)

### TECHNICAL SPECIFICATIONS

28132 - HAPPYNEB II 28135 - HAPPYNEB III

Voltage:	230V/50 Hz	
Maximum pressure:	280 kPa	250 kPa
Operating pressure:	110 kPa	90 kPa
Air flow:	15 l/min	14 l/min
Dimensions:	31x22x13 cm	
Weight:	2.3 kg	2 kg
Noise level	58 db	58 db
Temporary use:	Continuous use	30/30 min ON/OFF
Class of risk - norms	Ila - Class II, Type B	

## ATOMIZER 2 SPEEDS, PISTON NEBULIZER FOR FAMILY USE

• 28094 ATOMIZER NEBULIZER - 2 speeds


Piston-type compressor with 2 speeds for family use. With accessory compartment separated from cord compartment for improved hygiene.

• 28093 FILTER - spare - box of 3

### TECHNICAL SPECIFICATIONS

Operating voltage:	230 V - 50 Hz
Operating cycle:	continuous
Operating pressure:	speed 1: 45 kPa - speed 2: 60 kPa
Air Flow:	speed 1: 8 l/min - speed 2: 11 l/min
Nebulization rate:	speed 1: 0.2 ml/min - speed 2: 0.35 ml/min
Particle size:	80% < 5 µm
Max pressure:	1.85 bar / 185 kPa
Weight:	1.4 kg
Noise level:	56 db

Class of risk: Ila



Standard accessories

MADE IN ITALY

### STANDARD ACCESSORIES

Nebjet bulb with connector  
Adult and child mask  
Mouth piece and nose piece  
Air tube and 3 air filter



CE 0051

28094

Accessories compartment

## EOLO NEBULIZER - PISTON

CE 0476

• 28097 EOLO NEBULIZER - piston

• 28091 EOLO NEBULIZER - piston - UK plug

Innovative, portable, easy to use nebulizer for home use, recommended to nebulize antibiotics and bronchodilator drugs. Plastic body with high thermal insulation. Supplied with adult and pediatric face mask, bulb, mouthpiece, air tubing, air filter.

Multilingual user manual and box (GB, FR, IT, DE, ES, PT, GR, PL\*, Arabic\*). Warranty 2 years.

• 28095 FILTER - box of 20 pcs.

MADE IN ITALY

### TECHNICAL SPECIFICATIONS

	28097 EOLO	28102 MISTRAL
Operating voltage:	230V - 50/60Hz - 170VA 110V or 60Hz on request	230V - 50/60 Hz - 170VA
Operating pressure:	1.1 bar	1.1 bar
Air flow:	14 l/min	14 l/min
Nebulization rate	0.4 ml/min	0.35 ml/min
Particle size	< 5 µm	< 5 µm
Max Pressure:	2.5 bar	2.5 bar
Dimensions:	22x14.5x12 cm - 1.7 kg	13x8.9x14.6 cm - 1.5 kg
Noise level (EN 13544-1)	55 db	60 db
Class of risk	Ila	Ila
Norms:	insulation class, Type B	insulation class, Type BF

\*Box only, not manual



28097

## MISTRAL NEBULIZER - PISTON

• 28102 MISTRAL NEBULIZER - piston

Compact portable nebulizer for home use.

Duty cycle: 20 min on / 40 min off.

Supplied with Hi Flo bulb, adult and pediatric mask with string, mouthpiece, nose piece, air tubing and air filter.

Multilingual user manual and box: GB, FR, IT, ES, PT, DE.

• 28088 FILTER - box of 20

• 28103 CARRYING BAG - optional

CE 0476



28102



# NEBULIZERS FOR PROFESSIONAL AND HOSPITAL USE


**28089**

Nasaljet is a quick effective nasal irrigation device for rinsing the nasal and rhino-pharyngeal cavities


**28090**
**CONTINUOUS USE COMPRESSOR**


## PROFESSIONAL NEBULIZERS

Piston compressor nebulizers for professional and home care use. They embody all the dictates of modern aerosol therapy techniques. Reliable and simple to use, also by inexperienced users. Manual: GB, FR, IT, DE, ES.

GIMA code	PROFESSIONAL NEBULIZER
<b>28134</b>	Hospyneb professional
<b>28090</b>	Comp-a neb professional
<b>28089</b>	Nasaljet
<b>28176</b>	Compressor - spare for 28134
<b>28152</b>	Connecting rod and crank group 3AC260 - spare for 28134
<b>28153</b>	Cylinder 3A1062 - spare for 24134, 28090
<b>28145</b>	Filter - spare

- **28105 CORSIA PROFESSIONAL NEBULIZER - piston**
- **28092 CORSIA PROFESSIONAL NEBULIZER - piston - without manometer**

Piston-type compressor nebulizers designed for continuous use. High performance with any type of drug, ideal for intensive hospital and clinic use. Recommended for atomizing antibiotics and bronchodilator drugs. Manufactured with high thermal


**28105**
**CONTINUOUS USE COMPRESSOR**

**28134**

## TECHNICAL SPECIFICATIONS

	HOSPYNEB	COMP-A NEB
Operating voltage:	230 V - 50/60 Hz	230 V - 50 Hz
Size:	28x19xh 17 cm	19.6x35.7xh 18.5 cm
Max pressure:	350 kPa (3.5 bar)	250 kPa
Noise level:	60 dBA	55 dBA
Operating pressure:	0-130 kPa (0-1.3 bar)	0-110 kPa
Weight:	4.1 kg	2.5 kg
Air Flow:	15 l/min	
MDD class:	Ila	

## STANDARD ACCESSORIES

Fasterjet nebulizer with valve system  
Nosepiece irrigation (polypropylene)  
Mouthpiece (polypropylene) with valve (silicone)  
Adult and child mask (PVC DEHP free)  
Air tube (PVC DEHP free) and spare filter.  
Nasaljet (only with 28090).



and electric insulation plastic chassis in accordance with the latest European Safety regulations. The oil-free piston compressor has long durability and is equipped with the highly efficient HI-FLO jet nebulizer to guarantee quick and accurate drug delivery. Easy to handle and transport.

- **28104 FILTER - spare - box of 2**
- **28217 2 PIN British plug - optional**

## TECHNICAL SPECIFICATIONS

Operating Voltage:	220-230 V - 50/60 Hz
Power consumption:	184 VA
Max pressure:	250 kPa (2.5 bar)
Air flow:	16 l/min
Operating pressure:	130 kPa (1.30 bar)
Operating air flow:	5.2 l/min at 130 kPa
Nebulization rate:	0.50 ml/min with 4 ml solution
MMAD:	3.25 µm GSD: 3.45
Size:	255x190xh 105 mm
Noise level:	approx 57 db
Weight:	2.2 kg

## STANDARD ACCESSORIES

HI-FLO Jet bulb	Mouthpiece	Nose piece
Adult and child mask	Air tube and air filter	
Multilingual user manual and box: GB, FR, IT, ES, DE, PT, RO, RU*, PL*, GR*		

\*Box only

**28092**


# NEBULIZER FOR INTENSIVE HOSPITAL USE

- **28060 CLINEB PRO NEBULIZER - piston**

High performing piston nebulizer for administration of any kind of drug, ideal for intensive hospital and clinical use. Its structure is made of a high thermal and electrical insulated plastic in accordance to safety European standards. Long life dry piston compressor and bulb with a valve system that allows to adjust the nebulization speed.

Class IIa - Insulation class (EN60601-1): Class II Type B.

- **28062 BULB - spare**
- **28063 FACE MASK - adult - spare**
- **28064 FACE MASK - pediatric - spare**
- **28217 2 PIN British plug - optional**

## TECHNICAL SPECIFICATIONS

Operating Voltage:	230 V - 50/60 Hz	Power consumption:	110 VA
Max pressure:	250 kPa (2.5 bar)	Air flow:	16 l/min
Operating pressure:	130 kPa (1.30 bar)	Operating air flow:	5.2 l/min at 130 kPa

MADE IN ITALY

## STANDARD ACCESSORIES

Bulb with valve  
Mouthpiece  
Adult and child mask  
Air tube and air filter  
Multilingual manual: GB, FR, IT, ES, DE


**28060**

# VEGA SUCTION UNITS, HIGH VACUUM, LOW AND HIGH FLOW

CE 0476

HIGH VACUUM  
HIGH FLOW

MADE IN ITALY



28211

28210

## VEGA SUCTION UNITS

A line of stylish, compact and reliable aspirators for small surgery. Silent, high flow and maintenance - free pumps allow long product life and durability. Recommended for nasal aspiration, oral aspiration, tracheal aspiration of body liquids (mucus, catarrh or blood) in adults or children. Equipped with vacuum regulator continuously adjustable, vacuum indicator, unbreakable 1,000 ml or 2,000 ml Makrolon® jar, autoclavable at 121°C with safety float control valve to prevent overflow. Optional APEC® jar autoclavable at 143°C. Manufactured in electric and thermal insulated plastic body.

**Flovac® autoclavable jars and disposable collection system:** in addition to standard autoclavable jar, a disposable collection system is available, composed by a rigid reusable jar, a polyethylene disposable liner with hermetically sealed cover and hydrophobic, antireflux, antibacterial filter operating as an overflow valve.


28211  
+  
28213

1 l polycarbonate  
autoclavable jar  
with overflow  
safety valve

28252  
Adaptor to connect catheter  
to silicone tube


28209

## STANDARD ACCESSORIES

Autoclavable jar (1 or 2 l) with overflow valve system  
Antibacterial and hydrophobic filter  
Set of silicone tubes 6x10 mm  
Conical connector for probes  
6 languages user manual (GB, FR, IT, DE, ES, PT)

28229



## TECHNICAL SPECIFICATIONS

	28209 VEGA UNO	28210 VEGA	28205, 28211 SUPERVEGA
Operating Voltage:	220-230 V - 50/60 Hz 120-127 V - 60 Hz (on request)	220-230 V - 50/60 Hz 110 V - 60 Hz (on request)	220-230 V - 50/60 Hz or 110-127 V - 60 Hz
Power consumption:	184 VA	184 VA	110 VA
Bottle capacity:	1,000 ml	1,000 ml	1,000 ml or 2,000 ml
Flow (air litres/min):	15 l/min	16 l/min	40 l/min
Max suction:	-0.75 bar (563 mm/Hg)	-0.75 bar (563mm/Hg)	-0.80 bar (600mm/Hg)
Operating cycle:	continuous	continuous	continuous
Noise level:	59.6 dBA	60.5 dBA	60.5 dBA
Size - weight:	25x19x16.5 cm - 2.2 kg	35x21x18 cm - 2.5 kg	35x21x18 cm - 3.6 kg
Norms:	EN 60601-1-1, EN 60601-1-2, EN 60601-1-11, 93/42/EEC		

GIMA code	VEGA SUCTION ASPIRATOR	Operating power	Flow
28209	Vega Uno	220-230 V - 50/60 Hz	15 l/m
28210	Vega	220-230 V - 50/60 Hz	16 l/m
28211	Super Vega 1l	220-230 V - 50/60 Hz	40 l/m
28205	Super Vega 1l with footswitch*	220-230 V - 50/60 Hz	40 l/m
28212	Super Vega 2l	220-230 V - 50/60 Hz	40 l/m
28189	Super Vega 1l	110-127 V - 60 Hz	40 l/m

\*With proximity: no touch ON/OFF function



GIMA code	SPARE ACCESSORIES FOR VEGA AND TOBII LINE
28229	Hydrophobic, antibacterial filter
28226	121°C autoclavable jar 1 l with cover and overflow system
28236	121°C autoclavable jar 2 l with cover and overflow system
28227	Cover and overflow valve system for 28226 and 28236
28185	143°C autoclavable jar 1 l with cover and overflow system
28186	143°C autoclavable jar 2 l with cover and overflow system
28184	Cover and overflow valve system for 28185 and 28186
28271	Flovac® disposable liner 1 l (cover + bag)
28268	Flovac® disposable liner 1 l (cover + bag) - box of 50
28270	Flovac® disposable jar for disposable liner 1 l
28273	Flovac® disposable liner 2 l (cover + bag)
28269	Flovac® disposable liner 2 l (cover + bag) - box of 50
28272	Flovac® jar for disposable liner 2 l Ø 13 cm top, 9.5 cm bottom
25468	Silicone tube 6x10 mm - roll of 30 m
28252	Adaptor to connect catheter to silicone tube
	Suction catheter - see at page 51
28213	Trolley for Vega and Super Vega (not for Vega Uno)
28276	Vacuum indicator for Vega and Super Vega (not for Vega Uno)
28217	2 pin British plug - optional



## PROFESSIONAL ASPIRATORS - HIGH VACUUM



CE 0051  
EN ISO 10079-1  
Class I  
Type B

MADE IN ITALY

28280-1

28244-6

1 l Autoclavable Jar

### ASPEED PROFESSIONAL SURGICAL ASPIRATORS

Piston-type continuous cycle electric aspirators give high performance and great durability. Equipped with a protective thermal cut-out relay. They require no maintenance or lubrication. A motor-protector cap totally prevents aspirated

liquids or secretions from reaching and damaging the vacuum pump. Ideal for clinical use.

GIMA code	ASPEED ASPIRATORS	Power	Pump	Case
28244	Aspeed 15 l	230 V	single	metal
28245	Aspeed 22 l	230 V	double	metal
28280	Aspeed 2 15 l	230 V	single	plastic
28281	Aspeed 2 22 l	230 V	double	plastic

GIMA code	ACCESSORIES AND SPARES FOR ASPEED
28255	Hydrophobic bacterial filter
28258	Autoclavable jar 1l with cover
28259	Disposable suction liner
25480	Silicone tube 6x12 mm - roll of 30 m
28254	Adaptor to connect catheter to silicone tube
28261	Adaptor kit to use jar 1l (28258) with ASPEED manufactured before 2007

**STANDARD ACCESSORIES**  
Autoclavable polycarbonate jar 1,000 cc with safety valve (overflow protection)  
Disposable suction liner 1 l  
Antibacterial hydrophobic filter  
Sterile disposable cannula  
Sterile manual flow regulator  
Set of atoxic sterilizable silicone tubes  
Power Cable  
User Manual: GB, FR, IT, DE, ES

TECHNICAL SPECIFICATIONS		ASPEED		ASPEED 2	
		28244	28245/6*	28280	28281
Operating voltage:		230 V-50 Hz		230 V - 50/60 Hz	
		*110-60 Hz		other voltage on request	
Bottle capacity:		1 l	1 l	1 l	1 l
High vacuum:		high flow	high flow	low flow	high flow
Air flow:		15 l/min	22 l/min	15 l/min	22 l/min
Adjustable vacuum level:		0 ÷ -0.85 bar (0 ÷ -85 kPa)			
Weight:		3.5 kg	4.2 kg	2.7 kg	3.4 kg
Case material:		metal		plastic	
Noise level:		53 dBA	63 dBA	63 dBA	63 dBA



## ASPEED 3.0 PROFESSIONAL SINGLE PUMP ASPIRATOR

- 28279 ASPEED 3.0 ASPIRATOR 16 l/min - 1 l
- 28319 ASPEED 3.0 ASPIRATOR 16 l/min - 2 l

Portable, compact reliable aspirator ideal for small surgery. Piston type continuous cycle electric medical device. High vacuum low flow. No maintenance or lubrication.

MADE IN ITALY

TECHNICAL SPECIFICATIONS	
Operating voltage:	230 V - 50 Hz
Power consumption:	max 150 VA
Bottle capacity:	1 l (28279) or 2 l (28319)
High vacuum:	low flow
Air flow:	16 l/min
Adjustable vacuum level:	0 ÷ -0.65 bar (0 ÷ -65 kPa)
Size:	300x170xh 260 mm
Weight:	2.3 kg
Noise level:	65 dBA
Operating cycle:	continuous
Class:	II
Type:	BF

**STANDARD ACCESSORIES**  
Autoclavable polycarbonate jar 1,000 cc or 2,000 cc with safety valve (28258 or 28294)  
Disposable liner 1 l (28259) only for 28258  
Antibacterial hydrophobic filter  
Sterile disposable cannula  
Sterile manual flow regulator  
Set of atoxic sterilizable silicone tubes  
Power Cable  
User Manual: GB, FR, IT, DE, ES



GIMA code	ACCESSORIES AND SPARES FOR ASPEED
28255	Hydrophobic bacterial filter - spare
28258	Autoclavable jar 1 l with cover
28294	Autoclavable jar 2 l with cover
28259	Disposable suction liner 1 l - spare
25480	Silicone tube 6x12 mm - roll of 30 m
28254	Adaptor to connect catheter to silicone tube

## SUPERVEGA BATTERY SUCTION ASPIRATORS

- 28243 SUPERVEGA BATTERY - plastic case - 16 l/min
  - 28247 SUPERVEGA BATTERY WITH FOOTSWITCH - plastic case - 16 l/min
  - 28190 SUPERVEGA BATTERY - plastic case - 36 l/min
  - 28248 SUPERVEGA BATTERY WITH FOOTSWITCH - plastic case - 36 l/min
  - 28213 TROLLEY FOR SUPERVEGA see page 201
- Professional, portable suction units for body, oral, nasal or tracheal liquids aspiration in adults or children. Supplied with three different operation options: AC/DC adapter, internal lead rechargeable battery and 12 V make it a versatile unit approved for NON-STOP operation without overheating. Visual and acoustic alarm indicating low battery level. Ergonomic handle ensures a comfortable and secure grip. Bottle with safety float control valve to prevent overflow.



28243

 1 l jar with  
overflow safety  
valve

28190

36 l/min

### TECHNICAL SPECIFICATIONS

Suction power:	16 air l/min (28243), 36 air l/min (28190)
Max suction:	28243, 28247: -0.75 bar (563 mm/Hg), 28190, 28248: -0.80 bar (600 mm/Hg)
Operating Voltage:	100-240 V - 50/60 Hz
Battery autonomy:	approx 80 min (28243), 60 min (28190)
Recharging time:	240 minutes
Noise level:	63 dBA (28243), 65.5 dBA (28190)
Size - Weight:	350x210x180 mm - 3.5 kg (28243), 4.05 kg (28190)
Norms:	Class II Type BF EN 60601-1-1, EN 60601-1-2, EN 60601-1-11, 93/42 EEC

CE 0476



### STANDARD ACCESSORIES

Bottle 1 l - autoclavable at 121°C  
AC/DC universal adapter (100-240V - 50-60Hz)  
Silicone tubing set  
Anti-bacterial filter  
Suction catheter  
Cigarette lighter adaptor (12V 4A)  
User manual (GB, IT, FR, DE, ES, GR, PL, RO, PT)

## SUPERVEGA 118 AND EVO BATTERY SUCTION ASPIRATORS

- 28240 SUPERVEGA 118 AMBULANCE BATTERY ASPIRATOR
- 28241 SUPERVEGA 118 BATTERY ASPIRATOR
- 28182 SUPERVEGA EVO AMBULANCE BATTERY ASPIRATOR
- 28183 SUPERVEGA EVO BATTERY ASPIRATOR

Electric medical and portable devices for nasal, oral and tracheal aspiration of body fluids in children or adults. Two or three options of operation: by 100-240 V power feeding, 12 V car adapter (28183 and 28241 only) or internal rechargeable battery.

Equipped with a long-life brushless motor eliminating smell and coal residuals.

**Large LCD (28182 and 28183 only)**

Clear reading of vacuum values along with soft keys for vacuum adjustment increase the accuracy of aspiration.

**FEEDBACK system and RPM (28182 and 28183 only)**

System controls and manages the power of aspiration, providing a long autonomy to the lightweight lithium-ion battery and quite noise level during operation. Built-in engine RPMs control with basic electronics.


**PROXIMITY function: NO-TOUCH ON/OFF**

It prevents and avoids cross-contamination in-between patients.

**Various options of jars**

Standard autoclavable (121°C) Makrolon® polycarbonate, optional FLOVAC® disposable liners or autoclavable (143°C) APEC® polycarbonate.

In compliance with EN 60601-1-11 (only 28183, 28241) for use in the home healthcare environment and carries IP22 degree protection. The ambulance wall bracket is 10g dynamically tested according to the EN 1789:2007 European norm (only 28182, 28240).



28240 - 28241



28182 - 28183

MADE IN ITALY

Carrying handle

PROXIMITY

RPM FEEDBACK\*

LITHIUM BATTERY

LCD DISPLAY\*

 AUTOMATIC  
VACUUM  
CONTROL

\*Only 28182, 28183


 AC/DC adapter +  
car adapter  
(28183, 28241 only)

 Wall bracket  
for ambulance  
(28182, 28240 only)

### STANDARD ACCESSORIES

Polycarbonate jar 1,000 ml with overflow valve system  
Silicone tube set with conical connector  
Universal power adapter (100-240V - 50/60 Hz)  
12V car adapter (only 28183, 28241)  
Support bracket for ambulance 20x16x16 cm (only 28182, 28240)  
Antibacterial filter  
Carrying bag (only 28182, 28240)  
User Manual GB, FR, IT, DE, ES

### TECHNICAL SPECIFICATIONS

Motor:	Oil-less and maintenance-free piston pump
Power:	Internal rechargeable Lithium battery (14.8 V - 5.2 A) - Autonomy 70 min Car-ambulance adapter (12 V - 4 A) - only 28183, 28241 AC/DC adapter 110-240 V, 50-60 Hz - only 28183, 28241 Recharge from support bracket - only 28182, 28240
Max vacuum (adjustable):	-0.75 Bar; -75 kPa; -563 mmHg
Max free air flow rate:	26 l/m (28182, 28183), 36 l/m (28240, 28241)
Size:	35x19x15 cm Weight: 2.7 kg
Duty cycle:	non stop operation (by mains or 12 V only)
Noise level min/max:	46.7/61.8 dBA (28182/83), 54.7/68.2 dBA (28240/41)

## ACCESSORIES FOR SUPERVEGA, SUPERVEGA 118, SUPERVEGA EVO

GIMA code	SPARE ACCESSORIES FOR SUPERVEGA, 118, EVO
28229	Hydrophobic, 99% antibacterial filter
28226	121°C autoclavable jar 1 l with cover and overflow system
28227	Cover and overflow valve system for 28226
28185	143°C autoclavable jar 1 l with cover and overflow system
28184	Cover and overflow valve system for 28185
28271	Flovac® disposable liner 1 l (cover + bag)
28268	Flovac® disposable liner 1 l (cover + bag) - box of 50
28270	Flovac® container for disposable liner 1 l

GIMA code	SPARE ACCESSORIES FOR SUPERVEGA, 118, EVO
25468	Silicone tube 6x10 mm - roll of 30 m
28252	Adaptor to connect catheter to silicone tube
	Suction catheter - see at page 51
28242	Battery for SuperVega/Tobi (28243*/28240) - spare
28251	Battery for SuperVega (28190/28243**) - spare
28238	Li-Ion battery for SuperVega 118 and Evo - spare
28276	Vacuum indicator for SuperVega line (not for Evo)
28218	2 pin British plug - optional

\*Up to S.N. 2141 (3 LED)

\*\*Since S.N. 3000 (1 LED)



# MINIASPEED BATTERY PRO SUCTION ASPIRATORS



28206

## • 28206 MINIASPEED BATTERY PRO - metal case - 30 l/min

High vacuum portable medical device for professional surgical aspiration.

- it can operate at 12 V (car) power supply, rechargeable batteries or directly by mains supply
- its two cylinders electro-compressor ensure high performances and long life
- up to 45 min. of autonomy with fully charged battery
- with 99% antibacterial hydrophobic filter
- equipped with autoclavable jar with safety valve, disposable suction liner and carrying bag.

## • 28207 CARRYING BAG for MiniAspeed Pro and Plus - spare

Disposable suction liner inside autoclavable jar


28258 +  
28259

### TECHNICAL SPECIFICATIONS MINI ASPEED

Operating Voltage:	100-240 V 50/60 Hz AC - 14 V DC 4.28 A
Size:	370x100x240 mm
Weight:	5.8 kg (include kit)
Max suction:	-0.85 bar
Suction power:	30 air l/min
Noise level:	65 dBA
Norms:	MDD 93/42/ECC (class IIa - annex IX) IEC 60601-1, UNI ENISO 10079-1

### STANDARD ACCESSORIES

Autoclavable jar 1000 cc with safety valve	Anti-bacterial hydrophobic filter
Silicone tubing set Ø 6x12 mm	Multivoltage battery charger
Disposable suction liner	Cigarette lighter power cord.
Sterile cannula	Shoulder carrying bag
	User manual (GB and IT)



# MINIASPEED BATTERY EVO PROFESSIONAL SUCTION ASPIRATORS

- 28282 MINIASPEED EVO BATTERY SUCTION - 1 l
  - 28283 MINIASPEED EVO BATTERY SUCTION - 1 l for ambulance
  - 28284 MINIASPEED EVO BATTERY SUCTION - 2 l
  - 28278 MINIASPEED EVO BATTERY SUCTION - 2 l for ambulance
- Professional portable high flow - high vacuum aspirators with integrated rechargeable batteries. It works at 12 V power supply with batteries or directly by mains supply, continuously at 110-230 V while recharging batteries.

Up to 45 minutes of autonomy with fully charged battery.

### TECHNICAL SPECIFICATIONS

Operating voltage:	with internal battery DC 12 V - 4 Ah with power supply 100÷240 V ~ 50/60 Hz - 14 VDC 4,28A
Power consumption:	max 50 W
Battery autonomy:	about 45 minutes, recharging time approx 6 hours
Size:	134x378xh 263 mm
Weight:	4.7 kg (5 kg version for ambulance)
Bottle capacity:	1,000 or 2,000 ml
Flow:	30 air litres/min
Noise level:	65 dBA at 1 m
Operating cycles:	continuous (45 min battery autonomy)
MAX vacuum:	0 ± 85 kPa
Norms:	MDD 93/42/ECC (Class IIa - annex IX) EN60601-1(IEC 60601-1) / EN60601-1-2 (IEC 60601-1-2) UNI EN ISO 10079-1/ UNI CEI EN ISO 14971
Degree of protections against ingress of liquids:	IP34d (IEC 529) Class II - Type B




Wall bracket for ambulance with recharging system

### STANDARD ACCESSORIES

Autoclavable 1 or 2 l jar with safety valve	2 bacterial hydrophobic filters
Sterile disposable cannula CH14	User manual: GB, IT, FR, DE, ES
Sterile disposable manual regulator	Power supply cord - 2 m
Disposable silicone liner 1 l (28282-3 only)	Shoulder carrying bag
Wall bracket for ambulance (only 28278, 28283)	Multivoltage battery charger
Cigarette lighter power cord (28282, 28284 only)	Silicone tubing set Ø 6x12 mm



28282



# ACCESSORIES FOR MINIASPEED BATTERY PRO AND EVO

GIMA code	ACCESSORIES AND SPARES FOR MINIASPEED
25480	Silicone tube 6x12 mm - roll of 30 m
28254	Adaptor for catheter
28258	Autoclavable jar 1,000 ml (with cover)
28259	Disposable suction liner 1 l for use with 28258
28294	Autoclavable jar 2,000 ml (with cover) for 28278, 28284

GIMA code	ACCESSORIES AND SPARES FOR MINIASPEED
28255	Hydrophobic 99% bacterial filter
28153	Cylinder 3A1062 - spare
28263	Battery
28256	Power supply with cable

## SUPERVEGA SUCTION ASPIRATOR ON TROLLEY

Vacuum indicator  
Max suction:  
600 mm Hg -  
0.80 bar

Silicone tubing  
8x14 mm

2 l jar

28191



Adjustable  
suction knob

Fixed height  
75 cm

Multilingual user  
manual: GB, FR,  
IT, DE, ES.

MADE IN ITALY

- 28191 SUPERVEGA on trolley - suction 2x2 l jar
  - 28192 SUPERVEGA on trolley - suction 2x2 l jar with footswitch
- Continuously adjustable vacuum, with indicator. Silicone connection tube 8x14 mm. 2 jars 2 l, made of sterilizable polycarbonate (autoclavable at 121°C). Approved for NON-STOP operation without overheating. Suction power: 40 air litres/min. Steel painted frame, fitted with 5 star base.

### TECHNICAL SPECIFICATIONS

Size: 38x36xh 92 cm Weight 6.2 kg  
Operating voltage: 220-230 V - 50/60 Hz; other on request  
Power consumption: 110 VA  
Maximum suction: -0.80 bar (600 mm Hg)  
Flow: 40 air litres/minute  
Operating cycle: continuous  
Noise level: 61.5 dBA  
Norms EN 60601-1-1, EN 60601-1-2 - C € 93/42 EEC - Class II - Type B

Supervega  
on trolley  
also fits  
Flovac® jars  
28272 for  
disposable  
liners  
28273.  
See below

## SUPERVEGA BATTERY SUCTION ASPIRATOR ON TROLLEY

Silicone tubing 8x14 mm

- 28193 SUPERVEGA BATTERY on trolley - suction 2x2 l jar
  - 28197 SUPERVEGA on trolley - suction 2x2 l jar with footswitch
- Professional portable suction unit for the aspiration of body liquids, oral, nasal and tracheal aspiration in adults or children. Suction power of 36 l/min. Double collection jars on a stand with five castors for easy transport. Two different working options: AC/DC adapter or rechargeable battery make it a versatile suction unit approved for NON-STOP operation without overheating. Visual and acoustic alarm indicating low battery level, vacuum-meter (bar & kPa) and vacuum regulator.

### TECHNICAL SPECIFICATIONS

Operating voltage: 100-240 V - 50/60 Hz  
Internal rechargeable Pb battery: 12V - 4A  
Battery autonomy: 60 min  
Recharging: 240 min  
Operating cycle: continuous with AC/DC  
Flow: 36 air litres/minute  
Noise level: 65.5 dBA  
Size - Weight: 32x30xh 99 cm - 7.9 kg

MADE IN ITALY


Five antistatic wheels  
with brake  
User manual:  
GB, FR, DE, IT, ES

## ACCESSORIES AND SPARES FOR CLINIC PLUS, HOSPI PLUS, SUPERVEGA ON TROLLEY



**AUTOCLAVABLE JARS WITH OVERFLOW VALVE SYSTEM**  
Equipped with screw cover with handle for easy grip, autoclavable silicone o-ring for tight seal, overflow valve system integrated in the cover, clear graduated scale in ml with 100 or 200 ml intervals. Suitable for central vacuum systems and Gima suction units. Available in two types of polycarbonate, Makrolon® and Apec®.

GIMA code	AUTOCLAVABLE JARS	Compatible with
<b>JARS IN MAKROLON® AUTOCLAVABLE UP TO 121°C</b>		
28236	Jar 2 l with cover - Makrolon®	2 l aspirators
28227	Cover for jar 2 l	28236
28228	Jar 4 l with cover - Makrolon®	4 or 5 l aspirators
28223	Cover for jar 4 l	28228
28221	Jar 5 l with cover - Makrolon®	4 or 5 l aspirators
28225	Cover for jar 5 l	28221
<b>JARS IN APEC® AUTOCLAVABLE UP TO 143°C</b>		
28186	Jar 2 l with cover - Apec®	2 l aspirators
28184	Cover for jar 2 l	28186
28187	Jar 5 l with cover - Apec®	4 or 5 l aspirators
28188	Cover for jar 5 l	28187
<b>ANTIBACTERIAL, HYDROPHOBIC FILTERS</b>		
28237	Hydrophobic, antibacterial filter	D, E
28239	Hydrophobic, antibacterial filter	A, B, C



### FLOVAC® DISPOSABLE LINERS

Equipped with polyethylene disposable liner, hydrophobic filter, overflow system, reusable container with clear graduated scale in ml with 50 ml intervals.

GIMA code	FLOVAC® JARS AND DISPOSABLE LINERS	Compatible with
28272	Reusable jar for disposable liner 2 l	B, C, D, E (only 2 l)*
28273	Disposable liner 2 l cover+bag	28272
28274	Reusable jar for disposable liner 3 l	B, C, D, E (only 2 l)*
28275	Disposable liner 3 l cover+bag	28274
GIMA code	SPARES	Compatible with
25482	Silicone tube 8x14 - roll of 30 m	A, B, C, D, E
28253	Adapter to connect catheter to silicone tube	25482
	Suction catheter see at page	28253
28276	Vacuum indicator Ø 50 mm - spare	A, B
28277	Vacuum indicator Ø 60 mm - spare	C, D, E
28265	Bottom base	C, E
28266	Bottom base	B
28267	Bottom base	D
28217	2 Pin British Plug - optional	All

\*Suitable also for MPR line using optional 2 l ring

LEGEND: A: SuperVega on trolley, B: Clinic, C: Clinic Plus, D: Hospital, E: Hospi Plus



# HIGH VACUUM, HIGH FLOW HOSPITAL SUCTION ASPIRATORS



**CLINIC PLUS  
and HOSPI PLUS**

Size: 460x850x420 mm  
Weight: 20 kg

2 antistatic castors  
and 2 with brake

MADE IN ITALY



**CLINIC PLUS  
and HOSPI PLUS MPR**

4 antistatic castors with brake

**MPR SYSTEM  
Multi purpose rail**

Customized  
Hospi Plus MPR with  
1x2 l jar, 1x5 l jar and safety trap

**28151**

Multipurpose stainless steel rail  
for maximum versatility allows to  
hang any accessory. Suitable for  
MPR models only

**28154,  
28155,  
28156**

Rings for: 2 or 5 l autoclavable jars,  
2 or 3 l Flovac

Designed for professional aspiration of bodily fluids, tissues or bones of patients during or after surgery.

Oilless and maintenance free piston type pumps provide high performances. Excellent suction capacities and max vacuum built up within a few seconds. Available with vacuum gauge and autoclavable jars made in Makrolon® with 200 ml (2 l jar) or 500 ml (4 or 5 l jars) graduation and 2-3 litres Flovac jars with disposable liners.

**Wide range of versions with different features**

- 60 l/m (Clinic Plus) or 90 l/m (Hospi Plus) flow rate;
- 2, 4 or 5 l jars;
- MPR system for versatility;
- footswitch and flow direction diverter.

**High standards of safety in overflow protection system**  
Double security valve integrated in the jar and hydrophobic filter (all models), safety trap bottle (only MPR models).

**MPR (Multi Purpose Rail) models**

This system enhances the versatility for easy and quick exchange of different accessories, with no need for tools. Equipped with five connections for rings of various diameters to fit jars of different sizes and types (2l, 3l, 5l), cannula holders and safety trap bottle.

## MAIN APPLICATIONS

EMERGENCY DEPT.  
GENERAL SURGERY

GYNAECOLOGY  
NEUROSURGERY  
OBSTETRICS

OPERATING THEATRE  
DENTAL PRACTICE



Clinic Plus Basic and Hospi Plus Basic



Clinic Plus Full and Hospi Plus Full with  
foot switch and electronic flow direction  
regulator



Multipurpose rail with 5 locking slots offers versatility to operators in changing accessories

## TECHNICAL SPECIFICATIONS

	CLINIC PLUS	HOSPI PLUS
Operating voltage:	230 V - 50/60 Hz or 110 V - 60 Hz	230 V - 50/60 Hz or 110 V - 60 Hz
Maximum suction:	- 0,90 bar (675 mmHg)	- 0,90 bar (675 mmHg)
Operating cycle:	continuous	continuous
Flow:	60 l/min	90 l/min
Power:	230 VA	385 VA
Noise level:	51,7 dBA	46,4 dBA
Norms:	EN 60601-1-1, EN 60601-1-2 93/42 EEC	EN 60601-1-1, EN 60601-1-2 93/42 EEC

## STANDARD ACCESSORIES CLINIC PLUS and HOSPI PLUS

	Clinic, Hospi basic	Clinic, Hospi full	Clinic basic MPR	Clinic full MPR	Hospi basic MPR	Hospi full MPR
121°C autoclavable jar with overflow valve system (2, 4 or 5 l)	2	2	2	2	2	2
Rings to accommodate 5 l jars	-	-	2	2	2	2
Safety Trap Bottle (220 ml)	-	-	1	2	1	2
Antibacterial & Hydrophobic Filter (single-patient)	1	1	1	1	2	2
Autoclavable silicone tubes Ø 8x14 mm length 150 cm	1	1	1	1	2	2
Conical Connector Ø 10-11-12mm	1	1	1	1	2	2
Air suction inlet	1	1	1	1	2	2
Footswitch with intermittent or continuous operation	-	1	-	1	-	1
Change-Over System from jar to jar by soft-touch keys	-	1	-	1	-	1
Power Cord with Schuko plug	1	1	1	1	1	1
Multilingual manual: GB, FR, IT, ES, DE, GR, PL, RO	1	1	1	1	1	1

Voltage		SUCTION ASPIRATORS CLINIC and HOSPI PLUS	Autoclava- ble Jars	Foot switch	Flow direction diverter*
230 V	110 V				
28194	28118	CLINIC Basic	2x2 l	-	-
28195	-	CLINIC Full	2x2 l	yes	yes
28196	-	CLINIC Basic	2x4 l	-	-
28198	28119**	CLINIC Full	2x4 l	yes	yes
28159	-	CLINIC Basic MPR	2x5 l	-	-
28160	-	CLINIC Full MPR	2x5 l	yes	yes
28200	-	HOSPI Basic	2x2 l	-	-
28203	-	HOSPI Full	2x2 l	yes	yes
28201	-	HOSPI Basic	2x4 l	-	-
28204	28120**	HOSPI Full	2x4 l	yes	yes
28161	-	HOSPI Basic MPR	2x5 l	-	-
28162	-	HOSPI Full MPR	2x5 l	yes	yes

\*Allows to direct suctioned liquids to any of the 2 jars \*\*with 2x5 l jars

GIMA code	ACCESSORIES FOR CLINIC/HOSPI PLUS MPR
28150	Safety trap bottle 220 ml - spare
28151	Multipurpose stainless steel rail - optional
28154	Ring for 2 l autoclavable jar - optional
28155	Ring for 5 l autoclavable jar - spare
28156	Ring for 2 or 3 l Flovac jar - optional

## MAXI ASPEED HIGH FLOW ASPIRATOR FOR HOSPITAL USE

CE 0051



28288  
28291  
28292

MADE IN ITALY




28285  
28286  
28289



Telescopic handle

Foot switch integrated with 28286, 28288, 28290, 28292



### TECHNICAL SPECIFICATIONS

Operating voltage: 230 V - 50/60 Hz Noise level: 50-60 dBA  
Air flow: 60 or 90 l/min Size: 470x580x560 mm  
Operating cycle: continuous Weight: 15 kg (60 l), 17 kg (90 l)  
Adjustable vacuum level: 0-0.90 bar (0-90 kPa) MDD class: IIa

### MAXI ASPEED SURGICAL ASPIRATORS

Surgical aspirators for aspiration of body liquids in operating theatres and hospitals.

#### Easy to carry

Equipped with 4 antistatic wheels with brake and carrying telescopic handle.

#### Developed to run continuously

Made of highly heat resistant, electrically insulated plastic material in conformity with latest European safety standards. Vacuum regulator with BAR/PSI vacuumeter and automatic flow direction regulator to easily switch from a jar to the other. Supplied with 2 autoclavable polycarbonate jars with safety valve (overflow protection), set of atoxic sterilizable silicone tubes, antibacterial hydrophobic filters (2) and multilingual manual (GB, FR, IT, DE, ES).

GIMA code	MAXI ASPEED	Jar	Power	Foot switch	Flow direction diverter*
28285	Maxi Aspeed 60 l	2x2 l	230 V	-	yes
28286	Maxi Aspeed 60 l	2x2 l	230 V	yes	yes
28288	Maxi Aspeed 60 l	2x4 l	230 V	yes	yes
28289	Maxi Aspeed 90 l	2x2 l	230 V	-	yes
28290	Maxi Aspeed 90 l	2x2 l	230 V	yes	yes
28291	Maxi Aspeed 90 l	2x4 l	230 V	-	yes
28292	Maxi Aspeed 90 l	2x4 l	230 V	yes	yes

\*Allows to direct suctioned liquids to any of the 2 jars

### ACCESSORIES

28294	Autoclavable jar 2 l with safety valve
28295	Autoclavable jar 4 l with safety valve
28297	Hydrophobic antibacterial filter
25482	Silicone tube - 8x14 mm - roll of 30 m
28293	Pre-cut silicone tube 8x14 - 1.3 m
28253	Adapter to connect catheter to silicone tube - spare Suction catheter see page 51

28297

## MEDICAL GRADE SILICONE TUBES FOR EXTERNAL USE

CE



MADE IN SPAIN

**SILICONE TUBES for external medical use - silicone 100%**  
Suitable for autoclaving (135°C - 2.2-2.5 bar) and Gamma Sterilization. Resistant to hot air up to 200°C. Infra-red vulcanization. Hours treatment at 200°C temperature in special oven. Anti-adherent, avoid incrustation and coagulation. Medical Grade - Transparent - Odourless

### TECHNICAL SPECIFICATIONS

Raw material: HTV-R-401/60 S - WACKER (D) Colour: translucent  
Hardness: 60° ±5% Shore - DIN 53505 Density: 1.17 g/ccm - DIN 53479A  
Tensility: 10.8 N/mm² - DIN 53504 S1 Stretch: 490/530% - DIN 53504S1  
Tear resistance: 34-35 N/mm - ASTM D 624 B  
Reverse pull elasticity: 51% - DIN 53512  
Compression set: (22h/175°C): 30-15% - DIN 53517

Made in European Union according to: US PHARMACOPEIA XXI  
EUROPEAN PHARMACOPEIA DIN 58367 - DIN 58362 - DIN 13098- FDA 177.2600 - BGA XV part A and B - BGA IX part B

GIMA code	Internal diameter x external diameter	Thickness mm	Minimum order
25450	1x3 mm	1 mm	roll of 100 m
25451	2x4 mm	1 mm	roll of 100 m
25452	3x5 mm	1 mm	roll of 100 m
25453	4x6 mm	1 mm	roll of 100 m
25455	6x8 mm	1 mm	roll of 30 m
25458	3x6 mm	1.5 mm	roll of 30 m
25459	4x7 mm	1.5 mm	roll of 30 m
25460	5x8 mm	1.5 mm	roll of 30 m
25461	6x9 mm	1.5 mm	roll of 30 m
25462	7x10 mm	1.5 mm	roll of 30 m
25466	4x8 mm	2 mm	roll of 30 m
25467	5x9 mm	2 mm	roll of 30 m
25468	6x10 mm	2 mm	roll of 30 m
25469	8x12 mm	2 mm	roll of 30 m
25470	10x14 mm	2 mm	roll of 30 m
25474	5x10 mm	2.5 mm	roll of 30 m
25475	7x12 mm	2.5 mm	roll of 30 m
25476	8x13 mm	2.5 mm	roll of 30 m
25477	10x15 mm	2.5 mm	roll of 30 m
25480	6x12 mm	3 mm	roll of 30 m
25481	7x13 mm	3 mm	roll of 30 m
25482	8x14 mm	3 mm	roll of 30 m
25483	9x15 mm	3 mm	roll of 30 m
25484	10x16 mm	3 mm	roll of 30 m
25485	12x18 mm	3 mm	roll of 30 m
25488	8x15 mm	3.5 mm	roll of 30 m
25491	10x20 mm	5 mm	roll of 30 m
25495	made to order		500 m

### MADE TO ORDER SILICONE TUBES\*

We can manufacture any size (minimum order 500 m)

\*delivery 30 days

## GELID COAGULATIVE POWDER

### • 28141 GELID COAGULATIVE POWDER 50 g - box of 25

Super absorbent polymer powder used to turn infected medical liquid waste into a gel-like substance. Mixed with liquid waste, it solidifies and reduces the risk associated with spills of organic liquids. 50 g of product have an absorption capacity of 3000 ml. It can be used for surgical and bronchial suction system (canister or bags); canister for laboratory's liquid; dialysis liquid...  
Material: sodium polycrylate cross-linked. Packed in aluminum pouch.

CE



28141



## HAND SUCTION PUMP

### • 28131 SINGLE PATIENT HAND SUCTION PUMP

Light and portable manual suction unit operated by one hand only to let the other hand free for important duties. Simple operation. Adjustable stroke knob provides different suction pressures.



Supplied with 550 mmHg handle, 300 ml canister, child and adult catheter

28131

#### TECHNICAL SPECIFICATIONS

Vacuum after 1 min at 20kPa vacuum:	≥ 15 kPa
Vacuum after 6 times suction:	≥ 20 kPa
Max. vacuum:	≥ 39.9 kPa
Disposable container volume:	300 ml
External cap:	Ø 17 mm
External catheter connection:	Ø 17 and 9 mm
Stroke adjustment:	turn to 50% or 100%
Size - weight:	52x42x44 cm - 230 g


## HAND SUCTION PUMP

### • 28180 HAND SUCTION UNIT

Designed to provide quick and effective pharyngeal and tracheal suction for emergency use. The adjustable stroke knob provides different suction pressure. Supplied with 250 ml bottle and 2 non sterile adult cannulas 17 cm (Ø 6 mm) and 19 cm (Ø 10 mm).

### • 28181 SPARE ADULT KIT

Includes 250 ml bottle and 2 non sterile adult cannulas 17 cm (Ø 6 mm) and 19 cm (Ø 10 mm).



CE

Jar 250 ml

Supplied with multi-lingual box and manual:  
GB, FR, IT, ES, DE, PT, PL, GR, Arabic.

28180

#### TECHNICAL SPECIFICATIONS

Max vacuum:	-400 mmHg	Weight: 260 g
Peak free airflow:	>20 l/min	Size: 230x60x190 mm
External diameter of catheter connection:	10 and 6 mm	

## SPENCER JET 300D

### • 28177 JET COMPACT PORTABLE SUCTION UNIT

Extremely compact suction device to remove fluids from the airway or respiratory system support. The negative pressure draws fluids through disposable tubing that is connected to the collection container. Easy view of the setted vacuum thanks to the LED indicators. Classification ISO: high vacuum / high flow.

Supplied with power cable, battery, disposable container with filter, disposable patient tube.

### • 28178 DISPOSABLE CONTAINER 300 ml with filter

### • 28179 POWER ADAPTER

MADE IN ITALY  
Class IIa Medical Device according to Dir. 93/42/CEE



28177

CE 0434

#### TECHNICAL SPECIFICATIONS

Size - Weight:	245x70x185 mm - 1.60 kg	IP grade	IP 12
Vacuum range:	from 50 to 550 mmHg	Battery:	12 V DC Ni-MH
Flow (free flow):	32 l/min	Battery operative time:	30 min ON, 30 min OFF
Noise level:	70 dB	Battery recharging time:	5 h
Electrical connector	100-240 VAC 47-63 Hz	Container capacity:	300 ml
Requirement:	0.75 A max: 12 VDC	Patient tube length:	1 m

## HAND/FOOT/KNEE SUCTION PUMP

### • 28220 TOBI MANUALE - manual suction aspirator

Tobi Manuale is simple to operate pressing pedal by foot, hand or knee. It is used to clear patient's airways safely and efficiently, anytime, anywhere. Precision and solidly built to assure long service life. Polycarbonate suction bottle with capacity 0.4 l, autoclavable at 121°C and spill-over protection. Bacterial filter included.

Multilingual user manual: GB, FR, IT, DE, ES, PT.

### • 28219 BOTTLE 0.4 l - spare

### • 28229 HYDROPHOBIC ANTIBACTERIAL FILTER - spare



MADE IN ITALY

CE 0476

28220

Jar 400 ml

#### TECHNICAL SPECIFICATIONS

Weight: 1.15 kg	Max suction -0.40 bar	Bottle capacity: 0.4 l
Size: 225x165x85 mm	Suction power: 22 l/min	

## ACCESSORIES FOR ASPIRATORS



28260

GIMA code	STAINLESS STEEL OR BRASS C/P ASPIRATION TUBES
28262	S/S Bierer Aspiration tube Ø 8 mm
28264	S/S Bierer Aspiration tube Ø 12 mm
	Supplied with removable connection cannula
28260	Set of 7 brass chrome plated uterine aspiration cannulas for abortion: 4 cannulas with side suction end (Ø 5, 6, 8, 9 mm), 3 cannulas with front suction end (Ø 7, 10, 11 mm) and one handle

■ S/S FRAIZER, ROSEN, NOVAK SUCTION CANNULA  
■ SUCTION CATHETERS

See page 46  
See page 51

## YANKAUER CANNULA

Ready-to-use rigid cannula for suction of fluids in surgical field. Anatomical and anti-slip handle for easy grip. Transparent to control the flow of suction fluids. Open tip with one central and four lateral holes (Ø 20 mm). Flexible, transparent and non-conductive suction tube. Single use. Phthalates and latex free. Packed in single pouch. Class IIa, sterile.



28173

28174

CE 0426

• 28173 YANKAUER CANNULA with open tip and suction tube - 25 cm - box of 50  
• 28174 YANKAUER CANNULA with bulb tip and suction tube - 25 cm - box of 50

## GIMA LED COLPOSCOPE

- **29600 COLPY - GIMA LED COLPOSCOPE**  
Easy to use LED colposcope mounted on a 5 wheels base (Ø 41 cm).

### COLPOSCOPE TECHNICAL SPECIFICATIONS

Magnifying: 8.2X with standard 10X eyepieces  
Field: 35 mm  
Optic system: stereo with inter-pupil adjustment and optic head at 45°  
Illumination: LED bulb  
Working distance: 28 cm  
Interpupillary distance: 48-77 mm  
Green filter  
Operating voltage: 100-240V, 50-60 Hz  
Norms: CLASS I Type B - IEC 601-1 CE 93/42/EEC.

- **29601 CAMERA CONNECTOR for 29602**

To connect a camera with standard "C mount" to GIMA colposcope.

- **29602 MC1 PAL CAMERA - for Colpy**

Fit the camera to one eyepiece and connect the video cable to a high definition monitor. Includes 29601.

- **29603 DL1 DIGITAL - USB 2.0 CAMERA**


with grabbing software for Colpy  
Fitted on one eyepiece, allows to show image on PC through USB connection, becoming a high definition videocolposcope. Includes 29601

### TECHNICAL SPECIFICATIONS - 29602

Camera sensor: 1/3" CCD  
Resolution: 480 lines  
Power: 230 V - 50/60 Hz  
RCA video composite output 3 m cable  
Head size: 38x40x70 mm

### TECHNICAL SPECIFICATIONS - 29603

CMOS 1/3" sensor  
Max resolution pictures 1280x1024 pixels  
Max resolution movie 440x480 pixels



Adjustable height observation 73-104 cm

MADE IN ITALY

29600

## ALLTION LED COLPOSCOPE

- **29612 ALLTION LED COLPOSCOPE - 9X**
- **29613 ALLTION LED COLPOSCOPE**

3,75X, 7X, 15X - > 28,000 LUX


High quality and complete colposcopes, with excellent optics and cold, longlife white light.

Compact, lightweight and easy to use offers superior quality at a competitive price. A special universal Teflon® ball joint gives user 360° easy motion for gross focus. Comes assembled, ready for use.

Manual: GB, IT.

### TECHNICAL SPECIFICATIONS

Magnification 9X (29612) or 3,75X, 7X, 15X (29613)  
Focus length: 316 (29612) or 300 mm (29613)  
Field of view: diameter 22 mm or 30.93/15.50/7.64  
Depth of field: > 4 mm (29612) or 18/4/2 mm (29613)  
Light intensity: > 28.000 lux  
Interchangeable adjustable eyepiece 12.5X  
Illumination: longlife 5.9V / 5W LED  
Superior optics with individually adjustable eyepiece  
Built-in rheostat for brightness adjustment  
Easily changeable, LED bulb  
User-selectable built-in green filter  
Two (gross/fine) focus adjustment handles  
Two (gross/fine) height adjustment handles (838-1194 mm)  
Smooth action control  
Main Power: 110V/220V



Two circles for measuring size of tissues

Fine focus adjustment handle

Gross height adjustment knob

360° motion

29613

Roller base for easy movement

## LED VIDEO COLPOSCOPES

- **29620 COLPRO LED VIDEO COLPOSCOPE**
- **29622 COLPRO LED VIDEO COLPOSCOPE - FULL HD**

The video colposcopes COLPRO are the perfect combination of an advanced video technology and the feedback received from gynaecologists, users and stakeholders. They are known for their ruggedness and versatility and they provide high resolution images of cervix and genital area for effective colposcopy diagnosis and treatment.

**5 levels of light intensity** to observe finest changes in tissue structure.

**Electronic Green Filter:** 4 different grades (5 for HD) ensure an optimal observation without any light loss.

**5 image colours settings** that guarantee best colour differentiation in epithelium.

**Mirror and E-flip image:** facility to change the direction of the image from left to right horizontally (mirror) or from upward to downward vertically (E-flip).

**Gamma processor:** assures high quality image processing for better visualization of vessels and tissue structure.

**Magnification up to 55 times and Auto-focus:** the colposcope focuses even if the patient moves. 1-55X (29620), 1-45X (29622).

**Remote control** allows to control the functions even from a distance.

**Freedom of connectivity:** can be connected to a TV or a monitor and to PC via USB. 2 video outputs can be taken on 2 different screens simultaneously.

**User friendly design:** ergonomic and user friendly design, easy to move. Height adjustable to have best positioning for colposcopy procedure.

**Maintenance free, shadowless LED light source**

- **72708 SONY LMD LCD MEDICAL MONITOR - 15" - support included**



29620

EMI/EMC tested

### TECHNICAL SPECIFICATIONS

Image processor: Sony Japan colour CCD  
Pixels: 1,200,000 (29620)  
2,000,000 (29622)  
Resolution: 825 TV Lines (29620)  
1,000 TV Lines (29622)  
E-flip: yes  
Mirror image: yes  
Electronic Shutter: automatic  
S/N ratio: >48 db (29620), >50 db (29622)  
Illumination: high MCD super bright white shadowless LED light  
Colour temperature: 7,000° K  
Test timer: yes  
Multigrade green filter: yes (4 grades, 5 for HD)  
Blue filter: yes  
Focus: automatic and manual  
Focus distance: 20-30 cm  
Zoom: 1-55X (29620), 1-45X (29622)  
Viewing area: Ø 170 mm - 10 mm  
Depth of view: Ø 200 mm - 5 mm  
Magnification display: Yes  
Average LED lamp life: 50,000 hours  
Video output: BNC and SVHS (both)  
YPBPR and DVI (29622 only)  
Safety standard: complies to IEC 60601 including EMC  
Power supply: 100-240 VAC, 50/60 Hz  
Made in Australia

## COLPOSCOPY IMAGE, VIDEO & PATIENT DATA MANAGEMENT SOFTWARE

- **29621 COLPOSCOPY SOFTWARE FOR COLPRO COLPOSCOPE AND COLPY WITH DIGITAL CAMERA**

A powerful IT tool in the hands of our busy gynaecologists to manage not only videos, images, clinical data and details of the patients, but also to provide them an opportunity to store, edit, burn on CD or DVD, print the detailed reports and use graphical data for presentation. Multilingual software (GB, ES, IT, DE, FR, PT, SE, NL, GR, Arabic). Footswitch for capturing and saving images.

This software supports composite and SVHS video output with help of video cable with RCA male connector.

Compatible with Windows 7 (64-bit) / XP / Vista, Windows 8 and 10 Operating Systems  
Easy to install and maintain. Password protected log-in to ensure data privacy

Enormous level of live recording facilities and image capturing at very high pixels simultaneously with just a click

Various kinds of colposcopy video clippings, movies, images for reference and education purpose have been incorporated in the software. Print out of reports with relevant details can be prepared for future follow-up of the patient

**Comparison** mode with linked images

**Forensic examination** & sexual abuse

Leep/Lieitz approach to treat high grade dysplasia

**Cryo surgery** report

Statistical data representation with graph

Multiformat 1-2-3-4 images diagnosis report

HAMMOND graph (biopsy graph)

Marking and highlighting





## LED VIDEO COLPOSCOPES WITH CAMERA

- 29624 AC-2311 LED VIDEO COLPOSCOPE WITH CAMERA
- 29625 AC-2311DA LED VIDEO COLPOSCOPE L-SHAPED ARM WITH CAMERA

### - Superb optical features:

- 1 - high resolution and good contrast
- 2 - real 3-dimensional precise image reproduction
- 3 - large depth of field
- 4 - wide field of view

Apochromatic optics design can correct the chromatic aberration of three types of coloured light effectively. It ensures the reduction and saturation of image colour and improves resolution, contrast and view depth of image.

### - 3-step magnification (3.75X - 7.5X - 15X)

Provides larger magnifying range and more selection from lowest magnification for an overview to high magnification for precise and close inspection and treatment.

### - Two optical circles for quick measuring size of tissue

### - Integrated green filter

It can help to recognize blood vessels

### - LED illumination

LED coaxial illuminator provides pure white colour light similar to sunlight to show real colour. Bulb life over 10,000 hours/10 years for long lasting performance. It saves your cost for the spare bulbs & electric charge.

### - Integrated camera

The images from integrated video camera can be transferred directly into a monitor or a TV, into a computer with USB adapter or stored into a hard disk recorder.

### - Full HD (1920x1080 p) HDMI output

### - Ergonomic design for comfortably long time precision operation

Supplied assembled and ready for use with manual in GB, FR, IT.

### • 29627 SOFTWARE FOR LED VIDEO COLPOSCOPES (29624-5)

HDMI capture card & professional colposcopy software set including: external capture card, software and driver U-Disc, 2 HDMI cables, HDMI connector, dongle for connecting AC-2311 to the desktop computer (or laptop) & monitor at the same time.

The software allows to take and collect images for every inspection in order to analyze, diagnose and detect diseases. It can be used in colposcope inspection and dynamic observation of operation treatment.

### Features:

- course for displaying, freezing, capturing and deleting image
- taking and collecting 1 to 100 colour images for every inspection
- operating system: Windows 7, Windows 8, Windows 10



TECHNICAL SPECIFICATIONS	
Total magnification:	3.75X, 7.5X, 15X, 300 mm focal length
Field of View:	Ø 79 mm, 39 mm, 19 mm
Depth of Field:	4.5 mm, 1.13 mm, 0.76 mm
Light intensity:	>25,000 LUX
Working height mm:	950 to 1250 (29624) - 950 to 1150 (29625)
Individually adjustable eyepiece:	16.7X
Right eyepiece with built-in two circles to measure the size of the problem you see	
Built-in rheostat for brightness adjustment	
User-selectable built-in green filter for enhanced contrast	
LED bulb is easily changeable	
Fine focus adjustment handles	
Two (Gross/Fine) height adjustment handles	
Power supply:	adapter input AC 100-240 V, 50-60Hz, output DC 12V3A
Weight:	8.5 kg (29624), 9 kg (29625)

175 standard atlas  
helpful to contrast, analyze and  
diagnose

### Software mark on images

Mark on pathological changes  
image, add remark, measure  
pathological change size and  
magnify partially or totally

### Input of clinic symptom

Printing of 19 kinds of reports, RCI

### evaluation function

### Cases information search and editing

Cases be searched by name, case number, age, date and be added, deleted, edited,

memorized and reviewed



## AMNIOCENTESIS NEEDLES

For transabdominal sampling of amniotic fluid (usually between 15<sup>th</sup> and 18<sup>th</sup> pregnancy well) for prenatal diagnosis of genetic disorders of the foetus.

It is also used for cytogenetic and biochemical studies. Accurate sharpening of the needle allows an easy and atraumatic insertion. Its mandrel is provided with an ultrasound detectable tip allowing an echo-guided insertion, and it is colour coded for an easy identification of the needle size. The needle is provided with an adjustable stopper to determine insertion depth, and with a female luer lock connector to collect the amniotic fluid through a syringe.

MADE IN ITALY

GIMA code	AMNIOCENTESIS NEEDLES - STERILE - box of 25
29636	Needle 20 G x 100 mm
29637	Needle 20 G x 120 mm
29638	Needle 20 G x 150 mm
29639	Needle 20 G x 180 mm
29640	Needle 21 G x 120 mm
29641	Needle 21 G x 150 mm

CE 0476

## SCHULTZE SALPINGOGRAPH

### • 29780 SALPINGOGRAPH

Instrument for hystero-salpingography and tubal insufflation, Prof. Gunter K. F. Schultze from Berlin type.

### • 29782 WATCH FOR SALPINGOGRAPH

### • 29785 HYSTERO SYRINGE - 20 cc - LUER LOCK - spare

**Riester**

CE 0124

MADE IN GERMANY



### HYSTEOSALPINGOGRAPH: STANDARD ACCESSORIES

Watch for hystero Hystero syringe 20 cc Luer Lock  
Rack-bar 3 interchangeable cones (small-medium-large)

Instrument can also be read in the dark thanks to the  
luminescent substance used on the scale



## FC1400 FOETAL MONITOR - 7" TOUCH SCREEN COLOUR TFT LCD

### • 29516 FC1400 SINGLE FOETAL MONITOR

### • 29517 FC1400 TWIN FOETAL MONITOR

Antepartum foetal monitor to measure Foetal Heart Rate (FHR), degree of material uterine contraction (UA: Uterine Activity), foetal movements (FM)

#### Superior data display

- 7" full touch screen colour TFT LCD (800x480)
- 2 display modes: graphic and text modes
- 72 hours of memory capacity

#### Extreme data accuracy and access

- high-accuracy and wide detection area
- easy on-screen scrolling function
- enduring watertight probes,



1 MHz probe  
Event marker

USB function memory Toco probe storage Wi-Fi convert  
Yellow/green LED alarm for easier recognition of device and patient status



2 display modes

10 smart keys for 16 functions



Compact probes and robust connector

1 MHz to minimize broken FHR waveforms even if the fetus moves

Trolley suitable for 29520 and 29516-7


#### Printout

- CTG interpretation report
- both standard and A4 size paper usable
- normal fax paper usable

#### Other advantages

- Wi-Fi central monitoring up to 16 beds (Option)
- PC compatible
- internal battery lasting 2-hours (Option)
- power adapter 100-240 V, 50-60 Hz
- multilingual internal software: GB, FR, IT, ES, PT, DE, PL, RO, RU, CZ, HU, BG, TR, KR, CN.

Recommended after week 30



Adjustable height

Weight 8 kg

29519

#### TECHNICAL SPECIFICATIONS

Dimensions	296x97.5xh 305.5 mm - Approx. 2.9kg
Display	7" TFT Wide LCD screen (800x480)
Thermal array printer:	print speed: 1, 2, 3 cm/min (real time) paper feeding function
Power	input: 100-240 V, 1.5-0.7 A, 50-60 Hz output: +18 V = 2.8 A
Li-ion battery (option)	4 hours (charging) - 2 hours (discharging)
External link	LAN, Wi-Fi, USB memory
Foetal heart rate	input signal: ultrasound pulsed doppler ultrasound frequency: 1.0 Mhz, 975 KHz ultrasound power: <10 mW/cm <sup>2</sup> FHR detection method: autocorrelation FHR range: 50-210 bpm $\pm$ 1 bpm (120-160)
Foetal movement measurement	detection source: ultrasound pulsed doppler, event marker
Uterine contraction	input source: external transducer with load cell reference control: one touch switch, auto zeroing measurement range: 0-99
Auto CTG analysis	average baseline FHR number of UC number of acceleration number of deceleration late deceleration early deceleration variable deceleration high episode low episode short term variability signal loss

## COST-EFFECTIVE SINGLE FOETAL MONITOR

### • 29520 FOETAL MONITOR GIMA FC 700

Cost-effective single foetal monitor

#### Extreme ultrasound doppler sensitivity

- high-accuracy with 1 Mhz frequency
- automatic/manual

Foetal Movement detection

- auto NST (Non-stress test) function from 10 min. to 1 hour.



Event marker



29520

#### Data printout

- CTG analysis printing
- A4 paper with perforation line
- plain thermal fax paper usable
- print speed 1, 2, 3 cm/min

#### Easy-to-use

- one- touch operation and easy setup
- alarm function (FHR high-low)
- s/w upgrade via internet

#### TECHNICAL SPECIFICATIONS

Dimensions	296x92.5xh 305.5 - approx. 2.9 kg
Display	7 segment LED - 2 channels (FHR, UC)
Thermal printer	print speed: 1, 2, 3 cm/min paper feeding function
Power adaptor	input: 100-240 VAC, 50-60 Hz, 1.2 A output: 18 VDC, 2.5 A
External link	RS-232C
Foetal heart rate	input signal: ultrasound pulsed doppler ultrasound frequency: 1.0 Mhz ultrasound power: <10 mW/cm <sup>2</sup> FHR detection method: auto correlation FHR range: 50-240 bpm $\pm$ 1 bpm (120-160) reference (zero) control: one touch switch measurement range: 0-99 units
Uterine contraction	detection source: ultrasound pulsed doppler average baseline FHR number of UC number of acceleration number of deceleration (late, early, variable) Tachycardia (moderate, severe) Bradycardia (moderate, severe)
Foetal movement measurement	detection source: ultrasound pulsed doppler
Auto CTG analysis	

## ACCESSORIES FOR FC700 AND FC1400 FOETAL MONITORS

For 29520	For old 29530-31	For 29516-17	ACCESSORIES FOR FOETAL MONITORS
29522	-	-	Paper roll - 215 mm x 23 m
-	29526	29526	Paper roll - 152 mm x 25 m - box of 10
29523	29532	29538, 29540	US doppler probe - spare
29524	-	-	UC/Toco probe up to S/N FF07XXX
29529	-	-	UC/Toco probe since S/N FF08XXX
-	29533	29539, 29541	Toco transducer - spare
29519	29519	29519	Trolley with 2 baskets (adjustable height)
-	29534	-	Battery NI-MH, 12 V, 2,600 mA
-	-	29536	Li-Ion battery
33747	33747	33747	AC adaptor
29525	29525	29525	Belt 5.3x148 cm
29521	-	29521	Event marker - spare

### • 29527 WIRELESS CENTRAL STATION FOR FOETAL MONITORS

Central station (PC, monitor, software, wireless, connection kit) to manage up to 16 monitors.



Wireless bluetooth 16 beds central system (distance 10-100 m)

#### STANDARD ACCESSORIES (29516, 29517, 29520, 29530, 29531)

1 US doppler probe (2 for 29517 and 29531)	1 ultrasonic gel	1 power cord
2 (29520) or 3 fixing belt (29516-7)	1 stand	1 user manual
1 TOCO probe	2 paper rolls	
1 marker for lying-in women	1 adaptor	



## GIMA FOETAL MONITOR PAPERS FOR DIFFERENT BRANDS

GIMA Code	FOETAL MONITOR manufacturer and model	Standard FHR rate/BPM**	Type	Width mm	Length mm or m	Sheet	Grid***	Min. order	GIMA Code	FOETAL MONITOR manufacturer and model	Standard FHR rate/BPM**	Type	Width mm	Length mm or m	Sheet	Grid***	Min. order
<b>BIONET</b>									<b>EDAN</b>								
29528	Fetalcare FC/1400	Int 60/200	roll	152	25	-	green	10	29569	Cadence II	US 30/240	pack	112	90	150	or/red	20
29522	Fetalcare FC/700	US 60/240	roll	215	23	-	green	5	29570	F/6-F/9	Int 60/200	pack	152	90	150	or/red	25
<b>COMEN</b>									29571	Cadence II	Int 60/200	pack	112	90	150	or/red	20
29556	Star 5000/C	Int 60/210	pack	112	100	150	or/red	20	<b>HEWLETT PACKARD</b>								
29557	Star 5000/D	US 30/240	pack	151	100	150	or/red	25	29576	M1911A	Int 60/200	pack	151	100	150	green	25
<b>COROMETRICS</b>									<b>SHENZHEN CREATIVE</b>								
29561	4305-BAO mod. 116-145-150-151-118	Int 60/200	pack	152	90	150	or/red	25	29556	PC-8000 PRO single	Int 60/210	pack	112	100	150	or/red	20
29562	4305-BAO mod. 116-145-150-151-118	US 30/240	pack	152	90	150	or/red	25	29558	PC-8000 PRO twins	Int 60/210	pack	151	100	150	or/red	25
									29557	PC-8000 PRO twins	US 30/240	pack	151	100	150	or/red	25
									<b>SONICAID</b>								
									29580	Meridian/800 - Team	White paper	pack	143	150	300	white	10

\*mm (pack) or m (roll)

\*\*International or US standard FHR rate/BPM

\*\*\*or/red: grid could be orange or red colour

## UNIVERSAL TRANSDUCER BELTS FOR FOETAL MONITORS


### • 29544 SINGLE PATIENT FOETAL BELTS - 100 pairs (1 pink +1 light blue)

Single patient elastic foetal belts to avoid cross-contamination. Soft and comfortable belts resistant to abrasion, corrosion, light and heat. Great elasticity and insulation. Performance: more than 1,000 stretches. Easy to wash, made of 85% polyester and spandex. Supplied with buttons.

### • 29545 REUSABLE FOETAL TRANSDUCER BELTS - box of 10

Reusable elastic fetal belt resistant to abrasion, corrosion, light and heat. Soft, comfortable and easy to wash and dry. Performance: more than 100,000 stretches. Made of 85% polyester and spandex. Supplied with buttons.

**COMPATIBILITY (29544,29545):** Bionet, EDAN, Philips M1350, Philips FM 20 series, GE, Corometrics, Sonicaid, Huntleigh and most foetal monitors.



## OBSTETRIC STETHOSCOPES

### • 32501 SHORT OBSTETRIC STETHOSCOPE - beech-wood

These stethoscopes are hand-craft manufactured, made of beech-wood accurately selected and seasoned for at least 3 years. They have a perfect finish with a special transparent varnish. Multilingual box: GB, FR, IT, ES, PT, DE, NL, PL, RO, HU, GR, Arabic.

### • 32505 PINARD STETHOSCOPE - aluminium



## LATEX PROBE COVERS



### • 29509 LATEX PROBE COVERS - transparent - bag of 1000 pcs - bulk

### • 29513 LATEX PROBE COVERS - transparent - box of 50

### • 29514 LATEX PROBE COVERS - transparent - box of 500

Probes for ecography and doppler. Length 17 cm, Ø 3.3 cm. Individually packed in single plastic bag, except 29509.

## ENEMA IRRIGATOR


### • 28720 ENEMA IRRIGATOR- 2 l capacity

Supplied in cardboard box with 2 cannulas (vaginal, anal), tap with opening lever, tube and carrying bag.

Multilingual box: GB, FR, IT, ES.



## GIMA FOETAL POCKET DOPPLERS



### • 29502 GIMA FOETAL DOPPLER G2002

Small, lightweight, high sensitivity pocket Doppler, with 2 MHz foetal probe, ideal for General Practitioner's or Midwife's use for routine antenatal foetal detection.

Pocket Doppler can be used to detect the beating foetal heart from about 10th week of gestation. It may be used to locate the position of the placenta, thus aiding in the early diagnosis of placenta praevia, to survey blood flow of the umbilical cord and to diagnose multiple pregnancies. Foetal signals are easily located using the lightweight narrow beam transducer while internal signal processing minimizes noise artefacts. Audio foetal heart signals are available to the user via the built-in loudspeaker or option headset, with output level controlled by rotary volume control.

### • 29511 ON/OFF MEMBRANE SWITCH for code 29502

### • 29503 GIMA FOETAL DOPPLER D2003 with display

Pocket foetal doppler with same specification as code 29502 but with built-in foetal heart rate processing. Foetal heart rate (FHR) is displayed on a large LCD display whilst internal signal process minimises noise artefacts.

### • 29505 GIMA FOETAL DOPPLER D2005 with display and waterproof probe

Same as code 29503 but waterproof probe and sealed electronics. All units are supplied in a nice bag with a tube of coupling gel and user manual in GB, FR, IT, ES, PT, DE, GR.

Battery not included.

### • 29512 ON/OFF MEMBRANE SWITCH for codes 29503, 29505

### • 32205 9V ALKALINE BATTERY



### TECHNICAL SPECIFICATION (CODES 29502 - 29503 - 29505)

Ultrasound	Frequency: 2 MHz continuous wave Transducer: 2 crystal narrow beam Output power: <10mW/mm <sup>2</sup> SATA Audio Response 300Hz -1 KHz autocorrelator (only code 29503 and 29505)
FHR (Fetal heart rate):	50-210 bpm (29503, 29505) 60-210 bpm (29502) resolution ± 1 bpm, accuracy ± 2 bpm
Unit Controls	Keys: 1 Key (for unit on/off) Controls: rotary volume
Indicators:	3 digit FHR LCD display (codes 29503, 29505) FHR pulse icon (codes 29503, 29505), Battery low icon
Power supply	Battery 9 V Alkaline Manganese Expected battery life: 8 hours
Output	Headset: Audio output to optional headset Serial: RS232 interface (codes 29503, 29505)-jack 35 mm
Material:	ABS / Noryl
Size:	150 mm by 75 mm Weight: 295 g (with transducer)
Classification:	Class I Type B - IEC 60601-1 CE 0120

## SONOTRAX DOPPLERS



**SUPPORT**  
2MHz, 3MHz, 4MHz, 8 MHz  
**WATERPROOF PROBES**

### 29493

#### TECHNICAL SPECIFICATIONS

Size: 32x85x138 mm  
Weight: 290 g (including battery)  
Heart rate range: 50-210 bpm  
Resolution: 1 bpm  
Accuracy: ± 3 bpm  
LCD display: 45x25 mm (only code 29491-93)  
Auto average and manual mode  
Recording length: 480 s / 240 s  
Auto power-off to save power  
Manual: GB, IT - on request: DE, ES, FR, PT.

GIMA code	DOPPLERS AND INTERCHANGEABLE PROBES - LATEX FREE	
29490	SONOTRAX LITE DOPPLER - without probe - with bag	
29491	SONOTRAX BASIC DOPPLER - with display - without probe - with carrying bag	
29493	SONOTRAX PRO II DOPPLER with backlit display built-in audio recorder and rechargeable batteries with battery charger - without probe - with carrying bag	29499
29496	2MHz waterproof probe - gynaecology	
29497	3MHz waterproof probe - gynaecology	
29498	4MHz waterproof probe - vascular	
29499	8MHz waterproof probe - vascular	
29500	Rechargeable Ni-Mh battery for 29493 - spare	29496

## GIMASONIC COLOUR DOPPLER

### COLOUR SCREEN POCKET DOPPLER

- built-in speaker
- TFT-LCD, real-time display of FHR
- three working modes: real-time FHR, average FHR and manual calculation
- display of FHR, bar graph and heartbeat waveform, red alarm for abnormal FHR
- low power consumption, continuously work for more than 8 hours with two "AA" batteries
- indication for probe-off and low battery
- range of probes for foetal or vascular use: 2, 3, 4, 8 MHz probe

Suitable for use after the 12<sup>th</sup> week of pregnancy

Multilingual box and manual: 29480

GB, FR, IT, ES, PT, DE.



29481  
Probe not included

### TECHNICAL SPECIFICATIONS

Ultrasound working frequency:	2 MHz ± 10%
Fetal heart rate:	range: 50-240 bpm resolution: 1 bpm accuracy: ± 2 bpm
Alarm:	high limit: 160 bpm low limit: 120 bpm
Ultrasound intensity:	< 5 mm/cm <sup>2</sup>
Auto power off after 1 minute no signal	
Size - weight:	135x92x29 mm - 245 g
Power supply:	2 AA Batteries LR6 - 1.5 V DC

GIMA code	GIMASONIC COLOUR SCREEN DOPPLER
29480	GIMASONIC Colour screen doppler - without probe
29481	2 MHz waterproof probe - gynaecology
29482	3 MHz waterproof probe - gynaecology
29484	8 MHz waterproof probe - vascular




## S/S GINAECOLOGY INSTRUMENTS AND KITS



26817

- **26817 HEGAR DILATORS SET** - chrome plated  
Include 14 dilators Ø 4-17 mm



26810

- **26810 GYNAECOLOGY KIT**  
Includes 4 instruments in a nylon bag. See page 45.

- **26801 FOERSTER FORCEPS** 25 cm
- **26802 SCHROEDER FORCEPS** 25 cm
- **26806 SCHUMACHER BIOPSY FORCEPS** 24 cm
- **26808 SCHUBERT BIOPSY FORCEPS** - 21 cm
- **26809 KOGAN ENDOSPECULUM** - 24 cm

**OTHER GYNAECOLOGY INSTRUMENTS**  
See page 45


## S/S DELIVERY SURGICAL SET



26966

- **26966 MINOR DELIVERY SET** - 25 pcs  
Kidney Dish 20 cm (8") - medium  
Kidney Dish 25 cm (10") - large  
Gallipot 150 ml - 6 oz - medium  
Brown Sadler episiotomy scissors - 14 cm  
Kocher artery forceps straight - 16 cm  
Kocher artery forceps straight - 18 cm  
Kocher artery forceps curved - 16 cm  
English TOE dissecting forceps plain - 14 cm  
English TOE dissecting forceps plain - 18 cm  
Dissecting forceps toothed 1x2 - 14 cm  
2 operating scissors sharp/blunt - straight - 15 cm  
2 operating scissors sharp/blunt - curved - 15 cm  
2 rampley sponge holding forceps - str. - 24 cm  
Museux Vulsellum forceps 8 mm - str. 24 cm  
3 Cusco vaginal specula - small, medium, large  
3 Sims vaginal specula - small, medium, large  
Umbilical scissors USA Patent - 10.5 cm  
Instrument tray with lid 45x30x6.2 cm

## UMBILICAL CLAMP




29942

MADE IN EUROPE

Extra safe clamp  
avoid accidental  
re-opening.  
Can be  
re-opened  
only by cutting  
back side

- **29942 X-SAFE UMBILICAL CORD CLAMP** - sterile - box of 500  
Disposable umbilical cord clamp to allow a proper clamping of all umbilical cords and prevent their outcoming from the closing comb. Individually packed in coupled cellophane (nylon/polyethylene) and medical paper to ensure safe hygienic conditions to user. Sterilized by ethylene oxide.

## GYNAECOLOGY SET - STERILE



Non woven bi-layer fabric gynaecology set

- **23641 GYNAECOLOGY SET** - sterile - box of 8  
1 table cover 150x200 cm with central absorbent band  
1 Mayo stand cover 80x145 cm  
1 gynaecology drape for lithotomy position 290x240 cm with adhesive hole, built-in leggings, bag for liquid collection with filter and drain valve  
1 drape 75x90 cm  
1 incision film 35x50 cm  
3 adhesive strips 10x50 cm  
4 towels 35x40 cm
- **23644 SET FOR CESAREAN SECTION** - sterile - box of 8  
1 table cover 150x200 cm with central absorbent band  
1 Mayo stand cover 80x145 cm  
1 drape for caesarean section  
260x200x310 cm with incision film and bag for liquid collection  
1 drape "baby blanket" 75x90 cm  
See picture at page 40


## MEMBRANE PERFORATOR



29945

- **29945 AMNIOTIC MEMBRANE PERFORATOR** - sterile - box of 600  
Disposable amniotic perforator. This system is thought to be completely safe to avoid lesions to the foetus. Supplied in single sterile envelope.


## I.D. BRACELET



29937

GIMA code	I.D. BRACELET	Colour	Minimum order
29936	Newborn	light blue	box of 100 pcs.
29937	Newborn	pink	box of 100 pcs.
29938	Mother	light blue	box of 100 pcs.
29939	Mother	pink	box of 100 pcs.

## CUPS FOR HYSTEROGRAPHY AND SIFT SCREW SYRINGE



CE 0459


29923 Connector for suction tube

29921 Cup for hysteroigraphy

- **29920 CUPS FOR HYSTEROGRAPHY** - 25 mm - sterile
- **29921 CUPS FOR HYSTEROGRAPHY** - 30 mm - sterile
- **29922 CUPS FOR HYSTEROGRAPHY** - 35 mm - sterile
- **29923 CUPS CONNECTOR** - sterile

Rigid, transparent tapered cup with a central conical cannula. Equipped with a 25 cm long flexible, pliable manipulator joined to the cup and two tubes equipped with clamps. One of these provides the vacuum, while the other injects the radiopaque medium. Perfect adhesion to the cervix by self-centering is ensured by the tapered shape of the cup and the progressive application of a vacuum to the cup. The suction cup/cannula unit is radiotransparent and allows the proximal area of the endocervix to be controlled. The radiologist is able to manipulate at a distance from the radioactive field while at the same time comfortably immobilizing the uterus. Latex free.


## IUD - INTRAUTERINE CONTRACEPTIVE DEVICE



• **29710 INTRAUTERINE DEVICE TCU380 PLUS - sterile**  
Sterile disposable medical device Class III for intrauterine contraception in women of child bearing age. Can be left inserted for a maximum of 5 years. Packed in a pouch with an insertion tube equipped with a movable flange to aid in gauging the right depth of insertion and a rod. Complies with ISO-7349.




• **29712 GYN-EAS IUD KIT - sterile**  
A complete disposable kit for IUD insertion including: 1 intrauterine device (IUD), 1 speculum medium size, 1 hystrometer, 1 pair of Pozzi tenaculum forceps, 1 Evolution forceps, 1 pair of thread-cutting scissors, 1 practitioner and 1 patient brochure.




• **29714 IUD INSERTION AND REMOVAL KIT - sterile**  
Disposable kit for IUD insertion and removal including: 1 Evolution Pozzi forceps, 1 long Littauer scissors, 1 Evolution long forceps.

## GYNAECOLOGY FORCEPS AND SCISSORS


• **29717 CHERON FORCEPS 25 cm - box of 25**  
Suitable for:  
- cervix cleaning/disinfection before any intervention (ex. IUD insertion) used with a gauze or a piece of cotton and disinfectant solution  
- IUD removal



• **29719 EVOLUTION LONG FORCEPS 25 cm - box of 25**  
Same applications as Cheron forceps, but with longer and thinner jaws.



• **29718 POZZI FORCEPS 25 cm - box of 25**  
Ergonomic, strong and thin single-use forceps suitable for grasping of the cervix, cervical cerclage, biopsies, conisations, IUD insertion (align cervix and womb with vagina axis).




• **29720 LONG LITTAUER SCISSORS 22 cm - box of 25**  
Suitable for cutting the IUD threads after the insertion.



Sterile disposable medical device, Class I. Latex free. Sterilized by ETO. Shelf life 5 years.

## FLEXIBLE HYSTEROMETERS

**SINGLE USE, STERILE, FLEXIBLE HYSTEROMETERS**  
Hysterometers with soft distal part on a rigid handle for IUD\* (29925, 29926). Hysterometer with progressive dilation distal part from CH 10 to CH 14 on 25 mm, suitable for IUS\*\* (29927).



GIMA code	HYSTEROMETERS SINGLE USE - STERILE - LATEX FREE	Ø	Minimum order
29925	Hysterometer CH 10 - 30 cm	3.3 mm	box of 25
29926	Hysterometer CH 12 - 30 cm	4.3 mm	box of 25
29927	Hysterometer CH 14 - 30 cm	4.67 mm	box of 25

\*IUD: Intra Uterine Device

\*\*IUS: Intra Uterine System

## EVOLUTION HYSTEROMETER

• **29929 EVOLUTION DOUBLE HYSTEROMETER 30 cm - box of 25**  
The most versatile, economical and eco-friendly single-use hysterometer. Estimating the uterine depth, checking cervical canal permeability and womb orientation. Sterile, disposable medical device, class I. Latex free, PVC free. Shelf life: 5 years.





## DISPOSABLE ANO/PROCTO/SIGMOIDOSCOPES

### • 25953 F.O. ILLUMINATION HEAD

Perfectly fits and illuminates GIMA, HEINE, WELCH ALLYN, GPS disposable anoscopes, rectoscopes, proctoscopes. It can be connected to a light source by a F.O. cable or to a LED illumination system. See page 239.

### • 25947 DISPOSABLE ANOSCOPE - sterile - box of 60

Length 10 cm, with stylet diameter 15 mm, suitable for treatment of haemorrhoids. Atoxic, phthalate and latex free.

The disposable anoscope is sold in a paper and polyethylene envelope sterilized in ethylene oxide. Made of transparent, atoxic, dust resistant plastic. Latex and phthalate free.

Disposable proctoscope see at page 218.

### HEINE UNISPEC DISPOSABLE TUBES

#### • 25944 HEINE UNISPEC DISPOSABLE ANOSCOPE 85x20 mm

E-003.19.925 - box of 25

#### • 25945 HEINE UNISPEC DISPOSABLE PROCTOSCOPE 130x20 mm

E-003.19.825 - box of 25

#### • 25946 HEINE UNISPEC DISPOSABLE SIGMOIDOSCOPE 250x20 mm

E-003.18.825 box of 25

2 lens (1.5 X and 2 X) included

25947 + 25953

10 cm

25947 - anoscope 10 cm

25953

Insufflator adaptor

Wolf / Acmi

Storz connectors included



25944

25945

25946

## ILLUMINATION OF F.O. ANO/PROCTO/SIGMOIDOSCOPES



### • 30799 ILLUMINATED HANDLE 6.0 VOLT

Independent light source for F.O. instruments. Direct connection to all F.O. instruments.

### • 30800 HALOGEN BULB - spare for 30799

### • 30803 GIMALED LIGHT SOURCE - see page 239

To connect anoscopes/rectoscopes/sigmoidoscope to GimaLed light source (30803) you need: F.O. cable (30818-30826), adaptor (30830) to connect cable to light source, 2 adaptors (30840, 30844) to connect sigmoidoscope to F.O. cable.

## F.O. ANOSCOPES, PROCTOSCOPES


F.O. ANOSCOPES




29405

F.O. PROCTOSCOPE

GIMA code	F.O. ANOSCOPES - PROCTOSCOPES	ADAPTOR included
29400	F.O. Anoscope Ø15x70 mm - with obturator	Wolf/Acme/Storz
29401	F.O. Anoscope Ø20x70 mm - with obturator	Wolf/Acme/Storz
29402	F.O. Anoscope Ø25x70 mm - with obturator	Wolf/Acme/Storz
29403	Set of 3 F.O. anoscopes in a case	Wolf/Acme/Storz
29405	F.O. Proctoscope Ø 20x130 mm - with obturator with 2.0X	Wolf/Acme/Storz
30840	ENDO STORZ ADAPTOR - to connect with Gima F.O. cable	



## F.O. SIGMOIDOSCOPES



GIMA code	F.O. SIGMOIDOSCOPES WITH 1.5X MAGNIFICATION SWIVEL LENS	ADAPTOR included
29410	F.O. Sigmoidoscope - 12x200 mm	Wolf/Acme/Storz
29411	F.O. Sigmoidoscope - 16x250 mm	Wolf/Acme/Storz
29412	F.O. Sigmoidoscope - 21x200 mm	Wolf/Acme/Storz
29413	F.O. Sigmoidoscope - 21x250 mm	Wolf/Acme/Storz
29414	F.O. Sigmoidoscope - 21x300 mm	Wolf/Acme/Storz
30840	ENDO STORZ ADAPTOR - to connect with Gima F.O. cable	

GIMA code	S/S ACCESSORIES FOR F.O. ANOSCOPES, PROCTOSCOPES, SIGMOIDOSCOPES
29420	Handle for Biopsy forceps
29421	Biopsy forceps 3.5x8 mm Cup Jaws - 420 mm
29422	Biopsy forceps 4 mm - Cutting Jaws - 420 mm
29425	Sponge Holding forceps - 400 mm
29426	Suction Tube - 400 mm
29427	Twin Bellow Insufflator

## AMNIOSCOPE: TUBES AND SET

### • 29970 AMNIOSCOPE SET includes 29971/2/3/5 and 30840

Set of three amnioscope tubes with shutter 200 mm length, 12, 16 and 20 mm diameter and a clamp for fibre optic light. All tubes are graduated in centimetres, have a rounded end and are sterilizable by any method. Supplied in a cordura bag (27129). To light amnioscope set you can use GimaLed light source (code 30803), adaptor (code 30830), F.O. cable (code 30818). Single tube needs adaptor for clamp (code 30840) and clamp (29975).

#### • 29971 AMNIOSCOPE TUBE 12x24x200 mm

#### • 29972 AMNIOSCOPE TUBE 16x24x200 mm

#### • 29973 AMNIOSCOPE TUBE 20x24x200 mm

#### • 29975 ANGLED CLAMP FOR LIGHT CONNECTION



To light amnioscope tubes you can use GIMALED light source and Fibre Optic cables see page 239.

## DISPOSABLE STERILE VAGINAL SPECULUM



**MIXED SIZES BOX:**  
20 small, 70 medium, 10 large

**SIDE SCREW SPECULUM - with gradual adjustment - sterile**  
Disposable sterile speculum with gradual screw-action adjustment. Available in 3 sizes.  
Made in Asia.

GIMA code	SIDE SCREW VAGINAL SPECULUM - STERILE	Minimum order
29983	SIDE SCREW speculum - small Ø 20 mm	box of 100
29984	SIDE SCREW speculum - medium Ø 28 mm	box of 100
29985	SIDE SCREW speculum - large Ø 33 mm	box of 100
29986	SIDE SCREW speculum - mixed* sizes	box of 100


\*mixed box includes 20 small, 70 medium, 10 large vaginal speculum



### CENTRAL PIN, MIDDLE SCREW, TACHE SPECULUM


Three different models of disposable sterile speculum.  
Sold in mixed box containing 3 sizes: small, medium, large.  
Made in Asia.

GIMA code	CENTRAL PIN / MIDDLE SCREW / TACHE STERILE	Minimum order
29991	CENTRAL PIN Speculum - mixed* sizes	box of 100
29995	MIDDLE SCREW Speculum - mixed* sizes	box of 100
29987	TACHE Speculum - mixed* sizes	box of 100



**CUSCO SPECULUM - with gradual adjustment - sterile**  
Disposable speculum with gradual screw-action adjustment. It is manufactured with the best non-toxic transparent material, comes in a single transparent vacuum pack and is sterilized with ethylene oxide. Sterilization is guaranteed by the special quality control label on each pack. Available 3 sizes distinguishable through screw colour.

GIMA code	CUSCO VAGINAL SPECULUM - STERILE	Minimum order
29976	CUSCO Speculum - small 85 x 20 mm	box of 120
29977	CUSCO Speculum - medium 90 x 28 mm	box of 120
29978	CUSCO Speculum - large 100 x 36 mm	box of 108



### PERNO SPECULUM - with central key adjustment

For dilation of the vaginal canal to expose the uterus neck. It allows the adjustment of the vaginal opening by positioning the blades and locking the central key. The smooth surface and rounded edges aid a comfortable introduction. The central key can be bent down for an easier introduction of cumbersome instruments. Available 3 sizes distinguishable through key colour.

GIMA code	PERNO VAGINAL SPECULUM - STERILE	Minimum order
29946	PERNO Speculum - small Ø 20 mm	box of 120
29947	PERNO Speculum - medium Ø 26 mm	box of 120
29948	PERNO Speculum - large Ø 30 mm	box of 120

## STAINLESS STEEL VAGINAL SPECULUM - CUSCO AND COLLIN



GIMA code	STAINLESS STEEL SPECULUM
29770	Cusco stainless steel speculum - small 75x32 mm
29771	Cusco stainless steel speculum - medium 85x35 mm
29772	Cusco stainless steel speculum - large 100x37 mm
29773	Cusco stainless steel speculum - virgin 75x17 mm
29763	HF Cusco stainless steel speculum - medium with insulation for HF applications and suction connector
29768	Collin stainless steel speculum - medium 100x35 mm



## STERILE PAP TEST KITS

Instructions:  
GB, IT, PT

CE 0373




29702

READY TO USE  
PAP TEST KIT

### • 29702 PAP TEST KIT - sterile - box of 100 pcs.

Pap-Test is a painless examination to detect the presence of any anomalous cells on the cervix. It allows an early diagnosis of uterus neck cancer. The functional configuration of the kit allows a ready to go operation.

The kit includes: two latex gloves, one perno speculum (medium size), one brush, one Ayre spatula (wooden), two slides and one box for them. Individually packed in sterile pouch.



29704

CE 0476

### • 29704 PAP TEST KIT - sterile - box of 50 pcs

The kit includes: one pair latex glove, one side-screw speculum (medium size), one GIMA brush ball, one Ayre spatula A size (wooden), two slides. Individually packed in sterile pouch.

### • 29703 PAP TEST KIT - sterile - box of 100 pcs

Same as 29702 but without speculum. Instructions: GB, FR, IT.

29703

## LUBRIGIMA: LUBRICANT GEL

### • 29960 LUBRIGIMA - 250 ml

Facilitates instruments insertion during gyn. examinations. Its special composition and high transparency do not alter the visual image when optical instruments are used. It does not contain spermicides and does not grease or stain. It has acid Ph and good electrical conductivity. Water soluble. Well absorbed by the skin, does not irritate the mucosa. LATEX FREE.

MADE IN ITALY



29960

## KLY LUBRICATING GEL

### • 29957 KLY LUBRICATING GEL

sachet 5 g - box of 100

### • 29959 KLY LUBRICATING GEL

tube 82 g - 1 tube

### • 29958 KLY LUBRICATING GEL

tube 42 g - sterile and paraben-free - 1 tube

Hypoallergenic lubricating gel, does not irritate skin, dissolves in water and is easily cleaned. It does not contain oil or oily substances. It has no toxic effects or odour. It is used in endoscopy, gastroscopy, colonoscopy and rectoscopy.

Each 100 g



29959

Multilingual box and manual (29958-9 only):  
GB, FR, IT, ES, DE, PT, GR, RU, TR, Arabic

## LUBRICATING GEL WITH CHLOREXIDINE

### • 29961 FARMAGEL® C LUBRICATING GEL WITH CHLOREXIDINE - single use squeeze bulb 12.5 g - sterile - box of 25


Farmagel® C is a sterile water-soluble, grease-free, transparent lubricating gel. Suitable for endoscopic procedures which require lubricating action. It reduces friction between probe and mucosa facilitating the entry of diagnostic or therapeutic devices into the body. It does not irritate and is easily removable from skin and clothing.

Ingredients: chlorhexidine (0.05%), hydroxyethyl cellulose, glycerin, purified water, hydrochloric acid. Class IIa medical device.

MADE IN ITALY




29961



CE 0467

## PROCTOSCOPE




CE 0476

### • 25957 PROCTOSCOPE adult - box of 50 pcs.

All proctoscopes are made in PS and packed in single sterile pouch. Disposable product for single use.

mm	A	B	C	D	E
25957	110.5	155	95	17.8	22

## AYRE SPATULA - BIRCH WOOD




Non sterile 29743

Sterile 29745

GIMA code	AYRE SPATULA - WOOD	Length	Minimum order
29743	Ayre Spatula A 5 boxes of 100 pcs = 500 pcs	18 cm	500 pcs.
29745	Sterile Ayre Spatula A Individually packed in sterile pouch, in box of 100	18 cm	100 pcs.

## AYRE SPATULA - PLASTIC



29748

29749

Used for ecto-cervical and posterior fornix cells sampler in uterus neck cancer screening procedures. 29746

GIMA code	AYRE SPATULA - PLASTIC	Material	Length	Minimum order
29746	Ayre Spatula Packed in plastic bags of 25 pcs., in carton of 400 pcs.	PP	18 cm	400 pcs.
29748	Sterile Ayre Spatula A Individually packed in sterile pouch, in box of 100	PP	18 cm	100 pcs.
29749	Sterile Ayre Spatula B Individually packed in sterile pouch, in box of 100	PP	18.8 cm	100 pcs.

## GIMA BRUSH



Sterile pack 29742

brush Ø=6 mm

CE 0123


MADE IN ITALY

20 cm

CE 29739-29740

- 29739 GIMA BRUSH - conical - bag of 25 pcs.
  - 29740 GIMA BRUSH - conical - box of 400 pcs.
- These single-use endocervical brushes are an efficient method of collecting vulval, endocervical and nasal surface samples for cytological/microbiological examinations. Non sterile. Packed in plastic bags of 25 units, in carton of 400 units.
- 29742 GIMA BRUSH - conical - STERILE - box of 500 pcs
- As code 29740, individually packed in sterile plastic bag. Multilingual manual: GB, FR, IT, ES, PT, DE, FI, GR, HR.

## GIMA BRUSH - STERILE



CE 0476

Special "ball" to avoid cervix puncture and patient pain during the procedure


29736

29735


20 cm

Each brush is packed in a single sterile pouch and box of 100 pouches

- 29735 GIMA BRUSH B - sterile - box of 100 pcs.
  - 29736 GIMA BRUSH BALL - sterile - box of 100 pcs.
- Each brush is packed in a single sterile pouch and box of 100 pouches.



## COTTON SWABS



29753 Label to write patient data

STERILE SWAB STICK


29754

29756

29750

GIMA code	COTTON SWABS	Shaft Material	Cotton Ø	Shaft length	Minimum order
29750	Cotton Swab Packed in plastic bags of 25 pcs., in carton of 400 pcs.	Plastic	1 cm	18 cm	400 pcs.
29753	Sterile Cotton Swab Packed in box of 100 pcs.	Plastic	15 cm	18 cm	100 pcs.
29754	Cotton Swab Packed in plastic bags of 100 pcs., in carton of 1000 pcs.	Wood	15 cm	18.8 cm	1,000 pcs.
29756	Cotton Swab Packed in plastic bags of 50 pcs., in carton of 500 pcs.	Wood	15 cm		500 pcs.

## WALLACH PAPETTE, GIMA COLLECTOR



WALLACH

29737

29738


29737

With Wallach papette all it takes is a simple rotating motion to collect a total sampling endocervical and ectocervical cells, including the transformation area, with less trauma.


GIMA code	PAPETTES	Material	Shaft length	Minimum order
29738	Wallach papette Packed in bag of 100 pcs with multilingual manual (GB, FR, IT, ES, PT, GR)	Plastic	16 cm	100 pcs.
29737	Sterile GIMA collector Packed in a single sterile pouch in box of 100 pouches	Plastic	19.5 cm	100 pcs.



## "KARMAN" AND "BERKELEY" INTRAUTERINE SUCTION CURETTES



Length 24 cm with connector, 20.5 cm without



Length 20 cm with connector, 17 cm without



GIMA code	"KARMAN" STYLE CURETTES FLEXIBLE - SINGLE USE - STERILE	Minimum order
29858	Karman Curette N° 4 - 4 mm x 24 cm	box of 20
29859	Karman Curette N° 5 - 5 mm x 24 cm	box of 20
29860	Karman Curette N° 6 - 6 mm x 24 cm	box of 20
29861	Karman Curette N° 7 - 7 mm x 24 cm	box of 20
29862	Karman Curette N° 8 - 8 mm x 24 cm	box of 20
29863	Karman Curette N° 9 - 9 mm x 24 cm	box of 20
29864	Karman Curette N° 10 - 10 mm x 24 cm	box of 20
29865	Karman Curette N° 11 - 11 mm x 24 cm	box of 20
29866	Karman Curette N° 12 - 12 mm x 24 cm	box of 20

MADE IN ITALY




GIMA code	"BERKELEY" STYLE CURETTES CURVED - RIGID - SINGLE USE - STERILE	Minimum order
29870	Berkeley Curette N° 7 - Ø 7 mm x 20 cm	box of 20
29871	Berkeley Curette N° 8 - Ø 8 mm x 20 cm	box of 20
29872	Berkeley Curette N° 9 - Ø 9 mm x 20 cm	box of 20
29873	Berkeley Curette N° 10 - Ø 10 mm x 20 cm	box of 20
29874	Berkeley Curette N° 11 - Ø 11 mm x 20 cm	box of 20
29875	Berkeley Curette N° 12 - Ø 12 mm x 20 cm	box of 20

## CANNULAS FOR ENDOMETRIAL SAMPLING



- 29826 PIPELLA 1 hole - disposable, sterile - box of 100
  - 29827 PIPELLA 4 holes - disposable, sterile - box of 100
- For endometrial cytologic sampling. It allows a painless and easy routine screening of the endometrium avoiding dilation and traction of the uterus neck.
- Hole: Ø 2.0-2.5 mm  
External diameter: 3.1 mm  
Length of cannula: 23.5 cm  
Length of handle: 26.5 cm

- 29940 ENDOGYN - disposable, sterile - box of 25
- For cytologic endometrial sampling. It allows a painless and easy routine screening of the endometrium avoiding dilation and traction of the uterus neck. An outer sheath covers a mandrel with asymmetrical "V" shaped blades on the top. Each arm features fine toothings and thin cutting edges which are able to remove and keep more endometrial tissue. The head of one of the two arms features a hemispherical head which, when it goes back inside the sheath, allows for previously removed tissue to be aspirated.



## MICROSCOPE SLIDES AND BOX



29775

29777

Twin frosted in both ends, ground edges, sandblasted band

29775

Single end frosted, sandblasted band, ground edges

29774

Plain side, ground edges

29776

**BOX FOR SLIDES**  
Plastic, transparent box for storage of up to three slides.

Multilingual box:  
GB, FR, IT, ES, PT, GR

### MICROSCOPE SLIDES

Size 76x26 mm, 1.0-1.2 mm thick 45° corners

GIMA code	MICROSCOPE SLIDES box of 200 pcs. (4 boxes of 50 pcs.)
29774	Plain side, ground edges
29775	Single end frosted, sandblasted band, ground edges
29777	Twin frosted in both ends, ground edges, sandblasted band
BOX FOR SLIDES	
29776	Box for slides - box of 20 pcs

## CITOLOGY FIXATION

- 29778 GIMAFIX SPRAY FOR CITOLOGY FIXATION - 250ml - box of 12
- Fixer for cytology.  
Composition: isopropanole, poly-ethylenglycole.  
It does not contain propellants deleterious for the ozone.



29778

MADE IN ITALY

# PREGNANCY TESTS: MIDSTREAM, STRIP AND CASSETTE

**SELF TESTS**

CE 0123

**29098**

**MIDSTREAM**

**29097**

**29103**

**CE 0197**

**Test di gravidanza**

Extra early detection 3 days before you miss your period

**SHELF LIFE 36 MONTHS**

Large wipe allows a better absorption of the urine sample reducing the risk of false results

**CUSTOMIZED PREGNANCY SELF TESTS**  
minimum 5,000 pcs.

GIMA offers a complete line of pregnancy tests, both for OTC market (self test) and for professional use. All products are packed in cardboard boxes with multilingual user manual (GB, IT, ES, FR, GR, PT, DE\*, PL\*). \*Manual only

Main features:

- each test is individually packed in sealed aluminium pouch
- very quick, in 3 minutes
- early detection: it can be used since the first day you miss your period (three days before for 29103)
- accuracy: 99.9% (29090-2), 99.0% (29097-8, 29103)
- sensitivity: 20 mIU/ml (29090, 29091, 29092, 29097, 29098) 10 mIU/ml (29103)
- clinically tested

**PROFESSIONAL TESTS**

**MIDSTREAM**

**29090**

**STRIP**

**29091**

**CASSETTE**

**29092**

**29090**

**29091**

**29092**

**Read results in 3 minutes (29090, 29097, 29098, 29103)**

Step 1

Step 2

Step 3

Positive

Negative

Invalid

Until complete colour change of the indicator

PREGNANCY TESTS			
GIMA code	SELF TESTS	Type	Package
29097	SELF TEST 20 mIU/ml	midstream	box of 1 pc
29098	SELF TEST 20 mIU/ml	midstream	box of 2 pcs
29103	ULTRA SELF TEST 10 mIU/ml	midstream (large wipe)	box of 1 pc
PROFESSIONAL TESTS			
29090	PROFESSIONAL TEST	midstream	box of 25 pcs
29091	PROFESSIONAL TEST	strip 4 mm	box of 50 pcs
29092	PROFESSIONAL TEST	cassette	box of 40 pcs

# ULTRA SENSITIVE OVULATION TESTS

## OVULATION TESTS:

Easy to use self test for determination of the highest peak of fertility in woman.

Early detection test, 99.9% accurate and clinically tested.

Sensitivity: 35 mIU/ml (29124), 30 mIU/ml (29125).

All products are packed in single aluminium pouches in a cardboard boxes with multilingual user manual (GB, IT, ES, FR, GR, PT, DE, PL).

Tests have 24 months expiry at production time.

Our stock may vary from 10 to 22 months.

Results in 3 minutes (29124) or 5 minutes (29125).

GIMA code	OVULATION TESTS	Type	Package
29124	SELF TEST	midstream	box of 5 pcs
29125	SELF TEST	strip 4 mm	box of 25 pcs

**SELF TEST**

CE 0123

**29124**

**29125**

**29124**

**29125**

# BASAL THERMOMETER

• 25608 DIGITAL BASAL THERMOMETER °C - hang box - water-proof

With 4 digits, 2 decimals, for fertility control.

**4 DIGITS, 2 DECIMALS**

CE 0476



25608

# PREGNANCY DISC

• 29099 PREGNANCY DISC

Forecasts the forthcoming date of birth.

Used by obstetrician and practitioners.

Useful for assessment of drug administration.

2 rotating discs riveted in the center: 108 mm diameter (base), 76 mm diameter (top).

Can be personalized with your logo for minimum 1,000 pcs.



**YOUR LOGO HERE**  
minimum 1,000 pcs.




## CHLAMYDIA RAPID TEST

• **29117 CHLAMYDIA TEST** - box of 20 tests  
Provide accurate results in 10 minutes, giving doctors immediate diagnosis.  
High sensitivity and specificity.  
Each box includes 20 tests, reagents, female cervical swabs, tubes, droppers, pipette and user manual. For professional use.

**Male/Female swab specimen**  
- Add reagent A and B to specimen  
- Add 3 drops of extracted specimen  
- Read results after 10 minutes

**Male urine specimen**  
- Add reagent B and A to specimen  
- Add 3 drops of extracted specimen  
- Read results after 10 minutes




CE 0123

## VAGINITIS TEST KIT

The test includes:  
1 test + vaginal swab  
+ fluid specimen  
(buffer solution)  
in single box +  
English/Italian  
manual

CE



### • 29111 VAGINITIS TEST KIT

A unique, easy-to-use and revolutionary test for gynecologists and operators. Finds the causes of the inflammation/vaginal infection in just 10 minutes. It replaces traditional bacterial tests that take days and costs only a tenth. When necessary dilute vaginal fluid specimen in a buffer solution and then transfer to reagent pad. The instruction manual contains a result guide and can be used to recognize: Trichomoniasis, negative gram bacteria, Gardnerella, Chlamydia, serious bacterial vaginitis. For professional use.

## GYN&CUBE PESSARY

• **29887 GYN&CUBE PESSARY** Ø 28/38 mm, h 38 mm - standard  
• **29888 GYN&CUBE PESSARY** Ø 32/44 mm, h 44 mm - large  
Silicone, autoclavable, latex free pessary with pyramidal shape and draining holes. Kevlar reinforced lanyard.  
Multilingual instructions: GB, FR, IT, ES, DE, NL.




**Indications:**  
- stress urinary incontinence during sustained exertion (aerobics, tennis, jogging)  
- moderate or exteriorized prolapse - moderate cystocele and rectocele  
- after childbirth, transient prolapse or incontinence.

## VAGINAL PH TEST

The kit contains:  
10 cotton swabs +  
10 reagent strips in  
an individual box  
with user manual  
(English + Italian)


CE



### • 29110 VAGINAL PH TEST - box of 10 pcs.

Quick test to determine vaginal PH.  
An easy routine test to check vaginal PH in just 1 minute to make sure it is within the physiological limits (< 4.7).  
An increase in the Ph level may indicate a change in the vaginal environment.  
This could mean there is a possible vaginitis.  
The test is ideal for pregnant women and for women with particular diseases such as diabetes. For professional use.

## RUBBER AND SILICONE PESSARY FOR UTERINE PROLAPSE - LATEX FREE



Individually packed in cardboard box. Multilingual box and instructions: GB, FR, IT, ES, PT, DE, GR.

GIMA code	RUBBER PESSARY - autoclavable*
30010	Rubber Pessary Ø 55 mm
30011	Rubber Pessary Ø 60 mm
30012	Rubber Pessary Ø 65 mm
30013	Rubber Pessary Ø 70 mm
30014	Rubber Pessary Ø 75 mm
30015	Rubber Pessary Ø 80 mm
30016	Rubber Pessary Ø 85 mm
30017	Rubber Pessary Ø 90 mm
30018	Rubber Pessary Ø 95 mm
30019	Rubber Pessary Ø 100 mm
SILICONE PESSARY - autoclavable*	
29892	Silicone Pessary Ø 55 mm
29893	Silicone Pessary Ø 60 mm
29894	Silicone Pessary Ø 65 mm
29895	Silicone Pessary Ø 70 mm
29896	Silicone Pessary Ø 75 mm
29897	Silicone Pessary Ø 80 mm
29898	Silicone Pessary Ø 85 mm
29899	Silicone Pessary Ø 90 mm
29900	Silicone Pessary Ø 95 mm
29901	Silicone Pessary Ø 100 mm
BLUE SILICONE PESSARY** - autoclavable*	
29905	Blue silicone Pessary Ø 70 mm
29906	Blue silicone Pessary Ø 75 mm
29907	Blue silicone Pessary Ø 80 mm

\*Autoclavable at 121°C/15 min or 134°C/10 min for up to 3 times  
\*\*Sterile

## DIATERMO MB 122 AND MB 160 MONO-BIPOLAR - 120 W - 160 W



### • 30540 DIATERMO MB 122 - mono-bipolar - 120 W

### • 30541 DIATERMO MB 160 - mono-bipolar - 160 W

MB 122 and 160 are HF electrocautery units suitable to perform middle monopolar or bipolar electrocautery.

By selection of the modes of operation they provide pure cut, coagulated cut, forced coagulation, soft coagulation and, with forceps, bipolar coagulation. The use of either split or normal neutral plate is allowed. MB 160 is recommended in case of damp operational fields, for instance mucous, with consequent need to have reserve of usable power. For these reasons, MB 160 is suggested for Gynecological and orthopedic surgery.

**Leading-Edge Technology.** This advanced concept device enables highly professional surgery intervention thanks to ergonomic and safety features derived from high power theatre apparatus.

**Complete safety.** Open Circuit (OC) Alarm warns the user that connection into the neutral plate has not been made or that the cable is disconnected or the neutral plate is not in contact with the patient. The alarm is signaled by an intermittent beep together with a flashing red light on the front panel. In this case HF emission for cut and coagulation operation is switched off.

**OVT Alarm.** The unit includes an internal circuit protection warning when the current delivery is exceeding.

#### STANDARD ACCESSORIES

- MB single-use two button handle
- MB waterproof foot-switch 30577 (usable as alternative to handle)
- MB flat neutral plate with cable 30564
- Power cable 2 m
- Kit of 6 (MB 122) or 10 (MB 160) short autoclavable electrodes, diam. 2.4 mm
- User manual: available in GB, ES, IT, FR, PL

\*Does not include foot switch and MB flat neutral plate with cable

#### TECHNICAL SPECIFICATIONS

	MB122	MB160	Crest Factor
Minimum preselectable power	0	0	
Level step	1	1	
Maximum output power CUT (W)	120 250Ω	160 250Ω	1.5
Maximum output power BLEND (W)	90 200Ω	120 200Ω	2.1
Maximum output power COAG FORCED (W)	80 150Ω	100 150Ω	2.0
Maximum output power COAG SOFT (W)	60 100Ω	80 100Ω	1.7
Maximum output power BIPOLAR (W)	40 100Ω	60 100Ω	1.5
Working frequency	600 kHz	600 kHz	
Weight kg	7	7	
Size LxHxD mm	260x110x265	260x110x265	
Operating voltage (switchable)	115 -230	115 -230	
Mains frequency (Hz)	50-60	50-60	
Fuses 230Vac (5x20) TIMED	2x 3.15A	2x 3.15A	
Fuses 115Vac (5x20) TIMED	2x 6.3A	2x 6.3A	
Electrical input power (VA)	300	350	
Electrical input current (230 Vac) (A)	1.3	1.5	
Electrical input current (115 Vac) (A)	2.6	3	
Five steps adjustable sound level (from 55- to 75dBA)	•	•	
Self-check	•	•	
Power accuracy output warning	•	•	
Split or not split patient plate allowed	•	•	
Last working condition storing	•	•	
Electrical Class (EN60601 - 1)	I CF	I CF	
MDD 93/42/EEC Class	II b	II b	
Patient circuit	F	F	

## MONOPOLAR ELECTROSURGERY UNIT - 50 W



### • 30516 DIATERMO 106 - 50W - monopolar

This HF electrocautery unit is particularly suitable for small operations and is recommended for dentistry, first aid and dermatology work. It offers precision of cut and immediate coagulation and give excellent results in a wide range of applications: from uterine coagulation to microcoagulation in dermatology. The modes of operation, CUT, COAG or BLEND,



#### TECHNICAL SPECIFICATIONS

Output power: CUT	50 W/400 ohm
COAG	40 W/400 ohm
BLEND	45 W/400 ohm
Working frequency:	600 kHz ±10%
Size: 180x180x100 mm	Weight: 2.8 kg
Operating Voltage: 115/230 V - 50/60 Hz switchable	
Electric input power: 90 VA	Fuse: 2x1 AT
Alarm for overheating	Footswitch operating
Norms: EN60601-1 Class I CF, EN60601-2-2 93/42/EEC (Class IIb)	
Warranty: 12 months	

#### STANDARD ACCESSORIES

- KIRKY single-use handle without buttons
- MB waterproof foot-switch (30577)
- Flat neutral plate with cable (30564)
- Kit of 6 short autoclavable electrodes, Ø 2.4 mm, length 5 cm
- Power cable 2 m - Schuko plug
- User manual: available in GB, IT, ES, FR

can be easily selected by a switch on the front panel. The complete isolation between patient and the unit and strict respect of international norms guarantee total safety.



## MONO-BIPOLAR ELECTROSURGICAL UNITS 80W, 120W, 160W



CASUALTY SURGERY  
PEDIATRIC SURGERY\*  
PLASTIC SURGERY\*  
VASCULAR SURGERY  
DERMATOLOGY  
FIRST AID  
OTORHINOLARYNGOLOGY  
UROLOGY\*  
GYNAECOLOGY  
VETERINARY  
DENTISTRY\*\*

\*Diatermo MB160 only  
\*\*Diatermo MB120 only



- 30627 DIATERMO MB 80D - mono-bipolar - 80 W
  - 30628 DIATERMO MB 120D - mono-bipolar - 120 W
  - 30629 DIATERMO MB 160D - mono-bipolar - 160 W
- Diatermo MB are high frequency electrosurgical units suitable for minor and medium surgery.
- MB allows pure CUT, cut-coagulation BLEND, superficial coagulation FORCED COAG, deep coagulation in absence of necrosis SOFT COAG and, with forceps, BIPOLAR coagulation. The digital reading of delivered power and the monitoring of operative function by microcontroller guarantee absolute reliability of working conditions.
- MB allows a highly professional surgery through ergonomic features. Neutral electrode connection and patient/plate contact are constantly monitored.
- The possibility of output functions and output power delivery control, by handle, allows surgical procedures without divert attention from operation field.

### Features:

- minimum invasive surgery
- possibility to use bipolar forceps
- possibility to use split neutral electrodes
- memorization of the last used settings
- power activation by pedal and/or handle
- digital adjustment and indication of the output power
- adjustment of the acoustic indicator intensity.

30629

MADE IN ITALY

CE 0051

### TECHNICAL SPECIFICATIONS

	MB 80D	MB 120D	MB 160D
Max output power CUT	80 W-250 Ω	120 W-250 Ω	160 W-250 Ω
Max output power BLEND	60 W-250 Ω	90 W-200 Ω	120 W-200 Ω
Max output power FORCED COAG	50 W-150 Ω	80 W-150 Ω	100 W-150 Ω
Max output power SOFT COAG	40 W-100 Ω	60 W-100 Ω	80 W-100 Ω
Max output power BIPOLAR	30 W-100 Ω	40 W-100 Ω	60 W-100 Ω
Working frequency	600 kHz	600 kHz	600 kHz
Patient circuit	F	F	F
Selectable input voltage	115 - 230 Vac	115 - 230 Vac	115 - 230 Vac
Mains frequency	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz
Electrical input power	230 VA	300 VA	350 VA
Size WxHxD mm	254x104x288	254x104x288	254x104x288
Weight	5 kgs	5 kgs	5 kgs
Controls:	Patient/Plate circuit monitoring, Output power monitoring, Self check control		
Safety:	EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class: I CF, MDD 93/42/EC Class: II b		

### STANDARD ACCESSORIES

MB single use two button handle  
MB waterproof foot switch 30577 (usable as alternative to handle)  
MB flat neutral plate with cable (30564)  
Kit of 10 short autoclavable electrodes, Ø 2.4 mm. Power cable: 2 m  
User manual: GB, IT, available on request FR, ES, PL

## MONOPOLAR ELECTROSURGERY UNITS 50W AND 80W



DENTISTRY  
DERMATOLOGY  
OUT PATIENT SURGERY  
FIRST AID  
VETERINARY\*  
VASCULAR SURGERY\*  
\*Diatermo 80 only

CE 0051

- 30625 DIATERMO 50 - monopolar
- 30626 DIATERMO 80 - monopolar

MADE IN ITALY

DIATERMO 50 and 80 are radiofrequency electrosurgical units suitable for minor monopolar surgery.

Diatermo 50 through the function selection makes pure cut, cut coagulation (CUT 1 - CUT 2) and pure coagulation possible. Diatermo 80 has a multifunction selector which makes cutting (CUT), cut coagulation (BLEND), coagulation (COAG) and micro-coagulation (MICRO) possible. The one-board microcontroller and digital display guarantee high safety and reliability under any conditions. They offer outstanding professional surgical results due to their ergonomic and superior safety features.

### TECHNICAL SPECIFICATIONS

	50	80
Max output power CUT	50 W-400 Ω	80 W-400 Ω
Max output power CUT/COAG1	45 W-400 Ω	-
Max output power CUT/COAG2	40 W-400 Ω	-
Max output power BLEND	-	60 W-400 Ω
Max output power COAG	40 W-400 Ω	50 W-400 Ω
Max output power MICRO	-	20 W-600 Ω
Working frequency	600 kHz	700 kHz
Patient circuit	F	F
Selectable input voltage	115 - 230 Vac	115 - 230 Vac
Mains frequency	50 - 60 Hz	50 - 60 Hz
Electrical input power	200 VA	230 VA
Size WxHxD mm	190x85x239	190x85x239
Weight	2.5 kg	2.5 kg
Controls:	Patient/Plate circuit monitoring, Output power monitoring, Self check control	
Safety:	EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class: I CF, MDD 93/42/EC Class: II b	

### STANDARD ACCESSORIES

Single use handle  
MB waterproof foot switch (30577)  
MB flat neutral plate with cable (30564)  
Kit of 6 short autoclavable electrodes, Ø 2.4 mm, length 5 cm (30501/2/4/7/9/10) see page 229  
Power cable 2 m - Schuko plug  
User manual: GB, IT, available on request FR, ES

# MONO-BIPOLAR ELECTROSURGICAL UNIT 200W



## • 30630 DIATERMO MB 200D - 200 W

MB 200D is a high frequency electrocautery equipment suitable for light and medium surgery, allows minimally invasive surgical procedure of resection, evaporation and coagulation.

MB 200D allows pure CUT, Cut-Coagulation BLEND, incision with reduced production of eschar ENHANCED, superficial coagulation FORCED COAG, deep coagulation in absence of necrosis SOFT COAG and BIPOLAR coagulation. Digital reading of delivered power and surveillance through microcontroller of the operational functions, assure absolute reliability of working conditions.

MB 200D allows a highly professional surgery through ergonomic and safety features. The connection of neutral electrode is constantly monitored. Safety control of patient/plate contact using split neutral electrode. Possibility to control the output functions and the delivery of output power by the handle, allows the surgical operation without diverting attention from the surgical field.

- patient-to-plate contact control

### STANDARD ACCESSORIES

MB two-button autoclavable handle (30536)  
 MB waterproof foot-switch (30577)  
 Flex steel neutral plate with cable (30555 + 30560)  
 Kit 10 short standard electrodes, Ø 2.4 mm (30500) Power cable 5 m  
 3 needle + 3 blade + 3 ball electrodes 7 cm Manual: available in GB, IT

- split return electrode use
- minimally invasive surgical treatment allowed
- monopolar and Bipolar independent output
- auto Start/Stop in Bipolar Coag
- working condition planning
- power delivery by pedal and/or handle
- digital regulation and indication of the output power
- sound level control
- adjustable power increment



### TECHNICAL SPECIFICATIONS

Maximum output power CUT	200W - 250Ω
Maximum output power ENHANCED	120W - 250Ω
Maximum output power BLEND	120W - 200Ω
Maximum output power FORCED COAG	150W - 150Ω
Maximum output power SOFT COAG	90W - 100Ω
Maximum output power BIPOLAR COAG	80W - 50Ω
Working frequency	600 kHz
Patient circuit	F
Mains voltage	115-230 Vac
Mains frequency	50-60 Hz
Electrical input power	350 VA
Size WxHxD mm	370x144x319
Weight	6 kgs
Controls:	Patient/Plate circuit monitoring, Output power monitoring, Self check control
Safety:	EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class: I CF, MDD 93/42/EC Class: II b

# DIATERMO MB 200 - MONO-BIPOLAR - 200W



MADE IN ITALY

### STANDARD ACCESSORIES

MB two-button autoclavable handle (30536)  
 MB waterproof foot-switch 30577 (usable in alternative to handle)  
 MB flat neutral metal plate with cable (30564)  
 Kit 10 short standard electrodes, Ø 2.4 mm (30500)  
 Power cable 2 m Manual: available in GB, IT

## • 30542 DIATERMO MB 200 - 200 W

DIATERMO MB200 is a HF electrocautery unit suitable to perform middle monopolar or bipolar electrocautery. The available waveforms and peak voltage value, as well as the accurate HF leakage current operation for polypectomy, TURP, intrauterine resections, endometriosis excision, etc. The units allow the accurate preset of the output power with as low as 1 Watt resolution and to perform coagulation by high crest factor current, to get an elevated thermal effect, as well as with low voltage low crest factor current, to get coagulation in absence of carbonization. Ten different programs related to ten different operative conditions could be stored and easily recalled by the surgeon. The use of either split or normal neutral plates are allowed. A special electronic circuit (Skin Plate Electronic Control) continuously checks if the plate is safely connected to the patient and detects unwanted short circuit in the connecting cable. An over time warning (OVT) is provided to prevent excessive heating of the tissue around the surgical target due to too long current delivery time.

### TECHNICAL SPECIFICATIONS

Crest factor				Weight kg	
Maximum output power CUT (W)	200	250Ω	1.5	Size LxHxD mm	8
Maximum output power CUT 90% (W)	200	250Ω	1.6	Selectable mains power(Vac)	360x150x265
Maximum output power CUT 80% (W)	200	250Ω	1.7	Mains frequency (Hz)	115 -230
Maximum output power CUT 70% (W)	200	250Ω	1.8	Fuses 115Vac - 230Vac (5x20) TIMED	50-60
Maximum output power BLEND (W)	120	200Ω	2.1	Power accuracy output warning system	2x 6.3A - 2x 3.15A
Maximum output power COAG FORCED (W)	150	150Ω	2.0	Split or not split patient plate allowed	•
Maximum output power COAG SOFT (W)	90	100Ω	1.7	Electrical Class (EN60601 - 1)	•
Maximum output power BIPOLAR COAG (W)	100	100Ω	1.5	MDD 93/42/EEC Class	I CF
Maximum output power BIPOLAR CUT (W)	120	250Ω	1.5	Patient circuit	II b
Working frequency	600 kHz			Duty cycle (action/pause) in seconds	F 10/30



## ■ MB 200 TOUCH MONO-BIPOLAR ELECTROSURGICAL UNIT 200W

### • 30693 DIATERMO MB 200 T - 200W

High Frequency electrosurgical equipment suitable for precision mono and bipolar surgery and micro-surgery, without tissue alterations.

It can also supply HF operative powers for programmable time as short as hundredths of a second.

The unit allows pure CUT, cut-coagulation BLEND, incision with reduced production of eschar ENHANCED, superficial coagulation FORCED COAG, deep coagulation in absence of necrosis SOFT COAG, bipolar CUT, COAG and SEALING, FULGURATION.

The digital reading of delivered power and the operational functions overseeing through microcontroller, assure absolute reliability of work conditions.

Diatermo MB 200 T allows a highly professional surgery due to user-friendly and safety solutions normally used.

The neutral electrode and patient/plate safety control are constantly monitored.

The possibility of output functions and output power delivery control, by handle, allows to perform surgery avoiding the surgeon to take his eyes off the operational field.

#### Software

Developed to provide a simple, functional and intuitive work experience.

Through one finger touch, you can customize screen, work settings, change cut or coagulation power and manage each device function.

#### STANDARD ACCESSORIES

Flex steel neutral plate with cable (30555+30560)  
Kit 10 short standard electrodes Ø 2.4 mm (30500)  
Power cable 5 m  
Reusable handle with switches (30536)

Holder for handle and electrodes  
Waterproof footswitch (30577)



30693

CASUALTY (R)	NEUROSURGERY (R)	PNEUMOLOGY (R)
ENDOSCOPY (R)	ORTHOPAEDICS (U)	TRANS URETHRAL RESECTION TUR (U)
FIRST AID (R)	OTORHINOLARYNGOLOGY (R)	UROLOGY (R)
GASTROENTEROLOGY (R)	PAEDIATRIC SURGERY (U)	VASCULAR SURGERY (R)
GENERAL SURGERY (U)	PLASTIC SURGERY (U)	VETERINARY (R)
GYNECOLOGY (R)		R = recommended U = usable

MADE IN ITALY

#### TECHNICAL SPECIFICATIONS

<b>Max power:</b>			
PURE CUT	200 W - 300 Ω	FULGURATION	100 W - 1000 Ω
BLEND	150 W - 300 Ω	BIPOLAR SEALING	200 W - 50 Ω
ENHANCED	150 W - 300 Ω	BIPOLAR COAG	120 W - 50 Ω
FORCED COAG	150 W - 200 Ω	BIPOLAR CUT	120 W - 50 Ω
SOFT COAG	100 W - 200 Ω		
RF power pulse:	emission time 10 ms - 30 sec, interval 1-30 F		
Patient circuit:	100 - 240 Vac - 750 VA		
Selectable input voltage:	360 KHz		
Working frequency:	370x145x300 mm - 6 kg		
Size (WxHxD) - Weight:	Patient/Plate circuit monitoring		
Controls:	Output power monitoring, Self check control		
Safety:	EN60601-1; EN60601-1-2; EN60601-2-2		
Electrical classification:	I CF MDD 93/42 / EC: II b		

## ■ MONO-BIPOLAR ELECTROSURGICAL UNITS 120W AND 200W



### • 30631 DIATERMO MB 120 FLASH

### • 30633 DIATERMO MB 200 FLASH

30631

Professional High Frequency ElectroSurgical equipment suitable for precision monopolar and bipolar surgery and micro-surgery without tissue alterations.

Surgical treatments with programmable timer operations up to milliseconds or with traditional mode.

MB FLASH allow pure CUT, cut-coagulation BLEND, incision

#### TECHNICAL SPECIFICATIONS

	MB 120F	MB 200F
Max output power CUT	120 W-250 Ω	200 W-250 Ω
Max output power BLEND	90 W-200 Ω	120 W-200 Ω
Max output power ENHANCED	90 W-250 Ω	120 W-250 Ω
Max output power FORCED COAG	80 W-150 Ω	150 W-150 Ω
Max output power SOFT COAG	60 W-100 Ω	90 W-100 Ω
Max output power BIPOLAR COAG	60 W-50 Ω	80 W-50 Ω
Working frequency	600 kHz	600 kHz
RF power pulse emission time	10ms - 30sec	10ms - 30sec
RF power pulse interval	1 - 9	1 - 9
Patient circuit	F	F
Selectable input voltage	115 - 230 Vac	115 - 230 Vac
Mains frequency	50 - 60 Hz	50 - 60 Hz
Electrical input power	300 VA	350 VA
Size WxHxD mm	370x144x319	370x144x319
Weight	6 kg	6 kg
Controls:	Patient/Plate circuit monitoring, Output power monitoring, Self check control	
Safety:	EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class: I CF, MDD 93/42/EC Class: II b	

OUTPATIENT SURGERY	PEDIATRIC SURGERY**	PODIATRY**
DERMATOLOGY	FIRST AID	PNEUMOLOGY**
VASCULAR SURGERY	PLASTIC SURGERY**	UROLOGY**
GYNECOLOGY	ENDOSCOPY	VETERINARY
DENTAL*	OPHTHALMOLOGY	GASTROENTEROLOGY
OTORHINOLARYNGOLOGY	NEUROSURGERY**	ORTHOPAEDICS**
	*Diatermo MB 120 only	**Diatermo MB 200 only

MADE IN ITALY

with reduced production of eschar ENHANCED, superficial coagulation FORCED COAG, deep coagulation in absence of necrosis SOFT COAG and BIPOLAR coagulation.

Digital reading of delivered power and the surveillance through microcontroller of the operational functions, assure absolute reliability of the working conditions. Connection of neutral electrode is constantly monitored. Safety control of patient/plate contact using split neutral electrode.

Possibility to control the output functions and the delivery of output power by handle, allows surgical operation without diverting attention from the surgical field.

#### Features:

- patient to plate contact control
- split return electrode use allowed
- minimally invasive surgical treatment allowed
- monopolar and Bipolar independent output
- auto Start/Stop in Bipolar Coag
- working condition planning
- power delivery by pedal and/or handle
- digital regulation and indication of the output power
- sound level control
- adjustable power increment
- RF power pulse emission time setting and interval setting

#### STANDARD ACCESSORIES

MB two-button autoclave handle (30536)	2 disposable rem ground pads (30493)
Flex steel neutral plate with cable (30555-30560)	Power cable 5m
MB waterproof footswitch (30577)	Microsurgery handle (30552)
Kit 10 short standard electrodes Ø 2.4 mm	Microsurgery needles 10 pieces
3 needle + 3 blade + 3 ball electrodes 7 cm	Manual: GB, IT

# ■ HIGH POWER ELECTROSURGICAL UNITS 300 AND 400 WATT



- 30634 DIATERMO MB 300D
- 30635 DIATERMO MB 400D

DIATERMO MB300D and MB400D are high frequency electro-surgical equipments suitable to supply power for monopolar cut and coagulated cut (with different levels of coagulation), bipolar cut and coagulation.

## TWIN OPERATIVE ACTIVITY

- two output channels for monopolar cutting
- two independent setting and output channels for the most frequent monopolar coagulation

## CONTROLLED CUTTING PROCEDURES

- enhanced cutting current for eschar free incision
- cutting current with selectable coagulating property for bleeding controlled dissection
- low capacitive coupling by slow BLEND current for endoscopic procedures

## TWIN CONTROLLED COAGULATION PROCEDURES

- SPEEDY coagulation and DEEP coagulation available to two operators
- SPRAY coagulation by hand switch or foot switch controls

## EXTENSIVE BIPOLAR FEATURES

- bipolar cutting current with selectable bleeding control

- slow BLEND cutting current
  - automatic start/stop coagulation functions
- SURGEON AND PATIENT TOTAL SAFETY**
- acceptability of contact impedance between patient body and return electrode continuously monitored by Skin Plate Electronic Control (SPEC)
  - H.F. Leakage currents continuously monitored
  - mains fluctuation automatically compensated before delivery of HF power

## PERSONALIZED PROCEDURES

- independent choice of coagulation currents and power levels by each of two operators
- up to 10 procedures can be configured and re-called

## EXTENSION DRIVER AND INTERLOCK SIGNALS

- driven output connection to external Argon Plasma unit and Smoke Evacuator unit

## AUTOMATIC SELF DIAGNOSIS

- automatic diagnostic control of the complete functionality of electronic unit and connected accessories with coded report of failures

MADE IN ITALY



OUTPATIENT SURGERY  
GENERAL SURGERY  
PAEDIATRIC SURGERY  
PLASTIC SURGERY  
THORAX SURGERY  
VASCULAR SURGERY  
DERMATOLOGY  
ENDOSCOPY

GASTROENTEROLOGY  
GYNAECOLOGY  
NEUROSURGERY  
ORTHOPEDICS  
OTORHINOLARINGOLOGY  
PNEUMOLOGY  
UROLOGY  
VETERINARY

30634

## TECHNICAL SPECIFICATIONS MB300/MB400

	MB 300	MB 400
Maximum out power monopolar pure CUT	300 W - 300 Ω	400 W - 300 Ω
Maximum out power monopolar cut-coag CUT80%	250 W - 300 Ω	350 W - 300 Ω
Maximum out power monopolar cut-coag CUT60%	200 W - 300 Ω	250 W - 300 Ω
Maximum out power monopolar cut-coag CUT40%	150 W - 300 Ω	200 W - 300 Ω
Maximum out power monopolar cut ENHANCED	200 W - 500 Ω	250 W - 500 Ω
Maximum out power monopolar cut-coag BLEND	200 W - 300 Ω	250 W - 300 Ω
Maximum out power monopolar coag SPEEDY	100 W - 500 Ω	120 W - 500 Ω
Maximum out power monopolar coag DEEP	100 W - 200 Ω	120 W - 200 Ω
Maximum out power monopolar coag SPRAY	70 W - 2000 Ω	100 W - 2000 Ω
Maximum out power monopolar coag SPRAY ARGON	70 W - 2000 Ω	100 W - 2000 Ω
Maximum out power bipolar CUT	95 W - 150 Ω	95 W - 150 Ω
Maximum out power bipolar cut-coag CUT80%	95 W - 150 Ω	95 W - 150 Ω
Maximum out power bipolar cut-coag CUT60%	95 W - 150 Ω	95 W - 150 Ω
Maximum out power bipolar cut-coag CUT40%	60 W - 150 Ω	60 W - 150 Ω
Maximum out power bipolar cut-coag BLEND	90 W - 150 Ω	90 W - 150 Ω
Maximum out power bipolar cut-coag BLEND	70 W - 100 Ω	70 W - 100 Ω
Working frequency monopolar / bipolar	425 kHz / 525 kHz	425 kHz / 525 kHz
Patient circuit	F	F
Selectable input voltage	115-230 Vac	115-230 Vac
Mains frequency	50-60 Hz	50-60 Hz
Electrical input voltage	1000 VA	1000 VA
Size WxHxD mm	470x150x400	470x150x400
Weight	17.5 Kgs	17.5 Kgs
Controls:	Patient/Plate circuit monitoring, Output power monitoring, Self check control	
Safety:	EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class: I CF, MDD 93/42/EC Class: II b	

## STANDARD ACCESSORIES

- 1 - Power supply cord 5 m
- 1 - Two-button autoclavable handle (30536)
- 5 - Two-button cold sterilizable handle (30551)
- 1 - Flex steel neutral plate (30555)
- 1 - Cable for flex plate (30560)
- 5 - Rem disposable ground pads (30493)
- 2 - HP double Water proof foot switch (30604)
- 3 - Short, general surgery blade electrode 7 cm
- 3 - Long, general surgery blade electrode 16 cm
- 3 - Short, general surgery ball electrode Ø 4 mm, 6 cm
- 1 - Electrode brush
- 1 - User manual (IT, GB)
- 1 - Service manual (IT, GB)





# ELECTROSURGICAL UNITS TOUCHSCREEN 300 AND 400 WATT



USE	300	400
DERMATOLOGY	R	U
ENDOSCOPY	R	U
GASTROENTEROLOGY	R	R
GENERAL SURGERY	R	R
GYNECOLOGY	R	U
NEUROSURGERY	R	R
ORTHOPAEDICS	U	R
OTORHINOLARYNGOLOGY	R	U
PAEDIATRIC SURGERY	R	R
PLASTIC SURGERY	R	R
PNEUMOLOGY	R	U
THORAX SURGERY	U	R
TRANS URETHRAL RESECTION (TUR)	U	R
UROLOGY	R	R
VASCULAR SURGERY	U	U
VETERINARY	R	U

R= recommended U= usable



MADE IN ITALY

- 30695 DIATERMO MB 300 T
- 30697 DIATERMO MB 400 T

Diatermo MB 300 T and MB 400 T, the new generation of electrosurgery, that allows two surgeons to work simultaneously.

A radiofrequency generator suitable for microsurgery and precise surgery in monopolar and bipolar modality. The simplicity of new Diatermo MB 300 T and MB 400 T allows you to use it without learning time, resulting in time savings. The initial setup and setting adjustments, during a surgery, can be easily selected through the large touchscreen.

## Performance, usability, design and reliability

- simultaneous activation of monopolar and bipolar
- power control depending on impedance
- activating power with pedal and / or handpiece
- neutral-patient electrode contact control
- cutting function under saline solution TUR
- modular cut in wet conditions BLEND
- vessel sealing to clamp vessels up to 7 mm
- possibility of use for minimally invasive surgery
- monopolar / bipolar functions
- auto-start / auto-stop in bipolar modality
- adjusting sound intensity

## An intuitive and logic work environment

Diatermo MB 300 T and MB 400 T have a particularly basic and intuitive work environment.

Horizontal matching between monitors, RGB light indications and connectors provide a clear and easy-to-read overview. The large 9" capacitive touchscreen, designed with a sleek flat front, ensures faster and more efficient cleaning in the operating room.

## State of the art device

Highly professional surgery with ergonomic and safety solutions.

Neutral electrode connection is constantly monitored: if a split neutral plate is used, the device will monitor the contact between the patient and the electrode.

## STANDARD ACCESSORIES

- Flex steel neutral plate with cable (30556+30560)
- 3 blade electrodes - 7 cm
- 3 blade electrodes - 16 cm
- 3 ball Ø 4 mm electrodes - 6 cm
- Reusable handle with switches (30536)
- MB waterproof foot switch (30608)
- Power cable 5 m

The possibility to switch the functions and active the power supply from the handpiece, allows surgical procedures without divert attention from operation field.

## Software

Developed to provide a simple, functional and intuitive work experience.

Through one finger touch, you can customize and save your work settings, change the cut or coagulation power and manage each device function.




## TECHNICAL SPECIFICATIONS

	MB 300 T	MB 400 T
Maximum output power PURE CUT	300 W - 300 Ω	400 W - 300 Ω
Maximum output power BLEND	200 W - 300 Ω	250 W - 300 Ω
Maximum output power ENHANCED	200 W - 300 Ω	250 W - 300 Ω
Maximum output power FORCED COAG	120 W - 150 Ω	150 W - 150 Ω
Maximum output power SOFT COAG	120 W - 200 Ω	150 W - 200 Ω
Maximum output power FULGURATION	80 W - 500 Ω	100 W - 500 Ω
Maximum output power BIPOLAR TUR	250 W - 200 Ω	300 W - 200 Ω
Maximum output power BIPOLAR CUT	150 W - 100 Ω	150 W - 100 Ω
Maximum output power BIPOLAR COAG	150 W - 50 Ω	150 W - 50 Ω
Maximum output power BIPOLAR SEALING	250 W - 50 Ω	250 W - 50 Ω
Working frequency	360 kHz	360 kHz
Patient circuit	F	F
Selectable input voltage	100-240 Vac	100-240 Vac
Mains frequency	50-60 Hz	50-60 Hz
Electrical input voltage	1000 VA	1000 VA
Size WxHxD mm	450x200x420	450x200x420
Weight	15.5 kg	15.5 kg

**Controls:** Patient/Plate circuit monitoring, Output power monitoring, Self check control, HF leakage currents control, Compensation of mains fluctuation  
**Safety:** EN60601-1, EN60601-1-2, EN60601-2-2, Electrical Class: I CF, MDD 93/42/EC Class: II b

# LAPAROSCOPIC STERILE ELECTRODES



Laparoscopic electrodes without suction for use with Diatermo MB 240/250/300/380/400 with connecting cable 4 mm (30609)

30605

GIMA code	LAPAROSCOPIC ELECTRODES - sterile
30605	L-Hook electrode - 36 cm
30606	J-Hook electrode - 36 cm
30607	Spatula electrode - 36 cm
30609	Monopolar cable - 4 mm - M - F - 3 m

## LOOP ELECTRODES Ø 2.4 mm - AUTOCLAVABLE OR DISPOSABLE

GIMA code	LOOP ELECTRODES - Ø 2.4 mm autoclavable at 134°C - non sterile	Shaft length	Electrode width	Electrode depth
30686	Square loop electrode	13 cm	10 mm	8 mm
30687	Loop electrode	13 cm	15 mm	8 mm
30688	Loop electrode	13 cm	20 mm	10 mm

GIMA code	LOOP ELECTRODES - Ø 2.4 mm disposable - sterile	Shaft length	Electrode width	Electrode depth	Minimum order
30677	Square loop electrode	13 cm	10 mm	8 mm	box of 10
30678	Loop electrode	13 cm	15 mm	8 mm	box of 10
30679	Loop electrode	13 cm	20 mm	10 mm	box of 10

## AUTOCLAVABLE ELECTRODES Ø 2.4 mm

GIMA code	Reference number	AUTOCLAVABLE ELECTRODES Ø 2.4 mm	Reference number	GIMA code
length 5 cm		minimum order: 6 pcs.	length 10 cm	
30501	1	Electrode wire 0.2 - straight	21	30521
30502	2	Electrode wire 0.2 - angled 45°	22	30522
30503	3	Electrode bend - Ø 4 - straight	23	30523
30504	4	Electrode bend - Ø 8 - straight	24	30524
30505	5	Electrode hook - angled 45°	25	30525
30506	6	Electrode wire 1 mm.- angled 45°	26	30526
30507	7	Electrode straight slip-knot - straight	27	30527
30508	8	Electrode angled slip-knot - straight	28	30528
30509	9	Electrode ball point - Ø 3 mm - angled 45°	29	30529
30510	10	Electrode ball point - Ø 3 mm - straight	30	30530
30500	SET	Set of 10 electrodes	SET	30531
length 7 cm		minimum order: 10 pcs.	length 15 cm	
30511	15	Needle electrode	35	30532
30512	16	Blade electrode	36	30533
30513	17	Ball electrode Ø 4 mm	37	30534

## SINGLE USE STERILE ELECTRODES Ø 2.4 mm

Length		SINGLE USE ELECTRODES Ø 2.4 mm
7 cm	15 cm	Sterile electrode - box of 24
30670	30674	Needle electrode - sterile electrode
30671	30675	Blade electrode - sterile
30672	30676	Ball Ø 4 mm electrode - sterile

## SINGLE USE NON-STICK STERILE ELECTRODES Ø 2.4 mm

GIMA code	NON-STICK SINGLE USE ELECTRODE Ø 2.4 mm	Length
30420	Blade electrode - sterile	7 cm
30422	Blade electrode - sterile	10 cm
30425	Needle electrode - sterile	10 cm
30429	Ball electrode - sterile	13 cm


## SINGLE USE STERILE TUNGSTEN NEEDLE ELECTRODES Ø 2.4 mm

Straight	Angled	TUNGSTEN MICRO NEEDLE ELECTRODES	Length
30370	30371	Tungsten electrode - sterile	5 cm
30372	30373	Tungsten electrode - sterile	6 cm
30374	30375	Tungsten electrode - sterile	7 cm

Tungsten needle has extremely high melting point (> 3400°C) which helps maintain sharpness.

## ELECTRODE CLEANING PAD

• 30537 ELECTRODE CLEANING PAD - 50x50 mm - box of 100  
Disposable sterile radiopaque abrasive tip cleaner pad.



30537



## 3-PIN MONOPOLAR HANDLE AND ELECTRODES Ø 4 mm

• **30480 AUTOCLAVABLE MB HANDLE Ø 4 mm - 100 times**  
Autoclavable handle up to 100 times for Ø 4 mm shaft electrodes with 3 m silicone cable and blade electrode.

- **30482 NEEDLE ELECTRODE Ø 4 mm** 30482
  - **30483 BLADE ELECTRODE Ø 4 mm** 30483
  - **30484 BALL ELECTRODE Ø 4 mm** 30484
- S/S electrodes autoclavable 100 times.  
Sold in box of 5.  
Length 5.5 cm.



## 3-PIN MONOPOLAR HANDLES FOR ELECTRODES Ø 2.4 mm

**VALLEYLAB CONNECTOR HANDLES with 2 "click" push-buttons**  
GIMA autoclavable electrosurgery pencils with CUT-COAG switch have been studied and tested to offer maximum reliability and functionality to the operator. MB handles are provided with a 3 Pin plug Valleylab type fitting all Gima mono-bipolar Diatermo MB (80, 120, 122, 132, 160, 200, 240, 300, 380, 400) and most of bipolar electrosurgical units: Aspen Lab, ES Generator, EMC Statome, Danieli, Braun, Berchtold, Ohmeda, Ritter, Conmed, Eschmann, Bovie, Martin, Kontron, Bard, Birtcher 771, Cobi, Valleylab, Led, Erbe...

### ■ AUTOCLAVABLE HANDLES

- **30554 MB AUTOCLAVABLE HANDLE - 100 times**  
Autoclavable handle with 2 large "click" push-buttons, provided with a 3 meter long silicone cable and a blade electrode. It can be autoclaved up to 100 times (electrode 20 times).
- **30545 MB AUTOCLAVABLE HANDLE - 100 times**  
Same as code 30554 but with a 5 m long silicone cable
- **30550 PRIMA MB AUTOCLAVABLE HANDLE - 60 times**  
Autoclavable handle with 2 large "click" push-button, provided with a 3 meter long silicone cable and a blade electrode. It can be autoclaved up to 60 times.
- **30548 STAR AUTOCLAVABLE HANDLE - 30 times**  
Same as code 30554 but autoclavable up to 30 times (electrode is autoclavable up to 20 times).
- **30539 ORION PLUS AUTOCLAVABLE HANDLE - 100 times**  
Same as 30554, but with a screw clamp locking system ensuring a safe contact and adapting to slightly different electrode diameters. High insulation to prevent liquid damage.
- **30536 SURGEON AUTOCLAVABLE HANDLE - 100 times**  
Autoclavable, waterproof handle with ergonomic grip. Coloured ring that indicates CUT and COAG push buttons. Provided with 3 m cable and blade electrode.

### ■ SINGLE USE HANDLE

- **30551 KIRKY SINGLE-USE HANDLE - STERILE**  
Single-use handle with "click" push-buttons for cut and coag. Includes blade electrode and 3.20 m cable.
- **30553 GIMA SINGLE-USE HANDLE - STERILE**  
Same as 30551 with 3 m cable.



## 1-PIN MONOPOLAR HANDLES FOR ELECTRODES Ø 2.4 mm


### 1 pin plug HANDLES for diatermo 50, 80, 106, 108

These handles are provided with a 1 Pin socket (4 mm) fitting all Gima Diatermo and most of electrosurgical units in the market. These handles **do not have push-buttons**.

- **30515 SURGEON 1 PIN AUTOCLAVABLE HANDLE - 100 times**  
Autoclavable, waterproof handle with ergonomic grip. Provided with 3 m cable and blade electrode
- **30519 AUTOCLAVABLE 50-80-106-108 HANDLE**  
Autoclavable handle without buttons, provided with a 3 meter long cable and a blade electrode. It can be autoclaved up to 100 times.
- **30518 KIRKY SINGLE-USE 50-80-106-108 HANDLE - STERILE**  
Single-use handle without button with blade electrode with 4 mm PIN connection.



## MONOPOLAR FORCEPS, SCISSORS AND CABLES



Monopolar forceps and scissors are provided with a 4 mm connection for standard monopolar cables. These can be used with all Gima, LED, Erbe and many other electrosurgical units in the market.

GIMA code	INSULATED MONOPOLAR INSTRUMENTS
30610	Monopolar cable - 4 mm pin - 3 m
30611	Mc INDOE straight monopolar forceps 15 cm (6")
30612	Bayonet monopolar forceps - 20 cm (7 1/2")
30613	Monopolar scissors - straight - 18 cm (7")
30614	Metzenbaum monopolar scissors - straight - 18 cm (7")
30615	Metzenbaum monopolar scissors - curved - 18 cm (7")

## 3M ELECTROSURGICAL GROUNDING PADS WITH SAFETY RING

- 30496 3M 9160 SPLIT GROUNDING PAD - box of 100
  - 30497 3M 9160F SPLIT GROUNDING PAD - box of 200 (40 pouches of 5 pieces)
  - 30498 3M 9165 SPLIT GROUNDING PAD - precorded - box of 40
- The 3M Universal Grounding Pads all have a conductor area of 15 square inches and come with the patented 3M Green Safety Ring technology which allows them to perform the same as grounding pads that are up to 33% larger in conductor area. Green Ring allows adult and pediatric use.

They have fluid resistance, non-woven backing which allows heat to pass through up to 25% faster than foam, and they have no minimum age or weight limit.



30496, 30497  
(3M 9160)



30498  
(3M 9165)

## HANDLES FOR ELECTROLYSIS NEEDLES

Needle handles for all GIMA Diatermo and electro-depilators

- 30552 HANDLE for electrolysis needles
- 30415 PROFESSIONAL HANDLE for electrolysis needles


30415



30552

1 pin (Ø 4mm)  
plug of above handles

## BALLET STERILE DISPOSABLE ELECTROLYSIS NEEDLES



30400-30401

30405-30406

30410-30411

Stainless steel	Gold plated	Insulated	ELECTROLYSIS NEEDLES - STERILE	Minimum order
30400	30405	30410	K2 needle - 0.055 mm (0.002")	box of 50
30401	30406	30411	K3 needle - 0.075 mm (0.003")	box of 50

### Ballet needles

Manufactured with a precise point and a mirror-like surface polish. The rounded tapered point of the needle assists the electrologist in locating the follicle opening and upon insertion the needle will slide smoothly and accurately to the base of the follicle.

### Stainless steel needles

Ideal for patients with strong healthy skin who respond well to electrolysis treatment.

### Insulated needles

Suggested for patients with high sensitivity to discomforts of electrolysis.

### 24 carat gold plated needles

For clients who suffer from allergies and sensitive skin.



## ELECTRODEPILATOR

### • 28340 ELECTRO-DEPILATOR 400

This device ensures a definitive depilation with thermolytic method. It delivers a current of radiofrequency to cause the heating and consequent coagulation of the papilla, reached through the introduction of a needle into the follicle of the hair. Provided with highly reliable electronic integrated components, with RF intensity adjustable with continuity and luminous working signal. It comes complete with footswitch, handpiece for depilation, depilation needle and power cable (2 m).

#### TECHNICAL SPECIFICATIONS

RF output frequency: 1.9 ±10% MHz  
Modulation: sinusoidal  
Maximum output power: 7 ±2Watt  
Size: 260x265x110 mm Weight: 4 kg  
Operating voltage: 115/230 V - 50/60 Hz switchable  
Norms: CEI 62-39 Class: I-BF

- 30552 HANDPIECE FOR DEPILATION
- 30577 FOOTSWITCH





## DISPOSABLE GROUND PADS - WITH/WITHOUT CABLE



**30563**  
Cable

**30495**  
Adult/pediatric REM disposable plate

**30489, 30492**  
Adult disposable plate

**30488, 30493**  
Adult REM disposable plate

**30487, 30491**  
Pediatric REM disposable plate

**30478**  
Plug Valleylab type of 30478 to electrosurgery unit

GIMA code	DISPOSABLE GROUND PADS WITH SOLID GEL - without cable	Minimum order
30491	REM GROUND PADS - pediatric	box of 25
30487	REM GROUND PADS - pediatric	box of 100
30492	GROUND PADS - adult	box of 25
30489	GROUND PADS - adult	box of 100
30493	REM GROUND PADS - adult	box of 25
30488	REM GROUND PADS - adult	box of 100
30495	REM NON WOVEN GROUND PAD - ad/ped	box of 100

*Pads need cable 30563 for Gima diatermo or other cable see below*

DISPOSABLE GROUND PADS WITH CABLE - 3m		
30476	PADS WITH CABLE Ø 6.3 mm plug	box of 25
30478	PADS WITH CABLE Valleylab type	box of 25

*All plates and cables are individually packed*

## CONNECTION CABLES FOR DISPOSABLE GROUND PADS

### CABLES TO CONNECT GROUND PADS TO ELECTROSURGERY UNITS

The bipolar universal connection cables are supplied with a bipolar clamp for connection to disposable ground pads with a tab (dimensions 22-25 mm).


Various connectors make the cables compatible with numerous electrosurgical devices.

The cable can be fixed to the surgical sheet during the operation thanks to a metal sliding clamp.

Latex free. Individually packed in sealed polyethylene pouch compliance to 93/42/EEC

Medical Device Class I.

**30563**



### COMPATIBLE ELECTROSURGERY UNITS

#### • 30563 CONNECTION CABLE FOR PLATES - 5 m - Universal jack mono plug 6.3 mm

Aesculap: TM, TM401  
Alexandra: D205, E300, 500D, 102/201, 2020/E, 202, MICRO180  
ALSA: All  
MF100, MF360/A360, 380100, 180  
Berchtold: Elektrotom 200, 390, 400, 540  
Birtcher: 772, 773, 737, 737XL, 774

Bovie: Bovie CSV, URO, BS, 400/400, 400SR, X10, X10L  
Burdick: U-7, SU-8  
Cameron-Miller: 26-1290  
Cobe: TS-403  
Concept: 9600, 9700, 9800, 9900  
Dolley: COBII 203T, 502, 503T, 505T  
Ems Davol: System 2000, 5000

Faset: Serie COBI  
Gima: all models  
GPS: all models  
I Cuatro: Megeri1  
Lamidey: Series Subtilec: All  
Series Surgilec: All  
Led: all models  
Martin: all models

Neomed: Series 3000, 3000A, 3002, 3006; 3010, 3020  
Philips: TS-403  
Ritter/Mdt: Solide State 400, 400B, 400SR  
Sidevan: Seb2  
Soxil: BP 2000, X10  
Thackray: T300S  
Torry: Lem 300 CST

#### • 30546 CONNECTION CABLE FOR PLATES - plug with spacer - 5 m - Universal jack mono plug 6.3 mm


Erbe: ACC, ICC, VIO, T

#### • 30547 CONNECTION CABLE FOR PLATES VALLEYLAB TYPE - 5 m - Universal Valleylab connection

Aspenlabs: Excalibur  
Valleylab: REM type devices  
Bowa

Conmed  
Erbe ICC International  
Erbe ACC International

## AUTOCLAVABLE METAL AND RUBBER PLATES



#### • 30566 METAL PLATE - needs cable 30563

#### • 30563 CABLE FOR PLATES - 5 m

#### • 30559 CABLE FOR PLATES - 2.5 m

#### • 30564 SURGEON NEUTRAL PLATE 16x12 cm - with cable

#### • 30561 ROD NEUTRAL ELECTRODE with cable for 30625\*

\*Available on request for other electrocautery

#### • 30555 FLEXI STEEL RUBBER PLATE 18x21 cm - needs cable 30560

#### • 30556 FLEXI STEEL REM RUBBER PLATE - needs cable 30560

#### • 30560 CABLE FOR RUBBER STEEL PLATES 30555 and 30556

#### • 30574 REM RUBBER PLATE 20x15 cm - needs cable 30575
























#### • 30575 CABLE FOR RUBBER PLATES 30573 and 30574

## BIPOLAR CABLES FOR MAJOR BRANDS



Quality highly flexible silicone bipolar cables 3 m long (10").  
Autoclavable at 134°C for minimum 20 times.  
Recommended EtO sterilization for max extended life.

Suitable for most generators, with connector for European or US forceps. Multilingual box and manual: GB, FR, IT, ES, PT, DE, SE PL, RO, GR, HR, Arabic


 <b>30642</b> <b>• 30642 BIPOLAR CABLE ADAPTOR</b>	 Connector to forceps		 Connector to electro-surgical unit		 Connector to forceps		 Connector to electro-surgical unit Pin distance 29 mm		  30642		 		 		 	
	<b>GIMA Code</b>	<b>30632</b>	<b>30618</b>	<b>30640</b>	<b>30637</b>	<b>30643</b>	<b>30618+ 30642</b>	<b>30617</b>	<b>30644</b>	<b>30639</b>	<b>30638</b>					
<b>Connector to forceps</b>	 EU	 US	 EU	 US	 EU	 US	 EU	 US	 EU	 EU						
<b>Compatibility brand/model</b>	GIMA: MB 240 MB 380 VALLEYLAB, CONMED, CODMAN, OLYMPUS		GIMA: MB 120 F, MB 200 F, MB 200 D, MB 200T, MB 300 D, MB 400 D, MB 300T, MB 400T LED: SURTRON 120, 200, 200T, 300, 300T, 400, 400T VALLEYLAB, EMC, DOLLEY		GIMA: MB 122, MB 160, MB 200, MB 202		GIMA: MB 80 D, MB 120 D, MB 160 D LED: SURTRON 80, 120, 160		MARTIN BERCHTOLD AESCULAP WOLF		ERBE SELECT DOWNS SIEMENS					

## DISPOSABLE BIPOLAR FORCEPS - VALLEYLAB CABLE

- 30300 DISPOSABLE JEWELER FORCEPS - 11.5 cm - tip 0.5 mm
- 30302 DISPOSABLE STRAIGHT FORCEPS - 20 cm - tip 1.0 mm
- 30304 DISPOSABLE STRAIGHT FORCEPS - 15 cm - angled tip 1.0 mm
- 30306 DISPOSABLE BAYONET FORCEPS - 20 cm - tip 1.0 mm


Disposable bipolar forceps are supplied with 3 m cable.

Valleylab plug (same connector as 30640).  
Sterilization by Ethylene Oxide (EtO).




## BIPOLAR SCISSORS

- 30310 BIPOLAR SCISSORS - 18 cm (7") - curved  
Needs bipolar cable 30315
- 30315 ETHICON SILICONE BIPOLAR CABLE - 3 m (10')  
For bipolar scissors. Connector 2.5 mm  
Compatibility: Valleylab, Conmed, Codman, Olympus, other.



## BIPOLAR ARTERY SEALER

- 30320 BIPOLAR ARTERY SEALER - 26 cm (10.5")  
Needs bipolar cable 30325
- 30325 SILICONE BIPOLAR ARTERY SEALER CABLE - 3 m (10')  
Connector 4 mm, Banana plug.  
Compatibility: Valleylab, Conmed, Codman, Olympus, other.



## FOOTSWITCHES AND BOARDS

GIMA code	FOOTSWITCHES FOR 50, 80, 106, MB 120, 122, 132, 160, 200, 202, 200 TOUCH
30577	MB waterproof footswitch - 2m cable
30578	MB waterproof footswitch - 3m cable
ANTIEXPLOSION FOOTSWITCH FOR MB 120, 122, 132, 160, 200, 202	
30602	Double antiexplosion, water proof MB footswitch
ANTIEXPLOSION FOOTSWITCHES FOR MB 240, 300D, 300T, 380, 400, 400D, 400T	
30603	Double antiexplosion, water proof footswitch - MB240-380
30604	Double antiexplosion, water proof footswitch - MB250-400-300D-400D
30608	Double antiexplosion, water proof footswitch - MB300-400 TOUCH
MAIN BOARD	
30557	Main board - specify model and serial number of diatermo with order
30558	Output board for MB 240, 250, 380, 400 - specify as above



It allows selection from pedal of CUT and COAG functions  
Antiexplosion and waterproof.



# UNIVERSAL HIGH QUALITY INSULATED BIPOLAR FORCEPS

## EUROPEAN CONNECTOR BIPOLAR FORCEPS

Binner electrodes for  
ENT application

30647

30648

30646

Ophthalmic/Micro forceps

MC PHERSON 30669

JEWELER 30665

JEWELER 30666

30667 General forceps

30654

Bayonet forceps

30652

Angled tip

30651



1639



ISO 13485

GIMA code	Model	Connector	Length		Tip style	Application	Tip size
			cm	inches			
30645	BINNER	EU	22 cm	8½"	ANGLED	ENT	-
30646	BINNER	EU	18 cm	7"	STRAIGHT	ENT	-
30647	BINNER	EU	18 cm	7"	ANGLED	ENT	-
30648	BINNER	EU	19 cm	7¾"	ANGLED 45°	ENT	-
30650	STRAIGHT	EU	18 cm	7"	STRAIGHT	GENERAL	1 mm round points
30656	STRAIGHT with irrigation	EU	18 cm	7"	STRAIGHT	GENERAL	1 mm round points
30651	STRAIGHT	EU	20 cm	7¾"	STRAIGHT	GENERAL	1 mm round points
30658	STRAIGHT	EU	20 cm	7¾"	STRAIGHT	GENERAL	2 mm round points
30652	STRAIGHT	EU	18 cm	7"	ANGLED	GENERAL	1 mm round points
30653	STRAIGHT	EU	20 cm	7¾"	ANGLED	GENERAL	1 mm round points
30657	BAYONET	EU	16.5 cm	6½"	STRAIGHT	GENERAL	1 mm round points
30654	BAYONET	EU	18 cm	7"	STRAIGHT	GENERAL	1 mm round points
30655	BAYONET	EU	20 cm	7¾"	STRAIGHT	GENERAL	1 mm round points
30659	BAYONET	EU	22 cm	8¾"	STRAIGHT	GENERAL	1 mm round points
30663	BAYONET	EU	24 cm	9½"	STRAIGHT	GENERAL	1 mm round points
30660	STRAIGHT	EU	18 cm	7"	ANGLED	GENERAL	0.3 mm points
30661	STRAIGHT	EU	18 cm	7"	STRAIGHT	GENERAL	0.3 mm points
30662	STRAIGHT	EU	20 cm	7¾"	STRAIGHT	GENERAL	0.3 mm points
30664	ADSON	EU	12.1 cm	6"	STRAIGHT	GENERAL	1 mm round points
30665	JEWELER 5	EU	11.5 cm	4½"	STRAIGHT	OPHTHALMIC/MICRO	0.25 mm points
30666	JEWELER 5	EU	11.5 cm	4½"	ANGLED	OPHTHALMIC/MICRO	0.25 mm points
30667	STRAIGHT	EU	15 cm	6"	STRAIGHT	OPHTHALMIC/MICRO	0.5 mm points
30668	STRAIGHT	EU	15 cm	6"	ANGLED	OPHTHALMIC/MICRO	0.5 mm points
30669	Mc PHERSON	EU	10.2 cm	4"	STRAIGHT	OPHTHALMIC/MICRO	0.5 mm points

Straight tip

Straight forceps

Irrigation

30656

**UNIVERSAL EUROPEAN CONNECTION**  
Our forceps are provided with a standard European connection enabling their use with GIMA Diathermy and electrosurgery units from the main European manufacturers.  
Multilingual instruction: GB, FR, IT, ES, PT, DE, GR.

## US CONNECTOR BIPOLAR FORCEPS

30621 SEMKIN

30622 CUSHING

30623 JANSEN BAYONET

GIMA code	Model	Connector	Length		Application	Straight tip Size
			cm	inches		
30620	ADSON	US	12.1 cm	4¾"	GENERAL/PLASTIC	1 mm round points
30621	SEMKIN	US	14 cm	5½"	GENERAL/PLASTIC	0.5 mm points
30622	CUSHING	US	15.9 cm	6¼"	GENERAL/PLASTIC	1 mm round points
30623	JANSEN BAYONET	US	17.8 cm	7"	GENERAL/PLASTIC	1 mm round points



ADSON

30620

UNIVERSAL US CONNECTOR

## EUROPEAN NON-STICK BIPOLAR FORCEPS

### NON-STICK BIPOLAR FORCEPS

Thanks to new Ag-Tech non-stick technology, the forceps stay clean, virtually eliminating the need for cleaning during

coagulation. A tip material with excellent thermal properties prevents the sticking of tissues. The non-stick effect is permanent and will not reduce with the use of forceps.

GIMA code	Model	Connector	Length		Tip style	Tip size
			cm	inches		
30460	STRAIGHT	EU	15	6"	STRAIGHT	1 mm
30461	STRAIGHT	EU	18	7"	STRAIGHT	1 mm
30462	STRAIGHT	EU	20	7¾"	STRAIGHT	1 mm
30464	STRAIGHT	EU	18	7"	ANGLED	1 mm
30465	STRAIGHT	EU	20	7¾"	ANGLED	1 mm
30468	BAYONET	EU	18	7"	STRAIGHT	1 mm
30469	BAYONET	EU	20	7¾"	STRAIGHT	1 mm
30472	JEWELER	EU	11.5	4.5"	STRAIGHT	0.7 mm
30473	JEWELER	EU	11.5	4.5"	ANGLED	0.7 mm
30474	ADSON	EU	12.1	4¾"	STRAIGHT	1 mm

30461

30468

30473

30474




## SMART CARTS FOR ELECTROSURGICAL UNITS

- **27895 SMART CART** - 2 shelves 40x36 cm + base
  - **27889 SMART CART** - 2 shelves 50x42 cm + base
  - **27890 SMART CART** - 2 shelves 60x42 cm + base
- Sturdy carts with painted powder steel base and aluminium frame. 2 shelves with protection edge on back, adjustable at different height.  
Suitable for all Gima electrosurgical units.  
Illustrated assembly instructions.

### TECHNICAL SPECIFICATIONS

	27895	27889	27890
Total load:	80 kg	80 kg	80 kg
Load x shelf:	15 kg	15 kg	15 kg
Size mm:	482x500xh 780	582x500xh 780	682x500xh 780
Weight:	13 kg	15 kg	17 kg



## CARTS FOR ELECTROSURGICAL UNITS

Ergonomic trolley designed to hold and carry electrosurgical units (including Argon units). The height of 915 mm with inclined top shelf allows easy reading of the unit's display. The trolley is provided with a second shelf with antiskid raised edges, two drawers placed at the base and a rear space with securing straps to hold two Argon cylinders. Upright stands can hold optional accessories. Made of epoxy-painted, tempered steel and aluminium. Available version with 4 socket group, fuses box, independent grounding plug, power cable 3m.

### TECHNICAL SPECIFICATIONS

Load capacity:	- Total load 200 kg	- Inclined shelf 50 kg
Inclined shelf:	42x45 cm (27864/6)	50x36 cm (27865/7)
Drawers and shelf:	42x36 cm (27864/6)	50x36 cm (27865/7)

### GIMA code CARTS FOR ELECTROSURGICAL UNITS

<b>27864</b>	DIATERMO CART - medium
<b>27865</b>	DIATERMO CART - large
<b>27866</b>	DIATERMO CART with power - medium
<b>27867</b>	DIATERMO CART with power - large



## ELECTROSURGERY SMOKE EVACUATOR

### • 30450 SMOKE EVACUATOR

An aspiration and filtering system for the smokes produced during the surgical procedures.

The smokes, generated during the surgical procedures, have a bad, strong and persistent smell. These smokes consist of water vapour, organic gas, visible or invisible solid particles and viral parts. So a good aspiration and filtration eliminates bad smells, reduce the bacteriological and/or viral risks, and improves vision of the zone of the operation area during the laparoscopic procedures.

Activation of the aspiration can be:

- **Automatic**, through the remote electronic system of automatic survey of the activation of the high frequency electrosurgical unit
- **Manual**

- **Through a foot switch (optional)**

The aspiration flow can be adjusted to suit the specific needs. For laparoscopic procedures there is a specific function L, quickly selectable. Smoke evacuator has an electronic control of the aspiration with the indication of the wearing status of

the filters. There are two different kinds of quickly replaceable ULPA type filters, with active carbons: the BLUE filter is the first filter and it is included with the unit for an initial time of use (5 hours), the RED filter is an optional spare part, developed for a long time use (20 hours).

They have connector of 7/8".

- **30451 ULPA FILTER (20 hours) RED** for 30450 since S.N. 0216383
- **30452 ULPA FILTER (20 hours) RED** for 30450 up to S.N. 0216382
- **30453 ASPIRATION KIT** - box of 6
- **30454 HANDLE ASPIRATION KIT** - sterile - box of 12
- **30577 MB WATERPROOF FOOTSWITCH** - 2 m

MADE IN ITALY

### TECHNICAL SPECIFICATIONS

Mains voltage:	230 V (115 V on request)
Mains frequency:	50/60 Hz
Electrical input power:	800 VA
Max vacuum flow rate:	1000 LPM (35 CFM)
Max static suction:	250 mbar (83 in H <sub>2</sub> O)
Filter type:	ULPA with active carbons
Filter efficiency:	99,999%
Particles diameter:	0.12 micron
Size:	370x144x319 mm
Weight:	4 kg

### STANDARD ACCESSORIES

ULPA filter (5 hours) blue  
Aspiration kit (A) filter + (B) pipe Ø 22 mm, length 2.4 m)  
handle aspiration kit (C) adapter 10 mm / 22 mm (D), pipe Ø 10 mm, length 1.8 m,  
(E) clip to fix the pipe to the handle, (F) adapter to the handle)  
Power cable






## CHANGE-A-TIP™ CAUTERIES WITH HIGH TEMPERATURES

### BOVIE CAUTERIES

Improved battery-operated cautery with a safety-enhanced design and a recessed button to reduce the potential for inadvertent activation.

- It also allows the practitioner to "snapped off" the end of the cautery for safe and effective battery removal.
- interchangeable sterile tips (non sterile tips for 30584 and 30590)
  - replaceable batteries
  - reusable handles
  - no sterilization necessary.



GIMA code	CAUTERY HANDLE AND INTERCHANGEABLE STERILE TIPS	Recommended for:	Minimum order
<b>30590</b>	Cautery handle "AA" (tip included)	All tips	1
<b>30568</b>	High temp loop tip	DER/ENT	box of 10
<b>30569</b>	High temp 2" flex loop tip	GYN/ENT	box of 10
<b>30570</b>	High temp 5" loop tip - long size	GYNAECOLOGY	box of 10
<b>30571</b>	High temp fine tip	DER/CARDIO	box of 10
<b>30576</b>	High temp elongated tip	VASECTOMY	box of 10
<b>30584</b>	High temp cautery kit (1 handle + 4 non sterile tips)		


## REUSABLE HIGH TEMPERATURE CAUTERY WITH REPLACEABLE TIP

### CAUTERIES - 1,200°C (2,200°F)

- interchangeable tips with nickel-chrome wire
- replaceable batteries
- reusable handles

Wide application in gynaecology, orthopedy, ear/nose/throat, dermatology and urology.

GIMA code	INTERCHANGEABLE TIP CAUTERIES MINIMUM ORDER: 10 TIPS
<b>30598</b>	Cautery handle "AA" (tip not included)
<b>30599</b>	High temp long fine tip - sterile - box of 10
<b>30600</b>	High temp large tip - sterile - box of 10
<b>30601</b>	High temp fine tip - sterile - box of 10



## DISPOSABLE HIGH/MEDIUM/LOW TEMPERATURE CAUTERIES

### • 30700 ELECTROCAUTERY - 1,200°C - fine tip - box of 10

Electrocautery is a sterile bipolar battery operated disposable device for the cauterization of small vessels. With a **fine tip** required in most of the surgeries.

### • 30701 ELECTROCAUTERY - 1,200°C - large tip - box of 10

Same as 30700, but with a large tip.

### • 30702 LONG SHAFT ELECTRO CAUTERY - 1,200°C - fine tip - box of 10

Same as 30700 but with the tip fixed on a 12 cm long shaft. Precise cauterization even in difficult access sites.


### • 30703 EMERGENCY ELECTROCAUTERY - 800°C - thick tip - box of 10

Same as 30700 but with "thick tip" for the perforation of nails in case of haematoma.

### • 30704 ELECTROCAUTERY - 600°C - fine tip - box of 10

Same as 30700 but with lower temperature 600°C. Especially designed for ophthalmology.

Applications	30700	30701	30702	30703	30704
Cardiovascular, thoracic surgery	x				
Proctology	x	x	x		
General surgery			x		
Gynaecology	x				
Surgical gynaecology			x		
Neurosurgery	x	x	x		
Orthopedic	x	x			
Urology	x				
Obstetrics	x				
Emergency ward				x	
Otolaryngology	x	x	x		
Plastic and reconstructive	x	x			
Ophthalmology	x				x
Dermatology	x				
Dental surgery	x				



Features	HTC (High Temperature Cautery)			MTC (Med. Temp. Cautery)	LTC (Low. Temp. Cautery)
	<b>30700</b>	<b>30701</b>	<b>30702</b>	<b>30703</b>	<b>30704</b>
Tip shape	Fine	Large	Fine	Thick	Fine
Tip length	28mm	28mm	125mm	28mm	28mm
Temperature °C/°F	1200/2200	1200/2200	1200/2200	800/1400	600/1100
Weight	65g	65g	78g	65g	45g

## HISTOFREEZER® CRYOSURGICAL SYSTEM

- **30591 HISTOFREEZER® - kit with applicator 2 mm**  
Two 80 ml aerosol bottles and 60 applicators 2 mm.
- **30592 HISTOFREEZER® - kit with applicator 5 mm**  
Two 80 ml aerosol bottles and 52 applicators 5 mm.
- **30589 HISTOFREEZER® - large kit mixed applicators**  
Two 80 ml aerosol bottles, 24 applicators 2 mm, 36 applicators 5 mm.
- **30585 HISTOFREEZER® - mini kit mixed applicators**  
One 80 ml aerosol bottle, 16 applicators 2 mm, 16 applicators 5 mm.

The Histofreezer® portable cryosurgical system is a low cost, highly effective cryosurgical agent that provides safe and effective treatment for warts and other common benign skin lesions. This therapeutic treatment makes use of local freezing for the controlled destruction or removal of living tissue.

Suitable for adults and children.

Multilingual box and manual in: GB, FR, IT, DE, ES, NL, PL.

From web you can download: GR, PT, TH, Arabic.

For professional use only.

9 types of benign lesions	% of resolution*
Verruca Vulgaris (Common Warts)	94%
Verruca Plantaris (Plantar Warts)	86%
Molluscum Contagiosum	100%
Lentigo (Age Spots)	100% - facial 99% - non facial
Condyloma (Genital Warts)	89%
Seborrheic Keratosis	95%
Acrochordon (Skin Tags)	100%
Verruca Plana (Flat Warts)	93%
Actinic keratosis (Facial and Non-Facial)	91% - facial 87% - non facial

\*Summary of resolution rates by type of lesion from a number of clinical trials obtained with histofreezer + post-treatment of 27% salicylic acid / 17% lactic acid

Saturated 2 mm applicators will stay cold for 90 seconds.



30591

Saturated 5 mm applicators will stay cold for 120 seconds.



30592



30585



30589

CE 0543

2 mm  
5 mm

**2 mm disposable applicator for small lesions**  
**5 mm disposable applicator for large lesions**

**CHARGE**  
custom applicator  
press valve until droplets start to form.

**INVERT**  
canister for 15 seconds for optimal freezing temperature.

**APPLY**  
a frozen applicator to lesion for 15-40 seconds.

## CRYOMEGA® AND CRYOCLEAR® MULTI-USE CRYOSURGICAL DEVICES

- **30586 CRYOMEGA® with 16 g cartridge - non-refillable**  
CryoOmega® dispenses liquid nitrous oxide (-89°C) the coldest portable cryogen and it is cleared for 16 common lesions including verrucae, skin tags, and seborrheic keratoses. Ideal choice in portable cryosurgery for physician offices looking for convenience and great first-time outcomes.

It provides clinically effective freezing with pinpoint precision.

No contact device for use on different patients at 1 cm distance.

Up to 300 seconds treatment time per device (approx 30 treatments of 10 seconds).

For medical healthcare professionals.

MADE IN USA



30586

N<sub>2</sub>O  
-89°C



CE 0543  
FDA

Multilingual pack and instructions  
(GB, FR, IT, ES, DE, NL, PL, FI).

Type of Lesion	Freeze time range (sec)*
Verruca Vulgaris	10-20
Verruca Plantaris	10-20
Molluscum Contagiosum	3-10
Skin Tags	5-10
Lentigo	2-5
Actinic Keratosis	5
Verruca Plana	5-15
Seborrheic Keratosis	5-10
Genital Lesions	5-12

\*Suggested freezing time as reported in literature

237

- **30587 CRYOCLEAR® with 16 g cartridge - non-refillable**

CryoClear® uses Carbon Dioxide which freezes at -79°C to a depth of no more than 2 mm into the skin, delivering a safe and clinically effective treatment to superficial skin indications. Over 95% high efficacy combined with less destruction of healthy tissue makes it perfect for treating age spots, sun spots, and skin tags. It offers a better and faster cryotherapy solution, even as combination treatment to chemical peels, facials, micro-needling or dermaplaining. No contact device for use on different patients at 0.5 cm distance. Up to 300 seconds treatment time per device (approx 60 treatments of 5 seconds). Suggested for use at aesthetics and cosmetic sites.

MADE IN USA



30587

CO<sub>2</sub>  
-79°C



CE 0543  
FDA

Multilingual pack and instructions  
(GB, FR, IT, ES, DE, NL, PL, FI).

Indication	Freeze time range (sec)*
Acne (cysts and scars)	5-10
Actinic Keratosis (sun spots)	5-10
Angiomas	5-10
Angiomas - spider angiomas	5-10
Keratosis Pilaris (Milia)	5
Lentigo (Age Spots)	5-10
Sebacaceous Hyperplasia	5
Skin Tags	5-10
Teleangiectases	None suggested

\*Suggested freezing time as reported in literature



## FLEXIBLE NOSEPHARYNGOSCOPE

### • 71604 FLEXIBLE NOSEPHARYNGOSCOPE with cable

The high precision multi-lens optics creates an optimal image. The thin insertion tubes are exceptionally maneuverable and have a special wide angle lens whereby a precise tip control and a remarkable depth of focus are reached. High quality materials guarantee excellent and homogeneous illumination.

The handpiece is ergonomically formed and the insertion tube is especially comfortable for the patient.

This naso-pharyngoscope, with its proven design, is guaranteed to bring years of trouble-free service.

- wide angle, multi-lens objectives for excellent image quality
- excellent ergonomics allows one hand operation
- suitable for mechanical cleaning and disinfection.




#### TECHNICAL SPECIFICATIONS 71604

Resolution: 12,000 pixels	Working length: 300 mm
Working Ø: 3.8 mm	Total length: 535 mm
Length of tip deflection: 20 mm	Tip deflection: up 140°, down 140°
Direction of view: 0°	Depth of focus: 6-1,000 mm
Weight: 260 g	Field of view: 70°



- 71610 ENDOSCOPY MOUTHPIECE - bag of 20 pcs Disposable bite blocks

Supplied in lightweight aluminium rigid case with fibre optic cable, leakage tester and user manual (GB, IT)



## OTOSCOPES

ACMI / WOLF / STORZ /  
OLYMPUS fitting



- 72004 OTOSCOPE Ø 4x45 mm - 0° - non autoclavable
- 72007 OTOSCOPE Ø 2.7x107.5 mm - 0° - non autoclavable
- 72008 OTOSCOPE Ø 2.7x107.5 mm - 30° - non autoclavable

## LARYNGOSCOPE

ACMI / WOLF / STORZ /  
OLYMPUS fitting



- 72021 LARYNGOSCOPE Ø 8x170 mm - 70° - non autoclavable


## SINUSCOPES

ACMI / WOLF / STORZ /  
OLYMPUS fitting



- 72010 SINUSCOPE Ø 4x175 mm - 0° - non autoclavable
- 72011 SINUSCOPE Ø 4x175 mm - 30° - non autoclavable
- 72012 SINUSCOPE Ø 4x175 mm - 70° - non autoclavable
- 72013 SINUSCOPE Ø 4x175 mm - 45° - non autoclavable

## LIGHT SOURCE HANDLE



Connection to any endoscope  
with Storz fitting

- 30795 FLYER HALOGEN HANDLE 2.5 V - light source for endoscopes
- 31478 BULB for 30795
- 30794 FLYER LED HANDLE 2.5 V - light source

Powerful handheld light source for endoscopes. 60,000 lux. Both flyer handles need 2xAAA batteries. Instructions: GB, FR, IT, ES, DE.

## Wi-Fi/USB CAMERA FOR ENDOSCOPES AND MICROSCOPES

- 32185 MICFIEYE - Wi-Fi/USB CAMERA (C-mount)
- 32186 C-MOUNT F18 ADAPTER FOR ENDOSCOPES
- 32187 MICROSCOPE ADAPTER Ø 23 mm

MICFIEYE is a Wi-Fi camera with C-mount and allows to digitalize the image on tablets, smartphones and PC using dedicated Apps and Softwares. MICFIEYE needs an adapter



32185+32187

32185+32186

Each camera is supplied with USB cable (1.2 m), USB AC adapter, user manual (GB, IT, FR, ES, DE), software can be downloaded free of charge from web


to be compatible with all optical devices such as microscopes, endoscopes, boroscopes, fiberscopes, C-mount lenses etc.

#### TECHNICAL SPECIFICATIONS

Camera Type:	Colour CMOS camera
Sensor:	1/4 Imax CMOS
Resolution:	1.3 MP
Image pixel:	320x240, 640x480, 1280x1024
Lens standard:	C-CS mount CCTV lens
Automatic optical features:	Gamma correction, exposure, white balance, black reference, flicker avoidance, defect identification, colour saturation
Button snapshot:	yes for Wi-Fi and USB mode
Dimension:	Ø 36x75 mm
Wi-Fi transmission distance:	≤5 m
Video resolution:	1.3 MP, 320x240, 640x480, 1280x1024
Frequency range:	2,400-24,835 GHz
Li-Ion battery:	Continuous working time - approx 2.5 hours
Power source:	5 V / 1A or USB (use only USB wall adaptors certified according to the CE and/or FCC regulations)
OS support:	iOS / Android / Windows / Mac
Software features:	USB and Wi-Fi MIC-fi: snapshot*, video recording, calibration and measurement. Take time lapsed picture, (only USB Micfieye)

\*Only available with Wi-Fi mode

## GIMALED LIGHT SOURCE



Optional connectors allow use with STORZ, WOLF, OLYMPUS, PENTAX, FUJINON cables

• **30803 GIMALED 200 K LIGHT SOURCE - 16 LED**  
Compact, lightweight, powerful light source for endoscopic use. A low noise fan provides the necessary cooling inside the metallic structure of the light source. Touch switch enables a variable light intensity. User manual in GB, ES, FR, IT, PT.

GIMA code	CONNECTORS FOR GIMALED LIGHT SOURCE TO DIFFERENT CABLES
30810	STORZ cable connector
30811	WOLF cable connector
30812	OLYMPUS cable connector
30815	PENTAX cable connector
30816	FUJINON cable connector

MADE IN ITALY

### TECHNICAL SPECIFICATIONS

Input for: GIMA, SCHOLLY and LUT cables	Power supply: 100-240V, 50/60 Hz
Illumination at 2.5 cm: 147,000 Lux $\pm$ 10 %	LED life: 60,000 hours
Colour temperature: 5000 K $\pm$ 5 %	Dimension: 27x17x h 11 cm
CRI (Colour Rendering Index): 89 Ra	Norms: IEC 60601-1,
Max power absorption: 34 VA	IEC 60601-2-18 Class II

## LED LIGHT SOURCE


• **27544 LED LIGHT SOURCE** 27544 Size: 30x25x12 cm  
Cold white light (5,500 °K, 200 lumen) for endoscopy use. It can be connected to endoscopes without need of F.O. cable. Handle connect directly to rigid endoscopes (Storz connection). 3 Watt power LED.

MADE IN ITALY

LCD display: 12.8x6.4 cm

Adjustable light

## F. O. HEAD LIGHTS



• **30853 WIDA FIBRE OPTIC HEAD LIGHT with F.O. cable**  
• **30854 WIDA PLUS FIBRE OPTIC HEAD LIGHT with F.O. cable**  
WIDA illumination systems are available in two versions: with professional and ergonomic headband but different focus. Both include F.O. cable with adaptor (30830) for connection to GIMALED light source (30803). Find below connectors to other light sources. Light beam can be focused through a focusing ring. Easy headband cleaning by removable and washable padding. Multilingual manual: GB, FR, IT, ES

• **30852 FOCUS DEVICE for 30850 (since lot 14 - May 2012), 30853**  
It reduces light in a very luminous spot  $\varnothing$  10 mm.



### Diameter focus:

DISTANCE	30853	30854
20 cm	7-14 cm	5-8 cm
30 cm	10-19 cm	7-12 cm
50 cm	11.5-25 cm	12-20 cm

An exceptionally bright headlight with an illumination head for coaxial, shadow-free illumination of the viewing area.



## SURGICAL FIBRE OPTIC LIGHT CABLES AND ADAPTORS



### 1 LIGHT SOURCE ADAPTORS to connect GIMA F.O. cables to light sources

• 30830 GIMA light source adaptor

• 30831 STORZ - AESCULAP - MARTIN light source adaptor

• 30832 WOLF - HENKE SASS - DYONICS - MEDICON - COMEG light source adaptor

• 30833 OLYMPUS light source ad.  
• 30834 ACMI light source adaptor  
• 30835 HEINE light source adaptor  
• 30836 FUJINON light source adaptor  
• 30837 PENTAX light source adaptor

### 2 ENDOSCOPE ADAPTORS - on the cables to connect endoscopes to GIMA F.O. cables

• 30840 ENDO STORZ adaptor

• 30841 ENDO WOLF adaptor

• 30842 ENDO ACMI, OLYMPUS-STRYKER adaptor

- 30817 FIBRE OPTIC CABLE 3.5 x 1,800 mm
- 30818 FIBRE OPTIC CABLE 4.8 x 1,800 mm
- 30822 FIBRE OPTIC CABLE 3.5 x 2,300 mm
- 30823 FIBRE OPTIC CABLE 4.8 x 2,300 mm
- 30826 FIBRE OPTIC CABLE 4.8 x 3,000 mm


High transmission surgical light cables, armoured but highly flexible with unique features:

- no burn outs
- strain relieved and protected by **silicone hose**
- **steam autoclavable** with warranty (12 months)
- light source end temperature resistant up to 134°C
- no electrical interferences with endoscopic surgery units
- kink resistant
- surgical stainless steel end fittings resist wear and corrosion
- stainless steel adaptors enables our cables to be used with other manufacturers halogen light sources/instruments

### 3 29975 FIBRE OPTIC CLAMP

ENDOSCOPE ADAPTORS - on the endoscope to connect endoscopes to GIMA F.O. cables


- 30844 STORZ/LUT ENDOSCOPE ADAPTORS
- 30845 WOLF ENDOSCOPE ADAPTORS





## GIMA ENT HEAD MIRRORS - BATTERY OR AC/DC TRANSFORMER USE

Simple adjustment of the band using rotating knob to fit any head size



31110

Comfortable, padded headband easy to remove for cleaning



31111

Head mirror Lux-100 with plug in transformer

### HEAD MIRRORS WITH TRANSFORMER

Supplied with plug-in transformer for direct power

Storz type head mirror

Silver coated mirror produces extremely bright light

Simple adjustment of the band using rotating knob



31108

Comfortable, padded head band easy to remove for cleaning

On/off switch on battery

Supplied with headband mounted CR-123A battery box for 2x3 V batteries (not included)



31109

### HEAD MIRRORS WITH BATTERY

Extension cable

Clar type head mirror

Silver coated mirror produces extremely bright light

LUX-100 AVAILABLE WITH LED LIGHT

Quality head mirrors Ø 55 or 100 mm to perfectly illuminate the examination area in every situation. Long life 6 V lamp provides bright and natural light, quality silver coated mirror allows optimum light reflection. Mirror and light beam can be easily and precisely adjusted. Supplied with multilingual manual: GB, FR, IT, ES, PT, DE, GR, Arabic.

STANDARD ACCESSORIES	LUX AC/DC TRANSFORMER 31110-31111	LUX BATTERY* 31107-31109	31112
Mirror with head band	•	•	•
Long life bulb	•	•	•
Head band mounted battery case** for 2 x 3V CR-123A	•	•	•
Plug in transformer* 100/240 V - 50/60 Hz with cable	•	•	•
Pocket battery case	•	•	•
Sturdy plastic case	•	•	•
Cordura bag	•	•	•
Extension cable 80 cm and on/off switch 30 cm cable	•	•	•

\*Supplied with interchangeable UK, US, EU plugs

\*\*Battery not included

GIMA code	LUX ENT MIRRORS
31108	LUX-55 battery*** head mirror - Ø 55 mm - 6 V
31109	LUX-100 battery*** head mirror - Ø 100 mm - 6 V
31107	LUX-100 battery*** LED head mirror - Ø 100 mm - 6 V
31110	LUX-55 AC/DC transformer head mirror - Ø 55 mm - 6 V
31111	LUX-100 AC/DC transformer head mirror - Ø 100 mm - 6 V
31114	Mirror for LUX-55 - spare
31115	Mirror for LUX-100 - spare
31116	Bulb for LUX mirrors 6V Vacuum type - spare
31119	Carrying bag for LUX mirrors - black
31117	Battery case for LUX mirror 31112/3 - spare
31124	Connecting cable 30 cm for 31107-9 - spare
31118	Plug in transformer* 100-220 V - 50/60 Hz with cable - spare for 31110-1 - optional for 31108-31109

\*\*\*Battery mounted on head mirror band

## 2 LED HEADBAND MAGNIFIER

### • 31168 2LED TWO-WAY REGULATION HEAD-WEARING MAGNIFIER with 5 lenses

Two-way regulation to adjust magnifier. Provided with 5 lenses 1.0x, 1.5x, 2.0x, 2.5x, 3.5x, which combined in group of two, ensure 11 different bigger magnifications and wider applications. For example, with lenses 1.0X and 2.5X magnification is 3.5X. Headband is made of PVC leather. It works with batteries, not included. Multilingual manual: GB, FR, IT, ES, PT, DE, SE, GR.



31168

## MAGNIFYING GLASSES

### • 30848 SMART MAGNIFYING GLASSES 2.5X

Spectacle frame with magnifying glasses allows the physician to have a magnified view of the visual field. Lightweight, it folds up and can be worn over spectacles. 2.5X zoom lens can be tilted to achieve optimum focus.



30848

## 4 W LED HEADLIGHT

### • 30849 H2O PRO LED HEADLIGHT

Compact and lightweight headlight with super bright Samsung 4W cool white LED.

Features:

Luminous intensity: high 350 lumen / low 30 lumen.

Range: 100 m high / 33 m low.

3 meters drop test, MCU control push switch (High/Low/Off).

PC material body with over-mould rubber head for maximum durability, 115° pivoting head.

Eye Risk Group 2, IP67 Dust proof and water proof, pass IK08 Impact.

10,000 switch cycle life, passed extreme temperature shock test.

Run time: high 3 hours, low 23 hours. 3xAAA battery included

• 32200 "AAA" ALKALINE BATTERIES - blister of 4 pcs - spare



30849

Size: 68x47x36.5 mm  
Weight: 75 g

## GIMA LED HEADLIGHT



Adjustable light spot at 420 mm with iris diaphragm: 20-80 mm

### TECHNICAL SPECIFICATIONS

Adjustable illumination light spot at 420 mm: 20-80 mm  
 Illumination at 200 mm working distance:  $\geq 75,000$  lux  
 Fluctuation distance: 12.5 mm  
 Angle range: vertical  $\pm 25^\circ$  adjustable  
 Weight of headlight (excluding head band): 69 g  
 Illumination source: extremely bright light, 5 W LED, life 20,000 hours  
 Battery: 7.4 V/4,400mAh lithium battery  
 Battery run-time: 7 hours continuous if fully charged battery (charging time: 5 h)  
 Voltage: 100-240 VAC, 50-60 Hz  
 Maximum input power: 30 W  
 Power adapter output: DC  $12 \pm 0.5$  V, 1.5 A  
 Electrical safety standard: EN60601-1, EN60601-2, Class II type BF

- 30939 GIMA LED HEADLIGHT
- 30941 BATTERY PACK for 30939, 30940 and 30890\* - spare
- \*Old Gima Led light need adaptor 30942 - light blue
- 30943 CORD BATTERY - HEADLIGHT - spare
- 30942 ADAPTOR FOR BATTERY PACK\*\*

\*\*Only for use of battery pack (30941) with old Gima head light (30890)

Led lamp without the heat of traditional halogen headlight. With a colour temperature of 5,000 °Kelvin, it provides bright, white, shadow-free light allowing the doctor to see tissue characteristics without distortion. Flexibility of operation using the rechargeable lithium battery, instead of direct power source. Comfortable lightweight headlight suitable for all kinds of surgery, ENT or dental applications. It can also be used while charging. Low-battery indicator light. Adapts to GIMA binocular loupes (codes 30892-8, 30910-5). Smart design, convenient for mobile diagnosis. Supplied in aluminium case with rechargeable 7.4 V / 4,400 mAh lithium battery and charger. Manual: GB, FR, IT, ES, DE, PT, GR, Arabic.



## SURGICAL LED HEADLIGHT

- 30936 GIMA 40 KL SURGICAL LED HEADLIGHT

Latest generation of portable headlight system offering high quality performance. Features:

- spot size adjustable by inner mini light grating
- precise light imaging by multi optical lens
- integrated cordless design


Supplied with battery and battery charger.

Multilingual manual: GB, FR, IT, ES, PT, DE, PL, GR.

- 30937 LITHIUM BATTERY 5W - spare

### TECHNICAL SPECIFICATIONS

Illumination source: 5W LED  
 Illumination intensity: 10-40,000 lux  
 Colour temperature: 6,000K  
 Spot size: Max 70 mm, Min 50 mm at 32 cm  
 Lamp working life: 50,000 hours  
 Battery: 3.7V Lithium Battery  
 Battery run time: 5-12 hours  
 Battery charging time: 3.6 hours  
 Input voltage: 100-240VAC  
 Weight: 200 g



## GIMA BINOCULAR LOUPES

### BINOCULAR LOUPES:

Lightweight, ergonomically superior Galilean-style flip-up loupes. Can be used independently or mounted on 30890, 30940.

Multi-coated and high grade glass lenses provide clean and sharp image. Eyepiece with wide field of view.

Deep focus to see object stereoscopically.

Loupes angles can be easily adjusted between  $0^\circ$  and  $40^\circ$  to minimize fatigue even after prolonged use.

6 mm up and down displacement.

Adjustable pupil distance to fit different face types.



Weight: 103 g



30897

All binocular loupes are supplied in a case

### STYLE BINOCULAR LOUPES:

Line of binocular loupes with same features of traditional line but mounted on a extra light, fashionable frame.



All binocular loupes have multilingual manual: GB, FR, IT, ES, PT, GR.

Weight: 111 g

30910

GIMA code	BINOCULAR LOUPES	Magnification	Working distance	Field of view Ø
30892	Binocular Loupe	2.5X	340 mm	80 mm
30894	Binocular Loupe	2.5X	420 mm	90 mm
30897	Binocular Loupe	3.5X	340 mm	50 mm
30898	Binocular Loupe	3.5X	420 mm	60 mm

GIMA code	STYLE BINOCULAR LOUPES	Magnification	Working distance	Field of view Ø
30910	Style binocular Loupe	2.5X	340 mm	80 mm
30911	Style binocular Loupe	2.5X	420 mm	90 mm
30914	Style binocular Loupe	3.5X	340 mm	50 mm
30915	Style binocular Loupe	3.5X	420 mm	60 mm



## HEINE LED HEAD LIGHT

90,000 LUX  
at 180 mm

5 YEARS  
WARRANTY

30884

POWERFUL LED  
ILLUMINATION

• 30884 HEINE ML4 LED<sup>HQ</sup>  
HEAD LIGHT - J.008.31.413

- LED in HQ; defining optimal light intensity (90,000 lux at 180 mm), brightness and homogeneity from edge to edge, and colour rendering (4,500 K, CRI >90, R9 >75). This ensures true colour tissue for the most accurate diagnosis.
- Coaxial illumination: ensures a completely shadow-free image and allows for excellent illumination of difficult to see areas
- Lithium Battery: for up to 8.5 hours of continuous working
- LED Thermal Management: guarantees consistent quality and performance throughout the LED's lifetime (50,000 hours)
- Adjustable illumination spot size: 30 to 80 mm spot size range (at 420 mm working distance) to fit any examination situation
- Comfortable and secure fit: multiple adjustment points and soft padding for comfort and stability even during long procedures
- Illumination Intensity Control: for precise brightness setting
- 30886 HEINE BINOCULAR LOUPE 2.5X-340 mm - J.000.31.370
- 30887 HEINE BINOCULAR LOUPE 2.5X-420 mm - J.000.31.371
- 30888 P2 POLARIZATION FILTER FOR ML4 AND 2.5X LOUPES - J.000.31.326

Rechargeable  
battery pack and  
direct mains trans-  
former included.



### TECHNICAL SPECIFICATIONS

Power supply:	mPack® Rechargeable Battery Pack with Li-ion battery and direct mains transformer
Illumination:	90,000 lux at a working distance of 180 mm
LED operating life:	50,000 hours
Spot adjustment:	30 mm to 80 mm illuminated field diameter (at 420 mm)
Colour temperature:	5,500°K

## HEINE BINOCULAR LOUPES

Only 42 g

30930,  
30931



Eyepieces individually adjustable

2.5 X loupes

### HEINE® S-FRAME® WITH BINOCULAR LOUPES

- Achromatic optics: crisp, bright image with colour-correction.
- Multi-coated, scratch-resistant silica glass lenses - produce crisp, clear images. High magnification with a large field of view and excellent depth of field.
- Water resistant
- Flexibility for precise adjustment: independently adjustable Pupillary Distance controls ensure precise alignment of the optics, for a stereoscopy view.
- i-View loupe mount; provides any angle of view and the possibility flips up and down the optics to exclude or re-include the magnification during any procedure.
- Different magnification and working distance.

GIMA code	BINOCULAR LOUPES	Magnification	Working distance	HEINE code
30930	Heine binocular loupes	2.5X	340 mm	C-000.32.355
30931	Heine binocular loupes	2.5X	420 mm	C-000.32.356
30932	Heine binocular loupes	4X	340 mm	C-000.32.431


• 30888 P2 POLARIZATION  
FILTER FOR ML4 AND 2.5X  
LOUPES - J.000.31.326

Set content: optics, S-frame with  
i-View loupe mount, detachable  
protective lenses, 2 sterilizable  
swivel levers, retaining cord,  
cleaning fluid, carrying case.



## RIESTER RI-FOCUS LED HEADLIGHT

- 30881 RI-FOCUS 6091 LED HEADLIGHT - with rechargeable batteries
- High performance LED headlight with battery compartment for fast and easy change of battery. Flexible hinge for a comfortable one-hand use of the LED illumination body.
- more efficient diagnosis due to white and high performance LED with up to 100,000 LUX and 50,000 hours lifetime
  - wireless headband with built-in battery compartment
  - particularly comfortable with balanced headband and one-hand operation
  - focusable LED lamp at a distance of 40 cm approx Ø 40 mm to 200 mm infinitely focusable
  - white LED with 6,000 °Kelvin, 140 lumen
  - significantly less heating and energy loss
  - rechargeable battery operation: approx 90 min with fully charged batteries
- Rechargeable AAA batteries and plug in 100-240 V charger included.



On/off switch on the  
battery compartment

Removable and  
washable  
inner padding

Weight 210 g  
without batteries

MADE IN GERMANY

30881

### TECHNICAL SPECIFICATIONS

Distance:	400 mm	200 mm
Lux max:	10,000	23,000
Circle of light max Ø:	200 mm	120 mm
Circle of light min Ø:	40 mm	30 mm

## GIMA LED MEDICAL HEADLIGHT

• 30879 GIMA 38 KL LED MEDICAL HEADLIGHT 3W

- with rechargeable batteries

- Advanced LED technology headlight with white and homogeneous light, ideal for all surgical and dental applications
- brilliant LED micro 3W provides free range of movement and wide field of view
  - coaxial illumination, shadow-free illumination of cavities, ideal for ENT and dental applications.
  - compact, lightweight, ensures perfect comfort
  - compact and long lasting aluminium housing, reduces heat build-up. Easy to clean.
  - individual adjustment of the angle of view.
  - 30878 LITHIUM BATTERY 3W - spare

Multilingual  
manual: GB, FR, IT,  
ES, PT, DE, PL, GR.



Supplied with battery  
and battery charger

On/off switch,  
brightness control and battery status  
LED on the battery  
compartment

30879

### TECHNICAL SPECIFICATIONS

Illumination:	38,000 lux	Brightness intensity: 0-100% adjustable
Light spot:	80 mm at 50 cm	Battery duration: 5-12 hours
	50 mm at 32 cm	Battery charging time: 3.6 hours
LED operating life:	up to 50,000 hours	Battery charger: 100-240 V, 50/60 Hz

# PENTALED 63N THEATRE LIGHTS

## PENTALED 63N

PentaLED 63N is a high-tech product designed to guarantee excellent performance levels. PENTALED 63N has 72 elliptical reflectors split into 8 modules, each containing 9 LEDs. The modules are mechanically focused by rotating the sterilizable handle. The multiplicity of the luminous sources and the elliptical geometry of the parabolas studied to reflect in the depth the light beams generated by the LEDs, grant scalytic light for a three-dimensional illumination without shadows.

MADE IN ITALY

### Comfortable use

Thanks to the principle of indirect light, the lamp oriented towards different positions does not dazzle the surgeon and the assistants. The size of the lit field is adjusted mechanically through handle according to the light required by the surgeon.

### Superior lighting features

Membrane keyboard activates the following functions:

- selection of the colour temperature 5,000°K and 4,500°K
- adjustment of the light intensity up to 160 Klx
- on/off
- endo light with colour selection (comfortable light for endoscopy intervention)

The colour temperature of 5,000°K stimulates the surgeons' concentration, does not strain their sight, reproduces the colour of the tissues faithfully and increases the definition of the edges.

### Reliable and long lasting performances

The modular construction of the electronic board that feeds the LEDs guarantees continuous light, even in the unlikely event that a LED or board component should fail. The lighting body is protected by tempered glass screen, covered by a special film avoiding any fallen down splinters in case of break.

### Easy manoeuvrability

The reduced dimensions and the light reflector provide extreme manoeuvrability and stability. Smooth 360° rotation. The extremely light structure, the aluminium treated bar attached to the upper front of the cupola, the ultra-thin dome (only 13 cm) allow simple movements.

### Battery group, TVCC camera, monitor holding arm on request

Every lamp can be supplied with an emergency battery group with automatic charger (hours autonomy: 1.5 (49200), 1.5 for 63N, 4 for 30N 1.5 (49202)), TVCC camera or monitor holding arm.

### Full certification

Complies with regulation EU2017/745 'Class I - Medical Device'.


QR manual: GB, FR, IT, ES, PT.

63N 160,000 LUX



RIMSA

CE



63N+30N 320,000 LUX  
(160,000+160,000 LUX)

GIMA code	PENTALED 63N THEATRE LIGHTS - CEILING*
49200	PENTALED 63N* - 160,000 LUX
49201	PENTALED 63N+30N double** - 320,000 LUX - compact
49202	PENTALED 63N+63N double** - 320,000 LUX - plus
*Ceiling >3.41 m needs 49220 **Ceiling >3.53 m needs 49220	
ACCESSORIES	
30738	Autoclavable handle - spare
49205	Monitor holding arm - stand alone
49206	IR remote control - single lamps
49207	IR remote control - double lamp
ACCESSORIES TO BE ORDERED WITH LIGHT	
49210	Battery group with automatic charger for 63N
49211	Battery group with automatic charger for 63N+30N
49212	Battery group with automatic charger for 63N+63N
49214	HD TVCC camera for 63N - including lamp setup
49215	Monitor holding arm - integrated with lamp
49220	Special structure for high ceiling



63N+63N 320,000 LUX  
(160,000+160,000 LUX)

TECHNICAL SPECIFICATIONS			
		63N	30N
Performance	Light intensity at 1 m distance (Ec)	klx 160	160
	Colour temperature: double selection	°K 4,500/5,000	4,500/5,000
	Colour rendering index (CRI)	Ra 96	96
	Light field diameter adjustable from/to	cm 16-30	14-28
	Total radiated energy Ee where the illumination reaches max level	W/m² 580	580
	Number of LED	72	30
	Diameter and focus adjustment	manual	manual
	Depth of illumination IEC 60601-0-41 L1+L2 at 60%	cm 56	65
	Depth of illumination IEC 60601-0-41 L1+L2 at 20%	cm 108	115
	Control of illuminance	% 20-100	20-100
	Endo LED light intensity min-max	klx 5-20	9-25
	Operating power (VAC)	V 100-240	100-240
	Operating power Vdc	V 24	24
	Electrical absorbed power	VA 67	60
	Frequency	Hz 50/60	50/60
Electrical data	Average LED life	h 60,000	60,000
	Colour	RAL 9003	9003
General data	Minimum height of the room	cm 260	260
	Outer reflector diameter	cm 63	40
	Useful lighting surface	cm² 1828	762
	Weight	kg 47	39



## GIMALED O.T. LED LIGHTS - 160,000 LUX

GimaLed light with **81 LEDs**: sophisticated design which combines excellent lighting features with exceptional mechanical characteristics for extra soft movement.

**Deep light**: 27 inner fixed Leds for central illumination and 54 LEDs (six modules of nine LEDs each) moved by servo-motor, allow surgeon to adjust light field diameter.

**Shadowless light**: 81 LEDs arranged on a round surface grant the best light emitting surface and avoid any shadow effect caused by any interposition between light beams and lighted surface.

**Bright light**: two colour selections, 4,000K and 4,600K, made of white LEDs only, no coloured shadow effect.

### Major features

- collimated light beams for a working distance from 70 to 160 cm
- high colour rendering index (CRI) 95, R9 >90
- optimisation of LED thermal management by heat dissipation convection to avoid illuminance reduction during surgery
- PMMA optical lenses and polycarbonate protective screen
- Zener to grant light in case of even one LED failure
- reduced consumption, high efficiency

Electronic control of light adjustment, colour temperature, light field diameter and endoscopy light.

GIMA code	GIMALED
49180	GimaLed-mobile - 160,000 Lux
49181	GimaLed-mobile with battery group and automatic charger
49182	GimaLed - ceiling* - 160,000 Lux
49183	GimaLed - ceiling** - double - 320,000 Lux
49197	Autoclavable handle
49205	Monitor holding arm - stand alone
49220	Special structure for high ceiling
49185	GimaLed wall remote control

Battery group available on request for all models

\*Ceiling >3.41 m needs 49220

\*\*Ceiling >3.53 m needs 49220

Small overall dimensions of cupola, perfectly balanced, ensure stable adjustment.

Ergonomic grip on the cupola and on the protective screen to hold and move the lamp

Motorised light field diameter adjustment through touch sensitive sterilisable handle or touch pad at the side of the cupola

49183

Thin and easy-to-adjust reflector

160,000 LUX

MADE IN ITALY

49180

### TECHNICAL SPECIFICATIONS

Light intensity at 1 m distance (Ec)	Klx 160, Klx 320 (only 49183)
2 Colour temperature - switchable	°K 4,000 and 4,600
Colour rendering index (CRI)	Ra 95
Light field Ø (adjustable)	11-35 cm
Light field Ø where illuminance reaches 10% of Ec (d10)	260 mm
Light field Ø where illuminance reaches 50% of Ec	150 mm
Total radiated energy Ee where illumination reaches max level	556 W/m <sup>2</sup>
Average LED life	hours 60,000
Power supply:	100-240 V - 50-60 Hz - 61-71 W
Regulations:	IEC 60601-2-41 - EU 2017/745

## PENTALED 30E SURGERY LAMP 160,000 LUX

### LED LIGHT INNOVATIVE TECHNOLOGY

A compact size hi-tech product that guarantees great performance levels. It has 30 elliptical reflectors split into 6 modules each containing 5 LEDs, providing 160,000 LUX - selectable 4,500 °K - 5,000 °K. By simply pressing the digital key, the surgeon can choose two different white light temperatures

- **E-view** innovative lens allows the surgeon to expand/narrow the illuminated operating field electronically, without altering intensity of light.

- **E-comfort** the indirect LEDs creates 3D shadowless illumination of the operating field, no risk of dazzling

- **E-white** only white LEDs to avoid risk of perception of colour temperature variations or coloured shadows

- **E-deep** centre of light is fitted with extra LEDs module specifically designed to reflect deep light. This means that surgeon can work with perfect 3D lighting.

**Battery and high definition camera on request.** Optional battery group with automatic charger (4 hours autonomy) and high definition integrated camera (for ceiling and wall models only).

GIMA code	PENTALED 30E
30780	Pentaled-mobile - 160,000 Lux
30779	Pentaled-mobile with battery group and automatic charger
30781	Pentaled - wall - 160,000 Lux
30782	Pentaled - ceiling* - 160,000 Lux
30783	Pentaled - ceiling** - double - 320,000 Lux
30785	Autoclavable handle - up to serial number 12071
30738	Autoclavable handle - since serial number 12072
49205	Monitor holding arm - stand alone
49220	Special structure for high ceiling (>3.8 m)

\*Ceiling >3.41 m needs 49220

\*\*Ceiling >3.53 m needs 49220

QR manual: GB, FR, IT, ES, PT.


An aluminium ring runs around the dome for easier positioning

30783


Aluminium structure tested for over 40,000 movements

RIMSA


MADE IN ITALY



30780



30781



30782

### TECHNICAL SPECIFICATIONS

Adjustable light intensity at 1 m distance (Ec)	Klx 160	Total radiated energy Ee where illumination reaches max level	W/m <sup>2</sup> 627
Colour temperature - switchable	°K 4,500 to 5,000	Average LED life	hours 60,000
Colour rendering index (CRI)	Ra 96	Power supply:	100-240 V - 50-60 Hz - 60 VA
Light field (electronically adjustable)	14-26 cm	Regulations:	IEC 60601-2-41 - EU 2017/745
Light field Ø where illuminance reaches 10% of Ec (d10)	mm 210		
Light field Ø where illuminance reaches 50% of Ec	mm 80		

## ■ QUATTROLUCI LED LIGHTS - 160,000 LUX

### QUATTROLUCI LED LIGHTS - 4 DOMES WITH 9 LEDS EACH

Aerodynamic design, extremely handy structure, high technology, quality and performance in one lamp. The multi-circular reflector, designed to light up the work area thoroughly and suppress all the shadows, is equipped with central handle to facilitate positioning.

Ultra-flat lighting body is equipped with ultra-resistant polycarbonate screen, which guarantees protection against possible accidental collisions. Its rotation on 4 axes facilitates positioning.


The dome consists of 36 LED lenses arranged radial fashion on 4 module of 9 LED each, to ensure light continuity even in the rare case of individual LED fault. Light intensity is 160,000 lux. Excellent for oral and maxillofacial surgery and aesthetic plastic surgery.

#### TECHNICAL SPECIFICATIONS


Light intensity:	160,000 lux at 1 m distance
Colour temperature:	4,900° K
36 LEDs average LED life:	>60,000 hours
CRI (Chromatic Rendering Index):	94
Diameter of the reflector:	60 cm
Diameter of illuminated field:	30 cm
Depth of illumination IEC 60601-2-41 (L1+L2) at 20%:	174 cm
	110 cm
Total radiated energy:	Ee 570 W/m <sup>2</sup>
Weight (ceiling, mobile, wall) kg:	15, 23, 14
Min./Max. height of the room (ceiling version):	255-334* cm
Power supply:	100-240V - 50/60 Hz
Norms:	IEC 60601-1, IEC 60601-2-41 - EU 2017/745

GIMA code	QUATTROLUCI LED LIGHTS
49150	Quattroluci Led light - trolley
49151	Quattroluci led light - trolley with battery group and automatic charger
49152	Quattroluci Led light - wall
49153	Quattroluci Led light - ceiling*
49154	Quattroluci Led light double - ceiling**
30788	Special structure for high ceiling
30738	Spare autoclavable handle - for scalytic 3 bulbs
Battery group available on request for all models***	

\*Ceiling >3.34 m needs 30788 \*\*Ceiling >3.58 m needs 30788 \*\*\*To be ordered with light



## ■ SATURNO LED LIGHTS - 50,000 LUX



### SATURNO LED MINOR SURGERY LAMP

SATURNO is a shadow-less type lamp suitable for small surgery, gynaecology and examination.

Available in three versions: mobile with castors, wall and ceiling.

- light beams are generated from 9 LEDs - 2.0 W each
- heat is dissipated through aluminium cover reflector
- selection of 2 different white light temperatures: 4,000 and 4,500 °K
- light intensity adjustable at 7 different levels through front digital panel
- luminous intensity 50,000 LUX at 1 m. Ø of illuminated field 28 cm
- adjustable friction bearing are mounted on every articulation of the lamp
- thanks to optical concept, no need to be focus adjusted

**Battery group with charger:** 4 hours autonomy, 6 hours recharging.

#### TECHNICAL SPECIFICATIONS


Light intensity at 1 m distance	Lux	50,000
Colour temperature adjustable	K°	4,000/4,500 ± 5%
9 LEDs	W	2.0 each (18 total)
Average LED life	hours	60,000
CRI (chromatic rendering Index)	Ra	95
Diameter of illuminated field	Ø cm	28
Depth of illumination IEC 60601-2-41 (L1+L2) at 60% of Ec	cm	110
Total radiated energy Ec	W/m <sup>2</sup>	186
Diameter of the reflector	cm	19.5
Useful lighting surface of the cupola	cm <sup>2</sup>	63
Weight (ceiling, mobile, wall)	kg	12 - 20 - 11
Power requirements	V, Hz	100-240, 50-60
Minimum height of the room (ceiling version)	cm	254.5
Standards: IEC 60601-1 IEC 60601-2-41, EU 2017/745, medical device of Class I		

GIMA code	SATURNO LED LIGHTS
49100	Saturno LED light - mobile stand
49101	Saturno LED light - mobile stand with battery group
49102	Saturno LED light - wall
49103	Saturno LED light - ceiling* (2.54-3.34 m)
30788	Special structure for high ceiling (>3.34 m)
30797	Spare autoclavable handle for Saturno
Battery group with automatic charger available on request for all models (to be installed at order)	

\*Ceiling >3.34 m needs 30788



# PENTALED 12 - 100,000\* LUX, PENTALED 28 - 120,000 LUX




## PentaLED 12

- 100,000\* Lux at 1 m
- indirect light with 12 elliptic reflectors. They reflect the light rays emitted by the LEDs. Does not dazzle and does not strain eyes.

## PentaLED 28

- 120,000 Lux at 1 m
- direct light with 28 LED lens
- double colour selection: 4,500 or 5,000 K
- light field adjustment

MADE IN ITALY



Light field adjustment for PENTALED 28

## PENTALED

PENTALED is a perfect combination of technological developments, innovation, ergonomics and compact design, ultra-light and handy structure.

Five versions available (trolley, ceiling, ceiling double, trolley with battery group and wall) and technical performances make PENTALED suitable for precision operations, diagnostic use, surgical rooms and small surgeries.

Battery group, with an autonomy of 2 hours (PentaLED 12) or 1.5 hours (PentaLED 28), is available on request also for wall and ceiling models.

## Cold LED light

Bright and cold light reproduces colours faithfully, assuring excellent definition of details.

## Ergonomic

PENTALED can be easily positioned by rotation on 4 axes:

- the dome has a 300° rotation
- the arm moves vertically thanks to a spring balancing system
- the reflector can be rotated on the vertical and horizontal axis.

Movements are possible through the sterilizable handle.

## 60,000 hours life time

The low power supply current and the heat dispersion through aluminium dome allow the LED a 60,000 hours lifetime.


## Light intensity adjustment

Light intensity adjustable through digital control



GIMA code	PENTALED 12 LEDS
30787	PentaLED 12 - trolley
30789	PentaLED 12 - ceiling* (for ceiling 2.54 to 3.34 m)
30790	PentaLED 12 - wall
30791	PentaLED 12 - trolley with battery group and automatic charger
30792	PentaLED 12+12 - ceiling** double (for ceiling 2.66 to 3.56)
30788	Special structure for high ceiling
30793	Autoclavable handle - spare
GIMA code	PENTALED 28 LEDS
49115	PentaLED 28 - trolley
49116	PentaLED 28 - ceiling* (for ceiling from 2.54 to 3.34 m)
49117	PentaLED 28 - wall
49118	PentaLED 28 - trolley with battery group and automatic charger
49119	PentaLED 28+28 - ceiling** double (for ceiling 2.66 to 3.56 m)
30788	Special structure for high ceiling
30793	Autoclavable handle - spare

\*Ceiling >3.34 m needs 30788 \*\*Ceiling >3.56 m needs 30788



## TECHNICAL SPECIFICATIONS

		PENTALED 12	PENTALED 28
Light intensity at 1 m distance	Lux	100,000	120,000
Colour temperature	K°	4,500	4,500/5,000
LED	No.	12	28
Average LED life	hours	60,000	60,000
CRI (Chromatic rendering Index)	Ra	95	95
Diameter of illuminated filed	Ø mm	160	135-270
Depth of illumination (L1+L2) at 60%	cm	75	92
Total radiated energy Ec	W/m²	370	456
Weight (ceiling, mobile, wall, double)	kg	13-21-12-20	
Power supply	V/Hz	100-240V, 50-60Hz	
Standards: IEC 60601-2-41, EU 2017/745, medical device of Class I			

■ **PRIMALED COLD LIGHT LAMP** - 105,000 LUX AT 50 cm

## PRIMALED COLD LIGHT LAMP WITH 9 LED LENSES

Appealing design and advanced technology.

**Design:** the round and ultra-flat shape of the light makes the product ergonomic and suitable for any type of installation.

**Ergo-Spring:** the movement of the articulated tubular arm is servo-assisted by a torsion spring which ensures ease of movement and stability.

**105,000 lux:** unique performance with 105,000 lux at 50 cm.

**Light intensity adjustment:** six different adjustment levels by the keys on the frontal panel.

**4,000-4,500 °K Colour temperature selection:** the comparison between the two colours (K) increases the visibility of details.

**Shadow suppression:** the radial layout of the lenses and the large-diameter lamp (195 mm) allow shadow suppression and three-dimensional lighting.

**Adjustable courtesy-light:** integrates ambient light with traditional concentrated light.

**Sterilizable removable grip:** allows best asepsis.

**Cold light:** the reduced emission of IR rays by the LEDs as well as the low power consumption allow minimum heat emission.

**60,000 hours LEDs life:** the top aluminium dome allows heat exchange, thus reducing the work temperature and considerably increasing the life cycle of the single LEDs.

**Interchangeable plugs:** transformer is integrated in the plug for a lighter and smooth movement of the arm.

Supplied with interchangeable plugs (UK, US, EU).

**Fully certified:** complies with IEC 60601-1 and 60601-1-2 general medical standards and to special standard IEC 60601-2-41

EU 2017/745 and is CE marked as a Class I medical device.

**Mechanical testing and user safety:** die-cast aluminium and tubular steel structure. The articulated arm has undergone mechanical testing for 40,000 continuous movements.

**Light continuity:** the modular design of the LED power circuit ensures light continuity even in case of a LED fault.

**Battery kit:** included with 49124, available in 45 days for 49125 (to be purchased with light).

GIMA code	PRIMALED FIX AND FLEX
<b>49124</b>	Primaled - flex light - trolley with battery
<b>49125</b>	Primaled - fix light - trolley
<b>49126</b>	Primaled - flex light - trolley
<b>49127</b>	Primaled - fix light - wall
<b>49128</b>	Primaled - flex light - wall
<b>30797</b>	Autoclavable handle
<b>30769</b>	Trolley - base Ø 61 cm - spare

## TECHNICAL SPECIFICATIONS

LED life: >60,000 hours Illuminated field at 50 cm: Ø 160 mm  
Light intensity: 105,000 lux at 50 cm, 30,000 lux at 1 m  
Colour temperature: 4,000-4,500 °K Colour rendering index: 95 Ra  
External diameter of the reflector: 195 mm  
Temperature increase in the operating area at 1 m: 1°C  
Adjustable height with castors: 600 mm - max 1,600 mm  
Power supply: 100-240V - 50/60 Hz Electric absorption: 20VA  
Weight: 10 kg (trolley included) Light intensity adjustment: 20-100%

The lamp lens has been designed to provide focused and deep lighting. Lighted field diameter is 16 cm at 0,5 m.

The following functions are

controlled by the keys on

the men

- on/off

- selection of the 4,000°K and 1,500°K


4,500°K colour temperatures  
- 6-level adjustment of the light intensity

- courtesy light



QR manual:  
GB, FR, IT, ES, PT

49125



 MS LED PLUS AND MS LED FLEX PLUS LIGHT - 65,000 LUX

- 49132 MS LED PLUS LIGHT - trolley
- 49133 MS LED FLEX PLUS LIGHT - trolley

Minor surgery luminaire with LED light source. Flexible or articulated arm with great precision allow regulation of the light in any position. High quality of materials makes it especially suitable for intensive use in surgery and examinations.

### Exceptional quality of LED light

Powerful LED light source offers exceptional light quality and a lifespan of more than 50,000 hours. The high performance of the colour Ra 97% depicts the exceptional quality of white light for an excellent distinction of fabrics and reproduction of all visible colours, naturally and precisely.

## Ergonomic design


The circular shape of the head and its handle in the lower part facilitate its exact positioning, clean and soft shapes which facilitate hygiene and cleanliness.

TECHNICAL SPECIFICATIONS			
Light source	LED 12W	Colour rendering	> 97%
Lux at 50 centimeters	65.000 lux	Lamp lifetime	50.000 hours
Adjustable light intensity	Yes	Arm length	90 cm (49132)
Colour temperature	4.500 °K		70 cm (49133)
Colour	White		





# HALOGEN AND LED LIGHTS FOR EXAMINATION AND MINOR SURGERY



## ALFA-FIX AND ALFA-FLEX

Three LED light sources with coinciding lenses and polycarbonate protection shield. Thanks to three independent light sources, shadows can be reduced and provide a deep cylindrical light with highly reduced heat irradiation. Each LED integrates a resistance to ensure the continuous operation of the lamp even in the rare case of a LED fault.

### Design


New design makes the lamp extremely easy to use and manoeuvre, with an additional rotation of the reflector.

### Touch control

The light intensity can be adjusted through the touch button, a smooth touch of the control allows to regulate the light intensity from 4% to 100%.

### Interchangeable plugs

The transformer, integrated in the plug for a lighter and smooth movement



of the arm structure, is supplied with interchangeable plugs (UK, US, EU).

### Flexible arm (30723-5)

The flexible arm ensures easier light positioning and is covered with a smooth white shrink-wrap sheath for easier cleaning and disinfection.

### Battery kit

Included with 30728, available in 45 days for 30723 (to be purchased with light). QR manual: GB, FR, IT, ES, PT.

GIMA code	ALFA-FIX AND ALFA-FLEX
30723	Alfa-flex LED - trolley
30724	Alfa-flex LED - wall
30725	Alfa-flex LED - table with clamp
30726	Alfa-fix LED - trolley
30727	Alfa-fix LED - wall
30728	Alfa-fix LED - trolley with battery


ACCESSORIES AND SPARE	
30766	Spare bulb Simplex - IRC 35 W for 30760-30763
30768	Spare trolley, base Ø 61 cm for Simplex and Alfaflex
30769	Spare trolley, base Ø 61 cm for Solesud2 and Alfafix
30775	Rail connection with clamp
30772	Spare glass Ø 8.5 cm for 30723-30727
30770	Spare glass Ø 12.3 cm for Solesud

Model	ALFA-FIX	ALFA-FLEX	LUXIFLEX		
Type of lighting	LED	LED	halogen	LED	LED Plus
Consumption (Watt)	8	8	35	6.5	10
Life of the bulbs (hours)	> 60,000	> 60,000	5,000	50,000	50,000
Light intensity at 50 cm (lux)	60,000	60,000	50,000	15,000	35,000
Light intensity at 1 m (lux)	20,000	20,000	-	-	-
Colour temperature ± 5% at 1 m (K)	4,500	4,500	4,000	4,500	4,500
Colour rendering index (Ra)%	94	94	95	80	97
Light field size at 50 cm (Ø mm)	150	150			
External Ø of the reflector (mm)	95	95	80	80	80
Colour	white	white	white	white	white
Norms	IEC 60601-1	IEC 60601-1	EN 60601-1-2		
Marks	EU 2017/745		CE 93/42		
Weight (kg)	5	5			
Operating voltage V	100-240	100-240	230	110/230	
Operating Hz	50/60			50/60	

- 30754 LUXIFLEX on trolley - halogen
  - 30756 LUXIFLEX on trolley - LED
  - 30755 LUXIFLEX PLUS on trolley - LED
- Stylish and versatile light for examination and minor surgery procedures in health-centres, clinics and hospitals. Suitable also for veterinary examinations and procedures. Class II.
- Safe low voltage operation without infrared radiation. Electronic transformer lodged at the bottom of the lamp. Flexible arm and 5 castors trolley allow easy use and movability.
- 30757 SPARE BULB LUXIFLEX - halogen



## ■ HYRIDIA 7 LED LIGHTS - 65,000 LUX



- 49040 HYRIDIA 7 LED LIGHT - flexible arm - trolley
  - 49041 HYRIDIA 7 LED LIGHT - metal spring arm - trolley
- 7 Leds 10 W medical procedure lights on trolley with flexible soft arm or metal spring arm. Digital brightness control.  
Manual: GB, FR, IT, ES, PT, DE, PL, GR.

### TECHNICAL SPECIFICATIONS

Consumption:	10 W	Light intensity and Light field Ø:		
Colour temperature:	4,800-5,500 °K	Illumination	Ø	Distance
External Ø of reflector:	89 mm	78,000 lux	9 cm	30 cm
Colour rendering index (CRI):	75 Ra	65,000 lux	12 cm	50 cm
Operating voltage:	110-265 V, 50/60 Hz	22,000 lux	18 cm	100 cm

## ■ LUMINA LED LIGHT




- 49035 LUMINA LED LIGHT - trolley
- Classic examination LED light with flexible arm.  
Manual: GB, FR, IT, ES, PT, DE, PL, GR.

### TECHNICAL SPECIFICATIONS

Consumption	3 W
Light intensity at 50/30 cm	37,000/89,000 lux
Colour temperature:	6,000 °K
External Ø of reflector:	75 mm
Colour rendering index (CRI):	75 Ra
Light field Ø:	4 cm at 50 cm
Operating voltage:	110-265 V, 50/60 Hz

## ■ RI-MAGIC® HP LED LIGHT

- 49050 RI-MAGIC® HP LED - desk
  - 49051 RI-MAGIC® HP LED - trolley
  - 49052 RI-MAGIC® HP LED - wall
- High performance medical LED light for examination and procedures.
- high performance LED, 6,000 °K
  - lifetime of the lamp up to 50,000 hours
  - significantly reduced heating and energy loss
  - focusing device at the front of the light head
  - highly flexible, long special arm can be bent in all directions
  - rheostat handle for infinitely variable regulation of light intensity.
- Manual in: GB, FR, IT, ES, DE, RU.



MADE IN GERMANY

### TECHNICAL SPECIFICATIONS

Distance:	1,000 mm	800 mm	600 mm	400 mm	200 mm
Lux max:	15,000	20,000	30,000	45,000	55,000
Circle of light max Ø:	340 mm	270 mm	215 mm	155 mm	90 mm
Circle of light min Ø:	40 mm	35 mm	30 mm	25 mm	20 mm
Operating voltage:	100-240 V,	50-60 Hz			

## ■ LED SPOT-ADJUSTED LIGHT

- 49047 LED SPOT-ADJUSTED LIGHT - trolley
- LED Spot examination lamp with multi-optical lens and light spot adjustable by inner mini light grating.
- Additional features:
- uniform and pure light spot
  - front optical lens
  - inner light grating
  - rear dual optical lens
  - 100 cm super long 360° free position and PVC coated flexible metal arm



### TECHNICAL SPECIFICATIONS

Bulbs/power:	1 LED / 5 W
Ø of lamp head:	25 mm
Illumination:	25,000 lux at 30 cm
	10,000 lux at 50 cm
	max 70 mm, min 15 mm at 30 cm
Light field Ø:	
Colour temperature:	4,800°-6,000° K
Lamphead:	Ø 25 mm, length 125 mm
Power supply:	100-260 V, 50/60 Hz
Power cord:	length 272 cm



## MAGNIFYING LED COLD LIGHTS - 3 DIOPTRES

### GIMANORD PLUS

This model features a biconvex magnifying lens in optical glass with Ø 120 mm. The cold LED light allows prolonged use, without causing any eyesight problem. Polycarbonate screen for protection of the light source. Suitable for dermatology use. Medical device Class I.

#### Design

The new design makes the lamp extremely easy to use and manoeuvre, with an additional rotation of the reflector.

#### Touch control


Touch button allows to adjust light intensity from 4% to 100% with a smooth touch.

#### Interchangeable plugs

The transformer, integrated in the plug for a lighter and smooth movements of the arm structure, is supplied with interchangeable plugs (UK, US, EU).

#### TECHNICAL SPECIFICATIONS

Light intensity at 0.5 m (Ec)	2,250 lux
Colour temperature	5,370 K
Colour rendering index (CRI)	95 Ra
R9	≥90
Operating voltage	100-240 V - 50/60 Hz
Absorbed power	16.5 W
Light head diameter	23 cm
Average life	>60.000 hours
Norms	IEC-60601-1, IEC-60601-2-41, EU 2017/745



Magnifying glass  
Ø 120 mm

30716  
30717

QR Manual:  
GB, FR, IT, ES, PT

MADE IN ITALY

GIMA code	LED MAGNIFYING LIGHTS
30716	GIMANORD PLUS - with table clamp
30717	GIMANORD PLUS on trolley
SPARES AND FIXING SYSTEMS	
30720	Plexiglass shield for 30716-9 - spare
30771	Plexiglass shield for 30750-1* - spare
30769	Trolley - base Ø 61 cm - spare
30774	Wall clamp - optional

\*Old models



## LED MAGNIFYING LAMP - 5 DIOPTRES

### • 30737 LUPA LED MAGNIFYING LIGHT - trolley

### • 30739 LUPA LED MAGNIFYING LIGHT - desk with clamp

Smartly designed white cold light LED lamp with 5-dioptres magnification. Generates a light without shadow. 5 wheels base and articulated arm allow easy movement. Manual in GB, FR, IT, ES, PT, DE. Medical device Class I.

#### TECHNICAL SPECIFICATIONS

Type of light:	60 LED - HF 6 W
Dioptres:	5
Lens:	Ø 12.7 cm
Colour temperature:	6,500 °K
Operating voltage:	110-230 V - 50/60 Hz
Class I	
Marks:	93/42/EEC
Lamp life:	40,000 hours



## LED MAGNIFYING LAMP - 3 DIOPTRES


### • 30736 DERMALED MAGNIFYING LAMP

Cold light LED lamp with 3 dioptres magnifying glass lens and brightness adjustment.

It comes with a high stability 5 wheels base and an articulated arm for easy movement and fixing of the lamp. Manual in GB, IT.


#### TECHNICAL SPECIFICATIONS

Type of light:	LED
Voltage:	7 W
Dioptres:	3 (large glass)
Colour temperature:	7,500-9,500 °K
Light intensity at 20 cm:	2,400 lux
Operating voltage:	100-240 V - 50/60 Hz
Net/Gross weight:	12.8-15 kg



## VISTA WOOD BLUE LIGHTS: TROLLEY AND MANUAL

- 31196 VISTA WOOD LAMP - handle
  - 31197 VISTA WOOD LAMP - trolley
- A Wood lamp is a diagnostic tool to diagnose the condition of skin. Different skin conditions under ultraviolet rays of the Wood lamp appear in different colours. These models have polished glass magnifying lens 10x6 cm - 3 dioptries. 9W special compact fluorescent tube at approximately 360 nm wavelength. Operating voltage: 230 V - 50 Hz. Manual in GB, FR, IT, ES, PT, DE.
- 31201 FLUORESCENT TUBE 9W - spare for 31196-31197




## MACRO LENS 12X

- 31155 SMARTPHONE MACRO LENS 12X
- Macro lens 12X for allergists, dermatologists, phlebologists, aesthetic surgeries. Can be mounted on any smartphone to take magnified images. Supplied with clip compatible with any smartphone, 10x10 cm wipe and multilingual manual (GB, FR, IT, ES, PT, DE, PL, GR).



## ECONOMIC WOOD LAMP



- 31200 WOOD LAMP
- Ultraviolet light for skin condition analysis. Size 30x21x7 cm. Operating voltage: 220-240 V, 50/60 Hz.
- 31202 FLUORESCENT TUBE - spare

## POCKET WOOD LIGHT



- 31189 POCKET WOOD LIGHT
- Pocket ultraviolet light, to detect skin disorders. Provided with replaceable fluorescent lamp. Power 6 W. Works with 4xAA batteries with 4-6 hours autonomy.
- 31190 FLUORESCENT TUBE - spare

## DIGITAL Wi-Fi POLARISED DERMATOSCOPE, CAPILLAROSCOPE, MICROSCOPE

An innovative line of handheld colour digital microscopes: dermatoscope with polarized filter, capillaroscope and iridoscope with Wi-Fi wireless transmission. Small, easy to operate, light and portable. They can be used with all the most popular smartphones, tablet and PC.

Basic software for acquisition of photos and videos. Google/Apple applications included. Designed in Italy, manufactured in China. Directive 93/43/CEE - Medical device Class I (only 32181 and 32183).



Professional software available for creation of patient database, image comparison and medical referrals

- 32181 Wi-Fi DERMATOSCOPE with polarized filter



- 32183 Wi-Fi CAPILLAROSCOPE



- 32184 Wi-Fi MICROSCOPE
- Advised to view the iris.

### MICROSCOPE SPECIFICATIONS

Magnification:	30X
Light source:	2 adjustable white LED+ 2 adjustable yellow LED
Lens:	High definition microscopy lens

### DERMATOSCOPE SPECIFICATIONS

Magnification:	5X to 200X
Light source:	8 adjustable white LED
Lens:	High definition microscopy lens

### CAPILLAROSCOPE SPECIFICATIONS

Magnification:	500X to 600X
Light source:	8 adjustable white LED
Lens:	High definition microscopy lens

### TECHNICAL SPECIFICATIONS

Operation system	Windows (7, 10), OS X, iOS, Android (it can be used by Wi-Fi or USB)	CAMERA
Photo and video resolution	1.3 MPixels - 1280x1024 (MJPG), 640x480 (MJPG), 320x240	Camera sensor CMOS 1/4"
Frame rate	15 fps 1,280x1,024, 30 fps 640x480 320x240	Optical features
Wi-Fi wireless transmission distance	Up to 5 m	Exposure: Auto, Gamma: Auto, White balance: Auto, Black reference: Auto
Power consumption	Max 2.5 W	
Li-ion battery	Continuous working time - appx. 2 hours, full charging time - appx. 2 hours	
Power source - Size - Weight	DC 5.0V / 1A - Ø 36x142 mm - 88 g	

### STANDARD ACCESSORIES

Caps of contact (only for 32181)  
USB AC adapter  
USB cable  
Quick manual  
Plastic stand  
Line calibration ruler (only 32181)  
Manual (GB, FR, IT, ES, DE)  
CD basic software Win (GB, FR, IT, ES, DE, UA, JP), Mac (GB)



## HEINE DELTA 20® T LED<sup>HQ</sup> DERMATOSCOPES 10X - 16X

• **31161 HEINE DELTA 20® T LED<sup>HQ</sup> DERMATOSCOPE 3.5V (Li-ion)** for polarization and immersion with rechargeable handle for mains socket and USB cable - K-262.28.388  
**Precision HEINE Optics** - high quality, achromatic optical system provides unsurpassed sharpness and resolution. Focusing system provides from 10X to 16X magnification for detection of even the smallest details and structures.  
**LED in HQ** - the new standard in LED illumination defining optimal light intensity, homogeneity and colour rendering for each individual examination - Colour temperature: 5.000 K, Colour Rendering Index (CRI) > 80 on a scale of 100. This ensures true tissue colour for the most accurate diagnosis.  
**Toggle between polarised and non-polarised illumination modes** - alternation between two modes with the press of a button, no exchange of contact plates necessary. Allows recognition of the "Blink Sign" when observing crystalline structures and presence of milia cysts, increasing diagnostic function.  
**Optional small contact plate** for difficult to access lesions.  
**Digital documentation capabilities** - Heine SLR photo adaptor allows to connect any Delta 20 dermatoscope to major brands of digital cameras.  
**LED Thermal Management** - ensure long-term performance and product stability. Carefully selected and applied heat-diffusing materials guarantee up to 50.000 hours.



Supplied with hard case, dermatoscopy compendium.

- **31162 HEINE DELTA T LED DERMATOSCOPE HEAD with contact plate with graduated scale** - K-008.34.221 (can be used with any Heine Beta handle). Supplied with compendium.
- **31179 SMALL CONTACT PLATE Ø 8 mm** - K-000.34.205
- **31171 SLR PHOTO ADAPTOR - for Canon**
- **31173 SLR PHOTO ADAPTOR - for Nikon**
- **31169 ADAPTOR CORD - 1.30 m**



## HEINE MINI 3000 DERMATOSCOPES

• **31184 HEINE MINI 3000 XENON-HALOGEN DERMATOSCOPE 10X - D-001.78.107**  
 Pocket dermatoscope with high-quality optics, 10X magnification with focusing optics, metal head.  
**Xenon Halogen bulb.** Concentrated, bright light for uniform illumination with exact colour rendering.  
**High quality colour-neutral optic system** with achromatic lenses, provides sharp images.  
**Contact plate without scale.**  
 Supplied with dermoscopic compendium.  
 Operates with AA batteries or rechargeable batteries (31693) + Mini 3000 NT charger (31692) not included.  
 • **31160 HEINE MINI 3000 LED<sup>HQ</sup> DERMATOSCOPE 10X - D-008-78-109** - same as 31184, with the addition of:  
**High-performance bright and homogeneous LED illumination** with an excellent colour rendering (index >95). Colour temperature 4,000 K.  
**Twice brighter light** compared to Xenon Halogen  
**Maintenance free.**  
**Fade-out function:** reduces illumination intensity with battery level to let you know when to replace.  
**Up to 10 hours operation time.**

- **31692 HEINE MINI 3000 NT CHARGER - X-001.99.484**
- **31693 BATTERY+BASE - X-001.99.487 + X-001.99.488**



## GIMA XENON HALOGEN SKIN SURFACE MICROSCOPE 10X

• **31187 GIMA XENON HALOGEN DERMATOSCOPE 2.5 V - 10X**  
 Advanced skin surface microscope offers long-lasting halogen illumination for the true tissue colour and 10X magnification for greater details, allowing accurate diagnoses of pigmented skin lesion.  
 Supplied in a useful bag, with spare autoclavable contact plate with 0-10 mm scale. Latex free.  
 • **32203 "C" BATTERIES - blister of 2 pcs.**  
 • **31479 XENON HALOGEN BULB - 2.5V - spare**  
 • **31185 SKIN LESION GAUGE - 21x5 cm**  
 Available with your logo for min. 2,000 pcs.




TECHNICAL SPECIFICATIONS			
Operating mode:	continuous	Frame rate:	15 frame/sec.
Camera:	Colour CMOS 1/2.5"	Image format:	bmp, jpg
LEDs:	4 white, 4 UV and 4 polarized adjustable LEDs	USB:	USB 2.0, 2 mt
Lens:	high definition microscopy lens	Battery:	Li-ion
Resolution:	1.3 Mpixel	Working time:	2 hours
		Power supply:	DC 5.0 V/1A
		Consumption:	Max 2.5 W
		Size - weight:	36x142 mm - 88 g

STANDARD ACCESSORIES		
USB cable	Ruler	1 Bag L + 1 bag S
USB AC Adapter	Contact closed cap	Quick guide + manual (GB, FR, IT, ES, DE)
USB foot pedal	Tube	CD Mic-Fi Derma Software

### TECHNICAL SPECIFICATIONS

Battery: 2x "C" or rechargeable battery (34479) + charger (31542)  
 Reticle contact plate  
 Easy to focus, with large focus ring



# RIESTER RCS-100 MEDICAL DIAGNOSTIC CAMERA SYSTEM



32150  
+  
32156

MADE IN GERMANY



Portable and versatile digital diagnostic camera. Multiple lens attachments, enabling instant sharing

## • 32150 RIESTER RCS-100 WIRELESS MEDICAL CAMERA SYSTEM - without lens

RCS-100 is a multi-functional, portable and versatile medical diagnostic camera system that allows the user to quickly and efficiently capture and share images and videos to improve diagnosis, monitoring, treatment and patient care. It provides the additional benefit of capturing and sharing the digital photograph or video of the ear canal and tympanic membrane, epidermis and dermis of skin, respectively. RCS-100 can be used with: general lens, otoscope lens, dermatoscope lens and endoscope adapters.

### Features:

- 5" full HD colour TFT-LCD display 1.280 x 720 pixels provides high resolution, scalable images with 2x - 8x magnification and digital zoom capabilities
- easy to use touch screen makes it quick to capture images and videos
- rotary wheel for one-handed operation minimises the risk of cross contamination as well as the capability to adjust focus and light intensity
- simple lens connection makes changing fast and easy
- li-ion battery offers 3.5 hours of operating time
- improved communication in remote areas
- images and videos can support medical notes allowing consistent monitoring of patient
- USB connection to transfer files to PC and for charging
- UVC function allows live picture display on a second screen, so the user can show what they can see and explain in real time
- Wifi connection

Multilingual manual: GB, FR, IT, ES, DE.

### ENDOSCOPE ADAPTER

compatible with C-mount standard



32152

### GENERAL IMAGING LENS



32155

### DERMATOSCOPE LENS

with digital ruler for measurements



32154

### OTOSCOPE LENS

with pneumatic otoscopy port



32156

GIMA code	Riester code	RCS-100 ACCESSORIES
32152	13277	Endoscope adapter 4° *
32153	13278	Endoscope adapter 9° *
32154	13270	Dermatoscope lens
32155	13271	General lens
32156	13272	Otoscope lens
32158	10801-532	Disposable ear speculum Ø 2 mm - box of 10
32159	10801-534	Disposable ear speculum Ø 4 mm - box of 10

## TECHNICAL SPECIFICATIONS

<b>Device</b> <b>Display:</b> TFT-LCD 5.0" touch screen display, 1280x720 pixels with 2x-8x magnification and digital zoom <b>Focus:</b> automatic/manual <b>CMOS pixels:</b> 8 MP <b>Image/video format:</b> picture: JPEG, video: MP4 <b>RAM:</b> 2G LPDDR3 <b>Rom:</b> 16GB <b>Extend Memory:</b> 16G wifi SD card <b>Battery:</b> 3.6V 2600mAh 18650 li-battery <b>Operating time:</b> video 3.5 hours (fully charged battery) <b>Charging time:</b> 3 hours <b>Adaptor:</b> input 100~240V 50~60Hz 0.3A output DC 5V/2A OTG and type-C USB <b>Size - weight:</b> 225x135x45 mm - 292g <b>*Endoscope adapter Compatibility:</b> Compatible with flexible and rigid endoscopes with diameters from 2.7mm to 10mm (two versions planned, one optimized for optics between 2.7-4mm and one for 4-10mm) from a broad range of leading manufacturers based on C-mount standard (e.g. Wolf, Storz, Olympus, Scholly) <b>Quick coupling:</b> Adapter can be attached to RCS-100 and a C-Mount endoscope quickly and it's ready to use <b>Dermatoscope lens</b> <b>Focal length/width:</b> 2.2 <b>Polarization:</b> dermis / epidermis <b>Field of view:</b> 30mm Ø	<b>Object Distance:</b> 0 mm <b>Magnification</b>  <b>Photography source:</b> LED color temperature: <b>Size - weight:</b> 62.1x62.1x36 mm - 108.5 g <b>General lens</b> <b>Focal length/width:</b> 2.0 <b>Field angle:</b> 78° <b>Depth of field scope:</b> 30mm ~ 4m <b>Lighting source:</b> natural light LED <b>Magnification</b> optical: 2x digital: 4x displayed: 2x-8x natural light LED 4000k 62.1x62.1x36 mm - 108.5 g  <b>LED colour temperance:</b> 5500k <b>Size - weight:</b> 60.5x 60.5x19.0 mm - 66.4 g <b>Otoscope lens</b> <b>Focal length/width:</b> 2.9 <b>Field of view:</b> 12mm Ø field of view at 25mm distance from viewing object (with 4mm specula size) 9mm Ø field of view at 15mm distance from viewing object (with 4mm specula size) 8mm Ø field of view at 10mm distance from viewing object (with 4mm specula size) 15mm, at max object distance FOC Ø: 15mm 10mm <b>Max object distance:</b> 15mm <b>Depth of field scope:</b> 10mm <b>Lighting source:</b> natural light LED <b>Magnification:</b> display: 6x <b>LED colour temperance:</b> 4000 K <b>Size - weight:</b> 73.5x40.0x40.0 mm - 96 g
---	--



## MD SCOPE VIDEO OTOSCOPE

### MD SCOPE VIDEO OTOSCOPE

#### Instant View

A clear and sharp image can be acquired and displayed instantly on a built-in screen. Just press a single button and wait for 3 seconds.

#### Real Time Interaction

Medical image can be captured and shared simultaneously to improve interaction between health professionals and patients.

#### Electronic medical record

A medical image is automatically generated to support most of the stand-alone health information system. Simply plug the cable into the video-out socket to retrieve the image.

With video  
otoscope  
MS102



25.5x16x7 cm

32163

#### • 32163 ELITE PACK MS102

- MD Scope with
- 1 camera probe 47 mm Ø 4.2 mm
- mini USB cable set
- 12 disposable specula
- internal Li-ion battery and charging cradle
- carrying case

Detachable camera modules  
are designed for different  
examinations as needed



32165 32167 32168 32169

Ear Ear + nose Oral Larynx



With video  
otoscope  
MS101

32162

#### • 32161 DELUXE PACK MS101 - 2 cameras

#### • 32162 DELUXE PACK MS101 - 4 cameras

- MD Scope with
- 2 camera probes 45 (Ø 5.2 mm)/150 (32161)
- 4 camera probes 45 (Ø 5.2 mm)/75/150/300 mm (32162)
- image dongle (32162 only)
- cable set (32176): USB and RCA cable, adaptor for image dongle
- 24 disposable specula
- 2 AA alkaline batteries
- carrying case

A video port provides  
simultaneous image  
to display  
on TV/monitor  
or to download  
to Mac/PC system




Image dongle



MS101

MS102

32161,  
32162

Size:  
7.5x6.3x21.2 cm

Weight:  
180 g

Colour  
LCD display  
2.4" (32161-2)  
3" (32163)

Image freeze  
function

Video out port

Image resolution  
320x240 pixels  
(32161-2)  
640x480 pixels  
(32163)

CE  
FDA  
US pat. n° 8206290

Size:  
9.5x8.5x21 cm  
Weight:  
250 g

Image zoom  
in/out

Built-in Image  
storage:  
1,000 photos

Brightness  
control

Li-ion  
rechargeable  
battery  
lifespan: 4 hours

32163

GIMA code	ACCESSORIES AND SPARE PARTS
32165	Camera probe 45 x Ø 5.2 mm - adult
32166	Camera probe 47 x Ø 4.2 mm - adult/child
32167	Long camera probe 75 x Ø 5.2 mm
32168	Flexible camera probe 150 x Ø 5.2 mm
32169	Long flexible camera probe 300 x Ø 5.2 mm
32172	Disposable rigid specula 37 x Ø 5 mm for 32165 - 32166 box of 250
32173	Reusable silicone specula 36 x Ø 4.2 mm for 32166 - box of 24
32175	Cradle for video otoscope 32160 - 32162
32176	Cable set (USB and RCA cable, adaptor)
32174	Charging cradle for video otoscope 32163

## DIGITAL Wi-Fi & USB VIDEOTOSCOPE + SOFTWARE



32180

Basic software included  
for acquisition of photos, videos,  
google/apple applications

#### • 32180 Wi-Fi & USB VIDEOTOSCOPE with software

Innovative, handheld colour digital Otoloscope with Wi-Fi wireless transmission. Small, easy to operate, light and portable. It can be used with all the most popular smartphones, tablets and even with PC. Designed in Italy, made in China.

#### • 32188 DISPOSABLE EAR SPECULUM Ø 3.5 mm - black - box of 100

#### • 32189 DISPOSABLE EAR SPECULUM Ø 4.3 mm - black - box of 100

#### • 32192 DISPOSABLE VET SPECULUM Ø 5/6/7 mm and Ø 7/8 mm slotted for Hartmann Tweezers - kit of 5



32192

#### TECHNICAL SPECIFICATIONS

Operation system:	Windows (7, 10), Mac (OS X 10.7 and following), iOS, Android
Photo and video resolution:	1.3 MPixels - 1,280x1,024 (MJPG), 640x480 (MJPG), 320x240
Frame rate:	15 fps 1280x1024, 30 fps 640x480 320x240
Wi-Fi wireless transmission distance:	up to 5 m
Power consumption:	max 2.5 W
Li-ion battery:	continuous working time - approx. 2 hours, full charging time - approx. 2 hours
Power source:	DC 5.0 V / 1A
Size - weight:	Ø 36x142 mm - 88 g
Camera	
Camera sensor:	CMOS 1/4"
Optical features:	Exposure: Auto, Gamma: Auto, White balance: Auto, Black reference: Auto
Otoscope	
Magnification:	25 X - 50 X
Focus range:	8-160 mm
Object distance:	1-160 mm
Light source:	4 adjustable white LED
Lens:	high definition microscopy lens
Software interface	Mic-Fi Apps for Android and iOS system and Mic-Fi softwares for PC and MAC

#### STANDARD ACCESSORIES

9 disposable speculum (3x3.5, 3x4.3, 3x5.0 mm)	Plastic stand
USB AC adapter and cable	Manual (GB, FR, IT, ES, DE)
CD basic software Win (GB, FR, IT, ES, DE, UA, JP) Mac (GB)	

## HEINE OMEGA® 600 HIGH-END LED<sup>HQ</sup> INDIRECT OPHTHALMOSCOPE

### • 31755 HEINE OMEGA 600 LED INDIRECT OPHTHALMOSCOPE - C-008.33.610

Omega 600 is a binocular lightweight high-end indirect ophthalmoscope which provides best optics, sharpest image and reliable colours. Possibility to explore the whole retina, including the far periphery, and to have better diagnostic due to unique visionBOOST function. VisionBOOST allows to safely increase illumination of the device above the regular light intensity, providing up to 20% more details of the observed area, especially in patients with ocular media opacities like cataracts. Features:

- sharpest fundus image due to superior glass optics
- brightest fundus image with true colour rendering thanks to unique LED<sup>HQ</sup>
- best 3D imaging due to unique Stereoscopic Adjustment Technology in dilated and undilated pupils, even with premature and newborns
- ergonomic positioning of controls and levers
- adaptable for right and left users
- flip-up function for more convenient patient interactions
- robust design made of high quality materials
- compact lithium battery
- electronics integrated in the headband
- best wearing comfort
- latex free.

MADE IN GERMANY

Supplied with battery, +2D eyepiece, E4-USBC power supply with cable, eyepiece 0D and multilingual manual: GB, FR, IT, ES, PT, DE, NL, SE, DK, NO, FI.

**Durable faux leather padding**  
Comfortable and easy to disinfect

**Practical, cable-free headband**  
maintenance-free and easy to disinfect thanks to smooth surface.

**Ultralight lithium polymer battery**  
operating time of up to 8 hours depending on illumination intensity.

**Intuitive locking of the optics unit** simply adjust height, distance and angle

**Up to 20 % better view in media opacities with visionboost.**  
From 3 to 100 %, or even up to 245 % for cataract examinations

**Aperture selection lever**  
HEINE diffusor, small, medium and large spot



**Yellow, blue or red-free filter**  
to adjust to diagnostic needs

**Best possible 3D imaging for any pupil size and peripheral views** thanks to the Stereoscopic Adjustment Technology

**High durability due to the sealed optics unit**  
**Better view due to non-reflective front glass** optimized for our unique, maintenance-free Led<sup>HQ</sup>

#### TECHNICAL SPECIFICATIONS

Material:	plastic, metal, glass, synthetic leather
Optical system:	aspherical illumination distance
Illuminance:	560 lux at 400 mm distance 1380 lux at 400 mm distance with Boost mode
Colour temperature:	3000 K
Colour rendering index (CRI):	min. 90
LED average life:	> 60,000 hours
Working distance:	400 mm
Illuminated field:	large spot: 400 mm distance Ø 62.5 ± 2.5 mm medium spot: 400 mm distance Ø 33 ± 2 mm small spot: 400 mm distance Ø 16.5 ± 1.5 mm

Field of view:	16D lens: 43°, 20D lens: 53°, 30D lens: 63°
Brightness control:	continuous between 3 and 100% (boost: 100 to 245%)
Vertical adjustment:	between -4° and +7°
Battery:	internal Lithium polymer battery
Average working time:	up to 8 hours
Charging time:	1.5 hours
Input:	USB 2.0 Type C, 5 V, 1.2 A
Power consumption:	6 W
Size - weight:	320x300x200 mm - 475 g
Packaging size:	255x190x410 mm
Norms:	93/42/EEC, EU 2017/745 - Class I

## WELCH ALLYN MACROVIEW™ OTOSCOPE

- 32100 MACROVIEW™ HEAD - 23810
- 32101 LITHIUM ION HANDLE WITH AC CHARGING MODULE 3.5 V - 71902

This otoscope features advanced optics that increase magnification while giving a nearly full view of the tympanic membrane - virtually eliminating the need for panning. With its easy-to-focus eyepiece, MacroView allows for enhanced visualization to help see past wax, locate fluid behind the eardrum, and even perform exams without your glasses.

- twice the field of view
- 30% greater magnification than a traditional otoscope
- better clarity and definition of landmarks
- ability to adjust focus for variable ear canal lengths or farsighted eyes

- 32106 KLEENSPEC® ADULT DISPOSABLE EAR SPECULA 4.25 mm - box of 850 pcs - 52434-UB
- 32105 KLEENSPEC® PEDIATRIC DISPOSABLE EAR SPECULA 2.75 mm - box of 850 pcs - 52432-UB
- 32135 SPARE HALOGEN BULB - 3.5 V - 06500 U

**Adjustable focus wheel** allows to accommodate for variable ear canal lengths and farsighted eyes a full view of the tympanic membrane

**Default focus position**  
(the dot and the line)

**Advanced optics**  
give you 2X the field of view and 30% greater magnification than a conventional otoscope



Welch Allyn®

**Tip grip** ensures ear specula is fastened securely and easily disposed

**Insufflation port** for pneumatic otoscopy

32100

**Lithium-ion handle with AC charger module** compatible with all Welch Allyn instrument heads 3.5 V

32101

## DIGITAL WI-FI & USB IRISCOPE WITH SOFTWARE AND CHINREST

- 32179 DIGITAL WI-FI IRISCOPE with software and stand
- Innovative handheld colour digital iriscopes with Wi-Fi wireless transmission. Small, easy to operate, light and portable. 2 adjustable white LEDs and 2 adjustable yellow LEDs. It can be used with all the most popular smartphones, tablet and even PC.

**Iridology professional software** (USB mode only) compatible with Windows 7, 8, 10, 11, available in GB, IT. Not medical device.

32179



Resolution: 5 Mpixel\*


\*only by USB mode

#### STANDARD ACCESSORIES

USB AC adapter	USB cable
Ring	Chinrest
Quick manual: GB, IT	
Software for Windows 7, 8, 10, 11 (GB, IT)	

#### TECHNICAL SPECIFICATIONS

Magnification:	30x
Camera:	CMOS 1/2.7"
Light source:	2 white leds and 2 yellow leds
LED system:	3.2 V/20 ma
Resolution:	5 Mpixel in USB mode
Lens:	high definition microscopy lens
Frame rate:	15 frames/second (1280x1024), 30 frames/second (640x480) 320x240
Power supply:	Li-ion battery, DC 5.0V/1A
Working time:	continuous working, 2 hours fully charged
Power consumption:	2.5 W
Size - weight:	Ø 36x142 mm - 88 g

















## HEINE ORIGINAL BULBS

HEINE BULBS	HEINE ref.	GIMA code	Compatible with following HEINE products
 Xenon 2.5 V	035	31769	Transilluminator Finoff alpha <sup>®</sup> F.O. and F.O. SP Laryngoscopes - Sanalon handle Glauco-test
 Xenon 2.5 V	037	31771	K100 and Beta <sup>®</sup> 100, Beta <sup>®</sup> 100 vet otoscopes Laryngeal mirrors F.O. mini 2000 otoscope Alpha <sup>®</sup> and Alpha F.O. otoscopes Mini/mini 3000/Alpha/Beta tongue holders
 Xenon 3.5 V	049	31787	F.O. Alpha <sup>®</sup> , Beta 100, K 100, Beta 100 vet otoscopes; Alpha <sup>®</sup> , Beta <sup>®</sup> tongue holders
 Miroflex ophthalmoscope	038	31773	Miroflex ophthalmoscope HFR2 spot retinoscope Delta <sup>®</sup> 10 dermatoscope
 Fibrilux mini otoscope	041	31774	Fibrilux mini otoscope Mini 2000 combilamp Mini 1000, 2000 cliplamp
 Alpha ophthalmoscope	042	31780	Alpha <sup>®</sup> ophthalmoscope Mini 2000 ophthalmoscope Alpha <sup>®</sup> Focalux, Mini 2000 Focalux Mini Miroflex ophthalmoscope
 Minilux otoscope	056	31770	Minilux otoscope Mini 2000 otoscope
 Beta <sup>®</sup> 200, 200 M2, 200S ophthalmoscopes - XHL 2.5 V	069	31781	Beta <sup>®</sup> 200, 200 M2, 200S ophthalmoscopes - XHL 2.5 V
 Beta <sup>®</sup> 200, 200 VET, 400; K 180 otoscopes Lambda 100 retinometer Delta <sup>®</sup> 10 plus dermatoscope	077	31772	Beta <sup>®</sup> 200, 200 VET, 400; K 180 otoscopes Lambda 100 retinometer Delta <sup>®</sup> 10 plus dermatoscope
 Beta 200, 200 M2, 200S ophthalmoscopes - XHL 3.5 V	070	31783	Beta 200, 200 M2, 200S ophthalmoscopes - XHL 3.5 V
 Beta 200, 200 Vet, K180 otoscopes lambda 100 retinometer otoscopes - XHL 3.5 V	078	31784	Beta 200, 200 Vet, K180 otoscopes lambda 100 retinometer otoscopes - XHL 3.5 V
 K180 <sup>®</sup> ophthalmoscope - 2.5 V	084	31782	K180 <sup>®</sup> ophthalmoscope - 2.5 V
 Mini 3000 F.O. otoscope	105	31776	Mini 3000 F.O. otoscope
 Mini 3000 ophthalmoscope	106	31777	Mini 3000 ophthalmoscope
 Mini 3000 combilamp and cliplamp - XHL 2.5 V	107	31778	Mini 3000 combilamp and cliplamp - XHL 2.5 V
 Mini 3000 dermatoscope	109	31779	Mini 3000 dermatoscope
 Mini 3000 otoscope	110	31775	Mini 3000 otoscope
 Alpha <sup>®</sup> , Beta 200 retinoscopes	089	31786	Alpha <sup>®</sup> , Beta 200 retinoscopes

## WELCH ALLYN BULBS

WELCH ALLYN BULBS	W. A. ref.	GIMA code	Compatible with following WELCH ALLYN products
 Anoscopes: 38800, 380, 385, 395 Illuminators: 41000, 26030 Old products: 235, 77900, 26000, 20100, 21600, 42700, 40510	00200-U	32120	Anoscopes: 38800, 380, 385, 395 Illuminators: 41000, 26030 Old products: 235, 77900, 26000, 20100, 21600, 42700, 40510
 Ophthalmoscope: 11710, strabismoscope: 12400, episcopes: 47300 Old ophthalmoscope: 11600, 11605, 11610 Retinoscope: 18000	03000-U	32123	Ophthalmoscope: 11710, strabismoscope: 12400, episcopes: 47300 Old ophthalmoscope: 11600, 11605, 11610 Retinoscope: 18000
 Otoscopes: 25020, 21700, 20200 Handle: 73500, holder: 28100 Illuminators: 27000, 27050, 26530, 41100, 43300 Old otoscopes: 25000, 25200, 20000	03100-U	32124	Otoscopes: 25020, 21700, 20200 Handle: 73500, holder: 28100 Illuminators: 27000, 27050, 26530, 41100, 43300 Old otoscopes: 25000, 25200, 20000
 Ophthalmoscope: 11511-11500	03300-U	32125	Ophthalmoscope: 11511-11500
 Otoscopes: 24011-24020-24000-24031-21110/1 Handle: 73550, Illuminators: 27200-27250-41110	03400-U	32126	Otoscopes: 24011-24020-24000-24031-21110/1 Handle: 73550, Illuminators: 27200-27250-41110
 Pan optic: 11810-11820-11800	03800-U	32127	Pan optic: 11810-11820-11800
 Exam light: 48400-48410	04100-U	32128	Exam light: 48400-48410
 Exam light: 48600, 48610-48625-48635, 48700	04200-U	32129	Exam light: 48600, 48610-48625-48635, 48700
 Ophthalmoscopes: 11400-11411-11470-11475	04400-U	32130	Ophthalmoscopes: 11400-11411-11470-11475
 Laryngo: 680, 690, 692 (size 1-2) Old laryngo: 634, 664, 674, 684, 694 (check size)	04700-U	32131	Laryngo: 680, 690, 692 (size 1-2) Old laryngo: 634, 664, 674, 684, 694 (check size)
 Laryngo: 680 (size 2-4), 690, 692 (size 3-4) Old laryngo: 634, 640, 664, 674, 684, 694 (check size)	04800-U	32132	Laryngo: 680 (size 2-4), 690, 692 (size 3-4) Old laryngo: 634, 640, 664, 674, 684, 694 (check size)
 Ophthalmoscope: 11720, 11730, 11735, 11620, 11630	04900-U	32133	Ophthalmoscope: 11720, 11730, 11735, 11620, 11630
 Laryngo handles: 60813, 60814, 60713, 60815, 60803, 60804	06000-U	32134	Laryngo handles: 60813, 60814, 60713, 60815, 60803, 60804
 Macroview otoscope: 23810, 23820	06500-U	32135	Macroview otoscope: 23810, 23820
 Handle: 73211, 73210, 78000, 73200	07800-U	32136	Handle: 73211, 73210, 78000, 73200

## RIESTER ORIGINAL BULBS

RIESTER BULBS	RIESTER ref.	GIMA code	Bulb	Compatible with following RIESTER products
 Vacuum 2.7 V	10421	31850	Vacuum 2.7 V	Otoscope uni <sup>®</sup> /speculight
 Vacuum 2.5 V	10424	31851	Vacuum 2.5 V	May-ophthalmoscope uni <sup>®</sup>
 XL 3.5 V xenon	10487	31825	XL 3.5 V xenon	Otoscope ri-scope <sup>®</sup> L1
 Pen-scope <sup>®</sup> and e-scope <sup>®</sup> otoscope	10488	31852	Vacuum 2.7 V	Pen-scope <sup>®</sup> and e-scope <sup>®</sup> otoscope
 Otoscope pen-scope <sup>®</sup> /ri-scope <sup>®</sup> L1 and e-scope <sup>®</sup>	10489	31560	XL 2.5 V	Otoscope pen-scope <sup>®</sup> /ri-scope <sup>®</sup> L1 and e-scope <sup>®</sup>
 Otoscope uni <sup>®</sup>	10590	31853	XL 2.5 V	Otoscope uni <sup>®</sup>
 Otoscope ri-mini <sup>®</sup> , ri-scope <sup>®</sup> L2/L3 and e-scope <sup>®</sup>	10600	31854	XL 2.5 V	Otoscope ri-mini <sup>®</sup> , ri-scope <sup>®</sup> L2/L3 and e-scope <sup>®</sup>
 Ophthalmoscope ri-mini/ ri-scope <sup>®</sup> L1, L2, L3, e-scope <sup>®</sup> , ri-derma <sup>®</sup>	10605	31562	XL 2.5 V	Ophthalmoscope ri-mini/ ri-scope <sup>®</sup> L1, L2, L3, e-scope <sup>®</sup> , ri-derma <sup>®</sup>
 Ri-scope <sup>®</sup> otoscope L2, L3	10607	31855	XL 3.5 V	Ri-scope <sup>®</sup> otoscope L2, L3
 Ri-scope <sup>®</sup> ophthalmoscope L1, L2, L3	10608	31826	XL 3.5 V	Ri-scope <sup>®</sup> ophthalmoscope L1, L2, L3
 E-scope F.O. otoscope	14041	31561	LED 3.7 V	E-scope F.O. otoscope
 E-scope ophthalmoscopes	14051	31563	LED 3.7 V	E-scope ophthalmoscopes



## COMPATIBLE GERMAN BULBS

GIMA BULBS	GIMA code	Compatible with the following products
<b>LARYNGOSCOPE BULBS - MADE IN GERMANY</b>		
 Conventional laryngoscope SMALL bulb 2.7 V	34324	Gima, Riester, And, Kawe, Timesco Truphatek and most of conventional laryngoscopes in the market (generally used for blades N° 00, 0, 1)
 Conventional laryngoscope LARGE bulb 2.7 V	34325	Gima, Riester, And, Kawe, Truphatek, Timesco and most of conventional laryngoscopes in the market (generally used for blades N° 2, 3, 4)
 Xenon halogen bulb for F.O. Laryngoscope and otoscope	34485	Gima, And, Kawe and most of F.O. laryngoscopes in the market. Compatible for products that use Heine Bulb # 035
<b>OTOSCOPE-OPHTHALMOSCOPE BULBS - MADE IN FRANCE-GERMANY</b>		
 Xenon halogen otoscope bulb	31795	Heine mini 3000 otoscopes
 Xenon halogen F.O. otoscope bulb	31796	Heine mini 3000 F.O. otoscopes
 Otoscope bulb 2.5 V	31449	Parker otoscopes and some otoscopes of Riester, Timesco and Kawe
 Ophthalmoscope bulb 2.5 V	31446	Parker ophthalmoscope Parker diagnostic sets
 Xenon halogen bulb for otoscope 2.5 V	31478	Gimalux otoscopes, Kawe and Riester mini otoscopes Compatible for products that use Heine bulb #037
 Halogen bulb for ophthalmoscope and dermatoscope 2.5 V	31479	Parker halogen ophthalmoscope
 Xenon halogen ophthalmoscope bulbs 3.5 V	31428	Gima Xenon - halogen diagnostic sets - ophthalmoscope
<b>OTO-OPHTHALMO-DERMATOSCOPE BULBS - OTHER COUNTRIES</b>		
 Halogen Dermatoscope bulb 2.5 V	31188	Gima dermatoscope Compatible for products that use Heine Bulb #038
 Xenon halogen otoscope bulbs 3.5 V	31427	Gima Xenon - halogen diagnostic sets - otoscope

# HEINE MINI 3000® XHL AND LED<sup>HQ</sup> OTO AND OPHTHALMOSCOPE



## MINI 3000 F.O. XENON OTOSCOPES

Powerful pocket otoscope in a unique compact design.

- **Xenon halogen** bulbs for bright illumination and accurate colour rendering.
- **20,000 on/off switch cycles** guaranteed
- **distal Fiber Optic (F.O.) Illumination:** Reflex-free illumination of tympanum and ear cana.
- **viewing window with 3X magnification and optimized casing surface** for razor-sharp images and minimal reflection. **Swivelling viewing window built into instrument.**
- **pneumatic testing** of the tympanum mobility by using the insufflation port and an optional connector
- **attachment clip with integrated on/off switch**
- **replaceable batteries:** size AA or optional rechargeable battery (31693) with mini NT table charger (31692).
- **2-piece handle and head.** Easy to maintain, flexible. Compatible with other handles.

## MINI 3000 F.O. LED<sup>HQ</sup> OTOSCOPES

All features of F.O. Xenon otoscopes with the addition of:

- **maintenance-free**, no need to ever change the LED
- LED thermal management for a **consistent light output throughout the whole working life**
- High-performance-LED: bright and absolutely homogeneous illumination with excellent colour rendering - colour temperature 4,000°K, colour rendering index >95, and >90 rendering index of the colour red
- **twice as bright** as Xenon Halogen instruments
- **exclusive Battery Performance Indicator**
- **exclusive fade-out function** reduces illumination intensity with battery level to let you know when to replace
- **operation time up to 10 hours**

### MINI 3000 OTOSCOPES 2.5 V

	BLACK		BLUE	
	GIMA code	HEINE code	GIMA code	HEINE code
Standard	31680	D-001.70.210	31681	D-001.70.210
F.O. Xenon	31684	D-001.70.110	31685	D-001.70.110
F.O. LED <sup>HQ</sup>	31676	D-008.70.110	31677	D-008.70.110

### MINI 3000 OTOSCOPE 2.5 V - RECHARGEABLE HANDLE\*\*

F.O. Xenon	31682	D-001.70.301	-	-
F.O. LED <sup>HQ</sup>	31683	D-008.70.301	-	-

Above otoscopes are supplied in a box with 5 disposable speculum Ø 4 mm and 5 Ø 2.5 mm

### MINI 3000 OTOSCOPE 2.5 V - hard case

F.O. LED <sup>HQ</sup>	31678	D-885.20.021	-	-
------------------------	-------	--------------	---	---

Supplied in hard case with 5 disposable speculum Ø 4 mm, 5 Ø 2.5 and 4 reusable speculum (Ø 2.4, 3, 4, 5 mm)



GIMA code	HEINE DISPOSABLE MINI EAR SPECULUM*	Minimum order
31501	HEINE dispenser for mini speculum - empty	-
31502	HEINE disposable Allspec® speculum Ø 2.5 mm - grey	dispenser of 250
31503	HEINE disposable Allspec® speculum Ø 4 mm - grey	dispenser of 250
31515	HEINE disposable Allspec® speculum Ø 2.5 mm - grey	box of 1000
31516	HEINE disposable Allspec® speculum Ø 4 mm - grey	box of 1000

\*Compatible with Heine Mini 2000/3000, K180, Beta 200, Beta 400

## MINI 3000 XENON OPHTHALMOSCOPES

Modern pocket ophthalmoscope with fixation star aperture.

- Excellent optics and best colour rendering in minimum size.
- **XHL Xenon Halogen Technology.** Concentrated bright light for perfect illumination, a brilliant image and accurate colour rendering
- **the HEINE optics produce crisp, clear images of the whole area under examination** and minimize the reflections
- **5 different apertures.** A full-function instrument incl. fixation star
- **grey filter** for light sensitive patients
- **range of lenses: 18 lenses from -20 D to +20 D**
- **easy workflow**, because ophthalmoscopy is possible without dilation of the pupils
- **attachment clip with integrated on/off switch**
- **replaceable batteries.** Size AA or optional rechargeable battery (31693) with mini NT table charger (31692).

## MINI 3000 LED<sup>HQ</sup> OPHTHALMOSCOPES

All features of Xenon ophthalmoscope with the addition of:

- **maintenance-free**, no need to ever replace the LED.
- LED thermal management for a **consistent light output throughout the whole working life.**
- high-performance-LED: bright and absolutely homogeneous illumination with an excellent colour rendering - colour temperature 4,000°K, colour rendering index >95, and >90 rendering index of the colour red.
- **exclusive battery performance indicator**
- **exclusive fade-out function** reduces illumination intensity with battery level to let you know when to replace.
- **operation time up to 10 hours.**

### MINI 3000 OPHTHALMOSCOPES 2.5 V

	BLACK		BLUE	
	GIMA code	HEINE code	GIMA code	HEINE code
Xenon	31686	D-001.71.120	31687	D 001.71.120
LED <sup>HQ</sup>	31688	D-008.71.120	-	-

### MINI 3000 OPHTHALMOSCOPES 2.5 V - RECHARGEABLE HANDLE\*\*

F.O. Xenon	31694	D-001.71.200	-	-
F.O. LED <sup>HQ</sup>	31695	D-008.71.200	-	-

### MINI 3000 OTO-OPHTHALMO SET - hard case

Xenon Set	31689	D-873.11.021	-	-
LED <sup>HQ</sup> Set	31696	D-886.11.021	-	-

Both set (Xenon or LED) include one F.O. otoscope head, one ophthalmoscope head, 2 handles, 4 reusable specula (Ø 2.4, 3, 4, 5 mm), 5 disposable specula Ø 4 mm and 5 Ø 2.5 mm in hard case.

NiMH rechargeable battery with bottom insert for Mini 3000 handles.



GIMA code	HEINE code	CHARGER AND ACCESSORIES
31691	D-000.80.101	MINI 3000 connector for pneumatic test
31692	X-001.99.484	HEINE MINI 3000 NT charger
31693	X-001.99.487 + X-001.99.488	BATTERY + BASE

\*\*Need Heine Mini 3000 NT charger (31692)



# SIGMA F.O. XENON OR LED OTO AND OPHTHALMO SETS



31527,  
31530,  
31529

31513,  
31524,  
31525,  
31526

FIBRE OPTIC  
OR F.O. LED

High quality pocket diagnostic instruments designed for professional use in ENT and ophthalmoscopy. Light weight and manufactured from impact resistant re-enforced plastic. Supplied in deluxe rigid plastic case or pouch with multilingual manual (GB, FR, IT, ES, PT, DE, GR, PL, RO, Arabic). Sigma otoscopes are compatible with Gima mini speculum (31485-8, 31491-2, 31495-9).

## Sigma otoscopes

High quality materials and top-notch workmanship ensure excellent reliability in every examination.

- swivel type window with 3X magnification lens for sharp images and minimal reflection
- distal fibre optic illumination with super bright Xenon/Halogen or LED light
- insufflation port for pneumatic testing of tympanic mobility (optional connector port 31532 and insufflation bulb 31483)
- standard or rechargeable handle. Optional metal endcap (31588) can convert any standard Sigma handle into rechargeable version.


## Sigma ophthalmoscopes

High quality optics in mini format makes this instrument ideal for house calls and rounds.

- super bright Xenon-Halogen or LED light
- 5 different apertures for almost all ophthalmic examinations
- range of lenses from -20 D to +20 D

+	1	2	3	4	6	8	10	15	20
-	1	2	3	4	6	8	10	15	20

Colour coded 18 lenses  
for excellent resolution



**Large spot:** for normal funduscopy

**Small spot:** for reduced reflection with small pupils

**Semi circle:** for reduced reflection with small pupils

**Fixation star:** for determination of central or eccentric fixation, suitable for children

**Red-free filter:** for contrast-enhancement when assessing fine vascular disorders

Rechargeable battery 31587  
Metal endcap 31588

## SIGMA F.O. OTOSCOPES AND OPHTHALMOSCOPES 2.5V - standard handle

OTOSCOPES*			OPHTHALMOSCOPES		Type	Packing
Black	Blue	Purple	Black			
31524	31523	31511	31530		Xenon-Halogen	Pouch
31525	-	-	31527		Xenon-Halogen	Case
31513	-	-	-		LED	Pouch
31526	31518	-	31529		LED	Case

## SIGMA F.O. LED OTOSCOPE AND OPHTHALMOSCOPE 2.5V - rechargeable\*\* handle with battery

31580	Otoscope with rechargeable handle and battery - black	LED	Pouch
31582	Ophthalmoscope with rechargeable handle and battery - black	LED	Pouch

\*Otoscopes are supplied with 14 disposable specula (7 with Ø 2.5 mm, 7 with Ø 4 mm)

\*\*Rechargeable handle can be used with "AA" standard batteries or rechargeable battery code 31587 (needs charging station code 31586)  
Full battery charge in 2.5 hours. Can be connected to PC or laptop via standard USB (Type C) cable (not included)



31511

GIMA code	SIGMA F.O. OTO-OPHTHALMOSCOPE SETS*** 2.5V - black	Type	Packing
31533	Oto-ophthalmoscope set with 1 handle	Xenon-Halogen	Case
31528	Oto-ophthalmoscope set with 2 handles	Xenon-Halogen	Case
31534	Oto-ophthalmoscope set with 2 handles	LED	Case
31584	Oto-ophthalmoscope set with 2 rechargeable handles and batteries	LED	Case

\*\*\*Oto-ophthalmo sets are supplied with oto and ophthalmo head, 1 handle (31533) or 2 handles (31528, 31534, 31584), 14 disposable specula (7 with Ø 2.5 mm, 7 with Ø 4 mm), 2 rechargeable batteries (31584)

GIMA code	SPARES AND ACCESSORIES	GIMA code	CHARGING SYSTEM
34485	Otoscope bulb - Xenon-Halogen 2.5 V	31586	Charging station
31531	Ophthalmoscope bulb - Xenon-Halogen 2.5 V	31587	Rechargeable battery
31532	Pneumatic connector port	31588	Metal endcap
31483	Insufflation bulb		



31586  
Charging station



31518



31527,  
31529



31533



31528,  
31534, 31584

# SIGMA-C LED OTOSCOPES

- 31591 SIGMA-C LED OTOSCOPE - black - pouch
- 31592 SIGMA-C LED OTOSCOPE - blue - pouch
- 31593 SIGMA-C LED OTOSCOPE - purple - pouch
- made of light weight impact resistant re-enforced plastic and highly corrosion resistant stainless steel material for exterior finish
- swivel type window with 3X magnification lens for sharp image and minimal reflection
- optional insufflation port for pneumatic testing of tympanic mobility (needs codes 31532 and 31483)
- compatible with Gima ear specula 31485-8, 31491-2, 31495-9
- 50.000 hours lifetime
- extended battery life of 50 hours
- colour temperature 4,300 K, CRI>95 ensures real colour.

Multilingual manual: GB, FR, IT, ES, PT, DE, GR, RO, PL, Arabic.



31591


31592

31593

31591

## E-SCOPE®: RIESTER OTO-OPHTHALMOSCOPES

- 31548 E-SCOPE® OTOSCOPE - HALOGEN 2.7V - black in pouch
  - 31549 E-SCOPE® OTOSCOPE - XENON 2.5V - white in pouch
  - 31550 E-SCOPE® OTOSCOPE - XENON 2.5V - black in pouch
  - 31552 E-SCOPE® F.O. OTOSCOPE - LED 3.7V - white in rigid case
  - 31553 E-SCOPE® F.O. OTOSCOPE - LED 3.7V - black in rigid case
- Halogen, direct Xenon or F.O. LED illumination otoscopes. Sealing precision optics pivoting to both sides with triple magnification for superior view



Suitable for performance of pneumatic tests (supplied without connector and insufflator)

- 31556 E-SCOPE® OPHTHALMOSCOPE - XENON 2.5 V - black - in rigid case
- 31557 E-SCOPE® OPHTHALMOSCOPE - F.O. - LED 3.7 V - white - in rigid case
- 31559 E-SCOPE® OPHTHALMOSCOPE - F.O. - LED 3.7 V - black - in rigid case

E-scope ophthalmoscopes are available with Xenon or LED illumination.

- with 2.5V Xenon or innovative 3.7V LED illumination for higher-contrast and more efficient diagnosis
- dioptre disc with 18 corrective lenses ( $\pm 1, 2, 3, 4, 6, 8, 10, 15, 20$ )
- easy-to-use aperture wheel with six apertures (fixation star, large circle, small circle, red free filter, blue filter, semi circle)
- high performance optics with aspherical condenser
- spectacle protection
- parallel optical path

MADE IN GERMANY



- 31558 E-SCOPE® DIAGNOSTIC KIT - white
  - 31564 E-SCOPE® DIAGNOSTIC KIT - black
- Oto-ophthalmoscope sets, LED 3.7V, in rigid case.
- 31560 E-SCOPE® OTOSCOPE - XENON 2.5 V BULB
  - 31561 E-SCOPE® OTOSCOPE - LED 3.7 V BULB
  - 31562 E-SCOPE® OPHTHALMOSCOPE - XENON 2.5 V BULB
  - 31563 E-SCOPE® OPHTHALMOSCOPE - LED 3.7 V BULB
  - 31817 RIESTER® EAR SPECULUM Ø 2.5 mm - autoclav. - box of 10
  - 31819 RIESTER® EAR SPECULUM Ø 4 mm - autoclav. - box of 10
  - 31566 E-SCOPE® EAR SPECULUM Ø 2.5 mm - disposable - box of 100
  - 31567 E-SCOPE® EAR SPECULUM Ø 4 mm - disposable - box of 100

## LUXAMED AURIS LED OTOSCOPES



- 31570 LUXAMED AURIS LED 2.5V OTOSCOPE - black
  - 31571 LUXAMED AURIS LED 2.5V OTOSCOPE - blue
  - 31572 LUXAMED AURIS LED 3.7V USB OTOSCOPE - black
- Innovative otoscopes that combine best handcraft production with selected materials with the most modern technology. Two-components handle (aluminium/fibre-glass reinforced) with electronic ON/OFF switch and dimmer.

Features:

- LED-Ring illumination with 6 LEDs (concentric), no fibre optic. The functionality is not affected (patent DE202013104278U1) if a single LED fails.

**LUXAMED®**

- automatic switchoff after 3 minutes
- approx. 100,000 hours life expectancy of LEDs
- approx. 10,000 Lux intensity of illumination
- approx. 4,000 K colour temperature
- pivoting 3-fold magnifying glass with locking function
- insufflation port for pneumatic test.

Supplied with 2xAAA alkaline batteries (31570/1) or lithium-ion rechargeable battery 3.7V (31572) 20 disposable ear funnels (10x2.5 mm and 10x4.0 mm) and manual (GB, IT, DE). See page 266 for compatible ear speculum.

MADE IN GERMANY



Recharger with USB plug - 3 adapters (EU, UK, US)



## RIESTER ELITEVUE



- **31860 RIESTER ELITEVUE LED OTOSCOPE 3.5 V - 2200-203**
  - **31863 RIESTER ELITEVUE LED OTO-OPHTHALMO L2 SET 3.5 V with C-handle for rechargeable Li-Ion battery - 2210-203**
- EliteVue offers twice the field of view and 66% greater magnification (at 15 mm distance) compared to standard otoscopes. Improved view of auditory canal and tympanic membrane guarantees more efficient diagnosis. Suitable for throat illumination. 4,000 K LED illumination (CRI: 92). 5X magnification.
- **31840 RI-CHARGER L 230 V - 10705**
  - **31841 RI-ACCU L 3.5 V Li-Ion BATTERY for "C" size - 10691**

## HEINE K180 OTO-OPHTHALMO



- **31740 HEINE K180 - F.O. OTO-OPHTHALMO SET - 2.5 V - A-279.10.118**
- Otoscope and ophthalmoscope K180 with BETA battery 2.5 V handle and a set of single use specula. Supplied in hard case.
- **31782 HEINE 084 OPHTHALMO BULB 2.5 V - spare - X-001.88.084**
  - **31772 HEINE 077 OTOSCOPE BULB - spare - X-001.88.077**
  - **31741 HEINE K180 OPHTHALMOSCOPE - 2.5 V C-182.10.118**
- 28 lenses from -35D to +40D supplied in pouch



## HEINE BETA 200 F.O. OTOSCOPES



- **31725 HEINE BETA 200 F.O. OTOSCOPE - 2.5V - B-141.10.118**
- F.O. Otoscope with BETA battery 2.5V handle with rheostat, a set of single use specula, a set of reusable specula and a spare bulb. Supplied in hard case. Solid all metal construction, a quality instrument with fibre optic illumination.
- **31772 HEINE 077 OTOSCOPE BULB - spare - X-001.88.077**
  - **31784 HEINE 078 OTOSCOPE BULB - X-002.88.078**

MADE IN GERMANY

- **31728 HEINE BETA 400 LED F.O. OTOSCOPE - B-143.24.420**
- Exclusive 4.2X magnification. LED in HQ with continuous brightness control. All metal housing and scratch resistant glass lenses. Colour temperature: 3,500 K. Colour rendering index (CRI) >97. Exceptional depth of field, provides sharp spatial image. LED otoscope with rechargeable handle supplied with 4 reusable speculum, 5 of both All Spec disposable speculum 2.5 and 4 mm Ø in a case with NT4 table charger (34374).

## HEINE BETA 200 AND 200S OPHTHALMOSCOPES



- **31730 HEINE BETA 200 HALOGEN OPHTHALMOSCOPE - 2.5 V - C-144.10.118**
- The unique aspherical optic system eliminates corneal and iris reflexes. The illuminated area of the retina remains fully visible even in case of small pupil (bright light). BETA 200 has 6 diaphragms with separately "green filter". It is recommended for small or expanded pupils; suitable for slit or fluorescent ophthalmoscopy as well as for fixation test. Range -35D to +40D. Supplied in hard case with replacement bulb.
- **31731 HEINE BETA 200 F.O. OPHTHALMOSCOPE - 3.5 V Li-ion - C-144.27.388**
- Same as 31730 but with USB rechargeable handle for mains socket and Li-ion batteries.
- **31783 HEINE 070 OPHTHALMOSCOPE BULB 3,5 V - X-002.88.070**



- **31735 HEINE BETA 200S OPHTHALMOSCOPE - 2.5 V - C-261.10.118**
- **31781 HEINE 069 OPHTHALMO BULB - 2.5 V - spare - X-001.88.069**
- **31737 HEINE BETA 200S LED OPHTHALMO - 3.5 V with USB rechargeable handle - C-261.28.388**

**Superior aspherical optics and 74 single-diopter steps**

- **optical system:** corneal and iris reflexes are eliminated. A full view is guaranteed even with small pupils.

- **XHL (Xenon Halogen Technology) or LED:** bright, white light.



- **recessed, multi-coated viewing window:** avoids stray light.

- **optics mounted on precision metal chassis.**
- **ergonomic shape:** instrument fits the orbita comfortably in any position.

- **7 apertures with separate red-free filter:**
- **lens range:** perfect focus even with high refractive errors.

- **exact colour rendering both with XHL and LED illumination**

MADE IN GERMANY



74 single diopters steps  
+ in 1 D steps: +1 through +38 D  
- in 1 D steps: -1 through -36 D



## VISIO 5 PLUS WALL DIAGNOSTIC STATION 3.5 V - XENON OR LED

### VISIO 5 PLUS WALL DIAGNOSTIC STATION 3.5 V

Modern design diagnostic station to satisfy all practitioners and clinics needs. Available with two configurations:

- oto-ophthalmoscope with disposable ear tip dispenser
  - ophthalmoscope only.
- Two illumination technologies: LED or Xenon-Halogen. Regulated output prolongs the bulb life and guarantees optimal light intensity.
- ergonomic designed non-slip handles
  - constant output transformer with integrated surge protection
  - soft start technology to introduce voltage gently, eliminates cold-shock when turning ON increasing bulb life
  - automatic ON-OFF switch once the handle is removed or replaced in the cradle
  - adjustable light intensity, low power consumption
  - precise brightness control, between 3 and 100%
  - spiral cord of 3 meters when stretched
- Supplied with multilingual manual: GB, FR, IT, ES.

#### TECHNICAL SPECIFICATIONS OPHTHALMOSCOPES

	31620-1-2	31623
Apertures	7	8
Focusing lenses	28	68
Diopters range	-20 to +40	-30 to +38
<b>Visio 5XE Plus additional features (31623)</b>		
Coaxial optics for easier examination of undilated pupils		
Detection of corneal abrasions with cobalt blue filter		
Polarizing filter to virtually eliminate corneal reflection		



#### APERTURES/ FILTER DIAL

Small light	•
Medium light	•
Large light	•
Blue light*	•
Grid	•
Slit	•
Half light	•
Red free light	•

\*5XE (31623 only)

GIMA code	VISIO 5 PLUS DIAGNOSTIC STATION
31620	Visio 5GE Plus oto-ophthalmo diagnostic station* - Xenon
31621	Visio 5GE Plus oto-ophthalmo diagnostic station* - LED
*Include power transformer, 2 handles, oto/ophthalmo heads, dispenser with 100 disposable grey speculum (50 Ø 2.5 mm, 50 Ø 4 mm), wall board for easy mounting or removal of diagnostic station.	
31622	Visio 5GE Plus ophthalmoscope diagnostic station - LED
31623	Visio 5XE Plus ophthalmoscope diagnostic station - LED
31428	Xenon bulb for ophthalmoscope - spare
31544	Xenon bulb for otoscope - spare
31485	Disposable mini ear speculum Ø 2.5 mm - grey - box of 100
31486	Disposable mini ear speculum Ø 4 mm - grey - box of 100

## VISIO 2000 F.O., XENON OTO, OPHTHALMO, ENT SETS - 3.5 V

Professional diagnostic sets with fiber optic illumination, Xenon light 3.5 V, rheostat to adjust the intensity of light. Made of resistant re-inforced plastic and durable easy locking system.

Supplied in deluxe case, should be used with charging station 31542 and Li-ion rechargeable battery 31541. Only plug-in set (31537) has direct AC connection and included battery (31547).

- 31535 VISIO 2000 F.O. XENON OTOSCOPE - 3.5 V
- 31536 VISIO 2000 F.O. XENON OPHTHALMOSCOPE - 3.5 V
- 31537 VISIO 2000 F.O. XENON OTO-OPHTHALMOSCOPE

#### PLUG-IN SET - 3.5 V - 2 pin plug

- 31538 VISIO 2000 F.O. XENON OTO-OPHTHALMOSCOPE - 3.5 V
- 31539 VISIO 2000 F.O. XENON DIAGNOSTIC SET - 3.5 V
- 31428 OPHTHALMOSCOPE BULB - spare
- 31544 OTOSCOPE BULB - spare
- 31541 LI-ION RECHARGEABLE BATTERY 3.5 V
- 31547 LI-ION RECHARGEABLE BATTERY 3.5 V for PLUG-IN HANDLE SET 31537- spare

- 31542 ZOOM CHARGING STATION

Supplied with EU 2 pin, UK and US plug

#### MINI EAR SPECULUM

Visio otoscopes are compatible with Gima speculum (31485-8, 31491-2, 31495-9). See page 266

Swivel type window with 3X magnification for sharp images and minimal reflection



Distal F.O. illumination with super bright Xenon light

Durable easy locking system

Rheostat

31535



Enhanced Xenon super bright light

31536

#### 6 apertures to select:



Red-free filter

31542

31541

31547



Plug-in handle

0	1	2	3	4	5	6	7	8	9	10	12	15	20	40
1	2	3	4	5	6	7	8	9	10	15	20	25		

Colour coded 28 lenses for perfect examination (GREEN for +, RED for -)



31535



31537



31538



31539

#### F.O. Xenon otoscope set 3.5 V

F.O. otoscope head, battery handle with bayonet lock, 1 set of 5 reusable eartips (2.5, 3.0, 4.0, 5.0 & 10.0 mm), tube of 14 disposable eartips (2.5 & 4.0 mm), spare bulb, in a rigid case.

#### F.O. Xenon ophthalmoscope set 3.5 V

31536 F.O. ophthalmoscope head, battery handle with bayonet lock, spare bulb, in a rigid case.

#### F.O. Xenon oto/ophthalmo plug-in set 3.5 V

F.O. otoscope head, F.O. ophthalmoscope head, battery handle with bayonet lock and plug-in, 1 set of 5 reusable eartips (2.5, 3.0, 4.0, 5.0 & 10.0 mm), tube of 14 disposable eartips (2.5 & 4.0 mm), spare oto and ophthalmoscope bulbs, rechargeable Li-ion battery 31547, in a rigid case.

#### F.O. Xenon oto/ophthalmo set 3.5 V

F.O. otoscope head, F.O. ophthalmoscope head, 2 battery handles with bayonet lock, nasal illuminator with F.O. light, 1 set of 5 reusable eartips (2.5, 3.0, 4.0, 5.0 & 10.0 mm), tube of 14 disposable eartips (2.5 & 4.0 mm), spare oto bulb, suitable also for nasal illuminator, and ophthalmoscope bulb, in a rigid case.

#### F.O. Xenon ENT diagnostic set 3.5 V

F.O. otoscope head, F.O. ophthalmoscope head, battery handle with bayonet lock, nasal illuminator with F.O. light, curved illuminator with bulb, plain mirror 20.0 mm, plastic tongue depressor, 1 set of 5 reusable eartips (2.5, 3.0, 4.0, 5.0 & 10.0 mm) tube of 14 disposable eartips (2.5 & 4.0 mm), spare oto and ophthalmoscope bulbs, in a rigid case.



# RI-FORMER® THE MODULAR DIAGNOSTIC STATION 3.5V



## RI-FORMER MODULAR DIAGNOSTIC STATION

The modular diagnostic station can be individually combined according to requirements and the room situation, it is variably extendable to the right and the left.

The basic Ri-former® module is available with one handle and can be supplemented with up to 4 further handle modules.

- 3.5V Xenon or LED illumination creates lighting conditions similar to daylight

- optimum electronic efficiency using an adjustable dimmer

- constant output voltage independent from the mains supply prolongs the service life of the lamps and guarantees optimum light intensity

- automatic switching on/off of handles when removing or replacing them in the handle unit saves energy and increases the service life of the lamps

- non-slip, ergonomically designed handles with rheostat: infinitely variable regulation of brightness as well as manual switching on/off possible on the handle


- spiral cord expandable up to 3 m



GIMA code	MODULAR DIAGNOSTIC STATION - XENON
31800	Ri-Former Diagnostic station 3.5-230V* 50/60 Hz-standard (include 2 handles oto and ophthalmoscope head, ear specula dispenser, clock)
31805	Ri-Former Diagnostic station 3.5-230V* 50/60 Hz-large (include 31800 + sphygmo) *available on request 120V - 50/60 Hz
	MODULAR DIAGNOSTIC STATION - LED
31801	Ri-Former Diagnostic station 3.5-230V* 50/60 Hz-standard (include 2 handles, LED oto and ophthalmoscope head, ear specula dispenser, clock)
31806	Ri-Former Diagnostic station 3.5-230V* 50/60 Hz-large (include 31801 + sphygmo) *available on request 120V - 50/60 Hz
	RI-FORMER MODULES AND HEADS
31809	Basic diagnostic station 1 handle 3.5 - 230V* 50/60 Hz
31810	Extension module 1 handle
31811	Ri-scope L2 otoscope head - Led 3.5V
31812	Ri-scope L1 otoscope head - Xenon 3.5V
31813	Ri-scope L1 ophthalmoscope head - Xenon 3.5V
31814	Ri-scope retinoscope head - Xenon 3.5V
31815	Ri-scope dermatoscope head - Led 3.5V
31817	Ri-scope L1, L2 ear speculum Ø 2.5 mm - autocl. 134°C - box of 10
31819	Ri-scope L1, L2 ear speculum Ø 4 mm - autocl. 134°C - box of 10
31827	Ri-scope L1, L2 ear speculum Ø 2.5 mm - disposable - box of 100
31828	Ri-scope L1, L2 ear speculum Ø 4 mm - disposable - box of 100
31820	Ri-spec ear specula dispenser - specula not included
31822	Sphygmomanometer with basket
31823	Ri-thermo N infrared thermometer with 40 covers
31824	Probe cover for 31823 - box of 100 - spare
31825	Xenon L1 otoscope bulb 3.5V - spare
31826	Xenon ophthalmoscope L1, L2, L3 bulb 3.5V - spare

\*Available on request 120V - 50/60 Hz

## RI-SCOPE® L: LED + Li-ion BATTERIES



**LED illumination: bright, white light with a nearly unlimited lifetime!**  
With its monochromatic white light (4,000° Kelvin) the lamp in the ri-scope®L provides cold light and true-colour. CRI > 90. Lamps with LED technology have a lifetime of at least 10,000 hours (compared to 20-30 hours with halogen and Xenon lamps) and are extremely energy-efficient.

### Li-ion batteries for great power

Higher charging capacity, longer lifetime, light-weight are the big advantages of Li-ions batteries. High performance for up to 1200 charging cycles. LEDs powered by lithium batteries can burn for up to 50 hours.

• 31829 RI-SCOPE L LED OTOSCOPE L2 - 2,5 V - AA handle - 3708

• 31830 RI-SCOPE L LED OTOSCOPE L2 - 3,5 V - C handle - 3703-550

Ri-scope®L otoscopes with optical glass and reduced reflection combine excellent optical properties and unparalleled performance with the reliability and efficiency of LED/lithium-ion technology (31830 only).

- optimal beaming and transmission of the light.

- bi-directional swivelling, sealing optical glass 3X

- Suitable for pneumatic test (supplied without ball).

- C handle runs Li-ion batteries, not included.

Supplied in deluxe hard case with one spare lamp, 4 reusable and 3 disposable ear specula.

Spare ear speculum: original 31817-31819 (autoclavable) or 31827 - 31828 (disposable). Compatible 31485 to 31499 (disposable) page 266

• 31832 RI-SCOPE L2 XENON OPHTHALMOSCOPE - 3,5 V

Enhanced basic model with separately engageable red-free, blue and polarization filters for each aperture.

- Diopter wheel with 29 corrective lenses Plus 1-10, 12, 15, 20, 40 Minus 1-10, 15, 20, 25, 30, 35

- Easy-to-operate aperture hand-wheel with semi-circle, small/medium/large circle, fixation star, and slit

- Includes filter wheel engageable for all apertures with symbol display, red-free filter, blue filter and polarization filter

• 31834 RI-SCOPE L LED OTOSCOPE L2 + XENON OPHTHALMOSCOPE L2 3.5 V - C handle

• 31826 XENON L1/L2/L3 OPHTHALMOSCOPE BULB 3,5 V - spare

• 31841 RI-ACCU L 3.5 V Li-ion BATTERY

for "C" size - 10691

• 31840 RI-CHARGER L 230 V

MADE IN GERMANY


Table recharge station (with wall holder)  
recharge 2 "C" handles with Li-ion batteries.




31840

## GIMA OTOSCOPES: PARKER LINE

VETERINARY OTOSCOPES AND SETS SEE PAGE 441-442



31442



31440

### PARKER OTOSCOPES

- reliable and indestructible high quality instrument
- suitable for everyday ear nose and throat examinations
- easily adjustable 2.5 V vacuum light (made in Germany)
- quality 3 times magnifying lens
- available with Plug in and snap (bayonet locking) or knurled screw type otoscope heads
- ideal for pneumatic tympanic membrane tests, can also be used for rhinoscopic examinations
- supplied with 3 autoclavable ear funnels in a colour coordinated zip bag.
- All latex free.
- require 2xC batteries (not included) 31542
- 31441 also works with rechargeable battery



31437

31436

31435

GIMA code	PARKER OTOSCOPES	Connection system	Ear Funnels
31435	Parker colour - green	Bayonet	Ø 2.5, 3.5, 4.5 mm
31436	Parker colour - blue	Bayonet	Ø 2.5, 3.5, 4.5 mm
31437	Parker colour - yellow	Bayonet	Ø 2.5, 3.5, 4.5 mm
31440	Parker - black	Screw	Ø 2.5, 3.5, 4.5 mm
31441	Parker with rechargeable handle	Bayonet	Ø 2.5, 3.5, 4.5 mm
31442	Parker veterinary - black	Screw	Ø 4, 5, 7 mm
31449	Spare bulb 2.5 V for Parker otoscopes 31435-6-7, 31440-1-2		
31542	Charging station for 31441		
34467	Rechargeable Li-ion battery 2.5 V / 2,200 mAh		

## PARKER DIAGNOSTIC SETS

### • 31471 PARKER DIAGNOSTIC SET

Lightweight, semi rigid nylon case with one Parker otoscope 2.5 V with rechargeable handle, 3 autoclavable ear speculum (Ø 2.5, 3.5 and 4.5 mm), 2 laryngeal mirrors (size 3 and 4), bent arm throat lamp, tongue spatula, adjustable nasal speculum.


• 31473 PARKER LARGE SET WITH OPHTHALMO Same as code 31471 with an ophthalmoscope head, support for single use tongue depressors and 1 tube of 14 single use specula (7x Ø 2.5, 7x Ø 4 mm).

• 31446 VACUUM BULB FOR OPHTHALMOSCOPE

• 31449 VACUUM BULB FOR OTOSCOPE

• 32203 "C" ALKALINE BATTERIES - blister of 2 pcs

• 34467 RECHARGEABLE LI-ION BATTERY 2.5 V - needs 31542



31471



31473

## LED OTOSCOPE - PEN LIGHT

### • 31300 COMBI SET

Dual function instrument features convertible diagnostic pen light and mini-otoscope with 3 different sizes (2.5, 3.5, 4.5 x 38 mm) of funnels or specula. White Led light. Packed in a gift box. Pupil gauge and dual slide rule printed on the penlight. Supplied with batteries (2xAAA).

• 32200 "AAA" ALKALINE BATTERIES - blister of 4 pcs

• 31345 REUSABLE EAR SPECULUM 2.5 mm - bag of 25

• 31346 REUSABLE EAR SPECULUM 4.5 mm - bag of 25



31300



## XENON-HALOGEN OTO AND OPHTHALMOSCOPE SET



Rechargeable handle for use with 2xC batteries or rechargeable battery (34467)

- **31475 XENON-HALOGEN PARKER OTOSCOPE**  
Same as PARKER Otoscope code 31440 but with halogen 2.5V bulb, and bayonet connection system. Supplied with 3 autoclavable ear funnels in a soft bag. Requires 2xC batteries (not included) or rechargeable battery.

- **31474 HALOGEN OPERATIVE PARKER OTOSCOPE**

Same as 31475 but with operative head.

- **31476 HALOGEN PARKER OPHTHALMOSCOPE**

2.5V halogen light for true tissue colour and consistent, long lasting illumination 24 colour coded lenses -25 to +40 dioptres for excellent resolution (green for +, red for -). Rubber eye brow rest to prevent scratching of eye-glasses. Illumination lens dial for clear identification of dioptre setting.

- **31477 HALOGEN OTO-OPHTHALMOSCOPE PARKER SET**

Diagnostic set including one handle, one halogen otoscope head and one halogen ophthalmoscope head, all in a plastic case.

- **31478 XENON-HALOGEN BULB FOR OTOSCOPE 2.5V**

- **31479 XENON-HALOGEN BULB FOR OPHTHALMOSCOPE 2.5V**

- **34467 RECHARGEABLE LI-ION BATTERY 2.5 V / 2,200 mAh**

- **31542 CHARGING STATION**

- **32203 "C" ALKALINE BATTERIES - blister of 2 pcs**



31474

31476

Supplied in a semi-rigid nylon bag with multi-lingual box and manual (GB, FR, IT, ES, PT, DE, GR, Arabic)



31475

31477



31476

+	1, 2, 3, 4, 5, 6, 8, 10, 12, 15, 20, 40
-	1, 2, 3, 4, 5, 6, 8, 10, 15, 20, 25

## XENON-HALOGEN DIAGNOSTIC SETS IN RIGID CASES

- **31480 XENON-HALOGEN DIAGNOSTIC SET - 3.5 V**

- **31482 XENON-HALOGEN OPERATIVE DIAGNOSTIC SET - 3.5 V**

Both xenon-halogen sets are supplied in plastic rigid case containing: one rechargeable handle, one otoscope head (operative for code 31482) one ophthalmoscope head, 3 autoclavable speculum Ø 2.5, 3.5, 4.5 mm, two laryngeal mirrors (size 3 and 4), adjustable nasal speculum, bent throat lamp, tongue spatula. Should be used with 31541 + 31542.

- **31427 XENON-HALOGEN OTOSCOPE BULB 3.5V**

- **31428 XENON-HALOGEN OPHTHALMO BULB 3.5V**

- **31542 CHARGING STATION - 100-240 V - 50/60 Hz**

See details at page 261.

- **31541 RE-CHARGEABLE LI-ION BATTERY 3.5V\***

\*For handles sold after may 2013



Operative otoscope head



31542



31480

## FIBRE OPTIC XENON-HALOGEN OTOSCOPES

- **31520 GIMALUX F.O. OTOSCOPE - black**

- **31521 GIMALUX F.O. OTOSCOPE - blue**

- **31522 GIMALUX F.O. OTOSCOPE - green**

High professional plastic otoscopes with extra bright halogen light provided by fibre optic system. Quality 3 times magnifying movable lens.

Output for pneumatic membrane test. Supplied with 14 single use mini speculums (7 Ø 2.5 and 7 Ø 4 mm) in a colour coordinated nylon bag. For mini ear-speculum see at page 266. All latex free.

- **34485 XENON-HALOGEN BULB 2.5V**  
Old model with chrome insufflation adapter need below bulb

- **31478 XENON-HALOGEN BULB 2.5V**  
for old models



Fibre optic system



Multilingual box and manual:  
GB, FR, IT, ES, PT,  
DE, GR, RO, HU,  
Arabic.



31521

31522





31520




## DISPOSABLE EAR-SPECULUM FOR "TRADITIONAL" OTOSCOPES

GIMA code	DISPOSABLE EAR - SPECULUM FOR OTOSCOPES OF DIFFERENT BRANDS	Colour	To be used with	Minimum order
31315	Disposable ear-speculum Ø 4 mm	Black	Riester (some models)	box of 200 pcs.
31504	Disposable ear-speculum Ø 2.5 mm	Black	Heine Beta 100, K100 and Eurolight,	box of 1000 pcs. (20 pack of 50)
31505	Disposable ear-speculum Ø 4 mm	Black	Kawe C10, C30, Combilight C10	box of 1000 pcs. (20 pack of 50)
31506	Disposable ear-speculum Ø 2.5 mm	White	Riester: Ri-star	dispenser of 250 pcs.
31507	Disposable ear-speculum Ø 4 mm	White		dispenser of 250 pcs.
31508	Disposable ear-speculum Ø 2.5 mm	Black	Welch Allyn: Pocket-pro; Pocket scope	dispenser of 250 pcs.
31509	Disposable ear-speculum Ø 4 mm	Black	Series 200, 250	dispenser of 250 pcs.

<p>Suitable for <b>RIESTER</b></p>  <p><b>31315</b></p>	<p>Suitable for <b>HEINE</b></p>  <p><b>31504-31505</b></p>	<p>Suitable for <b>RIESTER</b></p> <p>Multilingual box: GB, FR, IT, ES, PT, DE, GR, DK, Arabic.</p>  <p><b>31506-31507</b></p>	<p>Suitable for <b>WELCH-ALLYN</b></p> <p>Multilingual box: GB, FR, IT, ES, PT, DE, GR, DK, Arabic.</p>  <p><b>31508-31509</b></p>
--	--	--	---

## WELCH-ALLYN KLEENSPEC DISPOSABLE EAR SPECULUM

GIMA code	WELCH-ALLYN KLEENSPEC Disposable ear-speculum	Colour	To be used with	Minimum order	
72570	KleenSpec ear-speculum Ø 3 mm	Black	Welch-Allyn 20100, 20200	box of 100 (4 packs of 25 pcs.)	 <p><b>72570 72571</b></p>
72571	KleenSpec ear-speculum Ø 4 mm	Black	20202, 21600, 21700	box of 100 (4 packs of 25 pcs.)	
32105	KleenSpec ear-speculum Ø 2.75 mm	Black	Welch-Allyn, Macroview	box of 850	
32106	KleenSpec ear-speculum Ø 4.25 mm	Black	Riester Ri-scope L2, L3	box of 850	

## ALKALINE, LITHIUM AND ZINC-AIR "ACOUSTIC" BATTERIES\*



FOR GENERAL USE APPLICATIONS

MADE IN GERMANY

FOR ACOUSTIC

GIMA code	VARTA ALKALINE LONG LIFE POWER BATTERIES	Type	Blister	GIMA code	RAYOVAC ZINC- AIR "ACOUSTIC BATTERIES" - mercury free	Blister
32200	Varta ministilo - alkaline	AAA	4 pcs.	32220	Rayovac 675 - zinc air - acoustic	6 pcs.
32201	Varta stilo - alkaline	AA	4 pcs.	32221	Rayovac 13 - zinc air - acoustic	6 pcs.
32203	Varta half torch - alkaline	C	2 pcs.	32222	Rayovac 312 - zinc air - acoustic	6 pcs.
32204	Varta torch - alkaline	D	2 pcs.	32223	Rayovac 10 - zinc air - acoustic	6 pcs.
32205	Varta 9V - alkaline	9V	1 pc.			

\*All batteries are made in Germany except 32205 (made in China)



FOR ELECTRONIC

GIMA code	VARTA INDUSTRIAL ALKALINE BATTERIES	Type	Box*	GIMA code	VARTA LITHIUM BATTERIES - BUTTON	Blister
32226	Varta Industrial ministilo - alkaline	AAA	10 pcs.	32210	Varta 2016 - lithium button	1 pc.
32228	Varta Industrial stilo - alkaline	AA	10 pcs.	32211	Varta 2025 - lithium button	1 pc.
				32212	Varta 2032 - lithium button	1 pc.

## RECHARGEABLE BATTERIES AND CHARGERS

GIMA code	VARTA POWER PLAY RECHARGEABLE BATTERIES	Type	Blister
32235	Varta ministilo - 1,000 mAh	AAA	2 pcs.
32236	Varta stilo - 2,600 mAh	AA	4 pcs.

GIMA code	CHARGERS FOR ANY BRAND***	Power supply	Sizes mm	Weight g	To be used with:	Recharging time	12V+USB adaptor
32241	Universal charger	100-240 V	172x109x53	403	AAA, AA, C, D, 9C	5 h	no
32238	LCD charger	110-240 V	72x116x32	170	AAA, AA	2 h	yes

\*\*\*Supplied without batteries





## GIMA DISPOSABLE EAR-SPECULUM FOR MINI OTOSCOPES OF DIFFERENT BRANDS

GIMA code	GIMA DISPOSABLE SPECULUM FOR MINI OTOSCOPES - LATEX FREE	Colour	Compatibility		Minimum order
			Direct fit	Fit with connector 31493	
31485	Disposable Mini ear-speculum Ø 2.5 mm - grey		Gima Gimalux, Sigma, Sigma C, Visio 5, Visio 2000 Heine mini 2000, 3000, K180/Beta 200/Beta 400 Riester Ri-Mini, Ri-scope L1-L2, E-scope, Pen-scope Kawe (Picolight, Combilight F030, Eurolight F030) Holtex Colson Luxamed	Gima: 31435-37, 31440-42, 31471, 31473, 31475, 31477, 31480, 31493 (Parker line)	dispenser of 250 dispenser of 250 dispenser of 250 dispenser of 250 pack of 100 pack of 100 box of 1,000 pack of 100 pack of 100 pack of 100 pack of 100
31486	Disposable Mini ear-speculum Ø 4 mm - grey				
31487	Disposable Mini ear-speculum Ø 2.5 mm - black				
31488	Disposable Mini ear-speculum Ø 4 mm - black				
31491	Disposable Mini ear-speculum Ø 2.5 mm - black				
31492	Disposable Mini ear-speculum Ø 4 mm - black				
31495	Disposable Mini ear-speculum mixed colours and Ø				
31496	Disposable Mini ear-speculum Ø 2.5 mm - blue				
31497	Disposable Mini ear-speculum Ø 4 mm - blue				
31498	Disposable Mini ear-speculum Ø 2.5 mm - green				
31499	Disposable Mini ear-speculum Ø 4 mm - green				
31501	HEINE dispenser for Mini ear-speculum - empty		31485-8, 31491-2, 31495-9	-	-
GIMA code	CONNECTORS FOR MINI EAR SPECULUM	Colour	To be used with GIMA codes		
31493	Connector to GIMA Parker otoscope for Mini ear-speculum		31435, 31436, 31437, 31440, 31441, 31442, 31471, 31473, 31475, 31477, 31480		
31494	ALLIGATOR connector (supplied with 100 ear speculum)		31435, 31436, 31437, 31440, 31441, 31442, 31471, 31473, 31475, 31477, 31480		



## HEINE DISPOSABLE MINI EAR-SPECULUM



GIMA code	HEINE DISPOSABLE MINI EAR SPECULUM*	Minimum order
31501	HEINE dispenser for mini speculum - empty	-
31502	HEINE disposable Allspec® speculum Ø 2.5 mm - grey	dispenser of 250
31503	HEINE disposable Allspec® speculum Ø 4 mm - grey	dispenser of 250
31515	HEINE disposable Allspec® speculum Ø 2.5 mm - grey	box of 1,000
31516	HEINE disposable Allspec® speculum Ø 4 mm - grey	box of 1,000

\*Compatible with Heine Mini 2000/3000, K180, Beta 200

## RIESTER MINI EAR-SPECULUM



GIMA code	AUTOCLAVABLE MINI EAR SPECULUM for all Riester otoscopes	Colour	Minimum order
31817	Riester ear speculum Ø 2.5 mm - black	Black	box of 10 pcs.
31819	Riester ear speculum Ø 4 mm - black	Black	box of 10 pcs.
DISPOSABLE MINI EAR SPECULUM			
Only for E-Scope otoscopes			
31566	E-Scope ear speculum Ø 2.5 mm - black	Black	box of 100 pcs.
31567	E-Scope ear speculum Ø 4 mm - black	Black	box of 100 pcs.
Only for Ri-Scope L1, L2 Pen- scope, Ri-mini			
31827	Ri-Scope ear speculum Ø 2.5 mm - black	Black	box of 100 pcs.
31828	Ri-Scope ear speculum Ø 4 mm - black	Black	box of 100 pcs.

## REUSABLE CANNULAS AND EAR SPECULUM

GIMA code	AUTOCLAVABLE SPECULUM FOR PARKER OTOSCOPES - LATEX FREE	Colour	To be used with GIMA code	Also compatible with	Minimum order
31447	Kit 3 autoclavable veterinary speculum Ø 4, 5, 7 mm	Black	31442		One kit
31448	Kit 3 autoclavable speculum Ø 2.5, 3.5, 4.5 mm	Black	31435-37, 31440-42, 31471, 31473, 31475, 31477, 31480	Heine®, Kawe, Riester	One kit
31451	Kit of 5 autoclavable speculum Ø 2.5, 3.5, 4.5, 5.5, 9 mm	Black	31435-37, 31440-42, 31471, 31473, 31475, 31477, 31480	Heine®, Kawe, Riester	One kit
31453	Kit of 3 metal veterinary cannulas (Ø 4, 5, 6 mm) + 2 slotted metal specula (Ø 7.5 and 9.4 mm)	Black	31422, 31424, 31425		One kit
31483	Pneumatic bulb for Otoscopes	Black	31435/36/37/40/42/71/73/75/77-31520/21/22, 31535	Heine, Kawe, Riester	-

\*Not compatible with Mini 3000

Gima autoclavable ear speculum 31447, 31448, 31451 features:  
 - made from resilient thermoplastic material  
 - smooth matte finish surface ensure easy cleaning  
 - Metallic bayonet lock for positive fit to otoscope  
 - autoclavable at 134°C



2 slotted models with 60 mm opening and round edges, ideal for instrumentation, atraumatic insertion  
 31453 5.0 mm 6.0 mm 9.4 mm  
 7.5 mm  
 4.0 mm  
 Matte inner surface to reduce risk of reflection. For use with Vet open otoscope heads. See page 443

## OTOSCILLO® ELECTRICAL IRRIGATOR

### • 25800 PROFESSIONAL OTOSCILLO®

Otosillo® is designed for automated ear rinsing both in hospitals and during private consultations. Innovative, compact, efficient and rapid, it combines the most sophisticated operating qualities with the best security guarantees, all in a single device.

Otosillo® is an electrical irrigation for simplified rinsing of the ear canal. The pulsating stream system makes it easier to remove cerumen, even at low pressure control, Otosillo® is particularly suitable for treatment of sensitive ear canals. It looks less alarming and it is easier to use, with greater accuracy and security, than the alternatives. The water basin is removable to allow easy filling and emptying. Supplied with automatic back stop behind disposable nozzle for preventing cross-infections.

Operating power: 220 V - 50/60 Hz.

### • 25817 SPARE HANDLE + TUBE

• 25814 DISPOSABLE TIPS SET  
(100 disposable tips, 1 disk, connector)  
for 25800 and 25815 (old Otosillo®)

### • 25818 DISPOSABLE TIPS for 25800

and 25815\* - box of 100

\*Needs 25814

MADE IN GERMANY



## GLASS-METAL AND ALL-METAL EAR SYRINGES



### GLASS-METAL JANET RECORD SYRINGES

High quality, reliable and accurate glass-metal syringes. Janet Record come complete with 2 cannulas, one conical, one oval. Individually packed in cardboard box.


GIMA code	GLASS-METAL SYRINGES COMPLETE WITH 2 CANNULAS
25801	Janet Record 50 cc - 13 x Ø 3.5 cm
25802	Janet Record 100 cc - 14 x Ø 4.7 cm
25803	Janet Record 200 cc
25804	Spare cannula for Janet Record (conical shape)
25805	Spare cannula for Janet Record (olive shape)
25861	Ear irrigation tip - single use - box of 40

### ALL-METAL SCHIMMELBUSCH SYRINGES

High quality, reliable and accurate syringes. Schimmelbusch come complete with 3 cannulas and ear bowl. Individually packed in cardboard box.

GIMA code	ALL-METAL SYRINGES COMPLETE WITH 3 CANNULAS AND EAR BOWL
25806	Schimmelbusch 50 cc
25807	Schimmelbusch 100 cc
25808	Schimmelbusch 200 cc
25809	Spare cannula for Schimmelbusch (conical shape)
25812	Spare cannula for Schimmelbusch (olive shape) small
25813	Spare cannula for Schimmelbusch (olive shape) large
25861	Ear irrigation tip - single use - box of 40

## HIGH CAPACITY POLYPROPYLENE SYRINGES



### HIGH CAPACITY POLYPROPYLENE SYRINGES - sterile

Sterile, single use, latex free syringes for ear and other purposes. Box in GB, FR, IT, ES, DE, PT, GR, RO, RU, YU, SA. Medical Device class IIa.

GIMA code	HIGH CAPACITY, POLYPROPYLENE SYRINGES STERILE - CATHETER CONE	Minimum order
23820	Syringe 60 ml	box of 20
23821	Syringe 100 ml	box of 25



## OTOCLEAR® EAR IRRIGATION SYSTEM

Kit includes:  
1 spray wash bottle  
20 otoclear tips  
1 ear basin



25858

- **25858 OTOCLEAR EAR SPRAY WASH**  
- manual, intermittent lavage  
- delivers greater volume compared to syringes or other manual devices  
- efficient design allows for two handed procedure

- **25861 OTOCLEAR EAR IRRIGATION TIPS**  
single use - box of 40 - spare  
Flared design protects against over-insertion. The tip directs three streams of water towards the walls of the ear canal, away from the tympanic membrane, creating a turbulent lavage that effectively dislodges the cerumen. The exit portal controls backsplash and directs drainage into a basin.
- **25862 EAR IRRIGATION BASINS** - box of 3 - spare



Thermometer for water temperature



Improved patient comfort thanks to the soft "gentle touch" design



Patented 3-stream action


## LOOP-SPOON EAR CURETTES

- **31470 GIMA EAR CURETTES** - box of 10 pcs  
Double function curettes: one side spoon, one side loop.  
Each curette is individually packed in a single pouch.

31470




## BIONIX EAR CURETTES




**FLEXLOOP:**  
For normal curettage  
Most flexible of all  
Least traumatic  
Rounded tips for comfort  
4 mm wide tip



**MICROLOOP:**  
For compact cerumen  
More rigid construction  
Tip can be angled for added strength  
Rounded tip for comfort  
3 mm wide tip



**INFANTScoop:**  
For the smallest ears  
For when a small scoop works better  
Can be used through an otoscope • Flexible  
2 mm wide tip



**CERASPOON:**  
For viscous cerumen  
For extensive cerumen buildup  
For when a large scoop works better  
4 mm wide tip

The complete cerumen management system

- **31462 FLEXLOOP** - white - box of 50 pcs
- **31464 INFANTScoop** - light blue - box of 50 pcs
- **31460 MICROLOOP** - green - box of 50 pcs
- **31467 CERASPOON** - yellow - box of 50 pcs

Our four styles of curettes give you the most effective, economical and safe way to remove cerumen - whatever the size of ear or consistency of cerumen.

**Patient comfort:** Metal curettes are cold, hard and sharp. BIONIX ear curettes with rounded plastic tips reduce trauma and risk of laceration. Latex free.

**Effectiveness:** Ear curettes can duplicate the effectiveness of metal curettes in almost any situation and their polypropylene composition makes them virtually unbreakable.

**Disposability:** Ear curettes don't require expensive and time-consuming sterilization and eliminate the risk of cross-contamination.



## LIGHTED EAR CURETTES

- **31450 KIT MIXED LIGHTED CURETTES**  
Kit is composed by 50 lighted curettes  
(8 FlexLoop and 7 of each of below other 6 tip styles) + LED illuminator + magnification lens



**MicroLoop®**  
3 mm diameter loop



**FlexLoop®**  
4 mm diameter tip



**InfantScoop®**  
2 mm diameter tip



**AngleLoop®**  
Angled 4 mm diameter loop



**WaveCurette™**  
new wave like 2.5 mm tip




**VersaLoop®**  
3 mm wide tip




**CeraSpoon®**  
4 mm wide tip



Scan QR code with your web enabled camera phone to see Video



Lighted ear curette for foreign body removal with LED illuminator



Lighted ear curette 3 mm tip with LED illuminator

- **31461 KIT MICROLOOP**
- **31463 KIT FLEXLOOP**
- **31465 KIT INFANTScoop**
- **31466 KIT ANGLELOOP**
- **31468 KIT VERSALoop**

All kits are composed by 50 lighted curettes + LED light source + magnification lens

- **31458 LIGHTED FORCEPS** - box of 10 + magnification lens + LED illuminator
- **31459 LIGHTED ARTICULATING CURETTES** - box of 25 + magnification lens + LED light source

Ear curette tip has a 90° range of motion. It articulates to assist in removal of cerumen from the ear canal



## WOOD TONGUE DEPRESSORS



**PERSONALIZATION**  
minimum: 100,000 pieces  
ask for leaflet

**25511**  
Multilingual box:  
GB, FR, IT, ES, PT, DE, GR, Arabic.

Quality tongue depressors manufactured with selected high quality smooth birch wood. Edges accurately finished. 150x18x1.6 mm. Individually packed in a paper envelope and sterilized.

GIMA code	WOOD TONGUE DEPRESSOR - STERILE
<b>25511</b>	Tongue depressor - box of 50
<b>25512</b>	Tongue depressor - box of 2,000 (40 boxes of 50 pcs)



**25509**

Wooden medical tongue depressors made of quality birch wood. Edges accurately finished. Size: 150x18x1.6 mm

GIMA code	WOOD TONGUE DEPRESSORS NON-STERILE
<b>25509</b>	Tongue depressor - box of 100
<b>25510</b>	Tongue depressor - box of 5,000 (50 boxes of 100 pcs)

## PLASTIC TONGUE DEPRESSORS



Multilingual box: GB, FR, IT, ES, DE, PT, GR, Arab

### • 25505 PLASTIC COLOURED TONGUE DEPRESSORS

Plastic tongue depressor animal shaped with bright colour. Each tongue depressor is individually packed in transparent pouch. Packed in box of 50 pieces.



Curved shape allows perfect vision during examination avoiding that the hand of examiner obstruct the vision

**25513**

Child side 15 mm      Adult side 20 mm  
Length 150 mm

### PLASTIC TONGUE DEPRESSOR


Translucent tongue depressors made of polystyrene with curved shape and smooth edges. One end in adult size and one end in child size. Latex and PVC free. Sterile model is individually packed in a peel-open pack (ethylene oxide).

GIMA code	PLASTIC TONGUE DEPRESSORS ADULT/PEDIATRIC NON-STERILE	CE
<b>25513</b>	Tongue depressor - box of 100	CE 0120
<b>25515</b>	Tongue depressor - box of 90	
<b>25516</b>	Tongue depressor - box of 1,800 (20 boxes of 90 pcs)	

## STERILE ENT KITS

### • 31456 STERILE ENT KIT A - box of 25 kit

Kit includes one plastic nasal speculum, one plastic tongue depressor and two (adult and pediatric size) plastic ear funnels in single sealed pouch.




### • 31457 STERILE ENT KIT B - box of 10 kit

Kit includes one plastic nasal speculum, one plastic tongue depressor, two (adult and pediatric size) plastic ear funnels, two plastic laryngeal mirrors, one plastic forceps, six cotton tip applicators, one napkin, all packed in a sterile plastic tray (22x12.5x3 cm).



## THROAT SCOPE®



Blade illuminates the entire mouth

Disposable blade automatically activated when inserted into the handle

Bright white, Led light doubles as a torch

20 hours continuous battery life

Blade grip

One handed operation

Re-usable handle with 3 powerful long life Led lights

CR2032 3V Lithium battery

**25496**

### • 25496 THROAT SCOPE® KIT

#### 1 handle + 50 blades - box

Illuminated tongue depressor, made of medical grade plastic, that allows the clinician a one handed operation for oral cavity examination. The light is guided by the blade to illuminate the mouth for a quick examination by the clinician. Light is automatically activated when you insert single use blade into the handle.

### • 25499 THROAT SCOPE® DISPOSABLE

#### BLADES - box of 100 - non sterile

### • 25500 THROAT SCOPE® DISPOSABLE

#### BLADES - box of 50 - non sterile



Simultaneously depresses the tongue and illuminates the mouth

## NASAL SPECULUM



Total blade depth: 33 mm

Total length: 13.2 cm

**31469**


bionix

The use of stainless steel speculum can be a chilling experience for the patient. Now you can combine patient comfort with effective treatment. Smooth, warm tips make disposable Nasal Speculum more comfortable and less alarming to the patient.

### • 31469 DISPOSABLE NASAL SPECULUM - box of 48

Innovative plastic, disposable nasal speculum with handle: allows superior view of nasal cavity. Helps extract foreign objects from nasal cavity. Facilitates packaging of cauterizing of bleeding noses. Latex free.

MADE IN USA



**31469**



## WELCH ALLYN PENLIGHT



- 25622 W.A. HALOGEN PENLIGHT with 2 x AAA batteries  
Professional bright white halogen light.  
Durable solid brass construction.
- 25618 BULB for W.A. PENLIGHT - spare

**WelchAllyn**

## HEINE MINI-C LED<sup>HQ</sup> LIGHT



- 25630 HEINE MINI-C EXAMINATION LIGHT LED<sup>HQ</sup> - D008.73.109  
Compact, long-life pocket diagnostic light.  
20,000 switch cycles guaranteed.  
Replaceable batteries size AAA (included).




MADE IN GERMANY

## TOP QUALITY BULB OR LED PENLIGHTS

Professional penlights, also suitable for diagnostic, with bulb or white LED with quick clip shifter mechanism or push button (25634).

Argenta and Elegance made of anodized aluminium, Nova in top-quality ABS plastic housing. Supplied with 2x1.5V AAA batteries.



BULB

MADE IN GERMANY




LED  
100,000 HOURS  
LIFETIME



GIMA code	Description	Light	Light intensity	Material	Supplied with batteries	Colour	Medical device	on/off by
25632	Argenta torch	bulb	4.5 lux	metal	2 x AAA	black	Class I	Pocket clip
25633	Argenta torch	bulb	4.5 lux	metal	2 x AAA	silver	Class I	Pocket clip
25638	Argenta torch	bulb	4.5 lux	metal	2 x AAA	green	Class I	Pocket clip
25634	Elegance torch	bulb	4.5 lux	metal	2 x AAA	blue	Class I	Push button
25440	Nova torch	LED	25,000 m	plastic	2 x AAA	white	Class I	Pocket clip
25442	Argenta torch	LED	25,000 m	metal	2 x AAA	blue	Class I	Pocket clip


## BULB OR LED TORCHES PENLIGHTS



BULB



PERSONALIZED  
TORCHES FOR  
QUANTITIES



LED

Pupil gauge and  
dual slide ruler

GIMA code	Description	Light	Material	Supplied with batteries	Colour	Packaging	Multilingual instructions	on/off by
25626	Alfa torch	bulb	plastic	2 x AAA	blue	Blister	GB, FR, IT, ES, PT DE	Pocket clip
25627	Alfa torch	bulb	plastic	2 x AAA	white	Blister	GB, FR, IT, ES, PT DE	Pocket clip
25639	Beta torch	bulb	stainless steel	2 x AAA	silver	Plastic case	GB, FR, IT, ES	Push button
25434	Stylo torch	bulb	metal	2 x AAA	white	Blister	GB, FR, IT, ES, PT DE	Push button
25641	Spirit torch	LED	chrome plated brass	2 x AAA	silver	Box	GB, FR, IT, ES	Pocket clip
25436	Omega Torch	LED	metal	2 x AAA	silver	Plastic case	GB, FR, IT, ES	Pocket clip
25437	Omega Torch	LED	metal	2 x AAA	gold	Plastic case	GB, FR, IT, ES	Pocket clip
25624	GIMA torch	LED	metal	1 x AAA	silver	Box	GB, FR, IT, ES	Push button

## DELTA PENLIGHTS WITH TONGUE DEPRESSOR HOLDER

- 25628 DELTA "LED" PENLIGHT - red
- 25629 DELTA "LED" PENLIGHT - blue

Delta penlights are supplied in aluminium box with 2 AAA batteries and holder for tongue depressors (tongue depressor not included).  
Box and instructions in:  
GB, FR, IT, ES, PT, DE.



25628

25629

- 25625 DELTA "LED" OTOSCOPE PENLIGHT - black

Same as 25628-9 but with otoscope head, 3 ear funnels and 5 black plastic tongue depressors.

- 31345 REUSABLE EAR SPECULUM 2.0 mm - bag of 25
- 31346 REUSABLE EAR SPECULUM 4.0 mm - bag of 25



25625

Box and  
instructions:  
GB, FR, IT, ES, PT, DE

25628

## ■ NEUROLOGICAL REFLEX PERCUSSORS - LATEX FREE



GIMA code	PERCUSSORS	Colour	Handle	Pin	Brush	Weight	Length
31270*	Buck Gima 2000	green	plastic/stainless steel	yes	yes	90 g	20 cm
31251*	Buck Classic	silver	chromed brass	yes	yes	90 g	18 cm
31252*	Buck colour-yellow	yellow	brass colour coated	yes	yes	105 g	19.5 cm
31271*	Dejerine Gima 2000	blue	plastic/stainless steel	yes	yes	115 g	21 cm
31254*	Dejerine Classic	silver	stainless steel	yes	yes	140 g	22 cm
31255*	Dejerine colour	red	stainless steel	yes	yes	140 g	22 cm
31256	Babinsky - Ø 4.5 cm	silver	chrome plated	yes	no	170 g	24 cm
31257	Queens - Ø 5 cm	silver	flexible plastic	no	no	100 g	33 cm
31258	Troemner	silver	stainless steel	no	no	200 g	23 cm
31260	Pinwheel	silver	chrome plated	no	no	50 g	18 cm
31272*	Babinsky-Gima 2000	green	plastic/stainless steel	no	yes	108 g	23.5 cm
31273*	Taylor Gima	red	plastic/stainless steel	no	yes	72 g	20 cm

\*Multilingual box: GB, FR, IT, ES, PT, DE, GR, Arabic



## ■ THERMO FEEL

### • 31278 THERMO FEEL


Useful tool for diagnosis of neuropathy in diabetes patients. Both sides (one stainless steel and one plastic) are alternatively put in contact with foot skin of the patient. Patient perception of cool or warm allows a first diagnosis of diabetes.



31278



## ■ MONOFILAMENT - SENSORY EVALUATOR



Diagnostic tool for detecting diabetic neuropathy.

31282

Supplied in pouch with multilingual user manual and 3 spare monofilaments

### • 31282 MONOFILAMENT TOOL - sensory evaluator

Plastic retractable monofilament with 3 spare monofilaments. Evaluates both diminishing and returning sensation (touch test). Examines levels of sensory function and changes in neuro status. Monofilament is calibrated at 10 g. Size: 13x2.5 cm + 4 cm monofilament

### • 31281 KIT OF 3 MONOFILAMENTS - spare



## ■ NEUROLOGICAL KIT



### • 31265 NEUROLOGICAL KIT - 3 hammers

31265


This kit includes 3 metal hammers in a foam box: Taylor hammer, Buck hammer and Babinsky hammer.

## ■ TWO POINTS DISCRIMINATOR

### • 31279 TWO POINTS DISCRIMINATOR



Plastic (ABS) caliper with scale printed on aluminium plate. Two point discrimination is the ability to discern that two nearby objects touching the skin are truly two distinct points, not one.

It is often tested with two sharp points during a neurological examination and reflects how finely innervated an area of skin is. Reliable and widely used technique for determining tactile gnosis.





## GERMAN-MADE DIAPASONS - TUNING FORKS



### ENT TUNING FORKS:

All made in Germany, with age-long craftsmanship experience, in special alloy that ensures maximum sound precision.

GIMA code	ENT TUNING FORKS
31230	Tuning fork 128 Hz* - with weight
31231	Tuning fork 256 Hz* - with weight
31232	Tuning fork 512 Hz
31233	Tuning fork 1024 Hz
31234	Tuning fork 2048 Hz
31235	Tuning fork 4096 Hz
31240	Set of 5 tuning forks in a stylish lined case (contains 128 Hz*, 256 Hz*, 512 Hz, 1024 Hz, 2048 Hz). <i>Tuning forks with asterisk * are supplied with weight</i>

### ENT/NEUROLOGY TUNING FORKS

All made of a special alloy and supplied with base. All tuning forks have multilingual manual and box: GB, FR, IT, ES, PT, GR. Additional DE, HU, RO, BG only for 31247.


MADE IN GERMANY

GIMA code	ENT/NEUROLOGY TUNING FORKS
31245	Tuning fork a1-440 Hz - ENT - 90 g
31246	Tuning fork - LUCAE - 85 g adjustable from c128 to h240 with foot
31247	Tuning fork C64, c128 - RYDEL SEIFFER detachable slider either C64 or c128 - 130 g

## ALUMINIUM ALLOY DIAPASONS - TUNING FORKS

- 31225 ALUMINIUM TUNING FORK 128 Hz
  - 31226 ALUMINIUM TUNING FORK 128 Hz - with foot
- Made of finest aluminium alloy and precisely shaped to meet highest requisites (standards) in medical field.

Resting pad for forehead



## NYSTAGMUS SPECTACLES - DR. FRENZEL

MADE IN GERMANY

- 31204 NYSTAGMUS SPECTACLES - DR. FRENZEL - black
- Easy to use in the search of spontaneous or provoked nystagmus. Fixed, biconvex lens + 18.0 diopters. Nystagmus spectacles should be connected only with < 4.2 V transformer as per safety norms 93/42/EEC. See code 31203 or 31214

- 31214 BATTERY handle for 31204
- Offers mobility during examination. Needs 3x1.5 V CLR14 batteries (not included). Manual GB, IT, SE.

- 31203 PLUG-IN TRANSFORMER for 31204 - 100-240 V, 47-63 Hz
  - 31206 BATTERY NYSTAGMUS SPECTACLES - DR. FRENZEL - black
- This model allows wireless working and is provided with power through the adjustable battery placed above the spectacle. Requires three 1.5 Volt batteries, size C LR14/AM-2 (baby cells). Illumination can be adjusted through a turn of the switch.

- 31208 NYSTAGMUS BULB - spare for 31204, 31206
  - 31207 LED BATTERY NYSTAGMUS SPECTACLES - white
  - 31209 LED POWER SUPPLY NYSTAGMUS SPECTACLES - white
- Same as 31206 with LED and inner function that makes easier watching the rashes within a particular time period (30, 60, 90 seconds). Same as 31204 with LED and rechargeable power supply.



Supplied with head strip

Multilingual manual:  
GB, FR, IT, ES, PT, GR

LED + BATTERY

Suggested for short examinations

31207

LED + POWER SUPPLY

Supplied with head strip, rechargeable power supply

31209

Adjustable illumination through a slight turn around of the switch

Multilingual manual:  
GB, FR, IT, ES, PT, GR

Manual:  
GB, IT

## USB VIDEONYSTAGMOSCOPE SYSTEMS

- 31213 VIDEO-NYSTAGMOSCOPE - USB - mask with Ir camera and USB cable
- Facilitate to view and register the Nystagmus through standard vestibular tests (both position and instrumental proof).

This system allows to view on the monitor or PC/Notebook images of patient eyes during tests and to make Visual Suppression Test (VST) through a green LED light inside the mask to allow fixation. Innovative technology allows to get quality images. Power 12V DC.


MADE IN ITALY



752x582 pixels resolution  
520 TV lines

31213

## OPTOMETRIC CHARTS



GIMA code	OPTOMETRIC CHARTS*	Working distance	Size cm
31301	SNELLEN eye chart with red/green bar visual acuity test	10 feet 3 m	23x35.5
31302	TUMBLING "E" colour vision chart-visual acuity screen	20 feet 6.1 m	23x35.5
31303	SNELLEN eye chart for visual acuity and colour vision test	20 feet 6.1 m	23x35.5
31304	SLOAN colour bar visual acuity chart	20 feet 6.1 m	23x35.5
31307	TUMBLING "E" eye chart	20 feet 6.1 m	28x56
31308	TRADITIONAL SNELLEN eye chart	20 feet 6.1 m	28x56
31309	MIXED DECIMAL chart**	10 feet 3 m	28x56
31310	EWING illiterate test chart	20 feet 6.1 m	28x56
31311	SLOAN near vision chart (2 sides printed)	16 inches 40 cm	18x23

\*Polypropylene natural white sheet, approx. thickness 0.8 to 1.0 mm Multilingual instructions: GB, FR, IT, ES \*\*Not suitable for Portugal

## LEA SYMBOLS AND NUMBERS VISION CARDS AND CHARTS



### • 31322 LEA SYMBOLS NEAR VISION CARD - 40 cm (16 inches)

This test measures near visual acuity with proportionally spaced (logMAR) lines on the front and lines with 25% and 50% spacing on the back. Response key printed on test card. Includes training cards and instructions. Card measures 20.3x25.4 cm (8x10").

### • 31323 LEA SYMBOLS 15-LINE DISTANT CHART - 3 m (10 feet)

This test is designed for vision screening at schools and assessment of vision of children with special needs beginning with age of 3 years. Has a hole for hanging the chart on the wall. Includes semi-transparent response key and instructions. 43x53.4 cm (17x21"). Folds to 43x26.7 (17x10.5").

### • 31324 LEA NUMBERS NEAR VISION CARD - 40 cm (16 inches)

Designed to measure visual acuity with a standard line test and with three tighter spaced tests; 50%, 25%, and 12.5%, which often reveal difficulties in seeing tightly crowded details. Card measures 20.3x25.4 cm (8x10").

### • 31325 LEA NUMBERS 15-LINE DISTANT CHART - 3 m (10 feet)

This test is designed for vision screening at schools and assessment of vision of children with special needs beginning with age of 5 years. Has hole for hanging on the wall. 45.7x50.8 cm (18x20"). Folds to 45.7x25.4 (18x10").

## LOW CONTRAST CHARTS



### • 31317 CONTRAST SENSITIVITY CARD - NEAR VISION 40 cm

size 40x34 cm

### • 31318 CONTRAST SENSITIVITY CHART - FROM A DISTANCE 3 m

size 77x61 cm  
It checks for the ability to distinguish light and dark (contrast). It can detect vision problems. Also useful to reveal in time regression or progression of the cataract disease.

## OCCLUDERS



### • 31275 EYE OCCLUDER - 170x200x3 mm

### • 31274 OCCLUDER - 154 x Ø 47 mm

Set of two tiger fun frosted glasses to be used as occluder during children examinations one to occlude each eye.

154 x Ø 47 mm

31274




31276

## OPTOMETRIC PENCILS

### • 31319 OPTOMETRIC PENCILS - set of 2 pcs

Set of two wooden puppets (red and white) used to capture attention during vision evaluation in young non-verbal children. Can also be used for test of convergence.





## LANG STEREOTEST®



- 31294 LANG STEREOTEST® I
- 31295 LANG STEREOTEST® II

LANG STEREOTEST® represents today's standard of random dot stereo tests without the need of 3D glasses, with very high sensitivity and specificity for stereopsis.

The test combines random dots and a lenticular grid surface, and has been designed for quick screening of binocular vision in all groups of age, including very young children.

While the test card is presented at reading distance, the patient is asked about what he sees and his eye movements are being observed.

Recognition of figures is only possible if the person has full global stereopsis, while patients with amblyopia and (even small angle) strabismus fail the test.

LANG STEREOTEST® I shows three stereo figures with disparities of 1200, 600 and 550 arcsec.

LANG STEREOTEST® II has four stereo figures with disparities of 600, 400, 200 and 200 arcsec, of which one is also monocularly visible.

- 31296 LANG FIXATION STICK
- 31297 LANG FIXATION CUBE - white
- 31298 LANG FIXATION CUBE - red

Quick and easy stereopsis test, even for small children



MADE IN SWITZERLAND

## STEREOPTIC TEST

- 31293 STEREOPTIC TEST

Test performed at a distance of 30-40 cm, allowing evaluation of eyes cooperation in providing one single image to the brain, starting from two separately showed figures.

Suitable for children from one year old and for adults in case of suspected strabismus, amblyopia or visual reduction.



Four stereo figures with disparities 200" (fish), 400" (star), 600" (tree) and ball always visible.



Gima stereoptic test contains one ball, one fish, one star, one tree. Ball visible by one eye only.

## WORTH LED LIGHT TEST


- 31289 WORTH LED LIGHT TEST - with red/green glasses

The Worth 4 dot test, is a clinical test for suppression of either the right or left eye. Suppression occurs during binocular vision, when the brain does not process the information received from either of the eyes. This is a common adaptation to strabismus, amblyopia, and aniseikonia. Battery not included, glasses included.

- 32201 "AA" ALKALINE BATTERIES - blister of 4 pcs
- Multilingual instructions: GB, FR, IT, ES, PT, DE, GR, Arabic.



## ISHIHARA COLOUR TEST



31291

MADE IN JAPAN

### ISHIHARA COLOUR TEST

Testing for colour deficiency requires high level of sensitivity and specificity. This series of plates is provided to detect colour blindness in people who can not read, and colour deficiency, since young age. Plates are designed with simple geometrical shapes, since the examinees may not be able to understand complicated pieces. Test gives quick and accurate assessment of colour vision deficiency of congenital origin.

Most cases are diagnosed with red-green deficiency which may be of two types:

- protan, which may be absolute (protanopia) or partial (protanomaly)
- deutan, which may be absolute (deutanopia) or partial (deutanomaly)

GIMA code	ISHIHARA COLOUR TEST
-----------	----------------------

31290	Book of 10 plates for illiterates
31291	Book of 24 plates
31292	Book of 38 plates



## GIMA COLOUR TEST

- 31288 GIMA ADULT COLOUR TEST - 15 plates
- 31286 GIMA PEDIATRIC COLOUR TEST - 10 plates

Single plates (11.5x11 cm) packed in a practical aluminium box (13.5x11.5x2.3 cm).

Multilingual box and instructions: GB, FR, IT, ES, PT, DE, PL, RO, LT, SK, Arabic



## SCHIÖTZ TONOMETER



- 31220 SCHIÖTZ TONOMETER - straight scale
- 31222 SCHIÖTZ TONOMETER - inclined scale

A masterpiece of precision mechanism, measures intraocular pressure according to Prof. Schiötz standards. Vital parts are made of stainless steel. High quality agate bearing for extremely long service life. Set 3 weights included (5.5-7.5-10 g). Scale specification 5. In black deluxe case with velvet-look inserts. Perfect reading of the scale with red pointer.

MADE IN GERMANY



CE 0124



31220 straight



31222 inclined

## MULTIUSE SOFT CASES

- 27137 MULTIUSE SOFT CASE - black
- 27138 MULTIUSE SOFT CASE - blue

Inner insert divides this bag into two compartments, one for stethoscope, one for nurse accessories. Bottom compartment with one elastic pocket and one transparent zipper pocket. Upper compartment with 6 elastic loops, one transparent zipper pocket and one mesh pocket. Double zip for easy access. Size: 28x12.5x6.5 cm. Supplied with carrying handle.



## CLASSIC CASE FOR STETHOSCOPES

- 32667 CLASSIC CASE FOR STETHOSCOPES - black
- 32668 CLASSIC CASE FOR STETHOSCOPES - burgundy
- 32669 CLASSIC CASE FOR STETHOSCOPES - turquoise

High quality protective hard case for classic style, single tube stethoscopes, available in 3 colours. Its design holds the stethoscope secured in place by a preformed interior, keeping the sensitive diaphragm and tubing protected. Lightweight EVA construction and strong protective outer shell covered in 1680D nylon.

Pre-formed moulded interior can also be removed for flexible usage. Sealed dustproof and waterproof zipper with rubber easy-grip zipper pulls for easy opening and closing.

Interior mesh pocket for additional accessory storage. Carry handle for easy transportation.

Outside size 28x16x5 cm; inside size 26.5x14.5x4 cm. Weight: 220 g



Preformed eartips holders


Removable EVA tray with multispandex fabric.

Mesh pocket with elastic, 14x19 cm.

## COVERS FOR STETHO

Covers for stetho for pediatric applications, fits every kind of stethoscopes.

GIMA code	COVERS FOR STETHOSCOPES
32653	Pig cover for stethoscopes
32654	Dragon cover for stethoscopes



## SPARE PARTS AND ACCESSORIES FOR STETHOSCOPES

GIMA code	QUALITY "Y" TUBING	Minimum order
32620	"Y" tubing mixed colours	box of 20
32621	"Y" tubing - black	box of 20
32622	"Y" tubing - green	box of 20
32623	"Y" tubing - blue	box of 20
32624	"Y" tubing - red	box of 20
32625	"Y" tubing - orange	box of 20
32626	"Y" tubing - light blue	box of 20
32627	"Y" tubing - yellow	box of 20
32628	"Y" tubing - purple	box of 20
32629	"Y" tubing - pink	box of 20
BINAURAL - DIAPHRAGM - HEADS		
32655	One head chest piece - black ring	10 pcs.
32656	Dual head chest piece - black ring	10 pcs.
32666	BERTA binaural - fixed	1
32678	Diaphragm Ø 45mm for Classic adult	10 pcs.
EARTIPS AND ADAPTORS		
32657	Standard eartips - rigid - universal	box of 10
32658	Rigid eartips screw-type - for Classic, Wan, Yton, Duca, Regalite	box of 10
32663	Mushroom eartips for Trad, Wan, Yton, Design, Linus, Regalite and classic stethoscopes	box of 10






## ■ TRAD STETHOSCOPES - GOOD VALUE FOR MONEY




**TRAD STETHOSCOPES: adult, pediatric**  
Traditional aluminium stethoscopes, lightweight and reliable.  
Chestpiece diaphragm Ø 43.5 mm (Ø 35 for pediatric model), bell Ø 30 mm (Ø 26.5 for pediatric model) external sizes.  
Brass binaural, non chill ring.  
Tubing: length 62 cm, int. Ø 4 mm, ext. Ø 8 mm.  
Supplied in cardboard box. Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.



GIMA code	TRAD STETHOSCOPES - LATEX FREE	
32557	TRAD single head - pediatric - pink	
32559	TRAD single head - pediatric - light blue	
32555	TRAD double head - pediatric - black	
32560	TRAD single head - black	
32561	TRAD single head - red	
32562	TRAD single head - blue	
32563	TRAD single head - yellow	
32564	TRAD single head - purple	
32558	TRAD single head - dark green	
32565	TRAD double head - black	
32566	TRAD double head - red	
32567	TRAD double head - blue	
32568	TRAD double head - dark green	
32678	Diaphragm Ø 44 mm - spare	

## ■ COLOURED TRAD STETHOSCOPES



**COLOURED TRAD STETHOSCOPES**  
Coloured aluminium stethoscopes, lightweight and reliable.  
Chestpiece diaphragm Ø 43.5 mm, bell Ø 30 mm external sizes.  
Brass binaural.  
Tubing: length 62 cm, int. Ø 4 mm, ext. Ø 8 mm.  
Supplied in cardboard box.  
Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.



GIMA code	COLOURED TRAD STETHOSCOPES - LATEX FREE	
51000	TRAD single head - black	
51001	TRAD single head - red	
51002	TRAD single head - blue	
51003	TRAD single head - yellow	
51004	TRAD single head - green	
51010	TRAD double head - black	
51011	TRAD double head - red	
51012	TRAD double head - blue	

## WAN STETHOSCOPES - ADULT



WAN STETHOSCOPES  
Chrome-plated

### WAN ADULT STETHOSCOPES

Features a chrome-plated zinc-alloy chestpiece, a screw-on plastic retaining ring, outer spring binaural and colour matched moulded PVC tubing with non-chill ring. Assure optimum acoustic performances.

Chestpiece: Ø 45 mm, bell Ø 30 mm.

Tubing: length 63 cm, int. Ø 4.2 mm, ext. Ø 8 mm.

Supplied in a cardboard box.

Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.

GIMA code	WAN STETHOSCOPES - LATEX FREE	
32569	WAN single head adult - black	
32570	WAN single head adult - royal blue	
32571	WAN single head adult - burgundy	
32572	WAN single head adult - orange	
32574	WAN double head adult - black	
32575	WAN double head adult - royal blue	
32576	WAN double head adult - burgundy	
32577	WAN double head adult - orange	
32678	Diaphragm Ø 44 mm - spare	

## PEDIATRIC-NEONATAL STETHOSCOPES



### WAN PEDIATRIC AND NEONATAL STETHOSCOPES:

Features a chrome-plated zinc-alloy chestpiece, a screw-on plastic retaining ring, outer spring binaural and colour matched moulded PVC tubing with non-chill ring. Assure optimum acoustic performances.

Chestpiece: Ø 35 mm, bell Ø 30 mm, (pediatric) or Ø 22 mm, bell Ø 19 mm (neonatal). Tubing length: 63 cm.


Supplied in a cardboard box. Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.

### WAN PLUS:

Same as standard with inner spring binaural, superior tubing quality and 2 pair of soft colour coordinated ear tips in different size.

GIMA code	WAN STETHOSCOPES - LATEX FREE	
32508	WAN double head neonatal - red	
32509	WAN double head neonatal - grey	
32513	WAN double head pediatric - light-blue	
32515	WAN double head pediatric - red	
32511	WAN PLUS double head pediatric - pink	
32506	WAN PLUS double head pediatric - black	

## YTON STETHOSCOPES



### YTON STETHOSCOPES:

Gima Yton stethoscopes with single or double head.

Solid aluminium chestpiece Ø 45 mm, bell Ø 30 mm (for double head), with colour coordinated plastic retaining ring.

"Duracote" finished.

Available in four different colours: dark green, dark blue, red and aqua blue.

Manual and box in 11 languages: GB, FR, IT, DE, ES, PT, GR, PL, SE, HU, Arabic.



GIMA code	YTON STETHOSCOPES - LATEX FREE	
49500	Yton single head - dark green	
49501	Yton single head - dark blue	
49502	Yton single head - red	
49503	Yton single head - aqua blue	
49510	Yton double head - dark green	
49511	Yton double head - dark blue	
49512	Yton double head - red	
49513	Yton double head - aqua blue	



## JOTARAP STETHOSCOPE: DOUBLE-HEAD, DOUBLE TUBE



Gima Sprague Rappaport type double-head, double-tube, latex free stethoscope at the price of a standard stethoscope.

### 5 in 1, five way convertible type stethoscope

This convertible stetho, zinc alloy treaded with chrome plated chestpiece drum fitting with different sized chestpieces bells, provides versatile acoustics for infants and adults for the detection of a wide range of heart and lung sounds.

GIMA code	JOTARAP STETHOSCOPE	
32579	JOTARAP - purple	
32580	JOTARAP - black	
32581	JOTARAP - blue	
32582	JOTARAP - neon orange	
32583	JOTARAP - green	
32584	JOTARAP - neon yellow	
32585	JOTARAP - light blue	
32586	JOTARAP - fuchsia	
32587	JOTARAP - transparent pink	
32590	ACCESSORY KIT - spare	

Chestpiece with small and large diaphragm.


### Double tubing for individual sound transmission

Two separate 56 cm (22") thick latex free wall tubing provide individual sound transmission from chestpiece to both sides of the ear.

**Complete in cardboard box with accessory kit (32590)**

It is supplied with an accessory pouch containing:

3 interchangeable plastic black non-chill bells, adult and pediatric spare diaphragm, one pair clear neoprene eartips, one pair black mushroom eartips. Multilingual manual (GB, FR, DE, IT, ES, PT, GR, PL, HU, SE, RO, NL, LV, SK, Arabic).



## LINUX STETHOSCOPES



- 32518 LINUX STETHOSCOPE - blue
- 32524 LINUX STETHOSCOPE - black
- 32529 LINUX STETHOSCOPE - red

Single head stethoscope with lightweight zinc alloy chestpiece plated with an attractive satin finish. The special design assures better performances by pushing the back of the head.

Non-chill diaphragm retaining rim for patient comfort. Stainless steel binaurals fixed at 15° angle for greater comfort and acoustic seal. Soft and flexible PVC tubing. Supplied in deluxe box with one pair of plastic eartips and PVC eartips. Manual and box in 11 languages: GB, FR, IT, ES, DE, PT, GR, PL, HU, SE, Arabic.

## ACOUSTIC EXCELLENCE DOUBLE HEAD STETHOSCOPES



**CLASSIC STAINLESS STEEL STETHOSCOPES - Adult and Pediatric**  
High quality stethoscope with **stainless steel chestpiece**, stainless steel double inner spring binaural and durable, elegantly moulded PVC tubing for unsurpassed acoustic performance. The colour coordinated flexible 55 cm (22") PVC "Y" tubing, non-chill ring and diaphragm retaining ring provide excellent patient comfort, while adding attractiveness. It comes in a foam lined box with 2 extra sets of soft eartips. Chestpiece: Ø 45 mm (adult), Ø 35 mm (pediatric). Manual and box in: GB, FR, DE, IT, ES, PT, GR, PL, HU, SE, RO, BG, Arabic.

### CLASSIC IN 11 COLOURS

	Black	Dark blue	Royal blue	Light blue	Green	Dark green	Burgundy	Orange	Red	Pink	Lilac
GIMA code	32531	32532	32533	32534	32535	32536	32537	32538	32539	32540	32541
ACCESSORIES - SPARES											
32678	Diaphragm Ø 44 mm - spare for Classic adult										
32664	Rigid eartips screw-type - white spare for Classic/Wan/Yton/Duca/Regalite										

GIMA code	CLASSIC DOUBLE HEAD S/S STETHOSCOPES - ADULT
32531	Classic adult - dark green
32532	Classic adult - orange
32533	Classic adult - light blue
32534	Classic adult - black
32535	Classic adult - burgundy
32536	Classic adult - dark blue
32537	Classic adult - green
32538	Classic adult - red
32539	Classic adult - pink
32540	Classic adult - royal blue
32541	Classic adult - lilac

	CLASSIC DOUBLE HEAD S/S TEACHING STETHOSCOPES	
32542	Classic Teaching - black <i>allows simultaneously auscultation by 2 people</i>	32542
	CLASSIC DOUBLE HEAD S/S STETHOSCOPES - PEDIATRIC	
32512	Classic pediatric - light-blue	
32516	Classic pediatric - black	

## CARDIOLOGY STETHOSCOPES

- 32550 CARDIOLOGY CLASSIC STETHOSCOPE - blue
  - 32551 CARDIOLOGY CLASSIC STETHOSCOPE - burgundy
  - 32552 CARDIOLOGY CLASSIC STETHOSCOPE - black
- Cardiology Classic offers acoustical excellence in a traditional design with superior durability. Its innovative features include:
- stainless steel chestpiece (Ø 33-44 mm) with extra deep cone-shaped bell for a superb low frequency response
  - stainless steel double inner spring binaural
  - ultra-sensitive diaphragm for unsurpassed amplification
  - durable, elegantly moulded 55.5 cm (22") PVC tubing (int. Ø 6.5 mm, ext. Ø 12 mm)
- Manual and box in 11 languages: GB, FR, DE, IT, ES, PT, GR, PL, HU, SE, Arabic.

- 32678 DIAPHRAGM Ø 44 mm - spare

*Colour coordinated non-chill ring and diaphragm retaining ring, PVC tubing*



32552

It comes in a foam lined box with 2 extra set of PVC eartips  
279

32552

## PROFESSIONAL STETHOSCOPE

- 32526 REGALITE - black
- Top quality single head stethoscope. Chromed plated chestpiece with "SUPERFLEX" inner spring binaural and 1 piece moulded, PVC tubing. Supplied in deluxe box, with spare soft eartips and one space diaphragm. Manual and box in 7 languages: GB, FR, IT, ES, PT, GR, Arabic.



32526

CE



## GIMA EVOLVE DUAL HEAD STETHOSCOPES



### GIMA EVOLVE DUAL HEAD STETHOSCOPES

High acoustics and sensitivity stethoscope line with 4 different heads and attractive selection of coloured tubing. Chestpiece combination with floating diaphragms which allow to hear low and high frequency sounds applying light or firm pressure on chestpiece. Stainless steel chestpiece can catch lower frequency sound sensitively. Its inner side is polished making it smooth and reducing sound's attenuation during sound detection. Attractive selection of fashion coloured and trendy tubes. New electrical plating technology for longer life and corrosion resistance.

#### Features

- dual head chestpiece (Ø 48 mm and 36 mm) with anti-chill rings
- ergonomic and soft silicone eartips for best comfort



- aluminium binaural with spring inserted into the tube (stainless steel for Rose Gold version)
- PVC tube Ø 10 mm, length 60 cm
- total length 75 cm

Supplied with nametag and spare kit in transparent case including 2 pairs of soft eartips and 2 floating diaphragms. Multilingual box and manual: GB, FR, IT, ES, PT, DE, NL, PL, CZ, BG, RO, HR, GR, SE, Arabic.

GIMA code	GIMA EVOLVE DUAL STETHOSCOPES - length 75 cm		
	SHINY HEAD SERIES	Binaural	Ring
49550	Gima Evolve - black	mirrored	black
49551	Gima Evolve - navy blue	mirrored	transparent
49552	Gima Evolve - burgundy	mirrored	black
49553	Gima Evolve - turquoise	mirrored	transparent
49554	Gima Evolve - grey	mirrored	transparent
49555	Gima Evolve - dark green	mirrored	transparent
49556	Gima Evolve - red	mirrored	transparent
SHINY HEAD SERIES - glitter tubing			
49563	Gima Evolve - ceil blue	mirrored	transparent
49564	Gima Evolve - teal green	mirrored	transparent
ALL BLACK HEAD SERIES			
49567	Gima Evolve - black	black	black
49568	Gima Evolve - caribbean blue	black	black
49569	Gima Evolve - emerald green	black	black
49570	Gima Evolve - chocolate	black	black
MULTICOLOUR HEAD SERIES			
49574	Gima Evolve - raspberry	mirrored	transparent
49575	Gima Evolve - black	black	black
ROSE GOLD HEAD SERIES			
49578	Gima Evolve - white	rose gold	transparent
SPARE KITS			
			Colour
49580	Kit: 2 floating diaphragms with rims, 2 pairs of eartips		black
49581	Kit: 2 floating diaphragms with rims, 2 pairs of eartips		transparent

## MEDIKALL CLEAN PROOF S HYGIENIC COVER FOR STETHOSCOPES

### • 32595 MEDIKALL CLEAN PROOF S - box of 500

Medikall clean Proof S is proven to be an effective disposable barrier for stethoscopes against germs. It doesn't decrease the quality of auscultation.

Easy to use, efficient through significant time saving and first of all: safe for protecting patients and physicians.

Multilingual box: GB, FR, IT, DE, ES, PT



**PROTECTION GUARANTEED**  
By the effective and safe germ barrier

**ERKA.**  
THE ORIGINAL  
Made in Germany since 1889

**TIME SAVING**  
Significant time saving compared to conventional disinfection with exposure time



MADE IN GERMANY

**QUALITY IMPROVEMENT**  
No loss in the quality of auscultation



**SAFETY**  
It avoids risk of cross contamination

## RIESTER RI-SONIC PCP-USB AND PCP-1 ELECTRONIC STETHOSCOPES

- 51320 RI-SONIC PCP-1 ELECTRONIC STETHO - 3.5 mm stereo plug
- 51321 RI-SONIC PCP-USB ELECTRONIC STETHO- USB plug



The Riester Ri-sonic are electronic stethoscopes designed to provide auscultatory sound via Telemedicine, computer or through mobile device platforms. This can be done in real time remotely or through sharing of recorded files.

- the PCP-USB or PCP-1 stethoscope plugs directly into any mobile platform, PC or tablet computer via eMurmur App
- patented piezo technology for picking up body sounds with minimal background artefacts
- patients can use the stethoscope on themselves
- easy to use with a guidance of a clinicians.

Ri-sonic Electronic Stethoscopes enable a clinician to listen to internal body sounds, such as heart, lung or bowel sounds, of a patient.

### TECHNICAL SPECIFICATIONS

Mode of operation:	continuous operation
Electrical protection:	Class II protection against electrical shock
Plug:	USB plug (51321), 3.5 mm stereo plug (51320)
Voltage:	Input: 2 V - 5 V DC
Classification:	Type BF applied part
Weight:	180 g (51321), 145 g (51320)
MDD Class:	Class IIa



## RIESTER DUPLEX® 2.0 STETHOSCOPES, SIMPLY BETTER HEARING









### RIESTER DUPLEX® 2.0 STAINLESS STEEL STETHOSCOPES

Duplex® 2.0 stethoscopes are distinguished by outstanding acoustic performance.

They have been completely new constructed to meet the challenges of daily diagnostic practice. Special design tube for better auscultation of adults, children/babies or new-borns.

- precision double chest-piece made of stainless steel with innovative membrane support
- anatomically shaped binaural with internal multiple spring for adjusting the contact pressure
- extra-soft, replaceable and pivotable ear-tips for perfect sealing at the ear canal and enhanced wear comfort
- innovative acoustic system with extraordinary auscultation for all frequency ranges

- special membrane for precise acoustics with novel non-chill rims for improved adaptation on the skin
- Supplied with name plate, replacement ear-tips and membrane.

Supplied with name plate, replacement ear tips and membrane.						
GIMA code	Riester code	RIESTER DUPLEX® 2.0 - STAINLESS STEEL - LATEX FREE				
		DUPLEX® 2.0 ADULT	Membrane	Length	Weight	
32333	4210-01	Duplex® 2.0 - black 	Ø 44 mm	74 cm	151 g	
32334	4210-02	Duplex® 2.0 - white 	Ø 44 mm	74 cm	151 g	
32335	4210-03	Duplex® 2.0 - blue 	Ø 44 mm	74 cm	151 g	
32336	4210-04	Duplex® 2.0 - red 	Ø 44 mm	74 cm	151 g	
DUPLEX® 2.0 PEDIATRIC						
32338	4220-02	Duplex® 2.0 - white 	Ø 32/23.5 mm	69 cm	124 g	
DUPLEX® 2.0 NEW-BORN						
32340	4230-02	Duplex® 2.0 - white 	Ø 24/17.5 mm	69 cm	105 g	

## RIESTER DUPLEX® STETHOSCOPES - ALUMINIUM CHEST-PIECE



### RIESTER DUPLEX® ALUMINIUM STETHOSCOPES

Riester DUPLEX® stethoscopes combine first-class quality at an attractive price. They offer outstanding acoustic performance for the daily challenges in office practices and hospitals.

Double-headed chest-piece in lightweight aluminium, galvanized. Special membrane for perfect auscultation with particularly flat and soft non-chill rims for improved adaptation on the skin. Bell Ø 36 mm.

Supplied with a pair of replacement ear-tips and a replacement membrane.

GIMA code	Riester code	RIESTER DUPLEX® - ALUMINIUM CHESTPIECE			
		DUPLEX® ADULT	Membrane	Length	Weight
51300	4001-01	Duplex® - black	Ø 48 mm	77 cm	151 g
51301	4001-02	Duplex® - slate grey	Ø 48 mm	77 cm	151 g
51302	4031-03	Duplex® - blue	Ø 48 mm	77 cm	151 g
51303	4033-05	Duplex® - green	Ø 48 mm	77 cm	151 g



## ERKA FINESSE STHETOSCOPIES



### FINESSE STETHOSCOPIES

With the reversible double chest-piece you'll be prepared for all eventualities in everyday medical practice. The membrane side guarantees optimal auscultation for the entire frequency spectrum and the open bell side is specifically designed for low frequencies.

### FINESSE<sup>2</sup> STETHOSCOPIES

The reversible, combined chest-piece has two membrane sides, each making the full frequency range perfectly audible. The large membrane is suitable for auscultation of adults and the small one for children or slim patients.

All Erka stethoscopes are supplied with carrying bag

FEATURES	Finesse Light	Finesse Finesse <sup>2</sup>
Pre-tensioned ERKA. convex membrane provides excellent resonance and sound.	X	X
Non-chill ring ensures highest patient comfort.		X
Superior polish, chromium-plated, non-porous surface and brass chest-piece ensure perfect surface hygiene.	X	X
Two internal channels run parallel in the stethoscope tubing preventing any noise caused by friction of two separate tubes.		X
Through the separately integrated spring in the tube, there is no acoustic loss from the chest-piece to the ear.		X
Ergonomic design and super soft tips provide excellent acoustic seal against external noise interference and maximize user's comfort.	X	X
Standard 15° inclined binaurals can be individually adapted to the specific ear canal of the user.	X	X



GIMA code	ERKA code	ERKA STETHOSCOPIES - tubing length - 55 cm
<b>FINESSE LIGHT ADULT - head Ø 44.5/33.5 mm</b>		
32250	520 000 10	Finesse light - black
32251	520 000 20	Finesse light - navy blue
32252	520 000 55	Finesse light - dark green
<b>FINESSE PEDIATRIC - head Ø 31/26.5 mm</b>		
32256	549 000 00	Finesse pediatric - black
32257	549 000 25	Finesse pediatric - light blue
32258	549 000 35	Finesse pediatric - pink
<b>FINESSE ADULT - head Ø 44.5/33.5 mm</b>		
32262	550 000 00	Finesse adult - black
32263	550 000 05	Finesse adult - dark grey
32264	550 000 20	Finesse adult - navy blue
32265	550 000 55	Finesse adult - dark green
32266	550 000 60	Finesse adult - burgundy
<b>FINESSE<sup>2</sup> PEDIATRIC - head Ø 30/21.3 mm</b>		
32270	536 000 00	Finesse <sup>2</sup> pediatric - black
32271	536 000 35	Finesse <sup>2</sup> pediatric - pink
<b>FINESSE<sup>2</sup> ADULT - head Ø 47/30 mm</b>		
32275	535 000 00	Finesse <sup>2</sup> adult - black
32276	535 000 05	Finesse <sup>2</sup> adult - dark grey
32277	535 000 20	Finesse <sup>2</sup> adult - navy blue

## ERKAPHON STETHOSCOPIES



Stethoscope with double chest piece is switchable from membrane to bell function. The membrane side is suitable for the auscultation of high and low frequency sounds while the bell side is designed for cardiac impulses.

### ERKAPHON STETHOSCOPIES:

High quality precision stethoscopes for excellent acoustics. All stethoscopes are equipped with 56 cm long Y tube, brass chrome-plated binaural and chest-piece (32350, 32358) or aluminium (32344-7), membrane Ø 44 mm, bell Ø 30 mm (32358 only).

GIMA code	ERKA code	ERKAPHON STETHOSCOPIES
<b>ERKAPHON FLAT CHESTPIECE - aluminium</b>		
32344	544 000 10	Erkaphon flat chestpiece - black
32345	544 000 20	Erkaphon flat chestpiece - navy blue
32346	544 000 25	Erkaphon flat chestpiece - light blue
32347	544 000 30	Erkaphon flat chestpiece - red
<b>ERKAPHON FLAT CHESTPIECE - chromed</b>		
32350	543 000 10	Erkaphon flat chestpiece - black
<b>ERKAPHON DOUBLE CHESTPIECE - chromed</b>		
32358	541 000 10	Erkaphon double chestpiece - black

# 3M™ LITTMANN® STETHOSCOPE USER GUIDE

## CHOOSE THE RIGHT STETHOSCOPE TO HELP YOU PERFORM AT YOUR BEST

3M™ Littmann® Stethoscopes feature adjustable headsets with soft-sealing eartips. Mechanical stethoscopes are designed with tunable technology to hear different frequency sounds by simply adjusting the pressure applied to the chestpiece.








Acoustic performance, high quality and comfort you need with a Littmann stethoscope.



Authorized  
Distributor



### ACOUSTIC PERFORMANCE LEVELS AND FEATURES

	6	7-8		9-10		10+	
							
	<b>Lightweight II S.E.</b>	<b>Classic II Paediatric and Infant</b>	<b>Master Classic II™</b>	<b>Classic III™ Monitoring</b>	<b>Cardiology IV™ Diagnostic</b>	<b>Master Cardiology™</b>	<b>CORE Digital</b>
	Ideal for taking blood pressure readings and making limited patient assessments.	Hard-working, dependable, clinical tools for physical assessment and monitoring of your patients, one long shift after another.			Provide outstanding acoustic sensitivity to help you perform detailed diagnostic auscultation. Useful in challenging and critical care environments.		High-performance auscultation. Hear more with amplification, noise cancellation and mobile connectivity.
Length	71 cm	71 cm	69 cm	69 cm	69 cm	69 cm	69 cm
Weight	118 g	105 g, 95 g	160 g	150 g	177 g	185 g	232 g
Warranty	2 years	3 years	3 years	5 years	7 years	7 years	2 years
Diaphragm	Tunable	Non-Tunable (Floating)	Tunable	Tunable (2)	Tunable (2)	Tunable	Tunable (2)
Approximate Chestpiece Ø	Double-sided: 5.2x4.5 cm 3.5x3.2 cm	Double-sided Paed.: 3.4 - 2.7 cm Infant: 2.8 - 1.7 cm	Single-sided: 4.3 cm	Double-sided Adult side: 4.3 cm Paediatric side: 3.4 cm	Double-sided Adult side: 4.3 cm Paediatric side: 3.4 cm	Single-sided: 4.8 cm	Double-sided Adult side: 4.3 cm Paediatric side: 3.4 cm
Features	Teardrop-shaped chestpiece Fits under blood pressure cuff	Specially designed for the smallest patients	Designed for easier grip and maneuvering	Convertible open bell	Convertible open bell Dual-lumen tubing	Dual-lumen tubing Best acoustic response in Littmann mechanical line	Up to 40x amplification* Switch from analog listening to digital. Eko App to capture, store and share data

\*At peak frequency, vs. analogue mode

### ORDERING INFORMATION AND TUBE COLOUR GUIDE

FINISH: CHESTPIECE/EARTUBE/STEM	Lightweight II S.E.	Classic II Infant	Classic II Paediatric	Master Classic II™	Classic III™ Monitoring		Cardiology IV™ Diagnostic		Master Cardiology™	CORE Digital
Standard Finish	2450 Black	2114 Black	2113 Black	2144L Black	5620 Black	5627 Burgundy	6152 Black	6156 Plum	2160 Black	
	2451 Burgundy	2114R Red	2113R Red	2146 Burgundy	5621 Grey	5633 Pearl Pink	6154 Navy	6158 Raspberry	2163 Burgundy	
	2452 Caribbean	2124 Caribbean	2119 Caribbean	2147 Navy	5622 Navy	5831 Plum	6155 Hunter Green	6184 Burgundy	2164 Navy	
	2454 Ceil Blue		2122 Raspberry		5623 Caribbean	5832 Lavender			2167 Plum	
	2456 Pearl Pink				5630 Ceil Blue	5835 Turquoise				
					5648 Raspberry	5839 Lemon-Lime				
All Black				2141 Black	5803 Black	5868 Burgundy	6163 Black	6168 Navy	2161 Black	8490 Black
Brass Finish									2175 Black	
Copper Finish					5809 Chocolate					
Smoke					5811 Black				2176 Black	
Rainbow/Brass/Brass		2157 Raspberry	2153 Caribbean		5806 Raspberry	5807 Caribbean				
Rainbow/Black/Black					5870 Black		6165 Black			
Mirror/Smoke/Smoke					5959 Ceil Blue	5863 Navy				
Mirror/Standard/Mirror							6177 Black	6170 Burgundy		
Champagne/Smoke/Smoke					5861 Black	5864 Burgundy	6179 Black			
Champagne/Black/Champagne							6176 Burgundy	6190 Caribbean		
High-Polish Rainbow/Black/Black							6242 Navy			
High-Polish Rainbow/Smoke/Smoke							6240 Black	6241 Raspberry		

#### COLOURED STEM SERIES (square inset represents stem colour)

Black/Black/Colour							6200 Black	6203 Black	
High-Polish Smoke/Black/Colour							6201 Black		
High-Polish Smoke/Smoke/Colour							6202 Navy	6204 Black	
Rainbow/Black/Colour							6232 Black	6234 Carb.	
Champagne/Champagne/Colour							6238 Grey		
Smoke/Smoke/Colour							6205 Plum		
Mirror/Smoke/Colour							6206 Hunter		
					5872 Turq.	5875 Lime			
					5873 Grey				
					5960 Plum	5962 Pink			

#### COMPONENTS: CHESTPIECE/EARTUBE/STEM

Standard Finish	All Black	Brass Finish	High-Polish Rainbow	Mirror
Copper Finish	Smoke	Champagne	High-Polish Smoke	Rainbow




## 3M™ SINGLE-PATIENT STETHOSCOPES

3M™ has developed a new stethoscope, which combines advanced acoustic engineering and infection prevention. It is intended for single-patient use, adult or child in an isolation area, and to be disposed when no longer needed. It helps to reduce potential risks of patient-to-patient cross-contamination, that could occur using reusable stethoscope.

- high-quality acoustics with clear and reliable sound
- soft and flexible earplugs isolate from noises
- pressure sensitive diaphragm allows to hear high and low frequency sounds, by varying pressure on the chestpiece.
- comfortable flexible headset and angled ear tubes provide an excellent seal
- flexible tubing, to easily move and position chestpiece
- easy-grip moulded chestpiece for multiple hand positions.

GIMA code	3M code	3M™ SINGLE-PATIENT STETHOSCOPES - length 72.4 cm	Minimum order
<b>Paediatric - head Ø 36.2 mm</b>			
51400	SPS-YP1010	3M™ Single-Patient - paediatric	box of 10
51405	SPS-YP1100	3M™ Single-Patient - paediatric	box of 100
<b>Adult - head Ø 45.2 mm</b>			
51410	SPS-YA1010	3M™ Single-Patient - adult	box of 10
51415	SPS-YA1100	3M™ Single-Patient - adult	box of 100



## 3M™ LITTMANN® LIGHTWEIGHT II

Tunable diaphragm for easy low and high frequency monitoring. Lightweight only 118 g. Headset made of aerospace alloy.

GIMA code	3M code	3M™ LITTMANN® LIGHTWEIGHT II S.E. - length 71 cm
32388	2456	■ Littmann® Lightweight II S.E. - pink
32389	2452	■ Littmann® Lightweight II S.E. - caribbean blue
32390	2450	■ Littmann® Lightweight II S.E. - black
32391	2451	■ Littmann® Lightweight II S.E. - burgundy
32392	2454	■ Littmann® Lightweight II S.E. - ceil blue
32393	2453	■ Littmann® Lightweight II S.E. - lilac



## 3M™ LITTMANN® ACCESSORIES

GIMA code	3M code	3M™ LITTMANN® ACCESSORIES
<b>TUNABLE DIAPHRAGM AND RIM + NON CHILL BELL SLEEVES + EARTIPS</b>		
51464	40005	■ For Classic II S.E. - black - blister
51465	40006	■ For Classic II S.E. - grey - blister
51466	40020	■ For Lightweight - black - blister
51467	40021	■ For Lightweight - light brown - blister
<b>TUNABLE DIAPHRAGM + RIM ASSEMBLY + EARTIPS</b>		
51470	40011	■ For Master Cardiology - black - blister
51471	40018	■ For Master Cardiology - grey - blister
51473	40022	■ For Master Classic™ - black - blister
51474	40023	■ For Master Classic™ - grey - blister
<b>TUNABLE DIAPHRAGM + 2 RIMS ASSEMBLY</b>		
51477	40012	■ For Classic II™ - Paediatric - black - blister
51478	40013	■ For Classic II™ - Infant - black - blister
<b>2 TUNABLE DIAPHRAGMS + RIM ASSEMBLY + EARTIPS</b>		
51482	40016	■ For Classic III™, Cardiology IV™, Core - black - blister
51483	40017	■ For Classic III™, Cardiology IV™, Core - grey - blister
<b>EAR TIPS for all models</b>		
51490	40001	■ Ear Tips - black - small and large - blister
51491	40002	■ Ear Tips - grey - small and large - blister
51494	40007	■ Name tag - black - blister
51495	40008	■ Name tag - grey - blister
<b>DIAPHRAGM + RETAINING RING - box of 5 pcs</b>		
32449	36572	■ For Cardiology III (small side) - black
32452	36554	■ For Master Cardiology - black
<b>DIAPHRAGM OR RETAINING RINGS</b>		
51445	MEMB/E3200	■ Diaphragm for Electronic 3100 - 3200 - black
32478	78808303222	■ Diaphragm for Electronic 3000 - dark grey
<b>NEOPRENE RINGS</b>		
32476	36547	■ Neoprene black ring - infant - box of 5
32455	36569	■ Neoprene grey ring - infant - box of 5
51455	36546	■ Neoprene black ring - pediatric - box of 5
32459	36544	■ Neoprene black ring - Classic II, Lightweight - box of 10



## 3M™ LITTMANN® CLASSIC III STETHOSCOPES

The 3M™ Littmann® Classic III™ Stethoscope offers high acoustic sensitivity for exceptional performance when doing general physical assessments.

- It features dual tunable diaphragms and updated design.
- versatile adult and pediatric two-sides chestpiece
  - dual single-piece tunable diaphragms (pressure sensitive)

- small-side diaphragm prevents debris in open bell
- high acoustic sensitivity
- snap tight soft-sealing eartips
- next generation longer-life tubing
- small side converts to open bell



**Authorized  
Distributor**

**3M**

CLASSIC III - RASPBERRY - RAINBOW FINISH



GIMA code	3M code	3M™ LITTMANN® CLASSIC III MIRROR/CHAMPAGNE
32239	5960	■ Littmann® Classic III - plum - mirror
32240	5962	■ Littmann® Classic III - pearl pink - mirror
32243	5861	■ Littmann® Classic III - black - champagne
32245	5863	■ Littmann® Classic III - navy blue - mirror
32246	5864	■ Littmann® Classic III - burgundy - champagne
32249	5959	■ Littmann® Classic III - ceil blue - mirror

GIMA code	3M code	3M™ LITTMANN® STETHOSCOPES - length 69 cm
CLASSIC III - head Ø 43/33 mm		
32290	5620	■ Littmann® Classic III - black
32291	5622	■ Littmann® Classic III - navy blue
32292	5648	■ Littmann® Classic III - raspberry
32293	5627	■ Littmann® Classic III - burgundy
32295	5832	■ Littmann® Classic III - lavender
32296	5835	■ Littmann® Classic III - turquoise
32297	5839	■ Littmann® Classic III - lemon - lime
32299	5621	■ Littmann® Classic III - grey
32300	5623	■ Littmann® Classic III - caribbean blue
32303	5630	■ Littmann® Classic III - ceil blue
32304	5633	■ Littmann® Classic III - pearl pink
32306	5831	■ Littmann® Classic III - plum
CLASSIC III SPECIAL EDITION - head Ø 43/33 mm		
32307	5872	■ Littmann® Classic III - turquoise - smoke chestpiece
32308	5870	■ Littmann® Classic III - black - rainbow finish
32310	5803	■ Littmann® Classic III - black edition
32311	5809	■ Littmann® Classic III - chocolate - copper fin.
32312	5806	■ Littmann® Classic III - raspberry - rainbow fin.
32313	5807	■ Littmann® Classic III - caribbean blue - rainbow fin.
32314	5811	■ Littmann® Classic III - black - smoke finish
32317	5868	■ Littmann® Classic III - burgundy - black finish
32319	5873	■ Littmann® Classic III - grey - smoke chestpiece
32320	5875	■ Littmann® Classic III - lime-green - smoke chestpiece



## 3M™ LITTMANN® CLASSIC II STETHOSCOPES



GIMA code	3M code	3M™ LITTMANN® STETHOSCOPES - length 71 cm
CLASSIC II PEDIATRIC - head Ø 33/25 mm		
32404	2113	■ Littmann® Classic II ped. - black
32405	2119	■ Littmann® Classic II ped. - caribbean blue
32406	2113R	■ Littmann® Classic II ped. - red
32407	2122	■ Littmann® Classic II ped. - raspberry
32381	2153	■ Littmann® Classic II ped. - caribbean blue - rainbow finish
CLASSIC II INFANT - head Ø 27/19 mm		
32376	2124	■ Littmann® Classic II infant - caribbean blue
32410	2114	■ Littmann® Classic II infant - black
32411	2114R	■ Littmann® Classic II infant - red
32380	2157	■ Littmann® Classic II infant - raspberry - rainbow finish

CLASSIC II  
INFANT



CLASSIC II  
PEDIATRIC



## 3M™ LITTMANN® MASTER CLASSIC II



MASTER CLASSIC II



MASTER CLASSIC II  
BLACK EDITION

GIMA code	3M code	3M™ LITTMANN® MASTER CLASSIC STETHOSCOPES length 69 cm - head Ø 44 mm
32425	2146	■ Littmann® Master Classic II - burgundy
32426	2144L	■ Littmann® Master Classic II - black
32471	2141	■ Littmann® Master Classic II - "black edition"



## 3M™ LITTMANN® CARDIOLOGY IV STETHOSCOPES

The 3M™ Cardiology IV helps to catch more of the subtle critical sounds, thanks to the improved acoustics and the new design.











Authorized  
Distributor




3M

- better audibility of high-frequency sounds
- tunable diaphragms for hearing both high and low frequency sounds without turning over the chestpiece (pressure sensitive)
- adult and paediatric sides for more versatility
- single-piece smooth diaphragm, easier to attach and clean
- longer-life tubing and snap tight soft-sealing eartips.

GIMA code	3M code	3M™ LITTMANN® STETHOSCOPES - length 69 cm		
CARDIOLOGY IV SPECIAL FINISH - head Ø 43/33 mm				
		Tubing	Finish	
32630	6205	 Littmann® Cardiology IV	plum	rainbow
32632	6163	 Littmann® Cardiology IV	black	black edition
32634	6165	 Littmann® Cardiology IV	black	rainbow
32635	6166	 Littmann® Cardiology IV	plum	smoke
32636	6168	 Littmann® Cardiology IV	navy blue	black
32639	6200	 Littmann® Cardiology IV	black	black - red stem
32640	6201	 Littmann® Cardiology IV	black	black - blue stem
32641	6203	 Littmann® Cardiology IV	black	black - violet stem

GIMA code	3M code	3M™ LITTMANN® STETHOSCOPES - length 69 cm			
CARDIOLOGY IV - head Ø 43/33 mm					
32606	6152	■	Littmann® Cardiology IV - black		
32607	6184	■	Littmann® Cardiology IV - burgundy		
32608	6154	■	Littmann® Cardiology IV - navy blue		
32609	6155	■	Littmann® Cardiology IV - hunter green		
32610	6156	■	Littmann® Cardiology IV - plum		
32612	6158	■	Littmann® Cardiology IV - raspberry		
CARDIOLOGY IV SPECIAL HIGH POLISH FINISH - head Ø 43/33 mm					
			Tubing	Finish	
32614	6232	■	Littmann® Cardiology IV	black	smoke
32615	6234	■	Littmann® Cardiology IV	caribbean blue	smoke
32616	6238	■	Littmann® Cardiology IV	grey	smoke
32617	6240	■	Littmann® Cardiology IV	black	rainbow
32618	6241	■	Littmann® Cardiology IV	raspberry	rainbow
32619	6242	■	Littmann® Cardiology IV	navy blue	rainbow
32642	6204	■	Littmann® Cardiology IV	black	smoke
32651	6202	■	Littmann® Cardiology IV	navy blue	smoke
CARDIOLOGY IV SPECIAL FINISH - head Ø 43/33 mm					
32643	6190	■	Littmann® Cardiology IV	caribbean blue	champagne
32644	6176	■	Littmann® Cardiology IV	burgundy	champagne
32647	6170	■	Littmann® Cardiology IV	burgundy	mirror
32648	6177	■	Littmann® Cardiology IV	black	mirror
32649	6179	■	Littmann® Cardiology IV	black/champagne	smoke
32674	6239	■	Littmann® Cardiology IV	plum	rainbow*

\*with violet stem



## 3M™ EKO CORE DIGITAL ATTACHMENT FOR CARDIOLOGY IV

### • 32594 3M EKO CORE DIGITAL ATTACHMENT - 8481

Eko CORE allows to transform Littmann Cardiology IV from analog into digital stethoscopes. Single button press digitally amplifies heart, lung and other body sounds up to 40x (at peak frequency vs. analog) adding automated murmur detection (88% sensitivity and specificity), active noise cancellation and wireless listening. Compatible with most major brands and vet stethoscopes. See page 287 for more details

3M



When ON, Eko CORE turns stethoscope into a smart detection tool, when OFF, stethoscope still works as an analog Cardiology IV. Supplied with rechargeable lithium battery (8 hour autonomy) and micro USB charging



## 3M™ LITTMANN® MASTER CARDIOLOGY STETHOSCOPES



Authorized  
Distributor



MASTER  
CARDIOLOGY

3M

MASTER  
CARDIOLOGY  
BLACK EDITION



GIMA code	3M code	3M™ LITTMANN® STETHOSCOPES - length 69 cm	
MASTER CARDIOLOGY - head Ø 51 mm			
32435	2160	■	Littmann® Master Cardiology - black
32436	2163	■	Littmann® Master Cardiology - burgundy
32437	2164	■	Littmann® Master Cardiology - navy blue
32439	2167	■	Littmann® Master Cardiology - plum
MASTER CARDIOLOGY SPECIAL EDITION - head Ø 51 mm			
32356	2175	■	Littmann® Master Card. - black - brass finish
32360	2176	■	Littmann® Master Card. - black - smoke edition
32473	2161	■	Littmann® Master Card. - black edition

## 3M™ LITTMANN® CORE DIGITAL STETHOSCOPES

### 3M™ LITTMANN® CORE DIGITAL STETHOSCOPES

The new 3M™ Littmann® CORE digital stethoscope features outstanding acoustics, comfort and quality of a Littmann® Cardiology IV stethoscope, enhanced by powerful CORE digital attachment technology. It is intended for professional and clinical use on pediatric and adult patients.

#### Eko software connection via Bluetooth

Software allows to capture (15, 30, 60 or 120 second recordings), visualize heart sound waveforms in real time, analyze and share recordings to monitor progression of a disease. Eko App is available for iOS and Android devices.

#### Active noise cancellation

It reduces unwanted background sounds allowing to auscultate with greater confidence.

#### Toggle between analog and amplified listening modes

Two tunable diaphragms (adult and pediatric) allow to listen both high and low frequency sounds by simply adjusting pressure on chestpiece.

#### Up to 40x amplification

Based on comparison of analog versus electronically assisted amplified listening with maximum volume at peak frequency (125 Hz). Adjustable volume by clicking buttons on the CORE side.

- Tunable, dual-sided stainless steel chestpiece with open or closed bell



Smartphone not included



GIMA code	3M code	3M™ LITTMANN® CORE DIGITAL STETHOSCOPE - length 69 cm	Tubing	Finish
32600	8490	Littmann® Core Digital	black	black
32601	8572	Littmann® Core Digital	black	rainbow
32602	8863	Littmann® Core Digital	black	copper
32603	8869	Littmann® Core Digital	black	mirror
32594	8481	EKO Core digital attachment - spare*		

\*See page 286

- rotating adult and pediatric chestpiece
  - soft-sealing ear tips conform to ears, providing an excellent acoustic seal and comfortable fit
  - fully charged battery lasts 8 hours in continuous transmission mode
  - 3 selectable filters: cardiac, pulmonary and wide
  - 7 sound amplification levels
  - heart murmur, tachycardia and bradycardia detection
- Supplied with USB cable, spare snap tight soft-sealing eartips, non-chill bell sleeve, multilingual user manual: GB, FR, IT, ES, PT, DE, NL, PL, HU, DK, SE, NO.



#### TECHNICAL SPECIFICATIONS

Chestpiece:	two-sided head size: 3.3 cm (1.3 inch) 4.3 cm (1.7 inch)
Membrane:	floating material: epoxy / glass fiber
Battery:	rechargeable battery
Operating time:	8 hours continuous transmission with fully charged battery
Overall length:	69 cm
Weight:	net: 232g chestpiece: 87g
Automatic shutdown:	5 min.

## LINKTOP DIGITAL STETHOSCOPE - WITH BLUETOOTH 5.0

### • 32599 LINKTOP STETHOSCOPE - with Bluetooth 5.0

This electronic stethoscope enables recording of respiratory and heart sounds by doctors, medical personnel and ordinary people. It is intended for adult, pediatric and infant patients, for both home and professional use.

#### Examination quality control

The system helps carry out the examination correctly: a step by step tutorial will guide you.

#### Easy contact with a doctor

Enables remote consultation sharing data with your doctor via e-mail or Social applications.

#### Noise control


It detects and automatically monitor excessive noise in the room, that might impact the results.

#### TECHNICAL SPECIFICATIONS

Operating mode:	continuous
Battery:	Built-in lithium-ion battery (non-removable) - 200mAh Power: 3.3-4.2V Charging voltage/current: 5V DC / 500mA Charger: magnetic USB
Diaphragm:	Diameter: 43.8 mm Material: polyurethane-coated silicone, non-chill diaphragm cover Type: digital electronic filtering, ambient noise reduction
Sound:	Transmission: via Bluetooth, headphone and recording cable Frequency range: 20-3 KHz Amplification: up to 24 X 85% ambient noise reduction
Auscultation mode:	remotely via Homedoctor System or via 3.5 mm headset
Size - Weight:	Ø 45 x h 26.1 mm - 62 g
Protection class:	Ila type BF, IP22.
Norms:	EN 60601-1: 2006+A11: 2011+A1: 2013+A12: 2014, EN 60601-1-2: 2015

### Automatic start/stop

Records sounds automatically once the stethoscope is put to the body correctly. The device does not analyze the recorded sounds. It operates with built-in Lithium battery.



iOS 11 or higher




Android 6.0 or higher

#### STANDARD ACCESSORIES

Mini jack 3.5 mm headset  
Mini jack 3.5 mm - mini jack 3.5 mm cable  
Magnetic USB charging cable  
User manual: GB, FR, IT, ES, DE



Free App download





# GIMA 5 IN 1 MULTIFUNCTIONAL HEALTH MONITOR



**5 in 1**  
Temperature  
Blood pressure  
SpO<sub>2</sub>  
ECG  
Respiration

Download Health monitor App via:



Blood Pressure Measurement

- **35192 GIMA 5 IN 1 MULTIFUNCTIONAL HEALTH MONITOR**  
Gima Health Monitor 5 in 1 is a small and portable multifunctional device, intended for measurement of 5 vital signs: temperature, blood pressure, blood oxygen, ECG heart rate and respiration rate.

Gima Health Monitor works with wireless connection for data transmission to a mobile phone application, where measurements are recorded and stored.

The device has infrared and pressure sensors to collect information. Health monitor free App (GB, IT)  
Supplied with magnetic detachable arm cuff, USB charging cable, multilingual manual (GB, FR, IT, ES, DE).

- **35193 CUFF 22-35 cm - spare**

## TECHNICAL SPECIFICATIONS

### Blood pressure Heart Rate

Measuring method: oscillometric  
Cuff size: 22-35 cm  
Measuring range: 0-300 mmHg  $\pm 3$  mmHg  
Heart rate: 40-180 bpm  $\pm 5\%$   
Systolic pressure: 60-230 mmHg  
Diastolic pressure: 40-130 mmHg

### ECG

Measurement mode: Single lead  
Input impedance:  $\geq 100$  K $\Omega$ ; Input circuit current:  $< 0.1$   $\mu$ A  
Calibration voltage: 1 mV  $\pm 0.05$  mV  
Sensitivity tolerance:  $< 10\%$   
50Hz interference suppression filter:  $> 20$  dB  
Maximum input range:  $\pm 4.5$  mV  
Polarization resistance voltage:  $\pm 300$  mV  
Amplitude variation:  $< 10\%$  Frequency response: 0.5-40 Hz

### Blood oxygen

Measuring method: reflective  
Method Measuring range: 90-99%  $\pm 2\%$   
**Temperature**  
Measuring method (forehead): infra-red  
Measuring range: 28-42°C  
Accuracy: 35-42°C  $\pm 0.3^\circ\text{C}$ ;  $< 35^\circ\text{C}$   $\pm 0.4^\circ\text{C}$

### Device

Power voltage: DC3.7V  
Built-in battery: rechargeable lithium-ion  
Battery life: 500 measurements  
Size - weight: 70x70x18.4 mm - 70g  
Wireless communication: Bluetooth 4.0  
Working frequency: 2.4000-2.4835 GHz  
Electric shock protection: BF-style applied part



# GIMA OTOSCOPE WITH CAMERA

- **35195 GIMA OTOSCOPE WITH CAMERA - Android**
- **35196 GIMA OTOSCOPE WITH CAMERA - Android + iOS**

Portable, handheld optical magnifying device with short focal length camera, intended for the examination of the ear, external auditory canal and tympanum.

The high resolution camera can provide great images and videos, there are 6 LED lights on the top of the camera which light the path and increase the visual field.

It has rechargeable battery and different connecting cables, based on phone type.

By connecting the otoscope to the App, videos and still images can be captured, transmitted and visualized on the device.

It is suitable for adults and children over 3 years old.

- **35197 SILICONE SPECULA for 35195-6 single patient - box of 50**

## TECHNICAL SPECIFICATIONS

**Camera:**  
Diameter: 3.9 mm  
Pixel: 1,000,000 pixels  
Resolution: 720 p  
Focal length: 1.5-2.0 cm  
Horizontal viewing angle: (FOV) 70°  
Frame rate: 15 fps  
Power supply: Lithium-ion battery (non-removable)  
Battery life: More than 500 charging cycles  
Charging voltage/current: 5V DC 2A/1A/500 mA  
Dimensions - weight: 134.5x  $\varnothing$  17.8 mm (5.3x $\varnothing$  0.7 inch) - 24.5 g  
Classification: BF type application part  
Protection class: IP22

## COMPATIBILITY

Mobile phone and tablets: Android 6.0 or higher (35195-6)  
Iphone: iOS 9.0 or higher (35196 only)



## STANDARD ACCESSORIES

1 Magnetic USB-C cable,  
1 Magnetic iOS cable,  
1 Micro USB adapter cable,  
1 Magnetic USB charging cable,  
1 Adaptor for tongue depressor  
Multilingual manual (GB, FR, IT, ES, DE).

## CHECKME™ LITE HEALTH MONITOR WITH BLUETOOTH

### • 35185 CHECKME™ LITE HEALTH MONITOR with bluetooth

Innovative all-in-one device with multiple functionalities into one compact and portable unit. It allows to measure simultaneously ECG, heart rate, QRS duration, SpO<sub>2</sub>, pulse rate and pulse index. With colour touch screen, well organized user interface and audio instructions, is very intuitive and easy to use. Clinical approved accuracy.

- supports both cable and cable-free measurement of ECG and SpO<sub>2</sub> (optional cable)
- checks, captures and identifies abnormal ECG in 20 sec.
- professional ECG algorithm provides heart rate, QRS duration, ST segment and rhythm analysis
- check blood oxygenation with built-in SpO<sub>2</sub> sensor in 20 sec
- high quality ECG waveform can be saved and replayed
- professional PC data management software for review and generating reports (compatible with windows OS) MyBeats Hub App.

### • 35190 EXTERNAL SpO<sub>2</sub> ADULT SENSOR - reusable - optional

**DAILY CHECK  
JUST TAKES  
20 SECONDS**

CE 0197

**ECG + HR + SpO<sub>2</sub> +  
QRS + Pulse Rate + PI**

Manual: GB, IT, ES, DE, FR  
Audio instructions:  
GB, PL, DE, IT, FR, ES, HU  
PC software: GB



35185

Size: 88x56x13 mm Weight: 64 g

#### STANDARD ACCESSORIES

PC software: GB Neck strap  
ECG cable Charging cable, micro D  
ECG electrodes

## CHECKME™ PRO VITAL SIGNS MONITORS - WIRELESS WITH BLUETOOTH

### • 35186 CHECKME™ PRO VITAL SIGNS MONITOR - with Bluetooth • 35187 CHECKME™ PRO VITAL SIGNS MONITOR WITH ECG HOLTER - with Bluetooth

All-in-one, compact, versatile and portable wireless vital signs monitors for checking your health anytime anywhere.

Wide range of application scenarios, including: outpatient, emergency, surgeries, telemedicine. MyBeats Hub App.

### • 35188 AIR BP BLOOD PRESSURE UNIT\* - optional

### • 35189 AIR BP BLOOD PRESSURE UNIT\* WITH DISPLAY - optional

Ultra-portable upper arm blood pressure device. See below.

\*Includes main unit, cuff and charge cable

### • 35190 EXTERNAL SpO<sub>2</sub> ADULT SENSOR - reusable - optional



Size: 88x56x13 mm  
Weight: 80 g

**ECG + SpO<sub>2</sub> +  
BP (needs 35188-9)  
+ Sleep Apnea +  
Temp + Pedometer  
+ 24 hours ECG  
holter (only 35187)**

CE 0197

#### STANDARD ACCESSORIES

ECG cable, SpO<sub>2</sub> sensor, ECG electrodes, charge cable, neck strip, user manual, protective cover, wrist band, Y adaptor and sport chest band (only 35187)

#### CHECKME™ PRO FEATURES

##### ECG

- supports both cable and cable-free operation
- 500 Hz sampling rate and wide bandwidth
- 30/60s waveform can be replayed
- professional ECG algorithm to provide Heart Rate, QRS duration, ST segment, QT/QTc interval, and rhythm analysis ECG holter (only 35187)
- easy to wear and use
- continuously record ECG for 24 hours
- check report and ECG waveform on APP or PC
- the report includes heart rate, rhythm and HRV (heart rate variability)
- holter report can be stored in Cloud, printed or saved as PDF

##### SpO<sub>2</sub>

- supports both cable and cable-free operation
- measurement of oxygen saturation, pulse rate and pulse strength

##### Sleep apnea screening

- SpO<sub>2</sub> monitor for OSA (Obstructive Sleep Apnea)
- records and tracks SpO<sub>2</sub> and Pulse Rate up to 10 hours
- mobile APP to check SpO<sub>2</sub> change in details

##### Blood Pressure via Bluetooth (needs code 35188 or 35189)

- manage all vital signs data together - see below

##### Temperature - Integrated infrared temperature sensor

- quick measurement with high accuracy
- safe and comfortable, no need to wake up child while sleeping

##### Pedometer

- accurately calculate steps, calories and amount of fat burned
- built-in high accuracy 3D smart sensor

##### APP - support iOS and Android

- built-in Bluetooth, all data can be exported from device to phone/tablet

##### PC browser

- medical data management software
- user data, user profile, readings and wave form can be exported from Checkme to the browser by USB

Manual: GB, ES, IT, DE, FR

Audio instructions: GB, ES, IT, DE, FR, PL, RU, HU

Pc software: GB

App: GB, DE, FR, ES



## AIR BP ULTRA-PORTABLE SMART BLOOD PRESSURE MONITOR

### • 35188 AIR BP BLOOD PRESSURE UNIT

### • 35189 AIR BP2 BLOOD PRESSURE UNIT WITH DISPLAY

Ultra-portable smart upper arm blood pressure device.

- one battery charge for 1000 measurements

- easy to use, robust and durable

- professional measurement

- readings:

- systolic, Diastolic, Pulse Rate;
- pulse Pressure, MAP (Mean Arterial Pressure)
- irregular heartbeat

- work with Smartphone

- real-time Virtual Mercury Column in App

- during measurement

- real-time Pulse Waveform



Smartphone  
not included



35189

- multi-patient Management

- unlimited recording

- works with Checkme Pro 35186, 35187.

- Supplied with cuff, charge cable and

- multilingual manual (GB, FR, IT, ES,

- DE).



#### TECHNICAL SPECIFICATIONS

##### Cuff:

Wireless:

Charge input:

Battery life:

Pressure measurement range:

Pulse rate:

Mobile App for iOS:

Mobile App for Android:

Size - weight:

Clinical accuracy:

Upper arm circumference: 22-42cm

Bluetooth 4.0 BLE

Micro USB, DC 5V

1000 measurements, rechargeable

0-300 mmHg ±3 mmHg

40 to 200 bpm ±2 bpm

iOS 9.0 or above, iPhone 4s/iPad 3 or above

Android 4.4 or above, with Bluetooth 4.0 BLE

68x20 mm (main unit) - 30g (main unit)

meet IEC 80601-2-30



# PC-300 SPOT CHECK BLUETOOTH MONITOR

**Standard:**  
SpO<sub>2</sub>, PR, NIBP, TEMP

**Optional ECG, GLUCOMETER**

FDA 510 (K)  
CE 0476

35162



Size:  
165x96x68 mm

Memory of  
6,000 NIBP measures



Bluetooth 2.0  
and 4.0 standard



## • 35162 PC-300 SPOT CHECK MONITOR

PC-300 handheld Spot-check monitor measures SpO<sub>2</sub>, Pulse Rate, NIBP and TEMP. Widely used in hospitals, clinics and family daily measurement. Equipped with Bluetooth and USB interface, allows to transfer data to PC, tablets and smartphone (Android and iOS).

- up to 6000 groups NIBP data storage, up to 100 different patients (each user can store 999 measurement records)
- quick ear probe TEMP measurement result in 5 seconds
- data transfer to PC/Smartphone by USB or Bluetooth
- optional NIBP pediatric cuff and SpO<sub>2</sub> pediatric probe
- optional ECG and Glucometer
- built-in rechargeable lithium battery
- communication protocols available on request

35162



### STANDARD ACCESSORIES

SpO<sub>2</sub> adult probe  
NIBP adult cuff  
Ear thermometer (probe covers not included)  
Lithium battery with charger  
Carrying bag  
User manual: GB, FR, IT, ES

### TECHNICAL SPECIFICATIONS

<b>SpO<sub>2</sub></b>	
Measuring range:	0-100%
Accuracy:	±3% (70-100%)
<b>Pulse Rate</b>	
Measuring range:	30-240 bpm
Accuracy:	±2% or ±2 bpm (whichever is greater)
*Root-mean-square value of deviation according to ISO 80601-2-61, ISO 9919	
<b>NIBP</b>	
Pressure range:	0-300 mmHg (0-39.9kpa)
Accuracy:	±3 mmHg
Measuring range:	Systolic pressure: 30-270 mmHg Diastolic pressure: 20-235 mmHg MAP: 10-220 mmHg
<b>TEMP</b>	
Measuring range:	32-43.0°C
Accuracy:	±0.2°C (36-39°C) - ±0.3°C (other)
Measuring time:	<5 s
<b>ECG (Optional)</b>	
Heart Rate measuring range:	30-240 bpm
Heart Rate accuracy:	±2 bpm or ±2% whichever is greater
Display scale:	5.0 mm/mV ±10%
Common-mode rejection ratio (CMRR):	≥60 dB
<b>Blood Glucose (Optional)</b>	
Measuring range:	20 to 600 mg/DL
SEE other specification at page 1	
<b>Power Supply</b>	
Battery:	3.7 V built-in Li-ion battery
Operating voltage:	3.6-4.2 VDC
Operating current:	≤800 mA
Charger:	100 - 240 VAC, 50/60 Hz, 5 VDC or USB

GIMA code	PC-300 ACCESSORIES	
35164	SpO <sub>2</sub> pediatric probe - optional	
35165	SpO <sub>2</sub> adult probe - spare	35165
35166	NIBP pediatric cuff 10-19 cm - with extension cable - optional	
35167	NIBP adult cuff 22-30 cm - spare	35167
35168	NIBP adult large cuff 27-42 cm	
35169	NIBP adult extra large cuff 40-48 cm	
35170	Ear infrared thermometer	
35171	Ear probe cover - box of 500	35170
35172	Lithium battery - spare	
35173	Carrying case	
<b>PC-300 ACCESSORIES: glucose and ECG (optional)</b>		
24108	GIMA Glucose monitor* - GB, IT, SE, FI	
24110	GIMA Glucose monitor Kit* - IT, ES	
24111	GIMA Glucose monitor Kit* - GB, FR	
24114	GIMA Glucose monitor Kit* - Bluetooth - GB, IT	
24118	Glucose strips - box of 25	
24119	Glucose strips - box of 50	
24120	Glucose strips - box of 100	
35176	USB cable for On Call Plus II glucose monitor	24108, 24110-1, 24114
35177	USB cable for Gima glucose monitor (24108/10/11/14)	
35178	ECG module** needs 33248	35178
33248	ECG pin lead cable 3 leads	33248

See glucose monitor accessories at page 1

See electrodes at page 333-334

\*Needs USB cable 35176 to connect to PC-300

\*\*ECG module can be used without 3 leads cable in palm mode

# ARMFIT+ BLOOD PRESSURE MONITOR WITH ECG

Vihealth App



## • 35198 ARMFIT+ BLOOD PRESSURE MONITOR WITH ECG

Armfit+ is intended to be used for real time monitoring, measuring, displaying, reviewing and storing ECG and blood pressure variations, at home or healthcare facilities. ECG can be recorded without cable only. Built-in Bluetooth wireless connectivity allows to share measurement records to mobile phones and tablets. Supplied with one adult cuff, charging cable, quick guide and multilingual manual in GB, FR, IT, ES, DE.



Start/stop button

FDA  
CE 0197

### ECG RECORDING WITHOUT CABLE



### TECHNICAL SPECIFICATIONS

<b>Blood Pressure Measurements</b>		<b>ECG Recording</b>		<b>Wireless:</b>	
Technology:	Oscillometric Method	Lead type:	Integrated ECG electrodes	Charge input:	Built-in Bluetooth 4.0
Pressure measurement range:	0-300 mmHg	Lead set:	Lead I, Lead II, Chest Lead	Battery type:	Micro USB, DC5V
Accuracy:	±3mmHg	ECG measurement:	30s recording	Battery run time:	Rechargeable lithium-polymer
Pulse rate range:	40 to 200 /min	Heart rate range:	30-250/min ±2 /min	Charge time:	500 measurements
Pulse rate accuracy:	±2 /min	ECG records:	10	Classifications	2 hours
Clinical accuracy:	Meet IEC80601-2-30	<b>Device</b>		Protection:	Type BF
Blood pressure records:	50	Size - weight (main unit):	135x45x20 mm - 240 g	Dust & water resistance:	IP22
		Cuff size:	Adult cuff: 22-42cm	Norms:	EN 60601-1-2

## GIMA BLUETOOTH BLOOD PRESSURE MONITOR



32916 Size 131x73x29.4 mm



Irregular  
Heartbeat  
Detection



Bluetooth  
Version



Excessive Body  
Motion Detector



2x60 Groups  
of Memory



### COMPATIBILITY

For iOS devices: The operating system must be iOS 8 or more, such as iPhone 4S, iPhone 5/5C/5S, iPhone 6/6 Plus and so on.  
For Android devices: The operating system must be 4.3 or more

- **32916 GIMA BLUETOOTH BLOOD PRESSURE MONITOR** Bluetooth BPM with innovative tubeless technology and super slim design. It measures blood pressure and heart rate, irregular heartbeat detection and excessive body motion.
  - Large LCD display 86x24 mm, blue mode display with backlight
  - comfortable cuff for arm circumference 22x42 cm (nylon outside + polyester inside in contact with skin)
  - date, time and low battery indication
  - 2 groups of memory (2 users)

Multilingual box and manual: GB, FR, IT, ES.

### TECHNICAL SPECIFICATIONS

Measuring method: Oscillometric - continuous mode operation  
Measurement range: Rated cuff pressure 0-299 mmHg  
Measurement pressure: SYS: 60-230 mmHg, DIA: 40-130 mmHg  
Pulse: 40-199 bpm  
Mechanical buttons: User 1 - User 2 - Query - Power  
Power supply: 3.7V - 1000 mAH built-in rechargeable li-polymer battery - battery life 2 years  
Charge power: up to 300 times  
AC Adaptor (included): Input 100-240V, 50-60Hz

## RI-CHAMPION® SMART PRO+

- **49950 RI-CHAMPION® SMART PRO+ BLOOD PRESSURE MONITOR - 1735 - adult cuff**
- **49951 RI-CHAMPION® SMART PRO+ BLOOD PRESSURE MONITOR WITH BLUETOOTH - 1735 BT - adult cuff**

A clinically validated blood pressure monitor, designed for fast and reliable readings. Advanced performance with irregular heartbeat detection and averaging capabilities: analysis of 3 successive blood pressure measurements.

- Optional Bluetooth® connectivity (only 49951)
- fast and quiet operation for home and professional use.
- 200 measurements on one set of 4 AA batteries
- large, easy to read backlit screen
- meets EN1060-4, NIBP clinical investigation
- **49955 ADULT SMALL CUFF 15-24 cm - 12632 - optional**
- **49956 ADULT CUFF 24-43 cm - 12633 - spare**
- **49957 AC ADAPTER - 12631 - optional**



Air tube length: 80 cm



49950

### TECHNICAL SPECIFICATIONS

Heart Rate Range: 40-199 beats/minute  
Systolic Measurement Range: 60-255 mmHg  
Diastolic Measurement Range: 30-195 mmHg  
Pulse Rate Measurement Range: 40-199 beats / minute  $\pm 4\%$  of reading  
Maximum Inflation Pressure: 280 mmHg  $\pm 3$  mmHg or  $\pm 2\%$  of reading  
Power Source/Supply: 4x 1.5 V AA alkaline batteries / DC + 6 V / 1 A  
Battery Life: 200 Readings  
Memory: maximum 400 memory records  
Size - weight: 141x121x72 mm - 350g\* \*without battery

Bluetooth®  
Connectivity  
(only 49951)

## ADULT AND PEDIATRIC B.P. MONITOR WITH SpO<sub>2</sub> OPTION

Supplied with large cuff, USB cable, software and multilingual manual (GB, FR, IT, ES, PT)



32902



PC software for data review, result analysis, trend chart observation and report print

### TECHNICAL SPECIFICATIONS SPHYGMO

Measurement method: oscillometric  
Measurement range: 0-39.6 kPa (0-297 mmHg) Resolution: 3 mmHg  
Accuracy: static pressure:  $\pm 0.4$  kPa ( $\pm 3$  mmHg)  
Inflation - Deflation: automatic inflation - automatic multistep deflation  
Display: 2.8" colour LCD screen, USB interface  
Power: four "AA" batteries or optional power adapter  
Safety: class II device type BF applied part  
Dimension - Weight: 130x110x80 mm - 300 g

- **32902 LEO ELECTRONIC SPHYGMOMANOMETER - with software** Electronic sphygmomanometer for fully automatic measurement of blood pressure provided with large, high definition colour LCD display.

- Suitable for adult, pediatric and neonatal use.
- data storage (3 users) for up to 100 groups of data
- automatic one-touch operation
- alarm function with possibility to set alarm limits
- dual scales: kPa and mmHg
- selection of five cuff sizes
- automatic power off
- optional SpO<sub>2</sub>

- **80556 POWER ADAPTOR**

### TECHNICAL SPECIFICATIONS SpO<sub>2</sub>

SpO<sub>2</sub> range: 0%-100% (resolution 1%)  $\pm 2\%$  (70% - 100%)  
PR range: 30-250 bpm, (resolution 1 bpm)  $\pm 2$  bpm or  $\pm 2\%$  (select larger)

GIMA code	SpO <sub>2</sub> PROBES
32903	SpO <sub>2</sub> reusable adult probe with 1.5 m cable
35107	SpO <sub>2</sub> reusable neonatal probe*
35109	SpO <sub>2</sub> disposable neonatal** and adult** probe*
32917	Extension cable for 35107, 35109 to 32902

\*Need extension cable 32917

\*\*Neonatal below 3 kg and adult over 40 kg

GIMA code	CUFFS	Size	Suitable for
80551	Small	6-11 cm	Child small
80552	Small/medium	10-19 cm	Child
80553	Medium	18-26 cm	Adult
80554	Large	25-35 cm	Adult large
80555	X-Large	32-43 cm	Adult extra large




# iHEALTH WIRELESS PERSONAL HEALTHCARE PRODUCTS

## iHEALTH MYVITALS APP - free

- track data, graphs and history
- multi-patient App (sort measurements data per users)
- free and secure data storage
- share results with your healthcare professional

To manage wireless:

- 1 iHEALTH PULSE OXIMETER - page 391
- 2 iHEALTH BODY ANALYSIS SCALE - page 94
- 3 iHEALTH B.P. MONITOR - ARM
- 4 iHEALTH B.P. MONITOR - WRIST



## iHEALTH products to manage your personal health

Bluetooth connectivity for iPad, iPhone, iPod and Android system, allow to easily measure and track personal data and share instantly with family or doctor.

The powerful iHealth MyVitals App will also allow to manage all your health data with custom graphs, statistics, trends and tracks the relation among various parameters such as blood pressure, weight, calorie intake and activities.

App compatible with all Apple and Android platforms.

Includes a free iHealth Cloud service.

iHealth MyVitals App available in: GB, FR, IT, ES, DE, NL, GR, HU, PT, RO, RU, TR, JP, KR, CN, AR. 2 years warranty.



## 3 iHEALTH TRACK CONNECTED ARM BLOOD PRESSURE MONITOR

CE 0197



European Society Hypertension



For iOS and Android version 4.4 +

See the list of compatible devices on [ihealthlabs.eu/support](http://ihealthlabs.eu/support)

### • 23499 iHEALTH TRACK CONNECTED ARM B.P.M.

- clinically validated blood pressure (ESH)
- systolic, diastolic and heart rate (number of beats per minute)
- evaluation of measurements as recommended by the WHO
- detection of arrhythmia
- colour changing display
- easy to use and comfortable
- 60 memories
- one-Click: save all your measurements in MyVitals App account

### iHEALTH MyVitals App:

- track data, graphs and history on the iHealth MyVitals App
- add measurement reminders, free and secure data storage
- share results with friends or healthcare professionals

### • 23497 ADULT CUFF - 22-42 cm - spare

### • 23498 OBESE CUFF - 42-48 cm

#### TECHNICAL SPECIFICATIONS

Connectivity: Bluetooth 4.0  
Size: 98x98x46 mm  
Cuff circumference: 22-42 cm  
Weight: 438 g (cuff + batteries included)  
Measuring method: Oscillometric, with automatic inflation and deflation

Power: 4x1.5V size AAA batteries  
Battery life: 250 measurements  
Range: Sys: 60-260 mmHg,  
Dia: 40-199 mmHg  
Pulse rate range: 40-180 bts/min

## 3 iHEALTH ARM B.P. MONITORS

CE 0197



Smart and thin blood pressure monitor with direct visualization on its LED screen of the last blood pressure measurement



European Society Hypertension



Easily saves all your measurements into the iHealth MyVitals App thanks to Bluetooth 4.0 synchronization

Weight: 232 g

### • 23495 iHEALTH NEO BP55 ARM B.P. MONITOR - with display

- medically validated blood pressure monitors
- easy to read wide Backlit screen
- measurement of blood pressure (systolic, diastolic) and of heart rate (number of beats per minute)
- detection of arrhythmia
- multiple users and unlimited memories
- view historical readings and WHO classification

Multilingual box and manual: GB, FR, IT, ES, DE, GR, PT, NL.

#### TECHNICAL SPECIFICATIONS

Connectivity: Bluetooth 4.0  
Dimensions: 135x55x12 mm  
Screen dimensions: 30.4x27.8 mm  
Cuff circumference: 22-42 cm  
Measuring method: Oscillometric, with automatic inflation and deflation  
Power: DC: 5 V, 1.0 A, 3.7 V, Li-ion battery  
Range: Sys: 60-260 mmHg  $\pm 3$  mmHg  
Dia: 40-199 mmHg  $\pm 3$  mmHg  
Pulse: 40-180 bts/min



23500

## 4 iHEALTH WRIST B.P. MONITORS

CE 0197



European Society Hypertension



### • 23501 iHEALTH SENSE BP7 WRIST B.P. MONITOR

### • 23502 iHEALTH VIEW BP7s WRIST B.P. MONITOR - with display

- medically validated blood pressure monitor
- easy to read wide Backlit screen (only 23502)
- measurement of blood pressure (systolic, diastolic) and of heart rate (number of beats per minute)
- detection of arrhythmia
- best wrist position sensor for optimum measurement
- evaluation of measurements as recommended by the WHO\*

Multilingual box and manual: GB, FR, IT, ES, DE, GR, PT, NL.

#### TECHNICAL SPECIFICATIONS

Connectivity: Bluetooth 4.0  
Dimensions: 72x74x17.6 mm  
Screen dimensions: 44x26 mm  
Cuff circumference: 13.5-22 cm  
Measuring method: Oscillometric, with automatic inflation and deflation  
Power: DC: 5 V, 1.0 A, 1x3.7 V, Li-ion 400 mAh  
Range: Sys: 60-260 mmHg  
Dia: 40-199 mmHg  
Pulse: 40-180 bts/min




23502

\*World Health Organization

## 24-HOUR ABPM, SpO<sub>2</sub> AND PULSE RATE AMBULATORY MONITOR

- **35110 GIMA ABPM + Pulse rate with software**
  - **35112 GIMA ABPM + Pulse rate with software and Bluetooth**
  - **35111 GIMA ABPM + Pulse rate + SpO<sub>2</sub> with software**
- GIMA ABPM module measures the blood pressure using the oscillometric method with step deflation. Two modes of measurement: manual and automatic. Each mode displays the diastolic, systolic and mean blood pressure. In the MANUAL mode, only one measurement is conducted for each time. In AUTO mode, the measurement is cycled and can be set at intervals: 5/10/15/20/30/45/60/90 min. (35111), 15/30/60/120/240 min. (35110), 15/20/30/40/60/90/120/240 min (35112).
- compact and portable, easy to use
  - suitable for adult, pediatric and neonatal patient
  - large colour LCD display of ABPM, SpO<sub>2</sub> and pulse rate
  - adjustable audible and visual alarms
  - real-time ambulatory monitoring 24 hours storage and review of date
  - clinically proven accuracy
  - all data can be transferred to a PC through Windows-based software or to a smartphone through Bluetooth (35112 only).
  - **35113 CHILDREN CUFF - arm circumference 18-26 cm - spare**
  - **35114 ADULT CUFF - arm circumference 25-35 cm**
  - **35115 ADULT LARGE CUFF - arm circumference 33-47 cm**
  - **35116 THIGH CUFF - thigh circumference 46-66 cm**
  - **35117 EXTENSION TUBE FOR CUFFS (35113/4/5/6) - 1.5 m - spare**
  - **35118 ADULT SpO<sub>2</sub> PROBE - reusable - spare**
  - **35119 CARRYING BAG - spare**



### STANDARD ACCESSORIES

- |  |   |
|--|---|
| Carrying bag   | Software (GB, FR, IT, DE, ES, PL, RO, SK, TR, RU) |
| 3 nylon cuffs (pediatric, adult, adult large) - latex free |   |
| SpO <sub>2</sub> probe (only code 35111)                   | Cuff connection tube 1.5 m                        |
| User manual: GB, IT, FR, ES, DE                            | Alkaline batteries                                |

\*Only for 35110, 35112



### TECHNICAL SPECIFICATIONS

<b>SpO<sub>2</sub> (35111 only)</b>	Alarm:	systolic	40-270 mmHg
Measurement range: 0-100%		diastolic	20-235 mmHg
Resolution: 1%		Map	10-270 mmHg
Accuracy: 70-100% ±2%			(35111 only)
Alarm range: 0-100%			
<b>NIBP</b>	<b>Pulse rate</b>		
Method: oscillometry	Range:	0-250 bpm (35111)	
Mode: manual/automatic/continuous		40-240 bpm (35110, 35112)	
Measurement range: 0-290 mmHg	Resolution:	1 bpm	
(0 KPa - 38.67 KPa)	Accuracy:	±1 bpm	
Automatic measurement interval:	Alarm range:	30-250 bpm	
5, 10, 15, 30, 45, 60, 90, 120 min. (35111)	<b>Device</b>		
15, 30, 60, 120, 240 min. (35110),	Display:	colour LCD	
15/20/30/40/60/90/120/240 min (35112)	Power:	two "AA", 1.5V alkaline batteries	
Resolution: 1 mmHg	Dimension:	128x69x36 mm	
Overpressure protection: 290 mmHg	Weight:	<350 g (including batteries)	
	<b>Operating system</b>		
	Windows XP/Seven, 8, 8.1, 10		
	(at 32 & 64 bit)		

## RIESTER RBP-100 BLOOD PRESSURE MONITOR

- **49960 RIESTER RBP-100 B.P. MONITOR - 1740 - table**
  - **49961 RIESTER RBP-100 B.P. MONITOR - 1741 - trolley**
- Clinical grade digital blood pressure monitor for fast and reliable readings. Clinically validated to **international standards BHS, ESH, AAMI**. Clinically validated for patients with special conditions: hypertension, diabetes, pregnancy, pre-eclampsia, arteriosclerosis, end-stage renal disease, obesity, elderly and children > 3 years of age. Two measurement modes: auscultatory (manual) and oscillometric (automated). Auscultatory mode with auto-deflate (3 mmHg/sec) provides consistent patient BP measurement and allows clinicians to verify automated readings without removing the cuff. Average mode (3x readings) allows for a more objective measurement for clinicians and helps mitigate the risk of elevated readings due to white coat hypertension. Interval settings in average mode 15, 30, 45, 60 sec. It measures BP and pulse range, systolic, diastolic, heart rate and MAP.

- easy to read 4" LCD screen
  - arrhythmia detection
  - large memory: 210 readings
  - easy to use one touch operation
  - display panel with WHO Blood Pressure Value Classification (colour coded)
- Supplied with 2.5 m air tube, 2 cuffs (M and L-XL), NiMH battery pack, AC/DC adapter (EU, US, UK, Austr.). Multilingual manual (GB, FR, IT, ES, DE, RU).

- **49964 RIESTER CHILDREN VELCRO CUFF 14-22 cm with connector - 162 - optional**



### TECHNICAL SPECIFICATIONS

Measurement mode:	oscillometric, auscultatory	Cuff pressure:	0-310 mmHg
Measurement rate:	systolic: 60-255 mmHg	Power supply:	AC/DC Adapter 7.5V/1.5A
	diastolic: 30-200 mmHg		NIMH AA 4.8V 2400 mAh
	pulse: 40-200 bpm		rechargeable battery pack
Accuracy:	static: ±3 mmHg	Battery:	1.000 measurements per full charge
	pulse: ±5%	Size - weight:	170x135x41 mm - 510g (device only)
Latex free cuffs:	M: 22-32cm, L-XL: 32-52cm	Certificates:	ISO EN13485, Medical Device Class IIa



## MICROLIFE AFIB BLOOD PRESSURE MONITOR - STROKE PREVENTION



Measurement range:  
20-280 mmHg (pressure),  
30-200 beat/minute (pulse)

CE 0044

Size: 160x80x32 mm  
Weight: 298 g including batteries

32881

- **32868 MICROLIFE WatchBP Home A (Professional use) + SOFTWARE**
- detection of atrial fibrillation (specific heart arrhythmia)
- embedded ESH/AHA measurement guidelines lead to accurate home measurement data physician can trust in
- automated data tabulations displays averages for morning, evening and overall measurement
- clinically tested (BHS protocol)
- MAM technology (automatic analysis of 3 consecutive measurements)
- 250 Data memory in «USUAL» mode
- USB port and mains adapter port
- low battery indication
- 4x1.5 V AA batteries

Supplied with carrying bag, USB cable, soft cuff 22-32 cm, software (GB) and manual (GB, IT, FR, DE). Other languages available from web (ES, DK, GR, FI, NL, NO, RU, SK, SE, UA).

- **32869 ADULT LARGE CUFF 32-42 cm**
- **32864 ADAPTER DC 6V, 600 mA**



microlife®

### DETECTION OF ATRIAL FIBRILLATION

#### MICROLIFE AFIB technology

An innovative and patented technology for the early detection of Atrial fibrillation (AF) **More than 30,000 fatal strokes can be prevented within the European Union by using Microlife AFIB Technology in primary care**

The new Microlife AFIB technology allows simultaneous blood pressure measurement and AF screening.

Microlife AFIB technology detects AF with high sensitivity (97-100%) and specificity (89%) as demonstrated in several clinical studies.

Nice guidelines for "Diagnosis and assessment of hypertension" recommended to use AFIB screening for routine blood pressure measurement in primary care.

AF screening by using a Microlife AFIB device is highly recommended in patients that have to monitor their blood pressure while at home.

- **32881 MICROLIFE AFIB ADVANCED EASY (Home use)**
- detection of atrial fibrillation (specific heart arrhythmia) with 1 measurement
- clinically tested according to the BHS
- ISO - EHS protocols and for "special patients" such as Diabetics, Elderly, Obese, Hypotensive, Pregnant
- MAM technology (automatic analysis of 3 consecutive measurements)
- 1 Data memory
- traffic light indicator
- low battery indicator
- mains adapter port
- world's latest technologies
- Clinically reliable measurements with AFIB & MAM
- special deflation valve allows beat detection up to 30 b/min (for bradycardic patients)
- Supplied with carrying bag, preformed conical cuff 22-42 cm, 4 AAA batteries 1.5V and user manual (GB, FR, IT, DE).
- **32866 ADAPTER DC 6V, 600 mA**
- **32884 ADULT CUFF M-L 22-42 cm - spare**
- **32885 ADULT CUFF L-XL 32-52 cm**



## OMRON PROFESSIONAL B.P. MONITOR

- **32936 OMRON DIGITAL AUTOMATIC B.P. MONITOR HEM-907**
- Professional B.P. monitor designed for clinical use in professional settings.

MADE IN JAPAN

- gold standard accuracy
- validated according to international protocols:

- 1- Association for the Advancement of Medical Instrumentation (AAMI)
  - 2- European Society of Hypertension
- International Protocol (ESH - IP)
  - intellisense technology

- irregular pulse indicator
- **3 modes of operation:**
- single mode,
- average mode,
- auscultation (manual mode).



Supplied with battery pack, adult cuff (22-32 cm), AC adapter.

- **32937 ADULT LARGE CUFF 32-42 cm**
- **32939 TROLLEY FOR OMRON HEM-907**


TECHNICAL SPECIFICATIONS	
Method:	Oscillometric
Measurement range:	pressure: 0-299 mmHg $\pm$ 3 mmHg or 2% pulse rate: 30-199 beats/min $\pm$ 5% of reading
Inflation:	automatic inflation with pumping
Deflation:	automatic deflation by electromagnetic control valve
Air release:	automatic rapid air release by electromagnetic control valve
Pressure detection:	electrostatic capacity semi-conductor pressure sensor
Power supply:	AC adapter (230 VAC, 50 Hz, 20 VA) Battery pack (4.8 VDC, 6W)
Electric shock protection method:	Class II B type
Dimension:	139x203x131 mm (5.1/2"x8"x5.1/6")
Weight:	approx. 910 g
Complies with:	EN 1060, EN60601-1-1 - 2007

32936

+

32939

CE 0197



# OMRON BLOOD PRESSURE METERS - CLINICALLY VALIDATED



The Intellisense™ technology ensures that the right inflation pressure is automatically detected. It detects irregular pulses and automatically decides if the measurement result is reliable or needs to be repeated. Only accurate results are displayed.



CE 0197

49915

• 32949 OMRON M7 INTELLI IT - HEM-7322-T-E

• 49915 OMRON M7 INTELLI IT - HEM-7361T-EBK

With Intelli Wrap Cuff 22-42 cm.

The connection to OMRON App allows to monitor parameters, create personalized programs, download and share data.

AFib (Atrial Fibrillation) detection function (only 49915).

OMRON BLOOD PRESSURE MONITOR SELECTION GUIDE								
FEATURES	M7 INTELLI IT	M6 COMFORT	M4 INTELLI IT	M3 COMFORT	M3	M2	RS7 INTELLI IT	RS4
Clinically validated*	X	X	X	X	X	X	X	X
Intellisense technology	X	X	X	X	X	X	X	X
Irregular heartbeats detector	X (AFib)	X (AFib)	X	X	X	X	X	X
Cuff wrap guide	X	X	X	X	X	X	X	X
Intelli Wrap Technology**	X	X	X	X	X	X	X	X
Pre-formed cuff***: model size (cm)	Intelli wrap 22-42	Intelli wrap 22-42	Intelli wrap 22-42	Intelli wrap 22-42	Easy cuff 22-42	Cuff 22-32	Wrist 13.5-21.5	Wrist 13.5-21.5
Memory measurem. x user	100x2	100x2	60x2	60x2	60x2	30	100x2	60
Guest mode	X	X	X	X	X	X	X	X
Body movement detection	X	X	X	X	X	X	X	X
Easy high blood pressure colour indicator****	X	X	X	X	X	X	X	X
Hypertension	X	X	X	X	X	X	X	X (morning)
Average last 3 measurements*****	X	X	X	X	X	X	X	X
3 consecutive measurements in AFib mode	X	X	X	X	X	X	X	X
Measurements comparison versus prior readings	X	X	X	X	X	X	X	X
App/Bluetooth Connection	X	X	X	X	X	X	X	X

\*To verify validations, please see [www.dableducational.org](http://www.dableducational.org)

\*\*360° accuracy: accurate measurements from any position around the upper arm

\*\*\*Pre-formed cuff, excluding M2, M3

\*\*\*\*Signal in case the values exceed the E.H.S. standards for domiciliary auto-measurements (85 systolic pressure and/or 135 diastolic pressure)

\*\*\*\*\*Average of 3 last measurements made within 10 min



49905

49906

49908

49910

• 49905 OMRON M3 HEM-7154-E  
With Easy cuff 22-42 cm.

• 49906 OMRON M3 COMFORT HEM-7155-E  
With Intelli Wrap Cuff 22-42 cm.

• 49908 OMRON M4 INTELLI IT HEM-7155T-EBK

With Intelli Wrap Cuff 22-42 cm. It monitors hypertension at home and automatically updates and transfers results to smartphones by Bluetooth on OMRON App.

• 49910 OMRON M6 COMFORT - HEM-7360-E

With Intelli Wrap Cuff 22-42 cm. It detects the possibility of Atrial fibrillation, enabling home monitoring. It also takes 3 consecutive readings at 30 second intervals, then displays the average to give more accurate indication of blood pressure.

**OMRON**



49902

• 49902 OMRON M2 HEM-7143-E  
With cuff 22-32 cm.

It has unique Intellisense™ Technology and features Irregular Heartbeat Detection. One-touch design and large display.

## MULTILINGUAL BOX AND MANUAL

Standard languages: GB, FR, IT, ES, DE, NL, RU, TR, Arabic  
Other languages: available on Omron website

## TECHNICAL SPECIFICATIONS

	49902 M2	49905 M3 49906 M3 COMFORT	49908 M4 INTELLI IT	49910 M6 COMFORT 49915 M7 INTELLI IT
Measuring method:	oscillometric	oscillometric	oscillometric	oscillometric
Measuring range: Pressure:	0 mmHg to 299 mmHg ± 3 mmHg	0 mmHg to 299 mmHg ± 3 mmHg	0 mmHg to 299 mmHg ± 3 mmHg	0 mmHg to 299 mmHg ± 3 mmHg
Pulse:	40 to 180 min ± 5% of display reading	40 to 180 min ± 5% of display reading	40 to 180 min ± 5% of display reading	40 to 180 min ± 5% of display reading
Memory (with date and time):	30	60x2 users	60x2 users	100x2 users
Inflation:	fuzzy logic controlled by electric pump	fuzzy logic controlled by electric pump	fuzzy logic controlled by electric pump	fuzzy logic controlled by electric pump
Deflation:	automatic pressure release valve	automatic pressure release valve	automatic pressure release valve	automatic pressure release valve
Rating:	DC 6V 4W	6VCC 4W	6VCC 4W	6VCC 4W
Power source:	4 "AA" batteries 1.5 V	4 "AA" batteries 1.5 V	4 "AA" batteries 1.5 V	4 "AA" batteries 1.5 V
Battery life (N° of measurements):	1000	1000	1000	1000
Protection against electric shock:	internally powered ME equipment (when using batteries)	internally powered ME equipment (when using batteries)	internally powered ME equipment (when using batteries)	internally powered ME equipment (when using batteries)
Weight (console+cuff) without batteries:	250+130 g	310+170 g	340+163 g	460+163 g
Size:	103x129xh 80 mm	105x153xh 87 mm	105x152xh 85 mm	191x120xh 85 mm
Cuff materials:	nylon and polyester	nylon and polyester	nylon and polyester	nylon and polyester
Measurable circumference (cm):	22-32 (arm)	22-42 (arm)	22-42 (arm)	22-42 (arm)

\*M3 Comfort weight 337+163 g



## OMRON EVOLV ALL IN ONE ARM BLOOD PRESSURE MONITOR

• **49900 OMRON EVOLV ALL IN ONE ARM BLOOD PRESSURE MONITOR**  
Easy to use, all in one upper arm blood pressure monitor takes accurate readings in any position around the upper arm and track progress via smartphone.

- All in one upper arm blood pressure monitor: no tubes, no wires, simply accurate

- **Intellisense Technology:** inflates the cuff to the ideal level

- **Intelli Wrap cuff:** for an easy and accurate reading

- **Clinically Validated:** proven reliability and accuracy under vigorous testing procedures by major health organisations.

- **Cuff Wrap guide:** indicates if the cuff is wrapped correctly, not too loose or too tight

- **OMRON connect App:** get connected, access anytime, see progress. Mobile application for iPhone / Android™.

Supplied with battery set, storage case, manuals.

Compatible with Alexa.

Multilingual box and manual: GB, FR, IT, ES, DE, NL, RU, TR, Arabic.

### TECHNICAL SPECIFICATIONS

Cuff Type:	Intelli Wrap Cuff 22-42 cm
Memory:	100 Readings
Cuff Wrap Guide:	Yes
Irregular Heartbeat Detection:	Yes
Body Movement Detection:	Yes
Validation:	Clinical Validation, Pregnancy Validation
Intellisense Technology:	Yes
Stroke Prevention:	Yes
Size:	12x17.3x12.5 cm



49900



With standard cuffs, 1-in-3 people measure their blood pressure incorrectly. EVOLV's Intelli Wrap Cuff Technology ensures 360° accuracy in any position around your upper arm.

3 YEARS WARRANTY



OMRON



EVOLV can sync your readings to your smartphone to track results, monitor progress, and get a deeper understanding of your health. See smartphone compatibility list on [omronconnect.com/emealen\\_gb/](http://omronconnect.com/emealen_gb/)

## OMRON WRIST BLOOD PRESSURE MONITORS

32946



CE 0197

• **32946 OMRON RS4 HEM-6181-E - wrist**  
Led positioning sensor and cuff wrap guide indicate if the cuff is positioned correctly.

Multilingual box and manual:

GB, FR, IT, ES, DE, NL, RU, TR, Arabic.

49923



CE 0197

• **49923 OMRON RS7 INTELLI IT - HEM-6232T-E - wrist**  
Intellisense technology makes measurement quick and comfortable. Advanced positioning sensor and cuff positioning guide for reliable measurements, which can be saved and tracked via Bluetooth through OMRON App. Multilingual box and manual: GB, FR, IT, ES, DE, NL, RU, TR, Arabic.



### TECHNICAL SPECIFICATIONS

	32946 RS4	49923 RS7
Measuring method:	oscillometric	
Measuring range:		
Pressure:	0 mmHg to 299 mmHg ± 3 mmHg	
Pulse:	40 to 180 min ± 5% of display reading	
Memory (with date and time):	60	100x2 users
Inflation:	automatic	
Deflation:	automatic	
Rating:	DC3 V 3.0W	
Power source:	2 "AAA" batteries 1.5 V	
Battery life (N° of measurements):	300	
Protection against electric shock:	internally powered ME equipment (when using batteries)	
Weight (console+cuff) without batteries:	86 g	91 g
Size (mm):	93x62xh 20	91x13xh 63
Cuff materials:	nylon and polyester	
Measurable circumference (cm):	13.5-21.5 (wrist)	

OMRON

## OMRON CUFFS AND ACCESSORIES



32933

Standard cuff 22-32 cm



32938

Easy adult cuff 22-42 cm



49920

Intelli Wrap cuff 22-42 cm

GIMA code	OMRON code	ACCESSORIES	Size	Compatibility				
				M2	M3	M3 Comfort	M4 Intelli IT	M6 Comfort
32930	HEM-CS24-E	Small cuff	17-22 cm	•	•			
32933	HEM-CR24	Adult cuff	22-32 cm	•	•			
32938	HEM-RML31	Easy adult cuff	22-42 cm	•	•			
49920	HEM-FL31-E	Intelli adult wrap cuff	22-42 cm			•	•	•
32929		AC/DC adaptor - optional		•	•	•	•	•

Fits normal and large arms eliminating inaccurate readings associated with incorrect positioning. AFib indication function.

OMRON

## EASYCHECK DIGITAL B.P. MONITOR

### • 49880 EASYCHECK DIGITAL BLOOD PRESSURE MONITOR

LED screen electronic sphygmomanometer with simple interface to measure systolic, diastolic and mean blood pressure as well as pulse rate. NIBP records can be reviewed.

For family and clinic use and for routine test.

Features:

- one-key measurement, easy to use
- records and stores up to 199 groups of measurements
- LED colour screen with big font easy to read
- automatic power off when there is no operation
- high pressure prompt
- low battery and error indication
- switchable: mmHg and kPa

Supplied with adult cuff and 4 alkaline batteries AA.

Multilingual manual in: GB, FR, IT, ES, PT, DE, PL, RO, GR, SE, HR, Arabic

- 49881 CUFF - adult - 22-32 cm - spare
- 80555 CUFF - adult X-large - 32-43 cm - optional
- 80556 POWER ADAPTOR 100-240V, 50/60 Hz - optional



Size: 128x100xh 72 mm  
Weight: 281 g



49980

#### TECHNICAL SPECIFICATIONS

Measurement method:	Oscillometry
Measurement range:	0 kPa (0 mmHg) - 39.6 kPa (297 mmHg)
Resolution:	0.133 kPa (1 mmHg) ±0.4 kPa (±3 mmHg)
PR measurement range:	40 bpm - 240 bpm
Inflation:	automatic inflation by force pump
Deflation:	automatic multistep deflation
Display:	LED large colour screen
Power:	Four "AA" batteries or optional 5V power adapter
Safety:	Class II Type BF

## SMART AUTOMATIC DIGITAL B.P. MONITOR - ESH VALIDATION



Display 62x43 mm LCD



European Society  
Hypertension

32921

### • 32921 SMART AUTOMATIC B.P. MONITOR with adult cuff

Compact, fully logic, multiuser, B.P.M. with innovative features:

- smart inflation technology for automatic pumping to proper pressure
- WHO blood pressure indicator
- IHB Irregular Heartbeat Detection
- average value of latest 3 readings
- 2x60 memories, date and time
- displays systolic, diastolic and pulse rate separately
- multilingual manual and box: GB, FR, IT, DE, ES, PT, PL, GR, Arabic

### • 32922 CUFF - adult - 22-30 cm (8-11") - black - spare

### • 32923 CUFF - adult large - 30-42 cm (11-16") - grey

### • 32920 CUFF - adult extra large - 42-48 cm (16-18.2") - grey

#### TECHNICAL SPECIFICATIONS

Measuring method:	oscillometric, automatic inflation and measurement
Measuring range:	cuff pressure: 0-300 mmHg ±3 mmHg
	pulse rate: 40~180 beats/min ±5% of reading
	systolic: 60-260 mmHg
	diastolic: 40-199 mmHg
Power supply:	4x "AA" batteries 1.5 V
Dimensions - Weight:	138x98x48 mm - 211 g (excluding batteries)
Arm cuff:	for arm circumferences 22-30 cm, 30-42 cm or 42-48 cm

## SMART AUTOMATIC DIGITAL WRIST B.P. MONITOR



32918



European Society  
Hypertension

Display 31.9x39.6 mm LCD

Multilingual manual  
and box: GB, FR, IT, DE,  
ES, PT, PL, GR, Arabic

### • 32918 SMART AUTOMATIC WRIST B.P. MONITOR

Compact, fully logic, B.P.M. with innovative features:

- smart inflation technology for automatic pumping to proper pressure
- WHO blood pressure indicator
- IHB Irregular Heartbeat Detection
- average value of latest 3 readings
- 2x60 memories, date and time
- displays systolic, diastolic and pulse rate separately

#### TECHNICAL SPECIFICATIONS

Measuring method:	oscillometric, automatic air inflation and measurement
Cuff pressure:	0-295 mmHg ±3 mmHg
Pulse rate range:	40~180 beats/min ±5% of reading
Range of measurement:	30-280 mmHg
Power supply:	2x "AAA" batteries 1.5 V
Dimensions - Weight:	84x64x28 mm - 110 g (excluding batteries)
Wrist cuff:	applicable for wrist circumferences 14-19.5 cm

## ANDON VALUE DIGITAL B.P. MONITOR

### • 32901 ANDON B.P. MONITOR

### • 32922 CUFF - adult - 22-30 cm - spare

### • 32923 CUFF - adult large - 30-42 cm

### • 32920 CUFF - adult extra large - 42-48 cm



- large easy to read LCD display, WHO blood pressure indicator
- 4 groups x 30 times with time and date stamp
- average of all saved measured blood pressure values for the last 7 days
- arrhythmia detection (HB)
- automatic switch-off.

Multilingual box and manual:

GB, FR, IT, ES, PT, DE

Measurement system	Oscillometric method
Measurement range	Pressure: 0~300 mmHg ±3 mmHg
	Pulse: 40~180 pulse/min ±5%
Power Source	4x1.5 V AAA batteries - not included
Dimensions - weight	107x80xh 52 mm - 170 g (ex. batteries)
LCD size	66x58.5 mm



32901

Cuff  
circumference:  
22-30 cm



## X-LIFE AUTOMATIC DIGITAL B.P. MONITORS - ESH VALIDATED

Size: 140x104x50 mm  
Weight: 247 g

LCD size 60x51 mm

Cuff size for arm  
circumferences  
23-33 cm



32924

Supplied with  
carrying bag



- **32924 X-LIFE B.P. MONITOR - arm**
  - **32926 X-LIFE B.P. MONITOR - wrist**
- Accurate and precise automatic digital blood pressure meters for smooth and fast measurements with innovative functions:
- **IHB:** irregular heartbeat detector
  - **WHO risk category indicator** (classifies your measurements in 6 stages of risk, from optimal to severe hypertension)
  - proven clinically to meet European Society of Hypertension ESH protocol
  - easy to read, wide angle display
  - 120 memories for 3 users: 3 zones of 40 memories each
  - start/stop unique button, with blue backlight



European Society  
Hypertension

Size: 74.5x74x30 mm  
Weight: 95 g

LCD size 34.5x42 mm

Cuff size for wrist  
circumferences  
13.5-19.5 cm



32926



Liquid crystal  
display

- multilingual manual and box: GB, FR, IT, ES
- memory average: automatically average last 3 memories
- **32925 SPARE CUFF for 32924 - adult**
- **32927 AC ADAPTOR for 32924**

### TECHNICAL SPECIFICATIONS

Measuring method:	oscillometric
Measuring range:	pressure: 0-300 mmHg pulse: 40-199 bpm
Accuracy:	pressure: $\pm 3$ mmHg pulse: $\pm 5\%$
Power supply:	arm type: 4xAAA alkaline batteries wrist type: 2xAAA alkaline batteries
Battery life:	arm type: 300 measures wrist type: 250 measures

## JOLLY DIGITAL B.P. MONITOR



European Society  
Hypertension



32777



- **32777 JOLLY DIGITAL BLOOD PRESSURE MONITOR**
- Professional Blood Pressure monitor for medical use.
- large easy-to-read illuminated LCD display 86x74 mm
  - WHO classification
  - arrhythmia detection (IHB)
  - 4-person memory zone - 30 memory space each
  - average of all saved measured values and morning and evening blood pressure of the last 7 days
  - time and date
  - automatic switch-off
- Multilingual manual and box:  
GB, FR, IT, ES, PT, DE, PL, GR.
- **32922 CUFF - adult -**  
22-30 cm (8-11") - black - spare
  - **32923 CUFF - adult large -**  
30-42 cm (11-16") - grey
  - **32920 CUFF - adult extra large -**  
42-48 cm (16-18.2") - grey



### TECHNICAL SPECIFICATIONS

Measurement system:	Oscillometric method
Measurement range:	Pressure: 0-300 mmHg $\pm 3$ mmHg Pulse: 40-180 pulse/min. $\pm 5\%$
Power source:	4x1.5 AAA batteries included
Outside dimension:	150x95xh 65 mm
Weight:	approx 235 g (without batteries)

## DOMINO DIGITAL B.P. MONITOR

Automatic inflation  
deflation



32803



- **32803 DOMINO DIGITAL BLOOD PRESSURE MONITOR**
  - **32804 DOMINO DIGITAL B.P.M. on trolley with basket**
- Professional Blood Pressure monitor for hospital and medical use.
- extra large LCD display with innovative design
  - date/time/ambient temperature ( $^{\circ}\text{C}/^{\circ}\text{F}$ ) display
  - IHB Irregular heartbeat detector
  - WHO blood pressure classification indicator
  - 120 memories (60 sets for 2 users)
  - alarm clock reminding function
- Multilingual manual and box:  
GB, FR, IT, ES, PT, DE, GR, Arabic
- **32802 AC ADAPTOR 230 V - 50 Hz**
  - **32809 ADULT CUFF - spare**
  - **32865 COILED TUBING**  
EXTENSION 3 m (42/45 spirals)



### TECHNICAL SPECIFICATIONS

Measuring range:	Pressure - 40-260 mmHg Pulse: 40-160 beats/min.
Accuracy:	Pressure $\pm 3$ mmHg Pulse: $\pm 5\%$
Power supply:	4x "AA" batteries or AC adaptor (option)
External dimension:	158x120xh 127 mm
Weight:	490 g

32804

## ERKA VARIO: DESK, WALL AND TROLLEY

- 32671 VARIO - desk - adult cuff - 285.20.481
  - 32672 VARIO - wall - adult cuff - 288.20.481+295.00.003
  - 32673 VARIO - trolley Ø 50 cm - adult cuff - 288.20.481+995.00.003
- Superior quality product, for use in consulting rooms or hospital. The Vario model consists of a high precision manometer in a high quality ABS housing with an integrated fastening spigot for individual variable swivelling, a big cuff basket in white powder coated sheet steel, a bulb holder and spiral tubing with bulb and air release valve. This high quality chromium-plated valve makes sensitive adjustments easy. The 150 mm scale is equipped with a mirrored exterior ring and non-reflective manometer glass.
- 32898 PEDIATRIC "SUPERB" CUFF 2 TUBES - 20.5-28 cm\*
  - 32899 ADULT "SUPERB" CUFF 2 TUBES - 27-35 cm\* - spare
  - 32900 LARGE "SUPERB" CUFF 2 TUBES - 34-43 cm\*

\*Arm circumference

### TECHNICAL SPECIFICATIONS

Height with basket:	260 mm (32672-3)
Width with basket:	180 mm (32672-3)
Depth with basket:	120 mm (32672-3)
Graduation:	0-300 mmHg $\pm 3$ mmHg
Weight with basket:	1,350 g
Height of trolley:	830-1,360 mm (adjustable)
Tubing system Ø:	18-25 mm
Swivel range:	up to 60 deg°

32671



Latex, PVC, DEHP  
free cuffs

Bulb  
holder

32673



## RIESTER BIG BEN®

- 32742 RIESTER BIG BEN® - rail (clamp code 32766 and rail not included)
  - 32743 RIESTER BIG BEN® - wall
  - 32746 RIESTER BIG BEN® - trolley Ø 54 cm - velcro adult cuff
  - 32740 RIESTER BIG BEN® - trolley Ø 54 cm - adult one piece cuff
  - 32748 RIESTER BIG BEN® - desk
- Aneroid sphygmomanometer, made of resistant plastic, with large dial (147 mm) and white pointer on black dial plate for easy-to-read measurements from 0 mmHg to 300 mmHg. Basket on back for cuff storage after use. Velcro-closure black cuff 2 tubes and long coil tubing. Latex free.
- 32766 RAIL CLAMP
- Universal clamp (for code 32742) for any rail.

MADE IN GERMANY



32748



32743

32766

32740,  
32746

## DAYTON DESK/WALL SPHYGMO

- 32745 DAYTON SPHYGMO - desk/wall model
- Provided with big dial (Ø 113 mm) for easy reading. Basket with handle easy to move and carry. Nylon cuff with D ring. Wall fixing. Size: 130x130x135 mm - Weight: 180g. Measuring range: 0-300 mmHg  $\pm 3$  mmHg.
- 32850 ADULT CUFF - black - spare
- Available also 32839, 32841, 32843, 32847, 32849 see page 305



Large basket  
with handle  
for cuff

CE 0123

PVC bladder  
and bulb

LATEX FREE



32745